



CSE 215: Programming Language II Lab

Lab – 15

List, Stack, Queue, Sets and Maps


Objective:

- To learn about stack and queue in java
- To learn to implement those in solving problems

Collection


The Collection interface defines the common operations for lists, vectors, stacks, queues, priority queues, and sets. Lists store an ordered collection of elements.

- Stacks store objects that are processed in a last-in, first-out fashion.
- Queues store objects that are processed in a first-in, first-out fashion.
- PriorityQueues store objects that are processed in the order of their priorities.




List

The List interface extends the Collection interface and defines a collection for storing elements in a sequential order. To create a list, use one of its two concrete classes: ArrayList or LinkedList.




The ArrayList class and the LinkedList class are two concrete implementations of the List interface. ArrayList stores elements in an array. LinkedList stores elements in a linked list.




Stack

Vector is a subclass of AbstractList, and Stack is a subclass of Vector in the.




Queue

The Queue interface extends java.util.Collection with additional insertion, extraction, and inspection operations



Sets and Maps

You can create a set using one of its three concrete classes: HashSet, LinkedHashSet, or TreeSet. The Set interface extends the Collection interface. It does not introduce new methods or constants, but it stipulates that an instance of Set contains no duplicate elements. The HashSet class is a concrete class that implements Set.



A map is a container object that stores a collection of key/value pairs. It enables fast retrieval, deletion, and updating of the pair through the key. A map stores the values along with the keys. The keys are like indexes.

<interface> <i>java.util.Map<K,V></i>	
<pre> +clear(): void +containsKey(key: Object): boolean +containsValue(value: Object): boolean +entrySet(): Set<Map.Entry<K,V>> +get(key: Object): V +isEmpty(): boolean +keySet(): Set<K> +put(key: K, value: V): V +putAll(m: Map<? extends K,? extends V>): void +remove(key: Object): V +size(): int +values(): Collection<V> </pre>	<pre> Removes all entries from this map. Returns true if this map contains an entry for the specified key. Returns true if this map maps one or more keys to the specified value. Returns a set consisting of the entries in this map. Returns the value for the specified key in this map. Returns true if this map contains no entries. Returns a set consisting of the keys in this map. Puts an entry into this map. Adds all the entries from m to this map. Removes the entries for the specified key. Returns the number of entries in this map. Returns a collection consisting of the values in this map. </pre>

The Map interface except the entrySet() method. The HashMap, LinkedHashMap, and TreeMap classes are three concrete implementations of the Map interface.

<i>java.util.HashMap<K,V></i>
<pre> +HashMap() +HashMap(initialCapacity: int,loadFactor: float) +HashMap(m: Map<? extends K, ? extends V>) </pre>

Lab Tasks

- Write a program that evaluate compound mathematical expressions with multiple operator and parentheses. For simplicity, assume that the operands are integers and the operators are of four types: +, -, *, and /. (e.g., (15 + 2) * 34 - 2)
Hint: The problem can be solved using two stacks, named operandStack and operatorStack, for storing operands and operators, respectively. Operands and operators are pushed into the stacks before they are processed. When an operator is processed, it is popped from operatorStack and applied to the first two operands from operandStack (the two operands are popped from operandStack). The resultant value is pushed back to operandStack.
- Write a program that uses a HashMap to store an entry consisting of a word and its count.
Hint: For each word, check whether it is already a key in the map. If not, add an entry to the map with the word as the key and value 1. Otherwise, increase the value for the word (key) by 1 in the map. Assume the words are case insensitive; e.g., Good is treated the same as good.