

BE FEARLESS USING RUST IN PRODUCTION

ROBOTXY

ME

- ▶ robotxy 陈雨琪
- ▶ Front-end Engineer @ Alibaba
 - ▶ Creative tools
 - ▶ Image rendering service
- ▶ <https://github.com/NoXF>
- ▶ xianyou.cyq@gmail.com

THIS TALK IS ABOUT

- ▶ Status
- ▶ Minolta
- ▶ Performance and Stability
- ▶ Problem and difficult
- ▶ Tips

STATUS

- ▶ Rust-nightly 1.35
- ▶ 40+ servers (32 core 2.50GHz 128G RAM)
- ▶ Dev since 2016

Language	Files	Lines	Code	Comments	Blanks
Dockerfile	1	15	12	0	3
GLSL	9	498	336	103	59
JSON	1	19	19	0	0
Markdown	3	96	96	0	0
Python	3	31	17	11	3
Rust	95	18646	16458	1003	1185
Shell	5	71	44	10	17
TOML	17	705	615	5	85
YAML	2	64	63	0	1
Total	136	20145	17660	1132	1353

USAGE

- ▶ Rust Web Server
 - ▶ Image rendering service
 - ▶ SVG parsing & rendering
 - ▶ Video encode & decode

USAGE

- ▶ Compute-intensive modules for Node.js
 - ▶ Algorithm

WHAT IS MINOLTA?

High-performance and real-time
image rendering service

```
https://alpha.alicdn.com/montage/24514-  
c3c2bc0b0be7980a4eaa463bf4f25ed0.jpg?  
content={"10":{"attrs":{"value":"https://  
img.alicdn.com/tfscom/  
TB1qkpoRFXXXXX.aXXXXXXXXXXXX.png"},"m  
ini":false,"papercut":false}},"12":{"attrs":  
{"value":"品质配饰"},"14":{"attrs":{"value":"整  
点下单立减"}}
```





WHAT IS MINOLTA?



PART2: MINOLTA

Layer



Image



Copy

清凉大作战 海量美衣零点开抢 特价两件包邮 Time: 2018.6.1-6.7

Special



PART2: MINOLTA

Layer



Image



Copy

Title

清凉大作战

subtitle

海量美衣零点开抢

action point

特价两件包邮

decorative

Time: 2018.6.1-6.7

Get copy type

Special



PART2: MINOLTA



AVG. RT 10ms
3000 QPS



LOGO

清凉大作战

海量美衣零点开抢

特价两件包邮

Time: 2017.6.1-6.7

换季美不停 美妆感恩季 美鞋新宠 时尚型男 休闲舒适箱包感恩盛宴 优雅气质 萌衣特卖惠

当季新品抢不停手

护肤转场价格触底

高跟诱惑释放自己

潮搭型格兼具保暖

百搭潮鞋搭配无限

轻巧耐用多隔层

闪闪发光皆礼物

百变萌搭库存有限

整点下单力减50
NEW ARRIVAL

大礼包继续送
SPECIAL SALE

预售新款立享八折
Time: 2018.6.18

春季热卖抢鲜购
HOT SALE

一件包邮
立即购买

新款包包抢先购
不容错过

畅销人气单品
尽在 618 大促

送好孩子漂亮衣服
马上收藏

PART 2: MINOLTA



LOGO

美鞋新宠

高跟诱惑释放自己

预售新款立享八折

Time: 2018.6.18



LOGO

箱包感恩盛宴

轻巧耐用多隔层

新款包包抢先购

不容错过



LOGO

优雅气质

闪闪发光皆礼物

畅销人气单品

尽在 618 大促



LOGO

美妆感恩季

护肤转场价格触底

大礼包继续送

SPECIAL SALE



LOGO

清凉大作战

海量美衣零点开抢

特价两件包邮

Time: 2017.6.1-6.7



LOGO

换季美不停

当季新品抢不停手

整点下单力减50

NEW ARRIVAL



LOGO

时尚型男

潮搭型格兼具保暖

春季热卖抢鲜购

HOT SALE



LOGO

休闲舒适

百搭潮鞋搭配无限

一件包邮

立即购买



LOGO

萌衣特卖惠

百变萌搭库存有限

送好孩子漂亮衣服

马上收藏

PART 3: PERFORMANCE

NODE

640x200

QPS: 60

RT: 200ms



NODE & NEON & RAYON

- ▶ Image resize in parallel
- ▶ Pixels blend in parallel
- ▶ GM(ImageMagick) commands

```
use image::{ RgbaImage, Pixel };
use rayon::prelude::*;

pub fn resize(img: &RgbaImage, width: u32, height: u32, value: u32) -> RgbaImage {
    let mut result = RgbaImage::new(width, height);
    let (original_width, original_height) = img.dimensions();
    let width_range: Vec<u32> = (0..width).collect();
    let x_ratio = original_width as f32 / width as f32;
    let y_ratio = original_height as f32 / height as f32;
    let mut f = vec![];
    width_range.par_chunks(value as usize).weight(10.0).map(|w| {
        let mut t = vec![];
        for x in w {
            for y in 0..height {
                let px = (*x as f32 * x_ratio).floor() as u32;
                let py = (y as f32 * y_ratio).floor() as u32;
                t.push((*x, y, *img.get_pixel(px, py)));
            }
        }
        t
    }).collect_into(&mut f);
    for i in f {
        for j in i {
            let (x, y, p) = j;
            result.put_pixel(x, y, p);
        }
    }
    result
}
```

NODE & NEON & RAYON

640x200

QPS: 60

RT: 200ms

640x200

QPS: 60

RT: 20ms

RUST


- ▶ Asynchronous everything
- ▶ Cache everywhere

ASYNCHRONOUS

“Async everything. By leveraging the Tokio project, all Gotham web framework types are async out of the box. Our async story is further enhanced by Hyper, a fast server that provides an elegant layer over stringly typed HTTP.”


—Gotham <https://github.com/gotham-rs/gotham>

ASYNCHRONOUS



CACHE EVERYWHERE

Layer



Image



Copy

Title

清凉大作战

subtitle

海量美衣零点开抢

action point

特价两件包邮

decorative

Time: 2018.6.1-6.7



RUST

640x200

QPS: 60

RT: 200ms

640x200

QPS: 60

RT: 20ms

640x200

QPS: 3000

RT: 10ms

BENCHMARK & DIFF

```
multiplepaths: Found 18058 paths
multiplepaths: Found 18058 paths
Running 1m test @ http://11.10.157.28
32 threads and 100 connections
Thread Stats   Avg      Stdev     Max   +/-  Stdev
  Latency    15.20ms   16.36ms  499.61ms   94.24%
  Req/Sec    209.94    29.99   383.00    74.36%
Latency Distribution
  50%    11.93ms
  75%    14.66ms
  90%    20.08ms
  99%    68.91ms
404826 requests in 1.00m, 15.23GB read
Requests/sec: 6735.86
Transfer/sec: 259.54MB
```



DEPLOY

► Rust-nightly RPM Package

Index of /taobao/7/x86_64/test

全选

批量删除

比较差异

 rust-nightly-1.34-20190313172945.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.33-20190108101857.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.33-20190107205434.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.32-1.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.30-2.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.30-1.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.27-2.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.27-1.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.26-1.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.25-1.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.24-1.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.22-6.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.22-4.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.22-3.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>

Index of /taobao/7/x86_64/current

全选

批量删除

 rust-nightly-1.35-20190313174000.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>
 rust-nightly-1.33-20190108104419.alios7.x86_64.rpm	文件列表	下载	删除	<input type="checkbox"/>

DEPLOY

- ▶ Crates mirror
 - ▶ Sync crates.index and crates
 - ▶ Create crates file server
- ▶ Configuration

```
→ minolta-rs (master) ✓ cat ~/.cargo/config
[source.crates-io]
registry = "https://github.com/rust-lang/crates.io-index"

replace-with = 'local'
[source.local]
registry = "https://gitlab.alibaba-inc.com/xianyou.cyq/crates.io-index.git"
```

MONITORS

- ▶ Warning: QPS
- ▶ Warning: RT
- ▶ Critical: CPU usage
- ▶ Critical: MEM usage
- ▶ Critical: Disk usage
- ▶ Urgent: Process

PART 5: PROBLEMS AND DIFFICULTIES

- ▶ Future is difficult, but async/await is coming soon

- ▶ Deploy

- ▶ The ecos

- ▶ concurr

- ▶ oss-rust-sdk

```
pub async fn get_template() -> Result<Template, Error> { ... }
pub async fn get_layer() -> Result<Layer, Error> { ... }
pub async fn get_image() -> Result<Image, Error> { ... }

pub async fn minolta(req: Request) -> Result<Response<Body>, Error> {
    const template = await!(get_template())?;
    const layer = await!(get_layer())?;
    const image = await!(get_image())?;
    const buffer = await!(merge(template, layer, image))?;
    Ok(Response::builder().body(buffer.into()))
}
```

TIPS

- ▶ Error handling
- ▶ Futures cheatsheet
- ▶ Use Node.js/Python/C++
- ▶ Be patient, rust is difficult

```
// Constructing leaf futures
fn empty ()      -> Future<T, E>
fn ok   (T)      -> Future<T, E>
fn err  (E)      -> Future<T, E>
fn result(Result<T, E>) -> Future<T, E>

// General future constructor
fn poll_fn(FnMut(thread_local!(Task)) -> Poll<T, E>) -> Future<T, E>

// Mapping futures
fn Future::map    (Future<T, E>, FnOnce(T) -> U) -> Future<U, E>
fn Future::map_err(Future<T, E>, FnOnce(E) -> F) -> Future<F, E>
fn Future::from_err(Future<T, E>, Into<E>>)      -> Future<T, E>

// Chaining (sequencing) futures
fn Future::then    (Future<T, E>, FnOnce(Result<T, E>) -> IntoFuture<U, E>) -> Future<U, E>
fn Future::and_then(Future<T, E>, FnOnce(T)          -> IntoFuture<U, E>) -> Future<U, E>
fn Future::or_else  (Future<T, E>, FnOnce(E)          -> IntoFuture<T, E>) -> Future<T, E>
fn Future::flatten  (Future<Future<T, E>, Into<E>>)    -> Future<T, E>

// Joining (waiting) futures
fn Future::join    (Future<T, E>, IntoFuture<U, E>) -> Future<T, U>, E>
fn Future::join3   (Future<T, E>, IntoFuture<U, E>, IntoFuture<V, E>) -> Future<T, U, V>, E>
fn Future::join4   (Future<T, E>, IntoFuture<U, E>, IntoFuture<V, E>, IntoFuture<W, E>) -> Future<T, U, V, W>, E>
fn Future::join5   (Future<T, E>, IntoFuture<U, E>, IntoFuture<V, E>, IntoFuture<W, E>, IntoFuture<X, E>) -> Future<T, U, V, W, X>, E>
fn join_all    (IntoIterator<IntoFuture<T, E>>) -> Future<Vec<T>, E>

// Selecting (racing) futures
fn Future::select (Future<T, E>, IntoFuture<T, E>) -> Future<T, Future<T, E>>
fn Future::select2(Future<T, E>, IntoFuture<U, E>) -> Future<Either<T, U>, E>
fn select_all    (IntoIterator<IntoFuture<T, E>>) -> Future<T, usize>
fn select_ok     (IntoIterator<IntoFuture<T, E>>) -> Future<T, Vec<T>>

// Utility
fn lazy    (FnOnce<T> -> IntoFuture<T, E>) -> Future<T, E>
fn loop_fn (S, FnMut(S) -> IntoFuture<Loop<T, S>, E>) -> Future<Loop<T, S>, E>
fn Future::boxed(Future<T, E>::Send + 'static) -> Future<T, E>

// Miscellaneous
fn Future::into_stream (Future<T, E>) -> Stream<T, E>
fn Future::flatten_stream(Future<Stream<T, E>, E>) -> Stream<T, E>
fn Future::fuse          (Future<T, E>) -> Future<T, E>
fn Future::catch_unwind  (Future<T, E> + UnwindSafe) -> Future<Result<T, E>, E>
fn Future::shared        (Future<T, E>) -> Future<SharedTle<T, E>, E>
fn Future::wait          (Future<T, E>) -> Result<T, E>
```

真香！



```
rc(E, Future<U, E>), (F, Future<T, E>))>>
e<T, E>>>
```

Thank you!  阿里巴巴 · 创意中心