


gradbars

Data bars and visual tables for L^AT_EX


Values, comparisons and trends, directly in your tables.

Gradients, rounded corners and a target



`\gradbar[rounded=2pt,target=80]{68}`

Signed values and uncertainty




`\gradbar[min=-50,max=50,error=8,theme=teal]{-24}`

Stacked contributions




`\gradstack{25,35,20}`

Before/after comparison and difference




`\graddumbbell[compare label=delta]{46}{72}`

An interval and its point estimate





`\gradrange[range point=64]{45}{82}`

Trends and missing observations



`\gradspark{30,65,NA,50,82}`

Visual tables: width allocation, spanning headers and best values

Evaluation		
Method		Score
A		82
B		91

```
\begin{gradtable}[width=\linewidth,
label width=8mm,column sep=3pt,
min graphic width=10mm,header align=c]
\gradcolumn{name}{Method}
\gradcolumn[type=bar,mark=best,
options={precision=0}]{score}{Score}
\gradheader{\gradspan{2}{Evaluation}}
\gradrow{A,82}
\gradrow{B,91}
\end{gradtable}
```

Shared options / Data semantics / Multipage tables

Contents

I	Quick start and data semantics	3
1	Installation and engine requirements	3
2	Choosing a graphic	4
3	Values, scales, labels and missing observations	5
II	Graphics and comparisons	6
4	Signed bars, targets, intervals and uncertainty	6
5	Stacked contributions and segment labels	7
6	Layered and dumbbell comparisons	8
7	Change annotations and relative differences	9
8	Sparklines and missing positions	10
9	Multiple references, bullet charts and grouped intervals	11
III	Appearance, labels and evaluation	13
10	Appearance, reusable styles and palettes	13
11	Overflow indicators and marker shapes	15
12	Quality: higher, lower, target or interval	16
13	Label placement, printing and practical limits	17
IV	Visual tables and data interfaces	18
14	Dedicated visual tables: gradtable	18
15	Comparison, composition and trend columns	19
16	Alignment, rules and spacing	20
17	Allocating a total table width	22
18	Multilevel headers and spanning titles	23
19	Grouped rows and best-value marking	24
20	Report and monochrome table presets	25
21	Reusable table styles and schemas	26
22	Multipage tables and repeated headers	27
23	CSV input and numeric table columns	29
V	Complete layout examples	30
24	A complete benchmark table	30
25	Two-column papers, print and slides	30
VI	Questions and interface reference	32
26	Frequently asked questions	32
27	Compact option reference	33
28	Table and annotation reference	34

Reading this manual. Start with data semantics, then choose a graphic. Appearance and evaluation rules precede the dedicated table interface; complete examples and the reference follow. Rendered examples use the source shown beside or below them. All data are illustrative. The English and Chinese manuals cover the same interfaces; their section and example numbers are independent.

Part I

Quick start and data semantics

1 Installation and engine requirements

Place `gradbars.sty` beside your main source, or install it in a local TEXMF tree under `tex/latex/gradbars`. Load it with `\usepackage {gradbars}`. Dependencies include TikZ/PGF, xparse, expl3, colcell, array, booktabs, colortbl and longtable. No shell escape or external data-conversion program is required.

The package has no inherent XeLaTeX requirement. PDF output with pdfLaTeX, XeLaTeX and LuaLaTeX is tested, including CSV input. The Chinese manual uses XeLaTeX with ctex and Fandol fonts. This English manual can be compiled with pdfLaTeX. The package itself does not load fontspec or ctex. Use an appropriate font and encoding setup for non-ASCII text in your own documents.

```
\documentclass{article}
\usepackage{booktabs,gradbars}
\begin{document}
\gradbarssetup{width=30mm,max=100,precision=1}
\begin{tabular}{lc}
\toprule
Model & Accuracy (\%) \\
\midrule
Baseline & \gradbar{72.4} \\
Proposed & \gradbar{92.7} \\
\bottomrule
\end{tabular}
\end{document}
```

No `tikzpicture` wrapper is needed. Commands may also be used inside an existing TikZ picture. Settings and named styles follow ordinary TeX grouping. Options are applied left to right: put a theme or preset before individual overrides.

2 Choosing a graphic

Question	Interface
How large is a value?	<code>\gradbar {value}</code> ; use a negative min for signed values.
How do two values compare?	<code>\gradcompare {reference}{current}</code> for layered bars; <code>\graddumbbell {reference}{current}</code> for connected points.
What are the bounds?	<code>\gradrange {lower}{upper}</code> for supplied endpoints.
What makes up the total?	<code>\gradstack {list}</code> for additive, common-unit contributions.
How does a series change?	<code>\gradspark {list}</code> for equally spaced observations.
What is the uncertainty?	<code>error minus</code> and <code>error plus</code> on a point estimate.

3 Values, scales, labels and missing observations

Defaults are `min=0` and `max=100`. The maximum must be positive and the minimum must be nonpositive. Decimal literals and macros expanding to decimals are accepted; expressions, thousands separators, units in input, and scientific input notation are not. Scientific notation is available as an output format.

Keep `min`, `max` and `width` identical within each comparison column. Zero is not missing. Empty input or uppercase NA denotes missing data for a single observation; missing stack segments are rejected. Overflow warns and clips geometry while preserving the original label. Use `overflow=error` for strict checking.


Raw values, calculated percentages and missing values	
	50.0
	25.0%
	50.0 ms
	0.0
	N/A
<code>\gradbar[max=200]{50}</code>	
<code>\gradbar[max=200,value format=percent]{50}</code>	
<code>\gradbar[max=200,unit={\,ms}]{50}</code>	
<code>\gradbar{0}</code>	
<code>\gradbar[missing text={N/A}]{NA}</code>	

`unit` appends text. `value format=percent` computes $100v/\text{max}$, ignores unit, and requires `min=0`. For values already expressed as percentages, use `unit={\%}`. `text` overrides the complete label without changing geometry. `precision` accepts integers from 0 to 6. `number format` is fixed, grouped or scientific. Missing labels do not acquire a unit or percent suffix.

Part II

Graphics and comparisons


4 Signed bars, targets, intervals and uncertainty



Error magnitudes are nonnegative distances from the observation, not absolute endpoints. Explain whether they represent standard deviation, standard error or confidence intervals in the table caption. Targets and bands are references, not automatically estimated uncertainty. A band must have ordered endpoints within the scale; invalid reference bands and targets cause errors.

Floating intervals require $\text{lower} \leq \text{upper}$; equal endpoints draw a cap, not an inflated bar. Both endpoints must be present or both missing. A range point must lie inside the original endpoints. Intervals reject error whiskers and quality thresholds. Default labels show the supplied endpoints. Lollipops show a point for zero, but no point for missing input.

5 Stacked contributions and segment labels



Positive and negative contributions accumulate independently from zero. Within each side, segment order follows input order. Negative segments require a negative min. Positive and negative subtotals are checked separately against the scale. The default total is the algebraic sum; `stack totals=separate` shows positive and negative subtotals. A zero net does not erase nonzero contributions.


Segment labels can be none, value, percent, name, name value or name percent. The percentage of a segment is

$$100|v_i|/\sum_j |v_j|,$$

including clipped contributions. These percentages represent shares of absolute activity, not shares of a potentially zero net. All-zero stacks do not calculate percentages. Stacks are not normalized to full width. Missing segments, empty lists, quality thresholds and error whiskers are rejected.

Provide one stack name per segment for named labels or automatic legends. Small labels move outside with leader lines; automatic black/white text follows the fill. Zero segments retain their palette and legend positions. Use a shared `\gradbarslegend` outside a table to avoid repeating the legend for every row.

6 Layered and dumbbell comparisons




Layered bars use a wide reference and a centered current layer. The `compare ratio` defaults to .45 and must be strictly between zero and one. Both lengths start from the common zero; they are not added or divided.

Dumbbells use a hollow reference point and a current point joined by a line. The default label is current / reference; delta means current minus reference. A missing endpoint suppresses the connector; delta is missing if either endpoint is missing. Equal endpoints overlap. Error whiskers refer to the current value. `compare color`, `marker size` and `stem width` control appearance. Dedicated comparison and spark commands retain their shape when applying presets.


7 Change annotations and relative differences

`compare annotation=none|arrow|bracket` adds a directional arrow or a difference bracket above a layered comparison or dumbbell. None is the default. Arrows point from reference to current; equal values omit the arrow. Missing either endpoint suppresses the annotation.



Relative change is $100(c - r)/|r|$ percent, where r is the reference and c is the current value. A zero reference or missing endpoint gives a missing label, not infinity. This differs from `value format=percent`, which uses the scale maximum. Positive changes carry a plus sign. Annotation text follows percent mode; other modes annotate the raw-unit difference. Reference names and change annotations share the upper area, so avoid crowding both into a narrow graphic.

8 Sparklines and missing positions



Observations are equally spaced. Empty fields and NA keep their horizontal position and break connections. The last label is the last position, not the last nonmissing observation. Default height is 4ex.

spark range=auto uses each row's extrema; compare shapes only with this mode. Use fixed with shared min, max, width and height to compare magnitudes across rows. Constant auto series are centered vertically; a singleton is centered horizontally. All-missing series show only a track and missing label. Fixed ranges use normal overflow rules. Auto ranges do not support computed-percent labels.

spark points can be extrema (default), all, last or none. Extrema mode marks all tied extrema and the last position if present. Low and high colors default to gradbarsOrange and gradbarsTeal. A constant series uses the high color; a non-extreme last point uses the line color. Point colors indicate position, not quality. Use color, stem width and marker size to style the line and points. Sparklines do not parse dates and do not use bar targets, error whiskers, bands or thresholds. Labels stay outside. Use a common observation grid for irregular dates.

9 Multiple references, bullet charts and grouped intervals

`references` takes records in the form `value/color/line style/name`. Enclose each record in braces. Styles are solid, dashed and dotted. Values must lie within min/max. Leave a name empty by retaining the final slash. Names use alternating heights, but long or closely spaced names may still overlap.

Several named references




```
\gradbar[width=85mm,height=9pt,precision=0,
  references={{40/gray/dotted/Baseline},
             {75/gradbarsTeal/dashed/Target},
             {95/gradbarsOrange/solid/Limit}}]{68}
```

`references={}` clears inherited references. They may coexist with `target`. References apply to bars, stacks, comparisons and intervals, not sparklines. Avoid slashes in names; compact tables can explain unnamed reference lines in a heading.

9.1 Bullet charts

`\gradbullet {value}` draws an actual value over explicit background grades. Provide `bullet bands` as upper-bound/color records. Bounds must strictly increase; the first band starts at min and the final bound must equal max. The default height is 12pt, with the actual bar occupying 40% of that height.

Actual performance, reference grades and targets




```
\gradbullet[width=85mm,max=120,precision=0,color=gradbarsBlue,
  bullet bands={{60/black!8},{90/black!16},{120/black!26}},
  references={{90/gradbarsTeal/dashed/Target},
             {110/gradbarsOrange/solid/Stretch}}]{82}
```

Grades do not classify performance automatically. Supply quality thresholds separately when needed. Explain the grades in a caption; use explicit gray shades for monochrome output. NA and zero retain their different meanings.

9.2 Several intervals in one cell

`\gradintervals {records}` accepts `name/lower/point/upper/color` records. Each record uses the same scale and graphic width; names align to the longest name. Use NA for an absent point, or NA for all three numbers for a missing record.

Comparable uncertainty intervals



```
\gradintervals[width=65mm,min=0,max=100,height=5pt,
  precision=0,row padding=4pt,references={{70/gray/dashed/}}]{
  {Method A/45/58/72/gradbarsBlue},
  {Method B/55/68/82/gradbarsTeal},
  {Method C/62/NA/88/gradbarsOrange}}
```

Points are supplied, never inferred. Lower must not exceed upper and a point must lie inside the original interval. Explain the confidence level if relevant. This command creates an indivisible inner table: names and endpoint labels add to its width, and records do not break across pages. Reference names repeat per record.


Part III

Appearance, labels and evaluation

10 Appearance, reusable styles and palettes

Seven themes are available: blue, teal, solid, gray, lbyellow, vibblue and cyblu. Nine predefined solid colors are lightgreen, lightyellow, lightblue, lightred, rose, skyblue, gold, lavender and peach. Use `color` for solid fill and `left color/right color` for a gradient. Standard `xcolor` expressions work.

A reusable layout style



```

\gradbarsstyle{paperrow}{preset=paper,width=45mm,max=100,precision=0}
\gradbar{style=paperrow}{82}

\graddumbbell{style=paperrow}{60}{82}

\gradbar[preset=report,target=90,thresholds={60,80}]{75}

\gradbar[preset=presentation]{92}


\gradbar[preset=outline]{70}

```

The paper preset uses thin solid bars, a faint track and outside values. Report uses thicker rounded bars; supply actual target and threshold values yourself. Presentation uses larger type and automatic inside placement. Outline uses hollow shapes with fine strokes. Presets do not invent data or scale limits.

Group palettes are categorical (six distinct colors), sequential (five blue levels), diverging (orange through neutral to teal), and mono (gray with textures). These palettes select by segment position, not by value; short lists cycle. Named categories instead preserve identity across reordered or subsetted data:

Stable category identity and a shared legend



```

\gradbarscategory{Compute}{gradbarsBlue}{diagonal}
\gradbarscategory{Storage}{gradbarsOrange}{dots}
\gradstack[stack names={Compute,Storage}]{60,30}

\gradstack[stack names={Storage,Compute}]{30,60}

\gradbarslegend[width=50mm]{Compute,Storage}

```


Registered names override positional colors and patterns; unregistered names fall back to the current palette. Definitions are scoped. In print/mono mode, category colors use gray while registered patterns remain. Legends use the same mapping. Patterns are none, diagonal, reverse, dots, crosshatch, horizontal and vertical. Use names

or textures alongside color when category distinctions matter.

11 Overflow indicators and marker shapes

`overflow mark=none|arrow|slash` indicates clipped values at scale boundaries. The default is none for individual graphics and arrow in `gradtable`. Exact boundary values do not produce a mark. `overflow=error` still rejects out-of-range data.

Clipping without hiding the original value



```
\gradbar[max=100,width=65mm,precision=0,overflow mark=arrow]{125}
```

```
\gradrange[min=-40,max=60,width=65mm,precision=0,
overflow mark=slash]{-55}{75}
```

Checks use raw values, interval and error endpoints, both comparison values and separate signed stack subtotals. Fixed-range sparklines check all present points. The mark indicates overflow, not quality or the amount beyond the boundary.

`marker shape` supports circle, square, diamond and triangle; `marker fill` supports solid and hollow. Dumbbell reference markers and interval estimates remain hollow to preserve their meaning. Marker size is the distance from the center to its boundary.

Shapes that remain distinguishable in monochrome



```
\gradbar[shape=lollipop,marker shape=square]{72}
```

```
\graddumbbell[marker shape=diamond]{48}{72}
```

```
\gradbar[shape=lollipop,marker shape=triangle,marker fill=hollow]{72}
```

12 Quality: higher, lower, target or interval

Higher and lower modes classify the raw value using two increasing thresholds. Lower reverses the quality colors without reversing geometry. Threshold colors are always ordered bad, intermediate, good.



Target mode evaluates $d = |v - t|$. Interval mode evaluates $d = \max(0, a - v, v - b)$ for an ordered closed interval $[a, b]$. These modes require two nonnegative increasing distance thresholds: $d \leq t_1$ is good, $t_1 < d \leq t_2$ intermediate, and $d > t_2$ bad. Thus thresholds of 0 and 10 classify values inside the interval, including its endpoints, as good. Quality target/range evaluate data; target/band draw optional references. Set them separately. Quality changes color, never positions or labels. It is not applied to stacks, floating intervals or sparklines.

13 Label placement, printing and practical limits

Labels support outside, inside, end, auto and none. Auto moves a label outside when it does not fit. End places it above the endpoint. Comparisons, lollipops, outlined bars and intervals with a range point move internal labels outside. Sparklines always use outside labels. `text color=auto` chooses black or white. `label width` reserves an outside slot; use the same sufficiently wide slot throughout a column. Long labels may require a wider column or a custom short text.

`row padding` reserves extra height above and below a graphic; it does not change the document's global row spacing. Use `arraystretch` or table row spacing when appropriate. Marker shapes reserve space consistently even when the first or last observation does not have a marker.

`print` applies gray fills, textures and white label backgrounds. Mono is a group palette using those settings. Provide textual category names and real values as well as visual distinctions. Outlined bars and legends are available through `outline=true` or the outline preset; print clears outline mode.

All collision handling is local to a graphic, not to the whole table. Complex axes, date parsing and large general-purpose plots are outside this package's scope. Automatic alternative descriptions are available when PDF tagging is enabled; see the tagging notes in the interface reference.

Part IV

Visual tables and data interfaces

14 Dedicated visual tables: gradtable

Declare columns, then supply data rows. No alignment separators or row-ending commands are needed.

`\gradcolumn [options]{id}{title}` requires a unique id; `\gradrow {cells}` provides comma-separated cells in declaration order. Protect text containing commas with braces. Use explicit NA for missing numbers.

Text, numbers and bars in one table

Method	Samples	Score
Method A	120	82.4
Method B	12 500	91.2
Method C	—	—

```
\begin{gradtable}[preset=paper,graphic width=48mm,
  text width=24mm,label width=14mm]
\gradcolumn{method}{Method}
\gradcolumn[type=number,options={precision=0}]{n}{Samples}
\gradcolumn[type=bar,options={max=100,precision=1}]{score}{Score}
\gradrow{Method A,120,82.4}
\gradrow{Method B,12500,91.2}
\gradrow{Method C,NA,NA}
\end{gradtable}
```

Column `options={...}` accepts drawing options such as min, max, precision, unit, theme, target and references. All rows share those options. Number columns format values without clipping them to a drawing scale.




All outside labels in a column are measured before rendering. The label slot is the greater of label width and the widest actual label, and aligns values right. Wider labels do not change the graphic scale. Equal fixed precision naturally aligns decimal points; mixed units or scientific notation only guarantee right alignment. Defaults are graphic width=32mm, text width=22mm and label width=18mm.

Declare every column before any group or data row. Every row must contain exactly one cell per column. Do not omit a missing field. Validation identifies the row and column id. Text wraps in text columns. By default the table uses its natural width; an explicit total width enables allocation as described below.

15 Comparison, composition and trend columns

Available types are text, number, bar, bullet, interval, compare, dumbbell, stack and spark. Compare and dumbbell cells use reference/current order; default labels display current/reference, while delta displays current minus reference. NA means both missing; 40/NA and NA/60 represent one missing endpoint.





Two views of the same comparison

Method	Values	Change
A	 68 / 40	 Δ 28
B	 60 / 75	 Δ -15
C	 - / 50	 -

```
\begin{gradtable}[text width=22mm,graphic width=32mm,
  label width=12mm,header align=c,column sep=6pt,row stretch=1.8]
\gradcolumn{name}{Method}
\gradcolumn[type=compare,options={max=100,precision=0}]{bars}{Values}
\gradcolumn[type=dumbbell,options={max=100,precision=0,
  compare label=delta,marker shape=diamond}]{change}{Change}
\gradrow{A,40/68,40/68}
\gradrow{B,75/60,75/60}
\gradrow{C,50/NA,50/NA}
\end{gradtable}
```

Stack and spark cells contain lists, so enclose each cell's list in braces. Whole-cell NA is supported. Missing individual stack contributions are not zero and must not be included in a total. A spark's missing last position retains a missing label rather than borrowing an earlier observation.

Composition and a common-scale trend

Project	Composition	Five periods
A	 80	 80
B	 65	 -
C	 -	 -

```
\begin{gradtable}[text width=22mm,graphic width=32mm,
  label width=12mm,header align=c,column sep=6pt,row stretch=1.8]
\gradcolumn{name}{Project}
\gradcolumn[type=stack,options={max=100,precision=0,
  stack colors={gradbarsBlue,gradbarsTeal,gold}}]{mix}{Composition}
\gradcolumn[type=spark,options={spark range=fixed,
  min=0,max=100,precision=0}]{trend}{Five periods}
\gradrow{A,{20,35,25},{35,48,NA,65,80}}
\gradrow{B,{30,20,15},{80,70,65,NA,NA}}
\gradrow{C,NA,NA}
\end{gradtable}
```

Keep stack categories in a consistent order or register named categories. Use a negative min for negative contributions. Use fixed spark ranges to compare magnitudes; auto scales each cell separately and only supports shape comparison.

16 Alignment, rules and spacing

Headers follow the corresponding column unless overridden. With `align=auto`, text and graphic columns align left and number columns align right. Column settings override table settings. Use `header align=c` for centered headings.

Horizontal alignment and vertically centered text



Left	Center	Right	Count
Method A	Method A	Method A	120
A longer name wraps within the text column	Short	Short	5

```
\begin{gradtable}[rules=grid,header align=c,valign=c,
  text width=30mm,column sep=5pt,row padding=3pt,
  header color=gradbarsBlue!8,rule color=gradbarsBlue!60!black]
\gradcolumn[align=l]{left}{Left}
\gradcolumn[align=c]{center}{Center}
\gradcolumn[align=r]{right}{Right}
\gradcolumn[type=number,align=c,width=20mm,
  options={precision=0}]{number}{Count}
\gradrow{Method A,Method A,Method A,120}
\gradrow{A longer name wraps within the text column,Short,Short,5}
\end{gradtable}
```

`valign=t|c|b` affects text columns only, using array's p/m/b paragraph boxes. Use `align=l`, `valign=c` for left-aligned, vertically centered text.

In natural-width mode, column width fixes text wrapping but is a minimum for number and graphic cells. Graphic width controls the plot, label width controls the numeric slot, and column width controls the cell. Graphic alignment moves the complete plot-plus-label cell; numeric labels remain right-aligned internally.

A centered score heading and graphic cell

Method	Score
A	 82
B	 —

```
\begin{gradtable}[rules=rows,header align=c,
  graphic width=28mm,label width=12mm,column sep=8pt,row stretch=1.4]
\gradcolumn[width=24mm,header align=l]{method}{Method}
\gradcolumn[type=bar,align=c,width=75mm,
  options={max=100,precision=0}]{score}{Score}
\gradrow{A,82}
\gradrow{B,NA}
\end{gradtable}
```



Option	Meaning
rules=booktabs	Default: top, header separator and bottom rules.
rules=rows	Also separates data rows horizontally.
rules=grid	Full horizontal/vertical grid and outer border.
rules=none	No table rules.
column sep	Horizontal padding per side of a column; default 6pt.
row stretch	Positive base row-height multiplier: paper/mono 1.2, report 1.5.
row padding	Extra height, default 0pt; does not scale graphics.
header color	Report defaults to gradbarsTrack; empty clears the fill.
rule color	Default black; local to this table.

Spacing and widths must be nonnegative. Cell alignment does not position the whole table: use an enclosing group with centering, raggedright or raggedleft.

17 Allocating a total table width

`width=\linewidth` allocates the available width without scaling text. Labels, fixed columns, padding and rules are reserved first; text columns and graphic areas share the remaining space. Values keep their original scale.

A fixed number column and flexible text and graphics

Setup		Evaluation	
Method name		Score	Samples
An improved method with a longer name		92.8	12 500
Baseline		84.6	320
Pending		–	80

```
\begin{gradtable}[width=\linewidth,header align=c,
  label width=12mm,column sep=6pt,row padding=2pt,
  min text width=18mm,min graphic width=15mm]
\gradcolumn[weight=1]{method}{Method name}
\gradcolumn[type=bar,weight=2,mark=both,
  options={max=100,precision=1}]{score}{Score}
\gradcolumn[type=number,width=18mm,
  options={precision=0}]{count}{Samples}
\gradheader{\gradspan{1}{Setup}\gradspan{2}{Evaluation}}
\gradrow{An improved method with a longer name,92.8,12500}
\gradrow{Baseline,84.6,320}
\gradrow{Pending,NA,80}
\end{gradtable}
```

Default `width=0pt` retains natural sizing. A positive column weight (default 1) shares space left after minimum widths, so `weight=2` does not mean exactly twice the final column width. Min text width and min graphic width default to 12mm; the latter excludes the label slot. Number columns do not stretch.

In total-width mode a column width fixes a text or graphic cell; number columns still grow to fit their labels. The allocated plot width overrides graphic width and any width in drawing options. Every row shares that allocated width. Headers and group titles may wrap; unbreakable words still need break points. An insufficient budget causes an error: increase the width, reduce padding or minimum widths, shorten units, or use fewer columns. Keep at least one flexible column when fixed columns leave unused space.

18 Multilevel headers and spanning titles

`\gradheader {...}` adds a header layer. Within it, `\gradspan {count}{title}` spans consecutive columns. Declare all columns first, then header layers, then groups and rows. Each layer must span exactly the total number of columns. Column titles form the bottom header layer.

Three header levels




Model evaluation			
Setup	Prediction quality		Latency
Method	Accuracy	F1	ms
A	91.4	89.7	24
B	93.2	91.5	31

```
\begin{gradtable}[rules=grid,header align=c,
  header color=gradbarsBlue!8,text width=28mm,
  column sep=8pt,row padding=3pt]
\gradcolumn[method]{Method}
\gradcolumn[type=number,width=24mm,
  options={precision=1}]{accuracy}{Accuracy}
\gradcolumn[type=number,width=24mm,
  options={precision=1}]{fscore}{F1}
\gradcolumn[type=number,width=24mm,
  options={precision=0}]{latency}{ms}
\gradheader{\gradspan{4}{Model evaluation}}
\gradheader{\gradspan{1}{Setup}\gradspan{2}{Prediction quality}
  \gradspan{1}{Latency}}
\gradrow{A,91.4,89.7,24}
\gradrow{B,93.2,91.5,31}
\end{gradtable}
```

Spanning titles are centered, follow header color and use the chosen rules. An empty title still occupies its declared span. Layers merge horizontally, not vertically. Schemas may include headers, but no columns may follow a header.

19 Grouped rows and best-value marking

`\gradgroup {title}` inserts a full-width group heading. Each group needs at least one data row. Groups do not alter scales or participate in ranking. Group color defaults to `gradbarsTrack`; an empty value removes it. Group sep defaults to 4pt. All rule styles support groups.

Ties, second-best values and lower-is-better metrics			
Method		Score	Time / s
Baselines			
A		82.4	12.8
B		90.2	<u>10.5</u>
Improved methods			
C		90.2	9.6
D		<u>86.7</u>	9.6
E		—	—

```

\begin{gradtable}[header align=c,text width=30mm,
  graphic width=38mm,label width=12mm,group sep=4pt]
\gradcolumn[method]{Method}
\gradcolumn[type=bar,mark=both,
  options={max=100,precision=1}]{score}{Score}
\gradcolumn[type=number,mark=both,width=24mm,
  options={better=lower,precision=1}]{time}{Time / s}
\gradgroup{Baselines}
\gradrow{A,82.4,12.8}
\gradrow{B,90.2,10.5}
\gradgroup{Improved methods}
\gradrow{C,90.2,9.6}
\gradrow{D,86.7,9.6}
\gradrow{E,NA,NA}
\end{gradtable}

```

Best values are bold and second-best values are underlined. Mark can be none (default), best or both, for number, bar and bullet columns. Ranking covers the whole table, across groups and pages. Use `better=higher` or `better=lower` inside column options; target-distance and interval-quality ranking are not supported.

Ranking uses raw values before rounding. Equal numbers (including 2 and 2.0) tie; second best is the next distinct value. NA is excluded and zero participates. An all-missing column has no marks; an all-equal column has no second best. Increase precision if rounding hides a distinction. For stacks or trends, add a separate number column defining the metric to rank. Explain the marking in a caption.

20 Report and monochrome table presets

Table presets are paper (thin solid bars and compact booktabs rules), report (tinted headings and taller rows) and mono (gray and textures). Column drawing options override the preset. Table presets and individual-graphic presets are separate interfaces.

Bullet and interval columns				
Project	Progress		Interval	
A		78		[65, 90]
B		92		[80, 98]
C		—		—

```

\begin{gradtable}[preset=report,graphic width=32mm,
  text width=19mm,label width=19mm]
  \gradcolumn{name}{Project}
  \gradcolumn[type=bullet,options={max=100,precision=0,
    bullet bands={{60/black!8},{85/black!16},{100/black!25}},
    target=85}]{actual}{Progress}
  \gradcolumn[type=interval,options={max=100,precision=0,
    color=gradbarsTeal}]{estimate}{Interval}
  \gradrow{A,78,65/78/90}
  \gradrow{B,92,80/92/98}
  \gradrow{C,NA,NA}
\end{gradtable}

```

Interval cells use lower/point/upper. NA in the point position omits only the point, while whole-cell NA omits the interval. The supplied point must lie inside the original endpoints. Bullet columns require explicit background bands.

Signed observations in monochrome				
Group	Change		Interval	
A		-12		[-25, 5]
B		28		[15, 45]

```

\begin{gradtable}[preset=mono,graphic width=32mm,
  text width=19mm,label width=19mm]
  \gradcolumn{name}{Group}
  \gradcolumn[type=bar,options={min=-40,max=60,precision=0}]{change}{Change}
  \gradcolumn[type=interval,options={min=-40,max=60,
    precision=0,marker shape=diamond}]{range}{Interval}
  \gradrow{A,-12,-25/-12/5}
  \gradrow{B,28,15/28/45}
\end{gradtable}

```

Default tables are indivisible and can be placed in table, table* or minipage. They do not infer ranges, calculate totals or load files automatically.



21 Reusable table styles and schemas


`\gradtablestyle {name}{keys}` saves table appearance.

`\gradtableschema {name}{body}` saves column and header declarations.

Use `style=name` and `\graduseschema {name}`. Definitions may be placed in the preamble. Redefinition replaces an earlier definition and follows TeX grouping.

Shared structure, different rule styles

Method	Score
Validation	
A	 <u>81.5</u>
B	 88.2

Method	Score
Test	
A	 <u>79.6</u>
B	 85.3

```
\gradtablestyle{benchmark}{rules=booktabs,header align=c,
  text width=30mm,graphic width=40mm,label width=12mm,
  row stretch=1.3,group color=gradbarsBlue!8}
\gradtableschema{benchmark}{
  \gradcolumn{method}{Method}
  \gradcolumn[type=bar,mark=both,
    options={max=100,precision=1}]{score}{Score}
}
\begin{gradtable}[style=benchmark]
  \graduseschema{benchmark}
  \gradgroup{Validation}
  \gradrow{A,81.5}
  \gradrow{B,88.2}
\end{gradtable}

\begin{gradtable}[style=benchmark,rules=grid]
  \graduseschema{benchmark}
  \gradgroup{Test}
  \gradrow{A,79.6}
  \gradrow{B,85.3}
\end{gradtable}
```

Options after style override it. Styles may reference other styles and schemas may compose schemas; cycles cause errors. Ids must remain unique. Apply schemas before any data or group. Each table measures and ranks its own data separately.

22 Multipage tables and repeated headers

`long=true` uses `longtable` to break between data rows. Every page repeats the full header, including spanning layers. Widths and ranking are computed for the entire table. A group heading stays with its first row; the remaining group may continue, but its name is not repeated automatically.

Place long tables directly in single-column body text, outside floats, minipages and nonbreakable example boxes. They cannot run in two-column mode. A single row cannot split. Use `caption` for a numbered title, label for referencing (requires `caption`), and `continued text` for continuation notices (default: (continued)). An empty `continued text` suppresses the notice. Compile twice to settle references.





The following table is typeset directly in this manual and can cross a page boundary. Its exact source is printed afterwards. Best values are bold and the next distinct values are underlined across all records.

Table 1: Grouped benchmark

Setup		Shared evaluation set			
Method		Score	Time / s		Interval
Experiment group A					
Method 01		70.0	8.0		[66, 74]
Method 02		77.2	11.1		[73, 81]
Method 03		84.4	14.2		[80, 88]
Method 04		91.0	17.0		[87, 95]
Method 05		70.2	20.1		[66, 74]
Method 06		77.4	23.2		[73, 81]
Method 07		84.0	9.0		[80, 88]
Method 08		<u>91.2</u>	12.1		[87, 95]
Experiment group B					
Method 09		70.4	15.2		[66, 74]
Method 10		77.0	18.0		[73, 81]
Method 11		84.2	21.1		[80, 88]
Method 12		91.4	24.2		[87, 95]
Method 13		70.0	10.0		[66, 74]
Method 14		77.2	13.1		[73, 81]
Method 15		84.4	16.2		[80, 88]
Method 16		91.0	19.0		[87, 95]
Experiment group C					
Method 17		70.2	22.1		[66, 74]
Method 18		77.4	<u>8.2</u>		[73, 81]
Method 19		84.0	11.0		[80, 88]

(continued)

Table 1: Grouped benchmark (continued)

Setup		Shared evaluation set			
Method		Score	Time / s	Interval	
Method 20		91.2	14.1		[87, 95]
Method 21		70.4	17.2		[66, 74]
Method 22		77.0	20.0		[73, 81]
Method 23		84.2	23.1		[80, 88]
Method 24		91.4	9.2		[87, 95]

Source of the multipage example

```

\begin{gradtable}[long=true,width=\linewidth,
caption={Grouped benchmark},label={tab:english-long},
continued text={(continued)},header align=c,
label width=12mm,column sep=6pt,row stretch=1.4,row padding=3pt]
\gradcolumn[weight=1]{method}{Method}
\gradcolumn[type=bar,weight=2,mark=both,
options={max=100,precision=1}]{score}{Score}
\gradcolumn[type=number,width=18mm,mark=both,
options={better=lower,precision=1}]{time}{Time / s}
\gradcolumn[type=interval,weight=1.5,
options={max=100,precision=0}]{range}{Interval}
\gradheader{\gradspan{1}{Setup}\gradspan{3}{Shared evaluation set}}
\gradgroup{Experiment group A}
\gradrow{Method 01,70.0,8.0,66/70/74}
\gradrow{Method 02,77.2,11.1,73/77/81}
\gradrow{Method 03,84.4,14.2,80/84/88}
\gradrow{Method 04,91.0,17.0,87/91/95}
\gradrow{Method 05,70.2,20.1,66/70/74}
\gradrow{Method 06,77.4,23.2,73/77/81}
\gradrow{Method 07,84.0,9.0,80/84/88}
\gradrow{Method 08,91.2,12.1,87/91/95}
\gradgroup{Experiment group B}
\gradrow{Method 09,70.4,15.2,66/70/74}
\gradrow{Method 10,77.0,18.0,73/77/81}
\gradrow{Method 11,84.2,21.1,80/84/88}
\gradrow{Method 12,91.4,24.2,87/91/95}
\gradrow{Method 13,70.0,10.0,66/70/74}
\gradrow{Method 14,77.2,13.1,73/77/81}
\gradrow{Method 15,84.4,16.2,80/84/88}
\gradrow{Method 16,91.0,19.0,87/91/95}
\gradgroup{Experiment group C}
\gradrow{Method 17,70.2,22.1,66/70/74}
\gradrow{Method 18,77.4,8.2,73/77/81}
\gradrow{Method 19,84.0,11.0,80/84/88}
\gradrow{Method 20,91.2,14.1,87/91/95}
\gradrow{Method 21,70.4,17.2,66/70/74}
\gradrow{Method 22,77.0,20.0,73/77/81}
\gradrow{Method 23,84.2,23.1,80/84/88}
\gradrow{Method 24,91.4,9.2,87/91/95}
\end{gradtable}

```




23 CSV input and numeric table columns

CSV files are read as characters, not executed as TeX. UTF-8 BOM, quoted commas, doubled quotes and custom missing tokens are supported. Fields must fit on a single line and the delimiter must be a comma. Headers must be unique and nonempty. The following source assumes a CSV file with Name and Score columns:

```
\gradbarsloadcsv{results}{results.csv}
\gradbarscsvtable{results}{Name}{Score}
\gradbarscsvstyle{shared}{results}{Score}
\gradbarcsv[style=shared]{results}{1}{Score}
\gradbarscsvcell{results}{1}{Name}
```

Rows are one-based. CSV range styles include zero and use a positive upper limit even for all-zero, all-negative or all-missing columns. Table generation does not automatically paginate. Keep your own longtable structure and use individual CSV cells when pagination matters. A dataset definition follows grouping.

Only numbers in a common-style column

Item	Value
A	 72
B	 -20
C	 0
D	 -

```
\gradbarcolumn{G}{width=35mm,min=-50,max=100,precision=0}
\begin{tabular}{@{}lG@{}}
\toprule
Item & \multicolumn{1}{l}{Value}\\midrule
A & 72\\ B & -20\\ C & 0\\ D & NA\\
\bottomrule
\end{tabular}
```








Numeric columns use `collcell`. Use `multicolumn` for text headings. They do not calculate a range and are not `siunitx` S columns. Avoid placing complete drawing commands in a numeric collection cell. `tabular` and `longtable` workflows are documented; a `tabularray`-specific collection interface is not implemented.

Part V

Complete layout examples

24 A complete benchmark table

Use shared scales within each column, explicit units and a stated ranking rule. This example combines a score, latency, before/after change and recent history. Best score and lowest latency are bold; missing observations remain missing.

Model comparison with a grouped header						
Setup	Performance		Comparison			
Method	Score	ms	Change	Five periods		
A	 82.4	14.8	 Δ 14.4			82.4
B	 91.6	18.2	 Δ 15.6			91.6
C	 87.3	11.5	 Δ 7.3			87.3
D	 78.9	9.6	 Δ -4.1			78.9

```

\begin{gradtable}[width=\linewidth,header align=c,
  label width=8mm,column sep=3pt,min text width=12mm,
  min graphic width=15mm,row stretch=1.7]
\gradcolumn[method]{Method}
\gradcolumn[type=bar,mark=best,weight=1.2,
  options={max=100,precision=1}]{score}{Score}
\gradcolumn[type=number,width=15mm,mark=best,
  options={better=lower,precision=1}]{time}{ms}
\gradcolumn[type=dumbbell,options={max=100,precision=1,
  compare label=delta}]{change}{Change}
\gradcolumn[type=spark,options={spark range=fixed,
  min=0,max=100,precision=1}]{trend}{Five periods}
\gradheader{\gradspan{1}{Setup}\gradspan{2}{Performance}
  \gradspan{2}{Comparison}}
\gradrow{A,82.4,14.8,68/82.4,{68,74,70,78,82.4}}
\gradrow{B,91.6,18.2,76/91.6,{76,81,78,87,91.6}}
\gradrow{C,87.3,11.5,80/87.3,{80,72,83,78,87.3}}
\gradrow{D,78.9,9.6,83/78.9,{83,72,79,74,78.9}}
\end{gradtable}

```

The dumbbell connects reference and current values, and its label shows their difference. All trends share 0–100 vertically and equal observation spacing. These numbers are demonstrations, not experimental findings.

25 Two-column papers, print and slides

25.1 A narrow paper column

Use `width=\linewidth` in the local column or minipage; reduce horizontal padding and the reserved label slot before reducing font size. A normal `gradtable` can be inside a table float; a wide `table*` can span both paper columns.

A table fitted to an 80mm column

Method	Score
Baseline	82.4
Proposed	91.6

```

\begin{minipage}{80mm}
\begin{gradtable}[width=\linewidth,preset=paper,header align=c,
  label width=8mm,column sep=3pt,min text width=12mm,
  min graphic width=15mm]
\gradcolumn[method]{Method}
\gradcolumn[type=bar,mark=best,
  options={max=100,precision=1}]{score}{Score}
\gradrow{Baseline,82.4}
\gradrow{Proposed,91.6}
\end{gradtable}
\end{minipage}

```

Use the multipage example in the preceding part for long results lists. Long mode must be outside floats and two-column text, rather than shrinking an entire long table.

25.2 Monochrome printing

Use `preset=mono` for tables, `print` for individual graphics, and registered textures for categories. Keep numeric labels and category names. Explain bold and underline marking. Print a sample at its final scale: very fine textures may disappear.

Category shares with a matching print legend



```

\gradstack[print,width=75mm,height=17pt,
  stack names={Train,Validation,Test},
  stack patterns={diagonal,dots,crosshatch},
  legend=true,segment labels=percent,precision=0]{60,25,15}

```

25.3 Beamer slides

Use fewer rows, larger text and stronger contrast. Individual graphics support `preset=presentation`. The following is a complete source for a separate slide:

```

\documentclass{beamer}
\usepackage{gradbars}
\begin{document}
\begin{frame}{Progress toward the target}
\gradbarssetup[preset=presentation,width=.6\linewidth,
  max=100,precision=0,target=90]
\gradbar{82}
\end{frame}
\end{document}

```

Ordinary tables can be placed in a frame. Long mode is not a mechanism for splitting a visual table into slides; choose the rows for each frame explicitly.

Part VI

Questions and interface reference

26 Frequently asked questions

Why does a long label overflow? Outside labels need room in addition to the plot. Increase label width, shorten a unit, or use text to give a shorter label. Gradtable measures the widest label per column; increase the total width or reduce padding if its reserved labels leave insufficient graphic space. Unbreakable text still needs explicit break opportunities.

How do I adjust row height? In gradtable use row stretch and row padding; for a standalone graphic use row padding. In a standard tabular, arraystretch also changes row height. References and change annotations may need additional headroom.

Why do equal values have different lengths? Use the same min, max and graphic width within a comparison column. Spark auto ranges rescale each series; use fixed for magnitude comparisons. Formatting does not change geometry.

Is NA the same as zero? No. Zero is an observed value and participates in ranking. NA is missing. A spark keeps its missing position and breaks the line. A missing stack contribution cannot safely be treated as zero.

Why did a table not break across pages? Normal gradtable is indivisible. Set long=true in single-column body text, outside a float or minipage. Individual rows cannot split. A group heading stays with its first row, but its name is not repeated on subsequent pages.

Why are two identical-looking labels ranked differently? Ranking uses raw values, not rounded labels. Increase precision. Ties mark all equal raw values; second best means the next distinct value across the whole table.

27 Compact option reference

Option	Default / meaning
width, height	24mm, 1.5ex; sparklines default to 4ex high.
min, max	0, 100; common scale.
precision, number format	1; fixed, grouped or scientific.
unit, text	Empty; suffix or complete custom label.
label, label width	outside, 4.5em.
rounded, row padding	0pt, 0pt; nonnegative lengths.
marker size, stem width	2pt, .6pt; positive lengths.
outline, outline width	false, .4pt; positive width.
compare color, compare ratio	black!20, .45; ratio strictly between 0 and 1.
compare label	values, delta or percent.
stack totals	net or separate.
stack colors	gradbarsBlue, gradbarsTeal, gold; cyclic.
stack names, legend	Empty list; false.
segment labels	none, value, percent, name, name value, name percent.
better	higher, lower, target, interval.
quality target, quality range	Required for their respective modes; no default.
spark range, spark points	auto; extrema.
overflow	clip or error.

28 Table and annotation reference

Interface / option	Purpose
<code>\gradcolumn [...]{id}{title}</code>	Declare a unique column before rows.
<code>\gradrow {cells}</code>	Comma-separated cells in column order.
<code>\gradheader {spans}</code>	Add a full header layer before data.
<code>\gradspan {n}{title}</code>	Span n consecutive columns in that layer.
<code>\gradgroup {title}</code>	Full-width heading followed by data.
<code>\gradtablestyle {name}{keys}</code>	Reuse table options with <code>style=name</code> .
<code>\gradtableschema {name}{body}</code>	Reuse declarations with <code>graduseschema</code> .
<code>mark=none best both</code>	Raw-value ranking for number/bar/bullet.
<code>width, weight</code>	Total width and flexible-column allocation.
<code>long=true</code>	Paginate, repeating complete headers.
<code>caption, label</code>	Long-table title and reference; label needs caption.
<code>overflow mark</code>	none, arrow or slash at clipped boundaries.
<code>marker shape</code>	circle, square, diamond or triangle.
<code>compare annotation</code>	none, arrow or bracket.
<code>compare label</code>	values, delta or percent.
<code>references</code>	value/color/style/name records.
<code>bullet bands</code>	Increasing upper-bound/color records ending at max.

Neither table buffering nor the drawing commands infer scientific meaning from your data. Set scales, units, uncertainty interpretation, category identity and quality direction explicitly. Horizontal header spans are supported; vertical cell merging and automatically computed summary rows are not.

28.1 Tagged PDF and alternative text

On a LaTeX distribution supporting PDF tagging, enable it with `DocumentMetadata` before `documentclass`. Independent graphics generate English alternative text from raw data: values, units, scales, error distances, reference lines, comparison endpoints and differences, stack segments and subtotals, and every spark observation including missing positions. Intervals describe supplied endpoints and estimates; confidence levels are not inferred. Legends describe their category names.

```
\DocumentMetadata{tagging=on,pdfstandard=ua-2,lang=en-US}
\documentclass{article}
\usepackage{gradbars}
\begin{document}
\gradbar{72}
\gradbar[alt={Accuracy: 72 percent, out of 100 percent.}]{72}
\graddumbbell[compare label=delta]{58}{76}
\end{document}
```

Use `alt` to supply context or another language. Empty `alt` restores automatic text; the existing `/tikz/alt` syntax remains supported. Accessibility defaults to `auto`. Use `accessibility=artifact` only when surrounding text fully conveys the graphic's information. `accessibility=off` leaves tagging to the surrounding code. These options do not change visible output when tagging is disabled.

Descriptions use raw values before rounding. The `text` option only changes the visual label; use `alt` to change its semantic description. Table measurement does not produce tags, so each rendered graphic cell has one description. Inside an existing TikZ picture, describe the complete graphic using the outer picture's `alt`. Automatic descriptions do not establish document-wide PDF/UA conformance: validate table headers, reading order, fonts and other content separately.

Contact and maintenance

Author and maintainer: SuFan (Tape5try). Contact 3546236610@qq.com or the [issue tracker](#). Include a minimal source, engine and log. Distributed under the MIT license.