



CONTACT

Building Products Information
contact.fr@nexans.com

Nexans PV H1Z2Z2-K SUN PLUS cables (1.5kV DC) are designed to comply with the international standards of the solar plants.

They are dedicated to the photovoltaic system direct current (D.C.) side with a nominal D.C. voltage of 1.5 kV and a maximum D.C. voltage of 1.8 kV.

These cables are suitable for permanent outdoor long-term use, under variable and harsh climate conditions.

They are designed and tested to operate at a normal maximum conductor temperature of 90°C and for 20,000 hours up to 120°C. Therefore, the expected period use is 30 to 40 years under normal usage conditions (lifetime acc. to Arrhenius-Diagram).

STANDARDS

Product EN 50618; IEC 62930

Test EN 60332-1-2; EN 61034-2

APPLICATION

Nexans PV H1Z2Z2-K SUN PLUS Cable (1.5kV DC)

CHARACTERISTICS

Construction characteristics

Conductor material	Tin Coated Copper Class 5 acc. To EN 60228
Conductor flexibility	Flexible class 5
Insulation	Cross-linked compound
Outer sheath	Cross-linked compound
Conductor shape	Circular

Dimensional characteristics

Number of cores	1
-----------------	---

Electrical characteristics

Rated Voltage U ₀ /U (U _m)	1.0/1.0 (1.2) kV AC 1.5/1.5 (1.8) kV DC
---	---

Mechanical characteristics

Bending	100 000 cycles in reverse bending
Frequent torsion	100 000 cycles
Tensile strength	50 N

Usage characteristics

Operating temperature, range	-40 ... 90 °C
Max. conductor temperature in service	120 °C
Packaging	Drum



Conductor flexibility
Flexible class 5



Rated Voltage U₀/U (U_m)
1.0/1.0 (1.2) kV AC
1.5/1.5 (1.8) kV DC



Operating temp.
-40 ... 90 °C



Max. conductor temp. in service
120 °C



Weather resistance
Excellent



U.V resistance
EN 50289-4-17 method A, for 720h. Nexans prestige test 4000h



Water proof
Passed 100 days 50°C water immersion test of EN 50525-2-21 annex D and E



Gases corrosivity
IEC 60754-2

Usage characteristics

Short-circuit max. conductor temperature	°C
Ozone resistance	EN 50396:2005
Weather resistance	Excellent
Outdoor Use	Condition AN 3 (high solar radiation), permanent according to EN 50565-1:2014
RoHS conform	RoHS 2011/65/EU
Thermal endurance	IEC 60216-1-2
U.V resistance	EN 50289-4-17 method A, for 720h. Nexans prestige test 4000h
Water proof	Passed 100 days 50°C water immersion test of EN 50525-2-21 annex D and E

Fire safety characteristics

Gases corrosivity	IEC 60754-2
Smoke density	IEC 61034-2
Flame retardant	EN 60332-1-2
Halogen free	IEC 60754-1; IEC 60754-2



Conductor flexibility
Flexible class 5



Rated Voltage U₀/U_m
1.0/1.0 (1.2) kV AC
1.5/1.5 (1.8) kV DC



Operating temp.
-40 ... 90 °C



Max. conductor
temp. in service
120 °C



Weather resistance
Excellent



U.V resistance
**EN 50289-4-17
method A, for
720h. Nexans
prestige test
4000h**



Water proof
**Passed 100 days
50°C water
immersion test of
EN 50525-2-21
annex D and E**



Gases corrosivity
IEC 60754-2

PV

