

Comparative Analysis: Fidelity-Based & Measurement-Free Quantum Classification

This report provides a formal technical review of quantum classification methods found in the project's literature repository ([Documents/](#)). It emphasizes **Measurement-Free (MF)** architectures and **Low-Shot** similarity algorithms.

1. Coherent Feedback Learning (The Absolute MF Baseline)

Reference: [Alvarez-Rodriguez et al. (2017)](file:///home/tarakesh/Work/Repo/measurement-free-quantum-classifier/Documents/refference_papers/Scholar%20review/quantum%20fidelity/s41598-017-13378-0.pdf)

- **Mechanism:** Encodes the classification logic into a time-delayed Schrödinger equation.
- **Shot Efficiency: Zero mid-circuit shots.** The system evolves unitarily toward the correct label.
- **Equation:**
$$\frac{d}{dt} |\psi(t)\rangle = -i \left[\kappa_1 H_{\text{int}} + \kappa_2 H_{\text{feedback}} \right] |\psi(t)\rangle$$

2. Coherent Amplitude/Phase Estimation (The Bit-by-Bit Approach)

Reference: [Patrick Rall (2021)](file:///home/tarakesh/Work/Repo/measurement-free-quantum-classifier/Documents/refference_papers/Scholar%20review/minimm%20measurement%20quant%20algo/q-2021-10-19-566.pdf)

- **Mechanism:** Uses **Singular Value Transformation (SVT)** to estimate similarity one bit at a time.
- **Shot Efficiency:** Achieves **Heisenberg-limited** accuracy ($\Theta(1/\epsilon)$ queries).
- **Advantage:** Does not require the Quantum Fourier Transform (QFT), making it much more robust for NISQ devices.
- **Expression:** $|0\rangle \langle \psi| \rightarrow |\text{overlap}\rangle \langle \psi|$ This "writes" the fidelity into a register without collapsing the original superposition.

3. Classical Shadows (Shadow Classification)

Reference: [Huang et al. (2020) & Yunfei Wang (2024)](file:///home/tarakesh/Work/Repo/measurement-free-quantum-classifier/Documents/refference_papers/Scholar%20review/NISQ%20hardware/2401.11351v2.pdf)

- **Mechanism:** Performs randomized Pauli measurements to create a "shadow" of the quantum state.
- **Shot Efficiency:** Allows tracking **logarithmic** shots relative to the number of samples. Once a shadow is created, you can compute INFINITE fidelities classically.
- **Equation:**
$$\hat{\rho} = \mathbb{E} [\mathcal{M}^{-1} (U^\dagger |b\rangle \langle b| U)]$$
 Where $\hat{\rho}$ is the reconstructed "shadow" that contains the fidelity information.

4. Destructive SWAP-Test (Ancilla-Free)

Reference: [Garcia-Escartin (2013) & Blank (2020)](file:///home/tarakesh/Work/Repo/measurement-free-quantum-classifier/Documents/refference_papers/Scholar%20review/quantum%20fidelity/s41534-020-0272-6.pdf)

- **Mechanism:** Removes the ancilla qubit entirely. Uses CNOTs followed by single-qubit measurements on both registers.
- **Shot Efficiency:** Far more efficient for hardware with limited connectivity.
- **Equation:** Considers the parity of the measurement outcomes b_1, b_2 : $F = 1 - 2 \cdot P(\text{parity yields odd})$

5. Comparative Shot-Efficiency Table

Method	Shots Required	Measurement-Free?	Best Use Case
Standard SWAP	$O(1/\epsilon^2)$	No	General Purpose
Coherent SVT	$\Theta(1/\epsilon)$	Yes	High Precision / Coherent Chains
Classical Shadows	$\log(M)$	Partial	Multi-class (Benign, Malignant, Cyst)
Destructive SWAP	Medium	No	Low-Qubit Count Chips
VQFE	High (Training)	No	Parameter Tuning

Project Conclusion

While the "Big 3" get most of the attention in textbooks, recent 2021-2024 research (like **Patrick Rall's SVT**) proves that we can achieve **classification without measurement collapse**. In our project, we use the **Interference Average (Phase B)** as a bridge: it uses the parallel nature of the SWAP-test to reduce the "effective" shots compared to testing prototypes one-by-one.