

---

# ISDO Training Regimes — Implementation Plan & Tracking Summary

---

## Scope

These regimes **build on Direction 1 (ISDO)**, which is **closed**. They **do not modify**:

- the ISDO observable
- the ISDO circuit (B')

They only define **how class states are constructed and updated**.

---

## Shared Foundations (Applies to All Regimes)

### Fixed Components (Never Trained)

- **Quantum circuit:** ISDO-B' (transition-based interference)
- **Measurement:** ancilla  $|\angle Z\rangle$
- **Decision rule:**  $\hat{y}(x) = \operatorname{sign}\big(\operatorname{Re}\langle\chi|\mid\psi(x)\rangle\big)$

### Learned Objects

- **Quantum class state(s)**  $|\chi\rangle$
- These are the **only trainable parameters**

### Data Pipeline

```
image
-> CNN
-> embedding ( $\mathbb{R}^{32}$ )
-> L2 normalize
->  $|\psi\rangle$ 
-> ISDO( $|\psi\rangle$ ,  $|\chi\rangle$ )
```

---

## Regime 1 — Static Prototype Aggregation (Baseline)

---

### Purpose

- Non-iterative baseline
  - Fast, stable, interpretable
  - Already implemented and validated
-

Definition

Given labeled embeddings:

- Class +1:  $\{|\phi_k^+\rangle\}$
- Class -1:  $\{|\phi_k^-\rangle\}$

Construct:

$$\boxed{|\chi\rangle = \operatorname{normalize}\left(\sum_k |\phi_k^+\rangle - \sum_k |\phi_k^-\rangle\right)}$$

---

Implementation Steps

1. Collect embeddings per class
2. Optionally cluster (KMeans) -> prototypes
3. Sum positive prototypes
4. Subtract negative prototypes
5. Normalize -> class state  $|\chi\rangle$

Inference

For each test sample:  $s = \operatorname{Re}\langle \chi | \psi \rangle \quad \rightarrow \quad \hat{y} = \operatorname{sign}(s)$

---

Properties

Aspect	Status
Training	One-shot
Updates	None
Stability	Very high
Circuit depth	Fixed
QML validity	Yes
Novelty	Moderate

---

When to Use

- Baseline comparisons
  - Low-data regimes
  - Cold-start initialization for Regime 2 or 3
-

# Regime 2 — Online / Incremental ISDO Training (Recommended Core)

---

## Purpose

- Enable **learning over time**
- Adapt class state to data distribution
- Avoid gradients, shots, or parameterized circuits

This is the **quantum perceptron regime**.

---

## Initialization (Cold Start)

Option A — Zero state:  $|\chi_0\rangle = |0\rangle^{\otimes n}$

Option B — Bootstrap (recommended):  $\boxed{|\chi_0\rangle = \operatorname{normalize}\left(\sum_{i=1}^K y_i |\psi_i\rangle\right)}$

---

## Online Update Rule

For each training sample  $(|\psi\rangle, y)$ , with  $y \in \{+1, -1\}$ :

1. Measure:  $s = \operatorname{Re}\langle\chi_t|\psi\rangle$
2. If correctly classified:

```
y * s >= 0 -> no update
```

3. If misclassified:  $\boxed{|\chi_{t+1}\rangle = \operatorname{normalize}\left(|\chi_t\rangle + \eta y |\psi\rangle\right)}$
- 

## Implementation Notes

- Update is **classical vector arithmetic**
  - Renormalize after every update
  - Learning rate  $\eta$  can be:
    - constant
    - decaying
    - adaptive
- 

## Properties

Aspect	Status
--------	--------

---

Aspect	Status
Training	Online
Updates	Deterministic
Gradients	None
Circuit	Fixed
Shot cost	Minimal
Interpretability	High
QML validity	Strong

When to Use

- Continual learning
- Streaming data
- Non-stationary datasets
- As the **main learning regime**

# Regime 3 — Multi-State Quantum Memory (Advanced / Nonlinear)

Purpose

- Increase expressivity
- Approximate nonlinear decision boundaries
- Avoid deep circuits or kernels

This is **ensemble learning in Hilbert space**.

Model Structure

Maintain a set of class states:  $\mathcal{M} = \{ |\chi^{(1)}\rangle, \dots, |\chi^{(M)}\rangle \}$

Each state:

- initialized independently
- trained independently (Regime 2 rule)

Inference Rule

For input  $|\psi\rangle$ :  $s_j = \operatorname{Re}\langle \chi^{(j)} | \psi \rangle$

Decision:  $\hat{y} = \operatorname{sign}(\max_j s_j)$

## Training Variants

### Variant A — Winner-updates

- Only the best-matching ( $\chi_j$ ) is updated

### Variant B — All-updates

- All memory states updated with different learning rates

### Variant C — Pruned memory

- Periodically discard low-utility states

---

## Properties

Aspect	Status
Expressivity	High
Circuit depth	Fixed
Parameters	Quantum states
Interpretability	Medium
QML novelty	Very high
Complexity	Moderate

---


## When to Use

- Nonlinear class boundaries
- Multimodal class distributions
- Few-shot / continual learning

---

# Relationship Between Regimes

---



- Regime 1 feeds Regime 2
- Regime 2 generalizes to Regime 3
- No regime invalidates ISDO

# Key Constraints (Must Not Violate)

---

- ✗ Do NOT train gate parameters
- ✗ Do NOT introduce variational ansätze
- ✗ Do NOT change the ISDO observable
- ✔ Always renormalize class states
- ✔ Updates must be linear combinations of embeddings

---

# Final Status Summary

---

Regime	Purpose	Status
Regime 1	Static baseline	Implemented
Regime 2	Online learning	Ready to implement
Regime 3	Nonlinear extension	Defined

---

## Recommended Next Action

**Implement Regime 2 end-to-end** on your existing embeddings and log:

- accuracy vs time
- number of updates
- stability of  $\chi^2$

Once Regime 2 is stable, Regime 3 becomes trivial.