

EQUIP. TAG	-
EQUIP. NAME	2T RISER CRANE
CAPACITY	100 L/min @ 210 bar
CONFIGURATION	1 x 100%

EQUIP. TAG	-
EQUIP. NAME	AUX PORTS 1 & 2
CAPACITY	20 L/min
CONFIGURATION	1 x 100%

EQUIP. TAG	-
EQUIP. NAME	FWD / AFT 20T HANDLING WINCH
CAPACITY	240 L/min @ 260 bar
CONFIGURATION	1 x 100%

EQUIP. TAG	-
EQUIP. NAME	FWD & AFT SONAR WINCH
CAPACITY	20 L/min
CONFIGURATION	1 x 100%

TP	DESCRIPTION	CONNECTION TYPE / SIZE	MATERIAL
P	HYDRAULIC PRESSURE	ISO 16028, FF QD 1/2" MALE	SS316L
T	HYDRAULIC RETURN	ISO 16028, FF QD 3/4" MALE	SS316L
D	HYDRAULIC DRAIN	ISO 16028, FF QD 3/4" MALE	SS316L

EQUIP. TAG	-
EQUIP. NAME	650T RISER PULL-IN WINCH
CAPACITY	980 L/min @ 260 bar
CONFIGURATION	1 x 100%

EQUIP. TAG	-
EQUIP. NAME	RISER SPOOLING DEVICE
CAPACITY	40 L/min @ 260 bar
CONFIGURATION	1 x 100%

TP	DESCRIPTION	CONNECTION TYPE / SIZE	MATERIAL
P	HYDRAULIC PRESSURE	20S (E024" CONE END FITTING)	SS316L
T	HYDRAULIC RETURN	22L (E024" CONE END FITTING)	SS316L
D	HYDRAULIC LEAK	18L (E024" CONE END FITTING)	SS316L

TP	DESCRIPTION	CONNECTION TYPE / SIZE	MATERIAL
P	HYDRAULIC PRESSURE	16S (E024" CONE END FITTING)	SS316L
T	HYDRAULIC RETURN	22L (E024" CONE END FITTING)	SS316L
D	HYDRAULIC DRAIN	15L (E024" CONE END FITTING)	SS316L

TP	DESCRIPTION	CONNECTION TYPE / SIZE	MATERIAL
P	HYDRAULIC PRESSURE	38S (E024" CONE END FITTING)	SS316L
T	HYDRAULIC RETURN	42L (E024" CONE END FITTING)	SS316L
D	HYDRAULIC DRAIN	18L (E024" CONE END FITTING)	SS316L

TP	DESCRIPTION	CONNECTION TYPE / SIZE	MATERIAL
P-1	HYDRAULIC PRESSURE	G 1 1/4" BSP	SS316L
P-2	HYDRAULIC PRESSURE	G 3/4" BSP	SS316L
T-1	HYDRAULIC RETURN	G 1 1/2" BSP	SS316L
T-2	HYDRAULIC RETURN	G 3/4" BSP	SS316L

TP	DESCRIPTION	CONNECTION TYPE / SIZE	MATERIAL
P	HYDRAULIC PRESSURE	2" SAE 6000#	SS316L
T	HYDRAULIC RETURN	3" SAE 3000#	SS316L
D	HYDRAULIC DRAIN	1 1/2" SAE 3000#	SS316L

TP	DESCRIPTION	CONNECTION TYPE / SIZE	MATERIAL
P	HYDRAULIC PRESSURE	25S (E024" CONE END FITTING)	SS316L
R	HYDRAULIC RETURN	35L (E024" CONE END FITTING)	SS316L
D	HYDRAULIC DRAIN	18L (E024" CONE END FITTING)	SS316L
A	HYDRAULIC OIL TO/FROM CRANE	25S, 20S OR 16S (E024" CONE END FITTING)	SS316L
B	HYDRAULIC OIL TO/FROM CRANE	25S, 20S OR 16S (E024" CONE END FITTING)	SS316L

SERVICE	HYDRAULIC OIL
DESIGN PRESSURE(Barg)	300
OPERATING PRESSURE(Barg)	280
DESIGN TEMPERATURE(°C)	80
OPERATING TEMPERATURE(°C)	60

B	R00	ISSUED FOR REVIEW						11/05/26	ZYL	DWJ	DC	SJL			
A	-	INTER-DISCIPLINE CHECK						17/03/26	ZYL	DWJ	DC	SJL			
GOE REV	OTC REV	REASON FOR USE						DATE	DRAWN	ISSUED	CHECKED	APPROVED			
DISCIPLINE: MR		SYSTEM NO: 65		AREA / MODULE: FHM		IMO NO: 8706014		PROJECT NO: SC26-2A		SCALE: N.T.S.		SIZE: A3			
SUPPLIER:				PROJECT: Sakarya Gas Field Dev't Phase-2a											
 OceanSTAR Elite				 GLOBAL OFFSHORE ENGINEERING				TITLE:							
								P&ID - HYDRAULIC SYSTEM FWD GIPSEY & RISER WINCHES & CRANE - SHEET 2							
CLIENT:				OTC DOC. NO: SC26-2A-GOE-FHM-MR-PID-105141								GOE REV. B		SHEET	
 OTC OFFSHORE TECHNOLOGY CENTER				LEG DOC. NO: -								OTC REV. R00		2 of 2	
				REF DOC. NO: -											
This drawing contains proprietary information and may not be transferred, reproduced or used to construct any project other than it was issued for without the written consent of GOE or their Client.															

GENERAL NOTES:

- FOR P&ID LEGEND SHEET SEE DRAWING: SC26-2A-GOE-FHM-MR-PID-105133 TO 105139.
- FOR MARINE PIPING AND VALVE MATERIAL SPECIFICATION SEE DOCUMENT: SC26-2A-GOE-FHM-EP-SPC-105001 (4517-BWO-L-SA-00002).
- PRECISE ROUTING TO BE DETERMINED ACCORDING TO SITE SITUATION FOR THE SHORTEST POSSIBLE ROUTES WITH AS LESS AS POSSIBLE OF ELBOWS AND BENDS.

NOTES:

- HYDRAULIC EMERGENCY STOP VALVE SUPPLIED BY ST GIPSEY CRANE VENDOR.
- BLIND FLANGE WITH THREADED HOLE TO CONNECT WITH TUBING.

HOLDS:

- DELETED.
- CONNECTION TO BE CONFIRMED BY GOE/AW.

REFERENCE:

- FOR 650T RISER PULL-IN WINCH, REFER TO (1) GA_AW EQUIPMENT AFT AND FWD SYSTEM, (2) 2103-550-00_D RISER PULL IN WINCH HYDRAULIC.
- FOR 20T FWD/AFT HANDLING WINCH AND CONTROL VALVE, REFER TO 2103-550-00_D.
- FOR 2T RISER CRANE AND VALVE BOX, REFER TO 26849-01-MODEL HYDRAULIC DIAGRAM KN-25 DECK CRANE.
- FOR FWD/AFT SONAR WINCH, REFER TO 2153-001-01_HYDRAULIC DIAGRAM.
- FOR RISER SPOOLING DEVICE, REFER TO 2103-500-00_B - 650T-RISER_PULL_IN_WINCH-HYDRAULIC.

LEGENDS:

NEW PIPE

HYDRAULIC EMERGENCY STOP VALVE

