

Taraxa PBFT

Version 1.0

February 01, 2025

Contents

| | |
|--|----------|
| 1 Consensus Protocol | 1 |
| 1.1 Round (p, r) Constants | 1 |
| 1.2 Round (p, r) Voting Instructions | 1 |

1 Consensus Protocol

1.1 Round (p, r) Constants

When user u starts round (p, r) , they reset their timer_u to 0 and other constants as follows:

- If $r = 1$:
 - $\lambda_r \in (500, 1500)$
 - $\Lambda_r = 4000$
- Otherwise if $r \geq 2$:
 - $\lambda_r = 2000$
 - $\Lambda_r = 17000$

1.2 Round (p, r) Voting Instructions

The voting instructions are as follows:

Step 1: **Proposal** - When $\text{timer}_u = 0$:

- If $r = 1$ or $r > 1$ and u has received a next-quorum for \perp from round $(p, r - 1)$, then u assembles a new block proposal B_u and propagates B_u and $H(B_u)$.
- Otherwise, if $r > 1$ and u has received a next-quorum for $H(B') \neq \perp$ from $(p, r - 1)$, then u propagates $H(B')$.

Step 2: **Filtering** - When $\text{timer}_u = 2\lambda_r$:

- If $r = 1$ or if $r > 1$ and u has received a next-quorum for \perp , then u selects the proposal with the minimum credential and soft-votes for it.
- Otherwise, if $r > 1$ and u has received a next-quorum for $H(B') \neq \perp$, then u soft-votes for $H(B')$.

Step 3: **Certifying** - While $\text{timer}_u \in (2\lambda_r, \max(4\lambda_r, \Lambda_r))$:

- If u receives a soft-quorum for $H(B)$ and a valid block B with $H(B) = H(B)$, then u cert-votes for $H(B)$.

Step $s = 2n$, where $n \in (2, \infty)$: **First Finishing Step** - When $\text{timer}_u = \max(4\lambda_r, \Lambda_r) + (s - 4)\lambda_r$:

- If i has certified some value v for round r , he next-votes v .
- Else if $(r \geq 2$ and i has seen $2t + 1$ next-votes for \perp for round $r - 1$), he next-votes \perp .
- Else he next-votes his starting value st_i^r .

Step $s = 2n + 1$, where $n \in (2, \infty)$: **Second Finishing Step** - When $\text{timer}_u = \max(4\lambda_r, \Lambda_r) + (s - 5)\lambda_r + 100\text{ms}$:

- If i sees $2t + 1$ soft-votes for some value $v \neq \perp$ for round r , then i next-votes v .
- If $(r \geq 2$ and i sees $2t + 1$ next-votes for \perp for round $r - 1$ and i has not certified in round r), then i next-votes \perp .