

#A. Patch and array extent

```
M1 // N := MAX_PIPES * 2
M2 struct dc_link *links[N];
M3 // get_host_router...(...)
M4 ...
M5 - for (i=0; i<N; ++i) {
M6 + for (i=0; i<N-1; ++i) {
M7 if (!dc->links[i] || ...)
M8 continue; ...
M9 if (hr_match) {
M10 primary=dc->links[i];
M11 secondary=dc->links[i+1];
M12 ...;
M13 break;
M14 }
M15 }
```

Vulnerable: $\max(i + 1) = N$
Fixed: $\max(i + 1) = N - 1$

1 extent N

2 B = N

4 B = N - 1

3 i + 1

---> Semantic links

→ Bound-to-access relation
Checker logic is abridged

#B. Starting checker

```
B1 checkASTCodeBody(F):
B2 for loop i < B:
B3 find access A[i+1]
B4 if no body guard:
B5 report(A[i+1])
```

5 Missing extent test; V/F: 1/1

#C. Automatic refinement

```
C1 checkASTCodeBody(F):
C2 keep loop/access discovery
C3 N = type_extent(A)
C4 max_index = (B-1)+1
C5 if max_index < N:
C6 suppress; else: warn
Tested guards normalized; no name filter
```

6 Extent-aware condition; V/F: 1/0



