

SUEZ_CANNEL UNIVERSITY
FACULTY OF COMPUTER SCIENCE AND
INFORMATION SYSTEM

Web programming
Programming without code

Team_no13

1)Problem:

We have a grave problem with writing codes ,such that a lot of tags in html from this point we make aproject that make Programming more simple and easier for beginner ,special in Web programming .

Solution:

This project that use programming without code (drag and drop) ,you can drag any tag you want to use from button section and drop in code section .

2) *Programming language we use :*

- We used a total of Web languages to establish this location as (*Html5 , CSS , Java script..*)
- HTML ::
We use it to create web page that use on it (form, div, textarea).
- CSS ::
 - to make style of the site
- JavaScript ::
To make function (allow_drop, drop, drag)
We use array to store tags.

3) *Documentation for project*

3.1) *Technical user documentation*

3.2) *End user documentation*

3.1) *Technical user documentation :*

*In this section we talk about how project work
And project life_cycle .
That help programmer to understand the code
and develop it easier.*

3.2) End user documentation :

*That help user to understand how the project
work.*

Let's start to explain life cycle for project

3.1.1) Array

3.1.2) Function allowDrop()

3.1.3) Function drag

3.1.4) Function drop

3.1.1)

```
var tags = {
  DOCTYPE : ' <!DOCTYPE html> ',
  html : ' <html> </html> ',
  title : ' <title> </title> ',
  head : ' <head> </head> ',
  body : ' <body> </body> ',
  UTF8 : '<meta charset="UTF-8">',
  p : '<p> </p>',
  h1 : '<h1> </h1>',
  h2 : '<h2> </h2>',
  h3 : '<h3> </h3>',
  h4 : '<h4> </h4>',
  h5 : '<h5> </h5>',
  h6 : '<h6> </h6>',
  img : '',
  a : '<a href="url"> </a>',
  mail : '<a href="mailto: text.com"> </a>',
  ul : '<ul style=""> </ul>',
  li : '<li> </li>',
  ol : '<ol type=""> </ol>',
  table : '<table border=""> </table>',
  caption : '<caption> </caption>',
  thead : '<thead> </thead>',
  tfoot : '<tfoot> </tfoot>',
  tbody : '<tbody> </tbody>',
  tr : '<tr> </tr>',
  td : '<td> </td>',
  form : ' <form method="" action=""> </form> ',
  text : ' <input type="text" name="" value="" size=""> ',
  password : ' <input type="password" name="" value="" size=""> ',
  button : ' <input type="button" name="" value="" size=""> ',
  checkbox : ' <input type="checkbox" name="" value="" size=""> ',
```

We use that array to store each tag including tag name and it's attribute.

This easy to function drag to call the value of tag

3.1.2)

```
function allowDrop(ev) {  
    ev.preventDefault();  
}
```

By default html don't allow drop ,this function allow drop with built in function preventDefault();

3.1.3)

```
function drag(ev) {  
    var data = ev.target.id;  
    var tag = tags[data];  
    ev.dataTransfer.setData("text",tag);  
}
```

This function operate on drag section when I set data and store in variable tag then use built in function dataTransfer.setData("text",tag); that take value of tag .

simply this function drag button from drag section into code section

3.1.4)

```
function drop(ev) {
    ev.preventDefault();
    var data = ev.dataTransfer.getData("text");
    var txtarea = document.getElementById("div2");
    var scrollTop = txtarea.scrollTop;
    var strPos = 0;
    var br = ((txtarea.selectionStart || txtarea.selectionStart == '0') ?
        "ff" : (document.selection ? "ie" : false) );
    if (br == "ie") {
        txtarea.focus();
        var range = document.selection.createRange();
        range.moveStart ('character', -txtarea.value.length);
        strPos = range.data.length;
    }
    else if (br == "ff") strPos = txtarea.selectionStart;

    var front = (txtarea.value).substring(0,strPos);
    var back = (txtarea.value).substring(strPos,txtarea.value.length);
    txtarea.value=front+data+back;
    strPos = strPos + data.length;
    if (br == "ie") {
        txtarea.focus();
        var range = document.selection.createRange();
        range.moveStart ('character', -txtarea.value.length);
        range.moveStart ('character', strPos);
        range.moveEnd ('character', 0);
        range.select();
    }
    else if (br == "ff") {
        txtarea.selectionStart = strPos;
        txtarea.selectionEnd = strPos;
        txtarea.focus();
    }
}
```

This function get data from function drag with variable data and built in function dataTransfer .getData("text"); that get data which is tag then

We use document.getElementById("div2"); and

Save it in variable txtarea which the id for txtarea

Simply drop function work in code section ...

3.3)

```
<form>
<input type="button" value="DOCTYPE" id="DOCTYPE" draggable="true" ondragstart="drag(event)">
<input type="button" value="html" id="html" draggable="true" ondragstart="drag(event)">
<input type="button" value="title" id="title" draggable="true" ondragstart="drag(event)">
<input type="button" value="head" id="head" draggable="true" ondragstart="drag(event)">
<input type="button" value="body" id="body" draggable="true" ondragstart="drag(event)">
<input type="button" value="UTF-8" id="UTF8" draggable="true" ondragstart="drag(event)">
<input type="button" value="p" id="p" draggable="true" ondragstart="drag(event)">
<input type="button" value="h1" id="h1" draggable="true" ondragstart="drag(event)">
<input type="button" value="h2" id="h2" draggable="true" ondragstart="drag(event)">
<input type="button" value="h3" id="h3" draggable="true" ondragstart="drag(event)">
<input type="button" value="h4" id="h4" draggable="true" ondragstart="drag(event)">
<input type="button" value="h5" id="h5" draggable="true" ondragstart="drag(event)">
<input type="button" value="h6" id="h6" draggable="true" ondragstart="drag(event)">
<input type="button" value="img" id="img" draggable="true" ondragstart="drag(event)">
<input type="button" value="link" id="a" draggable="true" ondragstart="drag(event)">
<input type="button" value="mail" id="mail" draggable="true" ondragstart="drag(event)">
<input type="button" value="ul" id="ul" draggable="true" ondragstart="drag(event)">
<input type="button" value="li" id="li" draggable="true" ondragstart="drag(event)">
<input type="button" value="ol" id="ol" draggable="true" ondragstart="drag(event)">
<input type="button" value="table" id="table" draggable="true" ondragstart="drag(event)">
<input type="button" value="caption" id="caption" draggable="true" ondragstart="drag(event)">
<input type="button" value="table head" id="thead" draggable="true" ondragstart="drag(event)">
<input type="button" value="table foot" id="tfoot" draggable="true" ondragstart="drag(event)">
<input type="button" value="table body" id="tbody" draggable="true" ondragstart="drag(event)">
<input type="button" value="insert row" id="tr" draggable="true" ondragstart="drag(event)">
<input type="button" value="insert data" id="td" draggable="true" ondragstart="drag(event)">
<input type="button" value="form" id="form" draggable="true" ondragstart="drag(event)">
<input type="button" value="text feild" id="text" draggable="true" ondragstart="drag(event)">
<input type="button" value="password feild" id="password" draggable="true" ondragstart="drag(event)">
<input type="button" value="button" id="button" draggable="true" ondragstart="drag(event)">
<input type="button" value="check box" id="checkbox" draggable="true" ondragstart="drag(event)">
```

This form we make to enter on it the button that each button has a value ,

We use the input tag and some attribute such as Type ,value , draggable.

NAMES

- 1. Abd elrahman abo zaid*
- 2. Tarek Hassan ahmed*
- 3. Mohamed abd elhamed*
- 4. Eslam abo matty*
- 5. Basuny glal basuny*
- 6. Belal mahros Mohamed*
- 7. Mohamed showky ali*