

## Artificial Neural Network (ANN) (3)

Dr. Mohammed Brahimi and Dr. Aicha Boutorh



## 1 Extensions and Variations

- Vanishing Gradients and ReLUs
- Weight Initialization and Unstable Gradients
- Handling Categorical Target Features: Softmax Output Layers and Cross-Entropy Loss Functions
- Early Stopping and Dropout: Preventing Overfitting

# Extensions and Variations

(1)



$$\begin{aligned}
 \delta_i &= \underbrace{\frac{\partial \mathcal{E}}{\partial a_i}}_{\delta_j} \times \frac{\partial a_i}{\partial z_i} \\
 &= w_{j,i} \times \underbrace{\delta_j}_{\delta_k} \times \frac{\partial a_i}{\partial z_i} \\
 &= w_{j,i} \times w_{k,j} \times \underbrace{\delta_k}_{\frac{\partial \mathcal{E}}{\partial a_k} \times \frac{\partial a_k}{\partial z_k}} \times \frac{\partial a_j}{\partial z_j} \times \frac{\partial a_i}{\partial z_i} \\
 &= w_{j,i} \times w_{k,j} \times \underbrace{\frac{\partial \mathcal{E}}{\partial a_k} \times \frac{\partial a_k}{\partial z_k}}_{\delta_k} \times \frac{\partial a_j}{\partial z_j} \times \frac{\partial a_i}{\partial z_i}
 \end{aligned}
 \tag{2}$$

$$rectifier(z) = \max(0, z) = \begin{cases} z & \text{if } z > 0 \\ 0 & \text{otherwise} \end{cases} \quad (3)$$

$$\frac{d}{dz}rectifier(z) = \begin{cases} 1 & \text{if } z > 0 \\ 0 & \text{otherwise} \end{cases} \quad (4)$$





**Figure 2:** An illustration of the forward propagation of  $d_2$  through the ReLU network showing the weights on each connection, and the weighted sum  $z$  and activation  $a$  value for each neuron in the network.







$$\begin{aligned}
\delta_k &= \frac{\partial \mathcal{E}}{\partial a_k} \times \frac{\partial a_k}{\partial z_i} \\
\delta_8 &= -0.0657 \times 1.0 \\
&= -0.0657 \\
\delta_7 &= (\delta_8 \times w_{8,7}) \times \frac{\partial a_7}{\partial z_7} \\
&= (-0.0657 \times -0.50) \times 1 \\
&= 0.0329 \\
\delta_6 &= (\delta_8 \times w_{8,6}) \times \frac{\partial a_6}{\partial z_6} \\
&= (-0.0657 \times 0.12) \times 1 \\
&= -0.0079 \\
\delta_5 &= ((\delta_6 \times w_{6,5}) + (\delta_7 \times w_{7,5})) \times \frac{\partial a_5}{\partial z_5} \\
&= ((-0.0079 \times 0.06) + (0.0329 \times -0.09)) \times 1 \\
&= -0.0034 \\
\delta_4 &= ((\delta_6 \times w_{6,4}) + (\delta_7 \times w_{7,4})) \times \frac{\partial a_4}{\partial z_4} \\
&= ((-0.0079 \times 0.10) + (0.0329 \times 0.14)) \times 0 \\
&= 0 \\
\delta_3 &= ((\delta_6 \times w_{6,3}) + (\delta_7 \times w_{7,3})) \times \frac{\partial a_3}{\partial z_3} \\
&= ((-0.0079 \times -0.04) + (0.0329 \times 0.20)) \times 0 \\
&= 0
\end{aligned}$$







$$rectifier_{leaky}(z) = \begin{cases} z & \text{if } z > 0 \\ 0.01 \times z & \text{otherwise} \end{cases} \quad (6)$$

$$\frac{d}{dz}rectifier_{leaky}(z) = \begin{cases} 1 & \text{if } z > 0 \\ 0.01 & \text{otherwise} \end{cases} \quad (7)$$






$$\frac{\partial \mathcal{E}}{\partial \lambda_i} = \frac{\partial \mathcal{E}}{\partial a_i} \times \frac{\partial a_i}{\partial \lambda_i} \quad (10)$$

$$\frac{\partial a_i}{\partial \lambda_i} = \begin{cases} 0 & \text{if } z_i > 0 \\ z_i & \text{otherwise} \end{cases} \quad (11)$$

$$\lambda_i \leftarrow \lambda_i - \alpha \times \frac{\partial \mathcal{E}}{\partial \lambda_i} \quad (12)$$


$$\delta_i = \underbrace{w_{j,i} \times w_{k,j}}_{\substack{\text{extreme weights} \\ \rightarrow \\ \text{unstable gradients}}} \times \frac{\partial \mathcal{E}}{\partial a_k} \times \underbrace{\frac{\partial a_k}{\partial z_k} \times \frac{\partial a_j}{\partial z_j} \times \frac{\partial a_i}{\partial z_i}}_{\substack{\text{extreme weights} \\ \rightarrow \\ \text{saturated activations} \\ \rightarrow \\ \text{vanishing gradients}}} \quad (13)$$

## Weight Initialization and Unstable Gradients




**Figure 5:** The architecture of the neural network used in the weight initialization experiments. Note that the neurons in this network use a linear activation function:  $a_i = z_i$ .

## Weight Initialization and Unstable Gradients



**Figure 6:** The internal dynamics of the network in Figure 5<sup>[19]</sup> during the first training iteration when the weights were initialized using a normal distribution with  $\mu=0.0$ ,  $\sigma=0.01$ .

## Weight Initialization and Unstable Gradients



**Figure 7:** The internal dynamics of the network in Figure 5<sup>[19]</sup> during the first training iteration when the weights were initialized using a normal distribution with  $\mu = 0.0$  and  $\sigma = 0.2$ .





$$\begin{aligned}
 \text{var}(z) &= \text{var}((w_1 \times d_1) + (w_2 \times d_2) + \dots (w_{n_{in}} \times d_{n_{in}})) \\
 &= \sum_{i=1}^{n_{in}} \text{var}(w_i \times d_i)
 \end{aligned} \tag{16}$$

$$\text{var}(w \times d) = [E(\mathbf{W})]^2 \text{var}(\mathbf{d}) + [E(\mathbf{d})]^2 \text{var}(\mathbf{W}) + \text{var}(\mathbf{W}) \text{var}(\mathbf{d}) \tag{17}$$

$$\text{var}(w \times d) = \text{var}(\mathbf{W}) \text{var}(\mathbf{d}) \tag{18}$$



$$\text{var}(z) = \sum_{i=1}^{n_{in}} \text{var}(w_i \times d_i) = n_{in} \text{var}(\mathbf{W}) \text{var}(\mathbf{d}) \quad (19)$$


$$\begin{aligned} \text{var}(Z^{(HL1)}) &= n_{in}^{(HL1)} \times \text{var}(\mathbf{W}^{(HL1)}) \times \text{var}(\mathbf{d}^{(HL1)}) & (20) \\ &= 2 \times 0.0001 \times 1 \\ &= 0.0002 \end{aligned}$$

$$\begin{aligned} \text{var}(Z^{(HL2)}) &= n_{in}^{(HL2)} \times \text{var}(\mathbf{W}^{(HL2)}) \times \text{var}(\mathbf{d}^{(HL2)}) & (21) \\ &= 100 \times 0.0001 \times 0.0002 \\ &= 0.000002 \end{aligned}$$

$$\text{var}(\mathbf{W}^{(k)}) = \frac{2}{n_{in}^{(k)} + n_{out}^{(k)}} \quad (22)$$

$$\text{var}(\mathbf{W}^{(k)}) = \frac{1}{n_{in}^{(k)}} \quad (23)$$

## Weight Initialization and Unstable Gradients




**Figure 8:** The internal dynamics of the network in Figure 5<sup>[19]</sup> during the first training iteration when the weights were initialized using Xavier initialization.

$$\text{var}(\mathbf{W}^{(k)}) = \frac{2}{n_{in}^{(k)}} \quad (24)$$

- Fully Connected Three-Layer ReLU Network:
  - Input Layer: 100 neurons
  - First Hidden Layer: 80 neurons (ReLU activation)
  - Second Hidden Layer: 50 neurons (ReLU activation)
  - Output Layer: 5 neurons

$$\begin{aligned}W^{(1)} &\sim \mathcal{N}\left(0, \sqrt{\frac{1}{100}}\right) \\W^{(2)} &\sim \mathcal{N}\left(0, \sqrt{\frac{2}{80}}\right) \\W^{(3)} &\sim \mathcal{N}\left(0, \sqrt{\frac{2}{50}}\right)\end{aligned}\tag{25}$$

## Weight Initialization and Unstable Gradients



**Figure 9:** The internal dynamics of the network in Figure 5<sup>[19]</sup>, using ReLUs, during the first training iteration when the weights were initialized using He initialization.



- 1 represent the target feature using **one-hot encoding**;
- 2 change the output layer of the network to be a **softmax layer**; and
- 3 change the error (or loss) function we use for training to be the **cross-entropy** function.


**Table 4:** The *range-normalized* hourly samples of ambient factors and full load electrical power output of a combined cycle power plant, rounded to two decimal places, and with the (binned) target feature represented using one-hot encoding.

| ID | AMBIENT TEMPERATURE | RELATIVE HUMIDITY | Electrical Output |               |             |
|----|---------------------|-------------------|-------------------|---------------|-------------|
|    | °C                  | %                 | <i>low</i>        | <i>medium</i> | <i>high</i> |
| 1  | 0.04                | 0.81              | 0                 | 0             | 1           |
| 2  | 0.84                | 0.58              | 1                 | 0             | 0           |
| 3  | 0.50                | 0.07              | 0                 | 1             | 0           |
| 4  | 0.53                | 1.00              | 0                 | 1             | 0           |

$$\varphi_{sm}(z_i) = \frac{e^{z_i}}{\sum_{j=1}^m e^{z_j}} \quad (26)$$

**Table 5:** The calculation of the softmax activation function  $\varphi_{sm}$  over a vector of three logits  $\mathbf{l}$ .

|                              | $\mathbf{l}_0$ | $\mathbf{l}_1$ | $\mathbf{l}_2$ |
|------------------------------|----------------|----------------|----------------|
| $\mathbf{l}$                 | 1.5            | -0.9           | 0.6            |
| $e^{\mathbf{l}_i}$           | 4.48168907     | 0.40656966     | 1.8221188      |
| $\sum_i e^{\mathbf{l}_i}$    |                |                | 6.71037753     |
| $\varphi_{sm}(\mathbf{l}_i)$ | 0.667874356    | 0.060588195    | 0.27153745     |



**Figure 10:** A schematic of a feedforward artificial neural network with a three-neuron softmax output layer.

$$L_{CE}(\mathbf{t}, \hat{\mathbf{P}}) = - \sum_j \mathbf{t}_j \ln(\hat{\mathbf{P}}_j) \quad (27)$$

$$L_{CE}(\mathbf{t}, \hat{\mathbf{P}}) = - \ln(\hat{\mathbf{P}}_\star) \quad (28)$$

$$\begin{aligned}
 L_{CE}(\mathbf{t}, \hat{\mathbf{P}}) &= - \sum_j \mathbf{t}_j \ln(\hat{\mathbf{P}}_j) \\
 &= - \left( \left( \mathbf{t}_0 \ln(\hat{\mathbf{P}}_0) \right) + \left( \mathbf{t}_1 \ln(\hat{\mathbf{P}}_1) \right) + \left( \mathbf{t}_2 \ln(\hat{\mathbf{P}}_2) \right) \right) \\
 &= - \left( \left( 0 \ln(\hat{\mathbf{P}}_0) \right) + \left( 1 \ln(\hat{\mathbf{P}}_1) \right) + \left( 0 \ln(\hat{\mathbf{P}}_2) \right) \right) \\
 &= -1 \ln(\hat{\mathbf{P}}_1) \tag{29}
 \end{aligned}$$

$$\delta_k = \frac{\partial \mathcal{E}}{\partial z_k} \quad (30)$$

$$= \frac{\partial L_{CE}(\mathbf{t}, \hat{\mathbf{P}})}{\partial \mathbf{l}_k} \quad (31)$$

$$= \frac{\partial -\ln(\hat{\mathbf{P}}_\star)}{\partial \mathbf{l}_k} \quad (32)$$

$$= \frac{\partial -\ln(\hat{\mathbf{P}}_\star)}{\partial (\hat{\mathbf{P}}_\star)} \times \frac{\partial (\hat{\mathbf{P}}_\star)}{\partial \mathbf{l}_k} \quad (33)$$



$$\frac{d \ln x}{dx} = \frac{1}{x} \quad (34)$$

$$\frac{\partial -\ln(\hat{\mathbf{P}}_{\star})}{\partial(\hat{\mathbf{P}}_{\star})} = -\frac{1}{\hat{\mathbf{P}}_{\star}} \quad (35)$$

$$\frac{\partial(\hat{\mathbf{P}}_{\star})}{\partial \mathbf{l}_k} = \begin{cases} \hat{\mathbf{P}}_{\star}(1 - \hat{\mathbf{P}}_k) & \text{if } k = \star \\ -\hat{\mathbf{P}}_{\star}\hat{\mathbf{P}}_k & \text{otherwise} \end{cases} \quad (36)$$

$$\delta_k = \frac{\partial -\ln(\hat{\mathbf{P}}_\star)}{\partial(\hat{\mathbf{P}}_\star)} \times \frac{\partial(\hat{\mathbf{P}}_\star)}{\partial \mathbf{l}_k} \quad (37)$$

$$= -\frac{1}{\hat{\mathbf{P}}_{\star}} \times \frac{\partial \left( \hat{\mathbf{P}}_{\star} \right)}{\partial \mathbf{l}_k} \quad (38)$$

$$= -\frac{1}{\hat{\mathbf{P}}_{\star}} \times \begin{cases} \hat{\mathbf{P}}_{\star} \left(1 - \hat{\mathbf{P}}_k\right) & \text{if } k = \star \\ -\hat{\mathbf{P}}_{\star} \hat{\mathbf{P}}_k & \text{otherwise} \end{cases} \quad (39)$$

$$= \begin{cases} -(1 - \hat{\mathbf{P}}_k) & \text{if } k = \star \\ \hat{\mathbf{P}}_k & \text{otherwise} \end{cases} \quad (40)$$

$$\delta_{k=\star} = -\left(1 - \hat{\mathbf{P}}_k\right) \quad (41)$$

$$\delta_{k \neq \star} = \hat{\mathbf{P}}_k \quad (42)$$



**Table 6:** The calculation of the softmax activations for each of the neurons in the output layer for each example in the mini-batch, and the calculation of the  $\delta$  for each neuron in the output layer for each example in the mini-batch.

|                                            | $d_1$       | $d_2$       | $d_3$       | $d_4$       |
|--------------------------------------------|-------------|-------------|-------------|-------------|
| Per Neuron Per Example logits              |             |             |             |             |
| Neuron 8                                   | 0.107653    | 0.106456    | 0.106093    | 0.107395    |
| Neuron 9                                   | 0.099377    | 0.098249    | 0.098227    | 0.098955    |
| Neuron 10                                  | 0.103000    | 0.104083    | 0.1040060   | 0.103460    |
| Per Neuron Per Example $e^{l_i}$           |             |             |             |             |
| Neuron 8                                   | 1.113661238 | 1.112328983 | 1.111925281 | 1.11337395  |
| Neuron 9                                   | 1.104482611 | 1.103237457 | 1.103213186 | 1.104016618 |
| Neuron 10                                  | 1.108491409 | 1.109692556 | 1.109607113 | 1.109001432 |
| $\sum_i e^{l_i}$                           | 3.326635258 | 3.325258996 | 3.324745579 | 3.326392    |
| Per Neuron Per Example Softmax Activations |             |             |             |             |
| Neuron 8                                   | 0.3348      | 0.3345      | 0.3344      | 0.3347      |
| Neuron 9                                   | 0.3320      | 0.3318      | 0.3318      | 0.3319      |
| Neuron 10                                  | 0.3332      | 0.3337      | 0.3337      | 0.3334      |
| Per Neuron Target One-Hot Encodings        |             |             |             |             |
| Neuron 8                                   | 0           | 1           | 0           | 0           |
| Neuron 9                                   | 0           | 0           | 1           | 1           |
| Neuron 10                                  | 1           | 0           | 0           | 0           |
| Per Neuron Per Example $\delta$ s          |             |             |             |             |
| Neuron 8                                   | 0.3348      | -0.6655     | 0.3344      | 0.3347      |
| Neuron 9                                   | 0.3320      | 0.3318      | -0.6682     | -0.6681     |
| Neuron 10                                  | -0.6668     | 0.3337      | 0.3337      | 0.3334      |

$$\begin{aligned}
 \Delta w_{9,6} &= \sum_{j=1}^4 \delta_{9,j} \times a_{6,j} \\
 &= (0.3320 \times 0.1145) + (0.3318 \times 0.1211) \\
 &\quad + (-0.6682 \times 0.1167) + (-0.6681 \times 0.1195) \\
 &= 0.038014 + 0.04018098 + -0.07797894 + -0.07983795 \\
 &= -0.07962191 \tag{43}
 \end{aligned}$$

$$\begin{aligned} w_{9,6} &= w_{9,6} - \alpha \times \Delta w_{9,6} \\ &= -0.07 - 0.01 \times -0.07962191 \\ &= -0.07 - (-0.000796219) \\ &= -0.069203781 \end{aligned} \quad (44)$$

---

## Algorithm 1 The early stopping algorithm

---


**Require:**  $p$  the patience parameter

**Require:**  $\mathcal{D}_\nu$  a validation set

```
1: bestValidationError =  $\infty$ 
2: tmpValidationError = 0
3:  $\theta$  = initial model parameters
4:  $\theta^{best} = 0$ 
5: patienceCount = 0
6: while patienceCount <  $p$  do
7:    $\theta$  = new model parameters after most recent weight update
8:   tmpValidationError = calculateValidationError( $\theta$ ,  $\mathcal{D}_\nu$ )
9:   if bestValidationError  $\geq$  tmpValidationError then
10:     bestValidationError = tmpValidationError
11:      $\theta^{best} = \theta$ 
12:   patienceCount = 0
13:   else
14:     patienceCount = patienceCount + 1
15:   end if
16: end while
17: return Best Model Parameters  $\theta^{best}$ 
```

---





---

## Algorithm 2 Extensions to Backpropagation to Use Inverted Dropout

---

**Require:**  $\rho$  probability that a neuron in a layer will not be dropped

▷ Forward Pass

```
1: for each input or hidden layer  $l$  do  
2:    $\mathbf{DropMask}^{(l)} = (m_1, \dots, m_{size(l)}) \sim \text{Bernoulli}(\rho)$   
3:    $\mathbf{a}^{(l)'} = \mathbf{a}^{(l)} \odot \mathbf{DropMax}^{(l)}$   
4:    $\mathbf{a}^{(l)''} = \frac{1}{\rho} \mathbf{a}^{(l)'}$   
5: end for
```

▷ Backward Pass

```
6: for each layer  $l$  in backward pass do  
7:    $\delta^{(l)} = \delta^{(l)} \odot \mathbf{DropMax}^{(l)}$   
8: end for
```

---