



# Machine Learning (SS 23)

## Assignment 3: Bayes

Mojtaba Nayyeri

[Mojtaba.Nayyeri@ipvs.uni-stuttgart.de](mailto:Mojtaba.Nayyeri@ipvs.uni-stuttgart.de)

Akram Sadat Hosseini

[Akram.Hosseini@ipvs.uni-stuttgart.de](mailto:Akram.Hosseini@ipvs.uni-stuttgart.de)

Nadeen Fathallah

[Nadeen.Fathallah@ipvs.uni-stuttgart.de](mailto:Nadeen.Fathallah@ipvs.uni-stuttgart.de)

Rodrigo Lopez Portillo Alcocer

[rodrigo.lopez-portillo-alcocer@ipvs.uni-stuttgart.de](mailto:rodrigo.lopez-portillo-alcocer@ipvs.uni-stuttgart.de)

Tim Schneider

[timphillip.schneider@ipvs.uni-stuttgart.de](mailto:timphillip.schneider@ipvs.uni-stuttgart.de)

Osama Mohammed

[osama.mohammed@ipvs.uni-stuttgart.de](mailto:osama.mohammed@ipvs.uni-stuttgart.de)

Daniel Frank

[daniel.frank@ipvs.uni-stuttgart.de](mailto:daniel.frank@ipvs.uni-stuttgart.de)

This assignment sheet consists of 2 pages, plus the 2 tasks contained in the .ipynb notebook.

Submit your solution in ILIAS as a single PDF file.<sup>1</sup> Make sure to list full names of all participants, matriculation number, study program and B.Sc. or M.Sc. on the first page. Optionally, you can *additionally* upload source files (e.g. PPTX files). If you have any questions, feel free to ask them in the exercise forum in ILIAS.

**Submission is open until Monday, 15th May 2023, 12:00 noon.**

---

<sup>1</sup>Your drawing software probably allows to export as PDF. An alternative option is to use a PDF printer. If you create multiple PDF files, use a merging tool (like [pdfarranger](#)) to combine the PDFs into a single file.



## Maximum Likelihood vs. Bayes

An unfair coin is tossed seven times and the event (head or tail) is recorded at each iteration. The observed sequence of events is  $\mathcal{D} = (x_1, x_2, \dots, x_7) = (\text{head}, \text{head}, \text{tail}, \text{tail}, \text{head}, \text{head}, \text{head})$ . We assume that all tosses  $x_1, x_2, \dots$  have been generated independently following the Bernoulli probability distribution

$$P(x \mid \theta) = \begin{cases} \theta & \text{if } x = \text{head} \\ 1 - \theta & \text{if } x = \text{tail} \end{cases}$$

where  $\theta \in [0, 1]$  is an unknown parameter.

1. State the likelihood function  $P(\mathcal{D} \mid \theta)$ , that depends on the parameter  $\theta$ .
2. Compute the maximum likelihood solution  $\hat{\theta}$ , and evaluate for this parameter the probability that the next two tosses are "head", that is, evaluate  $P(x_8 = \text{head}, x_9 = \text{head} \mid \hat{\theta})$ .
3. We now adopt a Bayesian view on this problem, where we assume a prior distribution for the parameter  $\theta$  defined as:

$$p(\theta) = \begin{cases} 1 & \text{if } 0 \leq \theta \leq 1 \\ 0 & \text{else} \end{cases}$$

Compute the posterior distribution  $p(\theta \mid \mathcal{D})$ , and evaluate the probability that the next two tosses are head, that is,

$$\int P(x_8 = \text{head}, x_9 = \text{head} \mid \theta) p(\theta \mid \mathcal{D}) d\theta$$