

Repo Chat API Endpoints

Example:

Type: POST
Path: /api/example
Input: { repoURL: string }
Response: { data: { message: string, data?: string } }
Usage:

Routes:

Route - /api/ingest

Type: POST
Path: /repo
Input: { repoURL: GitHub repo URL }
Response: { message: string, data: { success: bool, latestSHA?: commit SHA, message: string } }
Usage: To send a public GitHub URL to be ingested by the backend and stored

Route - /api/query

Type: POST
Path: /userQuery
Input: { query: string, repoURL: GitHub repo URL, chatHistory: [{ role: “user” or “assistant”, content: string }] }
Response: { message: string, data: { message: string, contextStats: { chunkCount: number, totalChars: number, filesReferenced: { fileName: string, relativePath: string, startLine: number, endLine: number, name: string } } } }
Usage: To query an existing ingested repo

Type: GET
Path: /getAllRepos
Input: {}
Response: { message: string, data: { repos: [repoURL: GitHub repo URL] } }
Usage: To get the URLs of all ingested repos

Type: POST (post was chosen to avoid using a query param)
Path: /getRepoByURL
Input: { repoURL: GitHub repo URL }
Response: { message: string, data: { repo: { _id: string, repoURL: GitHub repo URL, lastAccessed: date, latestSHA: string, fileTree: object } } }
Usage: To get the repo data of a specific ingested repo

Route - /api/health

Type: GET
Path: /check
Input: {}
Response: { message: string, data: { status: string, uptime: number } }
Usage: To check the health of the backend