

Rajalakshmi Engineering College

Name: Tarika A G

Email: 241801290@rajalakshmi.edu.in

Roll no: 241801290

Phone: 8807807801

Branch: REC

Department: I AI & DS FD

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1

Total Mark : 10

Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string *k*, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next *n* - 1 lines print the updated contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next *n* lines print the original contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

```
#include <stdio.h>
```

```
#include <string.h>
```

```
#define MAX_CONTACTS 50
```

```
typedef struct {
```

```
    char name[11];
    char phone[11];
} Contact;

void addContact(Contact contacts[], int *count, char name[], char phone[]) {
    strcpy(contacts[*count].name, name);
    strcpy(contacts[*count].phone, phone);
    (*count)++;
}
```

```
int findContactIndex(Contact contacts[], int count, char name[]) {
    for (int i = 0; i < count; i++) {
        if (strcmp(contacts[i].name, name) == 0) {
            return i;
        }
    }
    return -1;
}
```

```
void removeContact(Contact contacts[], int *count, char name[]) {
    int index = findContactIndex(contacts, *count, name);
    if (index != -1) {
        printf("The given key is removed!\n");
        for (int i = index; i < (*count) - 1; i++) {
            contacts[i] = contacts[i + 1];
        }
        (*count)--;
    } else {
        printf("The given key is not found!\n");
    }
}
```

```
void printContacts(Contact contacts[], int count) {
    for (int i = 0; i < count; i++) {
        printf("Key: %s; Value: %s\n", contacts[i].name, contacts[i].phone);
    }
}
```

```
int main() {
    int n;
    scanf("%d", &n);
```

```
Contact contacts[MAX_CONTACTS];
int count = 0;

for (int i = 0; i < n; i++) {
    char name[11], phone[11];
    scanf("%s %s", name, phone);
    addContact(contacts, &count, name, phone);
}

char key[11];
scanf("%s", key);

removeContact(contacts, &count, key);
printContacts(contacts, count);

return 0;
}
```

Status : Correct

Marks : 10/10