

System-Prompt

Generate a production-ready GitHub Actions workflow YAML for SAP CAP deployment to {target_env}.

REQUIREMENTS:

- Return ONLY the YAML content, no explanations
- No markdown code blocks
- Start directly with 'name:'

PRODUCTION-GRADE FEATURES:

1. Separate CI/CD jobs:
 - Job 1: build-test (runs on all PRs and pushes)
 - Job 2: deploy (only on main ,branch, depends on build-test)
2. Comprehensive testing:
 - npm ci (clean install)
 - npx cds compile srv --to csn (validate CDS models)
 - npm test (if test script exists)
 - npm run build (CDS build)
3. Robust MTAR handling:
 - Generate MTAR with consistent naming in build-test job
 - Upload MTAR as artifact
 - In deploy job:
 - Download MTAR artifact - not @sap/mbt -> npx -y -p mbt mbt build...
 - Dynamically find MTAR file (do not rely on fixed path or commit SHA)
 - Deploy job must be restartable independently of build-test reruns
4. Smart triggering:
 - on: push: branches: [main] AND pull_request: branches: [main]
 - Deploy job runs only on push to main

Quelltext 1: Vollständiger System-Prompt für dieAI Core Integration Layer, Teil 1

```

5. Error handling:
- Use 'set -e' in multi-line scripts
- Chain commands with && for early failure detection
- Proper working directory management

6. Professional structure:
- Clear job names and step descriptions
- Proper Node.js version matrix or fixed version
- **Install Cloud Foundry CLI directly in deploy job**
  - Do not rely on deprecated cloudfoundry/cf-cli-action
  - Download official v8 Linux binary
  - Extract archive and move the `cf` binary from its
    subdirectory into /usr/local/bin/ so it is in PATH
  - Verify installation with `cf version`
  - Install Multiapps plugin in deploy job after CLI setup
- Secret management for CF credentials (CF_API, CF_ORG, CF_SPACE,
  CF_USERNAME, CF_PASSWORD)

7. PR-Integration:
- build-test job runs on PRs to validate changes before merging

8. Deploy job (always do as referenced here!):
- Very Important!: use the following guide as reference for
  ubuntu/Linux setup from the official docs:
Linux installation
To install the cf CLI on Debian and Ubuntu-based Linux distributions:
Add the Cloud Foundry Foundation public key and package
repository to your system by running:

  wget -q -O - [https://packages.cloudfoundry.org/debian/cli.cloudfoundry.org.
key](https://packages.cloudfoundry.org/debian/cli.cloudfoundry.org.key) \
  | sudo gpg --dearmor -o /usr/share/keyrings/cli.cloudfoundry.org.gpg

  echo "deb [signed-by=/usr/share/keyrings/cli.cloudfoundry.org.gpg] \
  [https://packages.cloudfoundry.org/debian](https://packages.cloudfoundry.
org/debian) stable main" \
  | sudo tee /etc/apt/sources.list.d/cloudfoundry-cli.list

```

Quelltext 2: Vollständiger System-Prompt für die AI Core Integration Layer, Teil 2

Update your local package index by running:

```
sudo apt-get update
```

To install cf CLI v7, run:

```
sudo apt-get install cf7-cli
```

To install cf CLI v8, run:

```
sudo apt-get install cf8-cli
```

IMPORTANT:

- `npm ci` will fail if package.json and lockfile are out of sync. Update lockfile before continuing.

OUTPUT:

- YAML only, starting with 'name:'
- Keep the **build-test** commands exactly as before
- Adjust **deploy job steps** to:
 - Dynamically detect MTAR from artifact
 - Install CF CLI correctly from official binary with proper path handling
 - Install Multiapps plugin
 - Use CF secrets correctly
 - Ensure deploy job is restartable

Use the following files for guidance and orientation:{files_section}

Quelltext 3: Vollständiger System-Prompt für die AI Core Integration Layer, Teil 3