



EMBENTION

Assembly notes
hw_DAA/BASIC-101010

September 24, 2024

1. Components mount

1.A. SMD mount

- Number of mounting faces: 2
- Sn requirement:
 - RoHS compliant
 - REACH compliant
- Acceptance criteria under IPC-A-610 standard: Grade 3.

1.B. THT mount

- Number of mounting faces: 1
- Sn requirement:
 - RoHS compliant
 - REACH compliant
- Acceptance criteria under IPC-A-610 standard: Grade 3.

2. Attached files for mounting in Assembly's ZIP

The files included in ZIP archive are defined below:

1. SMD centroids file	→ hw_DAA_smd_centroid.xlsx
2. THT centroids file	→ hw_DAA_tht_centroid.xlsx
3. Bottom placement	→ hw_DAA_bottom_place.pdf
4. Bottom placement detailed	→ hw_DAA_bottom_place_detailed.pdf
5. Bottom placement mirrored	→ hw_DAA_bottom_place_mirror.pdf
6. Bottom placement detailed mirrored	→ hw_DAA_bottom_place_mirror_detailed.pdf
7. Top placements	→ hw_DAA_top_place.pdf
8. Top placement detailed	→ hw_DAA_top_place_detailed.pdf
9. BOM file	→ hw_DAA BOM.xlsx
10. Bottom layer silk*	→ hw_DAA.bsilk
11. Top copper layer*	→ hw_DAA.cmp
12. Silk screen layer. Top components*	→ hw_DAA.plc
13. Silk screen layer. Bottom components*	→ hw_DAA.pls
14. Bottom copper layer*	→ hw_DAA.sol
15. Solder mask layer. Top components*	→ hw_DAA.stc
16. Solder mask layer. Bottom components*	→ hw_DAA.sts
17. Top silk layer*	→ hw_DAA.tsilk
18. Assembly notes pdf file	→ hw_DAA.pdf

(*) Gerber file

3. Packaging

Pack with the necessary security measures that guarantee the physical and electrical integrity (ESD) of the assembly throughout the shipping and logistics handling process (foam protections, hard boxes, ESD materials, etc)