



EMBENTION

Assembly notes
hw_LM/BASIC-101010

January 8th, 2026

1. Components mount

1.A. SMD mount

- Number of mounting faces: 2
- Sn requirement:
 - RoHS compliant
 - REACH compliant
- Acceptance criteria under IPC-A-610J standard: Grade 3.

2. Attached files for mounting in Assembly's ZIP

The files included in ZIP archive are defined below:

1. SMD centroids file	→ hw_LM_centroids_smd.xlsx
2. Bottom placement	→ hw_LM_bottom_place.pdf
3. Bottom placement detailed	→ hw_LM_bottom_place_detailed.pdf
4. Bottom placement mirrored	→ hw_LM_bottom_place_mirror.pdf
5. Bottom placement detailed mirrored	→ hw_LM_bottom_place_mirror_detailed.pdf
6. Top placements	→ hw_LM_top_place.pdf
7. Top placement detailed	→ hw_LM_top_place_detailed.pdf
8. BOM file	→ hw_LM BOM.xlsx
9. Bottom layer silk*	→ hw_LM.bsilk
10. Top copper layer*	→ hw_LM.cmp
11. Silk screen layer. Top components*	→ hw_LM.plc
12. Silk screen layer. Bottom components*	→ hw_LM.pls
13. Bottom copper layer*	→ hw_LM.sol
14. Solder mask layer. Top components*	→ hw_LM.stc
15. Solder mask layer. Bottom components*	→ hw_LM.sts
16. Top silk layer*	→ hw_LM.tsilk
17. Assembly notes pdf file	→ hw_LM ASSEMBLY NOTES.pdf

(*) Gerber file

3. Packaging

Pack with the necessary security measures that guarantee the physical and electrical integrity (ESD) of the assembly throughout the shipping and logistics handling process (foam protections, hard boxes, ESD materials, etc)