



北京君正集成电路股份有限公司
Ingenic Semiconductor Co., Ltd.

1 Introduction.....	1
2 Display Driver Module.....	2
3 Audio Driver Module.....	2
4 Wlan Module.....	3
5 GMAC Driver Module.....	3
6 USB Driver Module.....	3
7 VPU Driver Module.....	4
8 Rotate Driver Module.....	4
9 ADC Module.....	5
10 PWM Module.....	5
11 CIM Module.....	5

key words	driver modularity instruction
abstract	
abbreviations	
reference material	Linux4.4 kernel development manual

:

3

:

4 W

:

5

:

:

6

:

:

:

:

7

felix is decoded by h264 and includes: stream parser, motion compensation, inverse quantization, IDCT, and De-block engines functions.

helix is h264 encoding, JPEG compression and decompression.

:

:

8

:

:

9

:

:

10

:

:

11

:

:

12

number	module	kernel size(byte)	kernel startup time(s)	image size of system(M)	description
0	unmodularized	4654163	4.6183	73.1	
1	Display modularization	4595915	2.956	73.1	logo cannot be displayed in modularization
2	Audio modularization	4571922	2.827	73.3	
3	Wlan modularization	4226352	2.477	74	
4	GMAC modularization	4195434	2.422	74	
5	USB modularization	3886832	2.166	74.8	
6	VPU modularization	3799059	2.137	74.9	
7	Rotate modularization	3793395	2.101	74.9	
8	ADC\PWM modularization	3787839	2.100	74.9	

Note: The startup time and file size in the table are not independent modeling of a single driver. All data are collected under the modular premise of the previous module.

Note: All options under Hardware I/O ports have been removed from the original configuration.