# WebAuthn Reference Implementation FIDO2: What, Why, How

Julian Stampfli

February 6, 2019

# Project source

https://github.com/Tartori/web-authn-demo

### Table of Contents

Introduction

WebAuthn - Registration

WebAuthn - Authentication

WebAuthn - Authenticator Data

Summary/Conclusion

Demo

### Table of Contents

#### Introduction

WebAuthn - Registration

WebAuthn - Authentication

WebAuthn - Authenticator Data

Summary/Conclusion

Demo

### **Passwords**

#### Drawbacks

- Hard to remember good passwords
- Weak passwords are chosen
- Passwords are reused

## **Passwords**

#### Drawbacks

- Hard to remember good passwords
- Weak passwords are chosen
- Passwords are reused

### **Benefits**

- EASY!!
- ..

# **Passwords**

#### Drawbacks

- Hard to remember good passwords
- Weak passwords are chosen
- Passwords are reused

### **Benefits**

- EASY!!
- ...
- People are used to them

### FIDO2

- Standard for Passwordless Authentication
- Easy to use(?)

## FIDO2

- Standard for Passwordless Authentication
- Easy to use(?)
- Authenticator (Token) instead of password

### FIDO2 vs Passwords

#### **Passwords**

- Have it remembered
- Enter it
- Hope it is protected

### FIDO2 vs Passwords

#### **Passwords**

- Have it remembered
- Enter it
- Hope it is protected

### FIDO2

- Bring your Authenticator
- Plug it in
- Press a button
- Like an OTP

### FIDO2 vs OTP

#### **OTP**

- Generated with shared secret
- Kind of like a password
- Secure against Replay attacks
- Weak against MitM
- Weak against verifier compromise

### FIDO2 vs OTP

#### **OTP**

- Generated with shared secret
- Kind of like a password
- Secure against Replay attacks
- Weak against MitM
- Weak against verifier compromise


#### FIDO2

- Generated with public key crypto
- Save(ish) against MitM
- Save against verifier compromise
- Save against remote attacks

### FIDO2 vs FIDO U2F

- FIDO U2F predecessor of FIDO2
- FIDO2 used for passwordless and second factor
- FIDO2 keeps the keys on Authenticator
- Interoperable

### How does FIDO2 work



### Table of Contents

Introduction

WebAuthn - Registration


WebAuthn - Authentication

WebAuthn - Authenticator Data

Summary/Conclusion

Demo

# Registration



# Create Registration JSON I

```
1
         "public-key": {
           "challenge": "UvwcjUM5UOASx2AK9...",
           "fidoResponse": "direct",
           "rp": {
5
             "name": "BFH",
6
             "id": "dev.webauthn.demo"
           "user": {
9
             "id": "lPVdjYV97NDuLLMg...",
10
             "name": "test".
11
             "displayName": "test"
12
13
```

# Create Registration JSON II

```
"pubKeyCredParams": [
1
               "type": "public-key",
3
               "alg": -7
           "attestation": "direct",
           "timeout": 60000,
10
```

# Registration Response

```
1
         "rawId": "qKk7sFYyBRex6K6twW5...",
         "response": {
           "attestationObject": "o2NmbXRm...",
           "clientDataJSON": "eyJjaGF..."
5
        "getClientExtensionResults": {},
        "id": "qKk7sFYyBRex6K6twW5...",
         "type": "public-key"
10
```

# Registration Response

- 19 Steps have to be completed
- 1-7 parse and validate clientDataJSON
- 8-13 parse and validate attestationObject
- 14 verify signature
- 15,16 verify trustworthiness
- 17,18 verify and update user data
- 19 fail if any step failed

### Client Data Parsed

### Attestation Data Parsed

```
"fmt": "packed",
         "attStmt": {
           "alg": -7,
4
           "sig": "MEQCIBRsm+gm5tY75S/uEk...",
5
           "x5c": [
             "MIICvDCCAaSgAwIBAgIEA63wEjA..."
9
         "authData": "kn8Lq9EV0MBhHa/k+ZE..."
10
11
```

### Table of Contents

Introduction

WebAuthn - Registration


WebAuthn - Authentication

WebAuthn - Authenticator Data

Summary/Conclusion

Demo

### Authentication



## Create Authentication JSON

```
1
         "public-key": {
           "challenge": "rfmx563tPscMU...",
           "rpId": "dev.webauthn.demo",
           "allowCredentials": [
6
               "type": "public-key",
               "id": "NWIv8Cd3lXkE8r4_..."
10
           "timeout": 60000,
11
12
13
```

# Authentication Response

```
"rawId": "NWIv8Cd3lXkE8r4_Ondf6f...",
         "response": {
           "authenticatorData": "kn8Lq9EV",
4
           "signature": "MEUCIAhdPPqzV69p...",
5
           "userHandle": "",
6
           "clientDataJSON": "eyJjaGFsbGV..."
7
         "getClientExtensionResults": {},
         "id": "NWIv8Cd31XkE8r4_Ondf6fPDe...",
10
         "type": "public-key"
11
12
```

# Authentication Response Steps

- 18 Steps have to be completed
- 1-3 validate user and authenticator
- 4 parse several fields
- 5-10,15 parse and validate clientDataJSON
- 11-14 parse and validate authenticator Data
- 16,17 verify signature and sign count
- 18 fail if any step failed

### Client Data Parsed

### Table of Contents

Introduction

WebAuthn - Registration

WebAuthn - Authentication

WebAuthn - Authenticator Data

Summary/Conclusion

Demo

### Authenticator Data

- RP ID hash
- Flags
- Sign Count
- Attested Credential Data (Registration)
- Extensions (Optional)

### Table of Contents

Introduction

WebAuthn - Registration

WebAuthn - Authentication

WebAuthn - Authenticator Data

Summary/Conclusion

Demo

### Conclusion

### Summary

- Passwordless
- Registration and authentication very similar
- Rather complex
- Need for libraries

### Conclusion

### Summary

- Passwordless
- Registration and authentication very similar
- Rather complex
- Need for libraries

#### Conclusion

- Wide adoption?
- Used in eID?
- Used internally?
- Complexity?
- User verification?

# Further Research

- FIDO2 over NFC
- Other authenticators
- Managing authenticators

### Table of Contents

Introduction

WebAuthn - Registration

WebAuthn - Authentication

WebAuthn - Authenticator Data

Summary/Conclusion

Demo

### Demo

 $\verb|https://dev.webauthn.demo:8888|$ 

# Questions

# Questions

https://github.com/Tartori/web-authn-demo