

Chapter 5 Trees

5.1 Introduction

5.1.1 Terminology


Definition: A tree is a finite set of one or more nodes such that

(1) There is a specially designated node called **root**.


(2) The remaining nodes are partitioned into $n \geq 0$ disjoint sets T_1, \dots, T_n , where each of these sets is a tree. T_1, \dots, T_n are called **subtrees** of the root.

Linear Lists And Trees

- Linear lists are useful for serially ordered data.
 - $(e_0, e_1, e_2, \dots, e_{n-1})$
 - Days of week.
 - Months in a year.
 - Students in this class.
- Trees are useful for hierarchically ordered data.




Department tree for a geographically-organized sales organization



Linux Directory Structure


A **node** stands for the item of information plus the branches to other nodes.

The number of subtrees of a node is its **degree**.
Nodes with degree 0 are **leaf** or **terminal** nodes,
others are **nonterminals**.



The roots of the subtrees of a node X are the **children** of X , X is the **parent** of its children. Children of the same parent are **siblings**.

The degree of a tree is the maximum of the degree of the nodes in the tree.



The **ancestors** of a node are all the nodes along the path from the root to that node.

The **level** of a node is defined by letting the root be at level 1, if a node is at level l , then its children are at $l+1$.

The **height** or **depth** of a tree is the maximum level of any node in the tree.




Fig. 5.2 A sample tree

5.1.2 Representation of Trees

For a tree of degree k , we could use a tree node that has fields for data and k pointers to the children as below:

Data	Child 1	Child 2	...	Child k
------	---------	---------	-----	-----------

Fig. 5.4 Possible node structure for a tree of degree k

However, this is very wasteful of space as Lemma 5.1 in the next slide shows.


Lemma 5.1: If T is a k -ary tree with n nodes, each having a fixed size as in Fig. 5.4, then $n(k-1)+1$ of the nk child fields are 0, $n \geq 1$.

Proof:

- each non-zero child field points to a node
- there is exactly one pointer to each node other than the root
- the number of non-zero child fields in an n node tree is $n-1$
- the number of zero fields is $nk-(n-1)=n(k-1)+1$.

Left Child-Right Sibling Representation



data	
left child	right sibling



5.2 Binary Trees

5.2.1 The Abstract Data Type

Definition: A binary tree is a finite set of nodes that either is empty or consists of a root and two disjoint binary trees called the left subtree and the right subtree.



ADT 5.1

```
template <class T>
```

```
class BinaryTree
```

```
{ // A finite set of nodes either empty or consisting of  
  // a root node, left BinaryTree and right BinaryTree.
```

```
public:
```

```
    BinaryTree ();
```

```
    // creates an empty binary tree
```

```
    bool IsEmpty ();
```

```
    // return true iff the binary tree is empty
```

```
    BinaryTree(BinaryTree<T>& bt1, T& item,  
                                                       BinaryTree<T>& bt2);
```

```
    // creates a binary tree whose left subtree is bt1,  
    // right subtree is bt2, and root node contain item.
```

```
    BinaryTree<T> LeftSubtree();
```

```
    // return the left subtree of *this
```


```
BinaryTree<T> RightSubtree();  
// return the right subtree of *this
```

```
T RootData();  
// return the data in the root of *this
```

```
};
```

Distinction between a binary tree and a tree:

- no tree has 0 node, but there is an empty binary tree.
- a binary tree's root always has two subtrees: the left and the right, although they may be empty.



So the above two binary trees are different: the first has an empty right subtree while the second has an empty left subtree. But as trees, they are the same.

In a binary tree, the number of non-empty subtrees of a node is its degree.

5.2.2 Properties of Binary Trees

Lemma 5.2 [Maximum number of nodes]:

- (1) The maximum number of nodes on level i of a binary tree is 2^{i-1} , $i \geq 1$.
- (2) The maximum number of nodes in a binary tree of depth k is $2^k - 1$, $k \geq 1$.

Proof:

Let M_i be the maximum number of nodes on level i

(1) Induction on level i .

$i = 1$, only the root, $M_i = 2^{1-1} = 2^0 = 1$.

Assume $M_{i-1} = 2^{i-2}$ for $i > 1$.

Since each node has a maximum degree of 2, $M_i = 2M_{i-1} = 2 \times 2^{i-2} = 2^{i-1}$.

(2) The maximum number of nodes in a binary tree of depth k is

$$\sum_{i=1}^k M_i = \sum_{i=1}^k 2^{i-1} = 2^k - 1$$

Lemma 5.3 [Relation between number of leaf nodes and degree-2 nodes]:

For any nonempty binary tree T , if n_0 is the number of leaf nodes and n_2 is the number of nodes of degree 2, then $n_0 = n_2 + 1$.

Proof:

Let n_1 be the number of nodes of degree 1 and n the total number of nodes, we have

$$n = n_0 + n_1 + n_2 \quad (5.1)$$

Each node except for the root has a branch leading into it. If B is the number of branches, then $n = B+1$. Since $B = n_1 + 2n_2$, we obtain

$$n = n_1 + 2n_2 + 1 \quad (5.2)$$

Subtracting Eq. (5.2) from Eq. (5.1) and rearranging terms, we get

$$n_0 = n_2 + 1.$$

Definition: A **full** binary tree of depth k is a binary tree of depth k having 2^k-1 nodes, $k \geq 0$.




Fig. 5.11 Full binary tree of depth 4

Sequential numbering of the nodes in full binary tree: nodes are numbered 1 to n , from level 1 to level k , and from left to right.

Definition: a binary tree with n nodes and depth k is **complete** iff its nodes corresponding to the nodes numbered from 1 to n in the full binary tree of depth k .

From Lemma 5.2, the height of a complete binary tree with n nodes is $\lceil \log_2(n+1) \rceil$.

5.2.3 Binary Trees Representations

5.2.3.1 Array Representation

The nodes may be stored in a **one dimensional array tree**, with the node sequentially numbered i being stored in $tree[i]$.

Lemma 5.4: If a **complete binary tree** with n nodes is represented sequentially, then for any nodes with index i , $1 \leq i \leq n$, we have

(1) $parent(i)$ is at $\lfloor i/2 \rfloor$ if $i \neq 1$. If $i = 1$, i is the root and has no parent.

(2) *LeftChild*(i) is at $2i$ if $2i \leq n$. If $2i > n$, i has no left child.


(3) *RightChild*(i) is at $2i + 1$ if $2i + 1 \leq n$. If $2i + 1 > n$, i has no right child.

Proof: We prove (2). (3) follows from (2) and the nodes numbering from left to right. (1) follows from (2) and (3).

We prove (2) by induction on i .

$i = 1$, clearly the left child is at 2 unless $2 > n$, in which case i has no left child.


Assume for all j , $1 \leq j \leq i$, *LeftChild*(j) is at $2j$.



The two nodes immediately preceding $LeftChild(i+1)$ are the right and left children of i , hence $LeftChild(i+1)$ is at $2i+2=2(i+1)$ unless $2(i+1)>n$, in which case $i+1$ has no left child.

The array representation can be used for all binary trees.

- for a complete binary tree---**no space wasted**.
- for a skewed tree of depth k , in the worst case, it will require $2^k - 1$ spaces of which only k will be used, as shown below:




5.2.3.2 Linked Representation

General problem of sequential representation: insertion and deletion cause data movement.

The problem can be easily overcome through linked representation.

```
template <class T> class Tree;  
class TreeNode {  
friend class Tree<T>;  
public:  
    TreeNode (T& e, TreeNode<T> *left, TreeNode<T> *right)  
        {data = e; leftChild = left; rightChild = right;}  
private:  
    T data;  
    TreeNode<T> *leftChild;  
    TreeNode<T> *rightChild;  
};
```



```
template <class T>
class Tree {
public:
    // Tree operations
    ...
private:
    TreeNode<T> *root;    //the access pointer to the tree
};
```

If necessary, a 4th field, *parent*, may be included in the node.

5.3 Binary Tree Traversal and Tree Iterators

5.3.1 Introduction

- L---moving left, V---visiting the node, R---moving right
- If we adopt the convention of traversing left before right, then only 3 traversals remain: LVR (**inorder**), LRV (**postorder**), VLR (**preorder**).
- There is a natural correspondence between these traversals and producing the infix, postfix and prefix of an expression.

We use the following expression tree to illustrate each of these traversals.




Fig. 5.16 expression tree

5.3.2 Inorder Traversal

```
template <class T>
void Tree<T>::Inorder()
{ // driver as a public member
    Inorder(root);
}
```

```
template <class T>
void Tree<T>::Inorder (TreeNode<T>* currentNode)
{ // workhorse as a private member of Tree
    if (CurrentNode) {
        Inorder(currentNode→leftChild);
        Visit(currentNode)
        Inorder(currentNode→rightChild);
    }
}
```

Assume the *Visit* function has a single line of code:

```
cout << CurrentNode→data;
```

For the tree of Fig. 5.16, the elements are output as:

A / B * C * D +E (infix)

5.3.3 Preorder Traversal

```
template <class T>  
void Tree<T>::Preorder()  
{ // Driver.  
    Preorder(root);  
}
```



```

template <class T>
void Tree<T>::Preorder(TreeNode<T>* currentNode)
{ // workhorse.
    if (currentNode) {
        Visit(currentNode);
        Preorder(currentNode→leftChild);
        Preorder(currentNode→rightChild);
    }
}

```

For the tree of Fig. 5.16, the elements are output as:
 + * * / A B C D E (prefix)

5.3.4 Postorder Traversal

```
template <class T>
void Tree<T>::Postorder()
{ // Driver.
    Postorder(root);
}

template <class T>
void Tree<T>::Postorder(TreeNode<T>* currentNode)
{ // Workhorse.
    if (currentNode) {
        Postorder(currentNode→leftChild);
        Postorder(currentNode→rightChild);
        Visit(currentNode);
    }
}
```

For the tree of Fig. 5.16, the elements are output as:
A B / C * D * E + (postfix)

5.3.5 Iterative Inorder Traversal

To implement a tree traversal by using iterators, we first need to implement a **non-recursive** tree traversal algorithm.

A direct way to do so is to use a **stack**.

```
1 template <class T>
2 void Tree<T>::NonrecInorder()
3 { // Nonrecursive inorder traversal using a stack
4   Stack<TreeNode<T>*> s; // declare and initialize a stack
5   TreeNode<T>* currentNode = root;
6   while (1) {
7     while (currentNode) { // move down leftChild
8       s.Push(currentNode); // add to stack
9       currentNode = currentNode→leftChild;
10    }
11    if (s.IsEmpty()) return;
12    currentNode = s.Top();
13    s.Pop(); // delete from stack
14    Visit(currentNode);
15    currentNode = currentNode→rightChild;
16  }
17}
```

The NonrecInorder USES-A template stack.

Definition: A data object of Type A USES-A data object of Type B if a Type A object uses a Type B object to perform a task. Typically, a Type B object is employed in a member function of Type A.

USES-A is similar to IS-IMPLEMENTED-IN-TERMS-OF, but the degree of using the Type B object is less.

Analysis of NonrecInorder:

- n ---the number of nodes in the tree.
- every node is placed on the stack once, line 8, 9 and 11 to 15 are executed n times.
- *currentNode* will equal 0 once for every 0 link, which is $2n_0 + n_1 = n_0 + n_1 + n_2 + 1 = n + 1$.

The computing time: $O(n)$.

The space required for the stack is equal to the depth of the tree.

Now we use the function *NonrecInorder* to obtain an inorder iterator for a tree.


The key observation is that **each iteration of the while loop of line 6-16** yields the next element in the inorder traversal of the tree.

```
class InorderIterator { // a public nested member class of Tree
public:
    InorderIterator() {currentNode = root;};
    T* Next( );
private:
    Stack<TreeNode<T>*> s;
    TreeNode<T>* currentNode;
};
```

```
T* InorderIterator::Next()
{
    while (currentNode) {
        s.Push(currentNode);
        currentNode = currentNode → LeftChild;
    }
    if (s.IsEmpty()) return 0;
    currentNode=s.Top();
    s.Pop();
    T& temp = currentNode → data;
    currentNode = currentNode → rightChild;
    return &temp;;
}
```


5.3.6 Level-order Traversal

Level-order traversal visits the nodes in the order suggested in the full binary tree nodes numbering.



The level-order traversal of the left tree is:

+ * E * D / C A B

To implement level-order traversal, we use a **queue**.

```

template <class T>
void Tree<T>::LevelOrder()
{ // traverse the binary tree in level order
    Queue<TreeNode<T>*> q;
    TreeNode<T>* currentNode = root;
    while (currentNode) {
        Visit(currentNode);
        if (currentNode→leftChild)
            q.Push(currentNode→leftChild);
        if (currentNode→rightChild)
            q.Push(currentNode→rightChild);
        if (q.IsEmpty())    return;
        currentNode = q.Front();
        q.Pop();
    }
}

```

5.4 Additional Binary Tree Operations

5.4.1 Copying Binary Trees

```
template <class T>
Tree<T>::Tree(const Tree<T>& s) // driver
{ // Copy constructor
    root = Copy(s.root);
}
```

```
template <class T>
TreeNode<T>* Tree<T>::Copy(TreeNode<T>* origNode)
// workhorse
{ // Return a pointer to an exact copy of the binary
  // tree rooted at origNode
  if (!origNode) return 0;
  return new TreeNode<T>(origNode→data,
                          Copy(origNode→leftChild),
                          Copy(origNode→rightChild));
}
```

5.4.2 Testing Equality

```
template <class T>
bool Tree<T>::operator==(const Tree& t) const
{
    return Equal(root, t.root);
}

template <class T>
bool Tree<T>::Equal(TreeNode<T>* a, TreeNode<T>* b)
{
    // Workhorse-
    if ((!a) && (!b)) return true; // both a and b are 0
    return (a && b                // both a and b are non-0
            && (a->data == b->data) //data is the same
            && Equal(a->leftChild, b->leftChild) //left equal
            && Equal(a->rightChild, b->rightChild)); //right equal
}
```

5.5 Threaded Binary Trees

5.5.1 Threads

Note that in the linked representation of binary tree, there are $n + 1 - 0$ links, which is more than actual pointers.

A clever way to make use of these 0 links is to replace them by pointers, called **threads**, to other nodes in the tree.

The threads are constructed using the following rules:

- (1) A **0 rightChild** field at node p is replaced by a pointer to the **inorder** successor of p .
- (2) A **0 leftChild** field at node p is replaced by a pointer to the **inorder** predecessor of p .

The following is a threaded tree, in which node *E* has a predecessor thread pointing to *B* and a successor thread to *A*.




Fig. 5.20 A threaded tree

To distinguish between threads and normal pointers, add two **Boolean** fields:

- *leftThread*
- *rightThread*

If $t \rightarrow \text{leftThread} == \text{true}$, then $t \rightarrow \text{leftChild}$ contains a thread, otherwise a pointer to left child. Similar for $t \rightarrow \text{rightThread}$.

```
template <class T>
class ThreadedNode {
friend class ThreadedTree;
private:
    bool leftThread;
    ThreadedNode *leftChild;
    T data;
    bool rightThread;
    ThreadedNode *rightChild;
};
```

```
template <class T>
class ThreadedTree {
public:
    // Tree operations
    ...
private:
    ThreadedNode *root;
};
```

Let *ThreadedInorderIterator* be a nested class of *ThreadedTree*:

```
class ThreadedInorderIterator {  
public:  
    T* Next();  
    ThreadedInorderIterator()  
        { currentNode = root; }  
private:  
    ThreadedNode<T> *currentNode;  
};
```

To make the left thread of the first node in inorder and the right thread of the last node in inorder un-dangling, we assume a **header node** for all threaded binary tree, let the two threads point to the header node.

The original tree is the **left subtree** of the header node, and the **rightChild** of header node points to the header node itself.




Fig.5.21 An empty threaded binary tree




Fig.5.22 memory representation of threaded tree

we can see:


- (1) The inorder successor of the header node is the first node in inorder;
- (2) The inorder successor of the last node in inorder is the header node.

5.5.2 Inorder Traversal of a Threaded Binary Tree

Observe:

(1) If $x \rightarrow \text{rightThread} == \text{true}$, the inorder successor of x is $x \rightarrow \text{rightChild}$;

(2) If $x \rightarrow \text{rightThread} == \mathbf{false}$, the inorder successor of x is obtained by following a path of *leftChild* from the right child of x until a node with *leftThread* == **true** is reached.



Thus we have:

```
T* ThreadedInorderIterator::Next()  
{// Return the inorder successor of currentNode  
  // in a threaded binary tree  
  ThreadedNode<T> *temp = currentNode→rightChild;  
  if (! currentNode→rightThread)  
    while (!temp→leftThread) temp=temp→leftChild;  
  currentNode = temp;  
  if (currentNode == root) return 0; //no next  
  else return &currentNode→data;  
}
```

Note that when *currentNode == root*, *Next()* return the 1st node of inorder, thus we can use the following function to do an inorder traversal of a threaded binary tree:

```
template <class T>
void ThreadedTree::Inorder()
{
    ThreadedInorderiterator ti;
    for (T* p = ti.Next(); p; p = ti.Next())
        Visit(*p);
}
```


Since each node is visited at most 2 times, the computing time is readily seen to be $O(n)$ for n nodes tree, and the traversal has been done **without using a stack**.

5.5.3 Inserting a Node into a Threaded Binary Tree


Insertion into a threaded tree provides the function for growing threaded tree.

We shall study only the case of inserting r as the right child of s . The left child case is similar.

(1) If $s \rightarrow \text{rightThread} == \text{true}$, as:



(2) If $s \rightarrow rightThread == \mathbf{false}$, as:



In both (1) and (2), actions ①, ②, ③ are the same, and ④ is special for (2).


```

template <class T>
void ThreadedTree<T>::InsertRight(ThreadedNode<T> *s,
                                     ThreadedNode<T> *r)
{ // Insert r as the right child of s
  r→rightChild = s→rightChild;           // ①
  r→rightThread = s→rightThread;         // ① note s!=t.root,
  r→leftChild = s;                         // ②
  r→leftThread = true;                     // ②
  s→rightChild = r;                        // ③
  s→rightThread = false;                   // ③
  if (! r→rightThread) { // case (2)
    ThreadedNode<T> *temp = InorderSucc(r); // ④
    temp→leftChild = r;                    // ④
  }
}

```

5.6 Heaps

5.6.1 Priority Queues

In a priority queue, the element to be deleted is the one with highest (or lowest) priority.

Assume type T is defined so that operators ($<$, $>$, etc.) compare element priorities.

ADT 5.2 MaxHeap

```
template <class T>
class MaxPQ {
public:
    virtual ~MaxPQ() { }
        // virtual destructor

    virtual bool IsEmpty() const = 0;
        // return true iff the priority queue is empty

    virtual const T& Top() const = 0;
        // return reference to max element

    virtual void Push(const T&) = 0;
        // add an element to the priority queue

    virtual void Pop() = 0;
        // delete element with max priority
};
```

The simplest way to represent a priority queue is as an unordered linear list:

- *IsEmpty* and *Push* in $O(1)$;
- *Top* and *Pop* in $O(n)$.

By using a max heap:

- *IsEmpty* and *Top* in $O(1)$;
- *Push* and *Pop* in **$O(\log n)$** .

5.6.2 Definition of a Max Heap

Definition:

A max (min) tree is a tree in which the key value in each node is no smaller (larger) than the key values in its children (if any).

A max (min) heap is a complete binary tree that is also a max (min) tree.




Fig. 5.24 Max heaps

Since max heap is a complete binary tree, we use an **array heap** to represent it.

Thus we have the template *MaxHeap* class, which derives from *MaxPQ*<*T*>, as in the next slide:

```
template <class T>
class MaxHeap: public MaxPQ <T>
{
public:
    MaxHeap (int theCapacity = 10);
    bool IsEmpty () { return heapSize == 0;}
    const T& Top() const;
    void Push(const T&);
    void Pop();
private:
    T* heap;           // element array
    int heapSize;      // number of elements in heap
    int capacity;      // size of the array heap
};
```




```

template <class T>
MaxHeap<T>::MaxHeap (int theCapacity = 10)
{ //constructor
    if (theCapacity < 1) throw “Capacity must be >= 1”;
    capacity = theCapacity;
    heapSize = 0;
    heap = new T[capacity+1]; //heap[0] not used
}
template <class T>
Inline T& MaxHeap<T>::Top()
{
    if (IsEmpty()) throw “The heap is empty”;
    return heap[1];
}

```

5.6.3 Insertion into a Max Heap

We use a **bubbling up** process to insert an element, begin at the node $i = \text{heapSize} + 1$, and compare its key with that of its parent. If its key is larger, put its parent into node i , all the way up until it is no larger or reach the root.



```

template <class T>
void MaxHeap<T>::Push(const T& e)
{ // insert e into the max heap
    if (heapSize == capacity) { // double the capacity
        ChangeSize1D(heap, capacity, 2*capacity);
        capacity *= 2;
    }
    int currentNode = ++heapSize;
    while (currentNode != 1 && heap[currentNode/2] < e)
    { // bubble up
        heap[currentNode] = heap[currentNode/2];
        currentNode /= 2;
    }
    heap[currentNode] = e;
}


```

Analysis of Push:

A complete binary tree with n nodes has a height $\lceil \log_2(n+1) \rceil$, the while loop is iterated $O(\log n)$ times, each takes $O(1)$ time, so the complexity is $O(\log n)$.

5.6.4 Deletion from a Max heap

The max element is to be deleted from node 1, we assume the element in node $heapSize$ to be in node 1, and $heapSize--$. Then we compare its key with that of its larger child. All the way down until it is no smaller or reach the leaf---**trickle down**.



```
template <class T>
void MaxHeap<T>::Pop()
{ // delete the max element.
    if (IsEmpty()) throw “Heap is empty. Cannot delete.”;
    heap[1].~T(); // delete the max

    // remove the last element from heap
    T lastE = heap[heapSize--];

    // trickle down
    int currentNode = 1; // root
    int child = 2;      // left child of currentNode
```

```
while (child <= heapSize)
{
    // set child to the larger child of currentNode
    if (child < heapSize && heap[child] < heap[child+1])
child++;

    // can we put lastE in currentNode?
    if (lastE >= heap[child])    break; // yes
    // no
    heap[currentNode] = heap[child]; // move child up
    currentNode = child; child *= 2; // move down a level
}
heap[currentNode] = lastE;
}
```

Analysis of Pop:

The height of a heap with n nodes is $\lceil \log_2(n+1) \rceil$, the while loop is iterated $O(\log n)$ times, each takes $O(1)$ time, so the complexity is $O(\log n)$.

5.7 Binary Search Trees

5.7.1 Definition

When arbitrary elements are to be searched or deleted, heap is not suitable.

A dictionary is a collection of pairs, each pair has a key and an associated element.

Although natural dictionaries may have several pairs with the same key, we assume here that no two pairs have the same key.

The specification of a dictionary is given as ADT 5.3.

ADT 5.3

```
template <class K, class E>  
class Dictionary {
```

```
public:
```

```
    virtual bool IsEmpty () const = 0;
```

```
    // return true iff the dictionary is empty
```

```
    virtual pair<K, E>* Get (const K&) const = 0;
```

```
    // return pointer to the pair with specified key;
```

```
    // return 0 if no such pair
```

```
    virtual void Insert (const pair<K, E>&) = 0;
```

```
    // insert the given pair; if key is a duplicate
```

```
    // update associated element
```

```
    virtual void Delete (const K&) = 0;
```

```
    // delete pair with specified key
```

```
};
```

The pair can be defined as:


```
template <class K, class E>  
struct pair  
{  
    K first;  
    E second;  
};
```

A binary search tree has a better performance when the functions to be performed are search, insert and delete.


Definition: **A binary search tree**, if not empty, satisfies the following properties:

- (1) The root has a key.
- (2) The keys (if any) in the left subtree are smaller than that in the root.
- (3) The keys (if any) in the right subtree are larger than that in the root.
- (4) The left and right subtrees are also binary search trees.


Note these properties imply that the keys must be distinct.



Binary search trees



It is not a binary search tree!



It is not a binary search tree!

5.7.2 Searching a Binary Search Tree

According to its properties, it is easy to search a binary search tree. Suppose search for an element with key k :

If $k ==$ the key in root, success;

If $x <$ the key in root, search the left subtree;

If $x >$ the key in root, search the right subtree.

Assume class BST derives from the class `Tree<pair<K, E>>`.


```

template <class K, class E> // Driver
pair<K, E>* BST<K, E>::Get(const K& k)
{ // Search *this for a pair with key k.
  return Get(root, k);
}

```

```

template <class K, class E> // Workhorse
pair<K, E>* BST<K, E>::Get(treeNode<pair<K, E>>* p,
                                const K& k)
{
  if (!p) return 0;
  if (k < p→data.first) return Get(p→leftChild, k);
  if (k > p→data.first) return Get(p→rightChild, k);
  return &p→data;
}

```

The recursive version can be easily changed into an iterative one as in the following:

```
template <class K, class E> // Iterative version
pair<K, E>* BST<K, E>::Get(const K& k)
{
    TreeNode<pair<K, E>>* currentNode = root;
    while (currentNode)
        if (k < currentNode→data.first)
            currentNode = currentNode→leftChild;
        else if (k > currentNode→data.first)
            currentNode = currentNode→rightChild;
        else return &currentNode→data;

    // no matching pairs
    return 0;
}
```


As can be seen, a binary search tree of height h can be search by key in $O(h)$ time.

Searching a binary search tree by rank

e.g., find the r th smallest element

an additional field *leftSize*, which is one plus the number of elements in the left subtree of the node

(key, leftSize)




```

template <class K, class E> //search by rank
pair<K, E>* BST<K, E>::RankGet(int r)
{
    TreeNode<pair<K, E>>* currentNode = root;
    while (currentNode)
        if (r < currentNode→leftSize)
            currentNode = currentNode→leftChild;
        else if (r > currentNode→leftSize)
        {
            r -= currentNode→leftSize;
            currentNode = currentNode→rightChild;
        }
        else return &currentNode→data;
    return 0;
}

```

5.7.3 Insertion into a Binary Search Tree

To insert a new element, search is carried out, if unsuccessful, then the element is inserted at the point the search terminated.



When the dictionary **already contains** a pair with key k , we simply **update** the element associated with this key to e .

```
template <class  $K$ , class  $E$ >
void  $BST<K, E>::Insert(\text{const pair}<K, E>\& \textit{thePair})$ 
{ // Insert thePair into the binary search tree
  // search for  $\textit{thePair.first}$ ,  $pp$  is parent of  $p$ 
   $TreeNode<\textit{pair}<K, E>> *p = \textit{root}, *pp = 0;$ 
  while ( $p$ ) {
     $pp = p;$ 
    if ( $\textit{thePair.first} < p \rightarrow \textit{data.first}$ )  $p = p \rightarrow \textit{leftChild};$ 
    else if ( $\textit{thePair.first} > p \rightarrow \textit{data.first}$ )  $p = p \rightarrow \textit{rightChild};$ 
    else // duplicate, update associated element
      { $p \rightarrow \textit{data.second} = \textit{thePair.second};$  return};
  }
```




```
// perform insertion
p = new TreeNode<pair<K, E>>(thePair, 0, 0);
if (root) // tree not empty
    if (thePair.first < pp→data.first) pp→leftChild = p;
    else pp→rightChild = p;
else root = p;
}
```

The time is $O(h)$.


5.7.4 Deletion from a Binary Search Tree

3 cases:


(1) deletion of a leaf: easy, set the corresponding child field of its parent to 0 and dispose the node.



(2) deletion of a nonleaf node with one child: easy, the child of the node takes the place of it and the node is disposed.



(3) deletion of a nonleaf node with two children: the element is replaced by either the largest in its leftChild or the smallest in its rightChild. Then delete that node, which has at most one child, in the subtree.



5.8 Selection Trees

5.8.1 Introduction

To merge k ordered sequences, called **runs**, we need to find the smallest from k possibilities, output it, and replace it with the next record in the corresponding run, then find the next smallest, and so on.

The most direct way is to make $k-1$ comparisons.

For $k > 2$, if we **make use of the knowledge obtained from the last comparisons**, the number of comparisons to find the next can be reduced.

Selection trees including **winner tree** and **loser tree** are suitable for this.


5.8.2 Winner trees

A winner tree is a complete binary tree in which each node represents the smaller (winner) of its children. The root represents the smallest.

The construction of a winner tree may be compared to the playing of a tournament.

Leaf node: the first record in the corresponding run.


Nonleaf node: contains an index to the winner of a tournament.



Actually, leaf nodes can be record *buffer*[0] to *buffer*[*k*-1]. The node number of *buffer*[*i*] in the tree is $k + i$.

Now record pointed by the root (*key* == 6) is output, *buffer*[3] is empty, the next record from run 3 (*key* == 15) is input to *buffer*[3].

To reconstruct the tree, tournament has to be played along the path from node 11 to the root.



The tournament is played between sibling nodes and the result put into the parent node. Lemma 5.4 may be used to compute the address of sibling and parent nodes efficiently.

Time of reconstruction: $O(\log_2 k)$

Time of setting up the tree: $O(k)$


5.8.3 Loser Trees

To simplify the restructuring we can use a loser tree.

A selection tree in which each nonleaf node retains a pointer to the loser is called a loser tree.

Actually, the loser in node p is **the loser of the winners of the children of p** .


The next slide shows a loser tree corresponding the previous winner tree.



15	20	20	15	15	11	95	18
16	38	30	25	50	16	99	20
run 0	run 1	run 2	run 3	run 4	run 5	run 6	run 7

Node 0 represents the overall winner.

After outputting *record*[3] (node 11, key 6), the tree is restructured by reading next record from run 3 and playing tournament along the path from node 11 to node 1, as in the next slide:



15	20	20	25	15	11	95	18
16	38	30	28	50	16	99	20
run 0	run 1	run 2	run 3	run 4	run 5	run 6	run 7

The records with which these tournaments are to be played are readily available from the parent nodes.

5.9 Forests

Definition: A forest is a set of $n \geq 0$ disjoint trees.




Fig. 5.34: Three-tree forest

5.9.1 Transforming a Forest into a Binary Tree

Definition: If T_1, \dots, T_n is a forest of trees, then the binary tree corresponding to this forest, denoted by $B(T_1, \dots, T_n)$,

(1) is empty if $n = 0$

(2) has root equal to $\text{root}(T_1)$; has left subtree equal to $B(T_{11}, \dots, T_{1m})$, where T_{11}, \dots, T_{1m} are the subtrees of $\text{root}(T_1)$; and has right subtree $B(T_2, \dots, T_n)$.




Fig. 5.35: Binary tree representation of forest of Fig.5.34

5.9.2 Forest Traversals

Let T be the corresponding binary tree of a forest F .

Visiting the nodes of F in **forest preorder** is defined as:

- (1) If F is empty then return.
- (2) Visit the root of the first tree of F .
- (3) Traverse the subtrees of the first tree in forest preorder.
- (4) Traverse the remaining trees of F in forest preorder.

Visiting the nodes of F in **forest inorder** is defined as:

- (1) If F is empty then return.
- (2) Traverse the subtrees of the first tree in forest inorder.
- (3) Visit the root of the first tree of F .
- (4) Traverse the remaining trees of F in forest inorder.

Visiting the nodes of F in **forest postorder** is defined as:

- (1) If F is empty then return.
- (2) Traverse the subtrees of the first tree in forest postorder.
- (3) Traverse the remaining trees of F in forest postorder.
- (4) Visit the root of the first tree of F .

In **level-order traversal** of F , nodes are visited by level, beginning with the roots of each trees in F . Within each level, from left to right.

5.10 Set Presentation

5.10.1 Introduction

Assume:


- Elements of the sets are the numbers $0, 1, 2, \dots, n-1$ (might be thought as indices).
- For any two sets $S_i, S_j, i \neq j, S_i \cap S_j = \emptyset$.

Operations:


- (1) Disjoint set union $S_i \cup S_j$.
- (2) Find(i)---find the set containing i .

The sets can be represented by trees:


$S_1 = \{0, 6, 7, 8\}$



$S_2 = \{1, 4, 9\}$




$S_3 = \{2, 3, 5\}$



The nodes are linked **from the children to the parent**.


5.10.2 Union and Find Operations

To do $S_1 \cup S_2$, simply make one of the trees a subtree of the other:



$S_1 \cup S_2$

To find the root of a set from its name, we can keep a pointer to the root with each set name.



Here we ignore the actual set names, just identify sets by their roots. The transition to set names is easy.

Since the set elements are numbered $0, 1, \dots, n-1$, we represent the tree nodes using an array $parent[n]$. The $parent[i]$ contains the parent pointer of node i (element i as well).

The root node has a parent of -1 .

The following is the array representation of S_1 , S_2 , and S_3 :

i	[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]	[8]	[9]
parent	-1	4	-1	2	-1	2	0	0	0	4

```
class Sets {  
  public:  
    // Set operations  
    ...  
  private:  
    int *parent;  
    int n; // number of set elements  
};  
Sets::Sets (int numberOfElements)  
{  
  if (numberOfElements < 2) throw “Must have at least 2  
elements.”;  
  n = numberOfElements;  
  parent = new int[n];  
  fill(parent, parent + n, -1);  
}
```

Now we have simple algorithm for union and find.

```
void Sets::SimpleUnion (int i, int j)
{ // Replace the disjoint sets with roots i and j, i!=j
  with their union
  parent[i] = j;
}

int Sets::SimpleFind (int i)
{ //find the root of the tree containing element i.
  while (parent[i] >= 0) i = parent[i];
  return i;
}
```

Analysis of SimpleUnion and SimpleFind:

Given $S_i = \{i\}$, $0 \leq i < n$, do

$Union(0,1), Union(1,2), \dots, Union(n-2,n-1), Find(0),$
 $Find(1), \dots, Find(n-1)$

$n-1$ unions take $O(n)$

n finds take $O(\sum_{i=1}^n i) = O(n^2)$.

Their performance characteristics are not very good.

We can improve performance by avoiding the creation of degenerate trees.




Definition [Weighting rule for $Union(i, j)$]: If the number of nodes in the tree with root i is less than that in the tree with root j , then make j the parent of i ; otherwise make i the parent of j .


For instance:




initial




Union(0,1)



Union(0,2)



...



We need a *count* field to know how many nodes in each tree, and it can be maintained in the *parent* field of the root as a negative number.


```

void Sets::WeightedUnion (int i, int j)
{ // Union sets with roots i and j,  $i \neq j$ , using the weighting
  rule
    //  $parent[i] = -count[i]$  and  $parent[j] = -count[j]$ 
    int temp = parent[i] + parent[j];
    if (parent[i] > parent[j]) { // i has fewer nodes
      parent[i] = j;
      parent[j] = temp;
    }
    else { // j has fewer nodes or
      // i and j have the same number of nodes
      parent[j] = i;
      parent[i] = temp;
    }
  }
}

```

Analysis of WeightedUnion and SimpleFind:

The time of WeightedUnion is $O(1)$.

The maximum time to perform a find is determined by:

Lemma 5.5: Assume we start with a forest of trees, each having one node. Let T be a tree with m nodes created as a result of a sequence of weighted unions. The height of T is no more than $\lfloor \log_2 m \rfloor + 1$.

Proof by induction:

$m = 1$, it is true.

Assume it is true for all trees with $i \leq m-1$ nodes.


For $i = m$, let T be a tree with m nodes created by WeightedUnion.

Consider the last union performed, $Union(k, j)$.

Let a be the number of nodes in tree j and $m-a$ that in tree k . without loss of generality, assume $1 \leq a \leq m/2$. Then the height of T is either the same as **that of k** or is **one more than that of j** .

If the former is the case, the height of $T \leq \lfloor \log_2 (m-a) \rfloor + 1 \leq \lfloor \log_2 m \rfloor + 1$.



If the latter is the case, the height of $T \leq \lfloor \log_2 a \rfloor + 2 \leq \lfloor \log_2 m/2 \rfloor + 2 = \lfloor \log_2 m \rfloor + 1$.



The time to process a find is $O(\log n)$ in a tree of n nodes. If an intermixed sequence of $u-1$ union and f find operations is to be processed, the time becomes $O(u + f \log u)$.

Further improvement in the find algorithm.

Definition [Collapsing rule] : If j is a node on the path from i to its root and $parent[i] \neq root(i)$, then set $parent[j]$ to $root(i)$.



$j=i, \dots, i_2, i_1$

```
int Sets::CollapsingFind (int i )  
{ // Find the root of tree containing element i. Use the  
  // collapsing rule to collapse all nodes from i to the root.  
  for (int r = i; parent[r] >= 0; r = parent[r]); // find the  
root  
  while ( i != r ) {  
    int s = parent[i];  
    parent[i] = r;  
    i = s;  
  }  
  return r;  
}
```

5.10.3 Application to Equivalent Classes

equivalence classes \Leftrightarrow disjoint sets

Initially, $parent[i] = -1, 0 \leq i \leq n-1$.

To process $i \equiv j$,

Let $x = find(i), y = find(j)$ --- 2 finds

If $x \neq y$ then $union(x, y)$ --- at most 1 union


Thus if we have n elements and m equivalence pairs, we need $2m$ finds and $\min\{n-1, m\}$ unions.

The total time is $O(n+2m \alpha(n+2m, n))$.


Example:

$n = 12$, process equivalence pairs:


$0 \equiv 4, 3 \equiv 1, 6 \equiv 10, 8 \equiv 9, 7 \equiv 4, 6 \equiv 8, 3 \equiv 5, 2 \equiv 11,$
 $11 \equiv 0$




(a) Initial trees



(b) After processing $0 \equiv 4$, $3 \equiv 1$, $6 \equiv 10$, and $8 \equiv 9$



(c) After processing $7 \equiv 4$, $6 \equiv 8$, $3 \equiv 5$, and $2 \equiv 11$




(d) After processing $11 \equiv 0$

5.11 Counting Binary Trees

How many **distinct** binary trees are there within **n** nodes?


□ $n = 0$ or $n = 1$?

□ $n = 2$?




Distinct binary trees with $n = 2$

□ $n = 3?$




Distinct binary trees with $n = 3$


Suppose we have the preorder sequence $A B C D E F G H I$ and the inorder sequence $B C A E D G H F I$ of the same binary tree. Does such a pair of sequences **uniquely** define a binary tree?



(a)



(b)



(c)

The number of distinct binary trees is equal to the number of distinct **inorder permutations obtainable from binary trees having the **preorder** permutation, $1, 2, \dots, n$.**

- ❑ An example: preorder permutation $(1, 2, 3)$
- ❑ Inorder permutations: $(1, 2, 3)$ $(1, 3, 2)$
 $(2, 1, 3)$ $(2, 3, 1)$ $(3, 2, 1)$
- ❑ Obtaining $(3, 1, 2)$ is impossible.

Let b_n be the number of distinct binary trees with n nodes. Preorder permutation is $(1, 2, \dots, n)$.

A root and two subtrees with i nodes and $n-i-1$ nodes, for $0 \leq i < n$.

Thus, $b_n = \sum_{i=0}^{n-1} b_i b_{n-i-1}$, $n \geq 1$, and $b_0 = 1$.

实验&作业

➤ **实验： P267: 10; P272-273: 1, 2.**

实验课上检查验收后提交源代码

➤ **作业： P258: 4; P296: 1; P323: 2, 4.**

提交截止时间： 11月20日晚22:00之前

注意：作业提交电子版，发送到助教邮箱，（可WORD/Latex编辑；也可手写拍照），建议文件格式为PDF，文件命名格式为“学号_姓名_第5章作业**”**