



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Experiment No.2
Convert an Infix expression to Postfix expression using stack ADT.
Name: Tarun Premnarayan Pathak
Roll No: 38
Date of Performance:25/07/23
Date of Submission: 01/08/23
Marks:
Sign:



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Experiment No. 2: Conversion of Infix to postfix expression using stack ADT

Aim: To convert infix expression to postfix expression using stack ADT.

Objective:

- 1) Understand the use of Stack.
- 2) Understand how to import an ADT in an application program.
- 3) Understand the instantiation of Stack ADT in an application program.
- 4) Understand how the member functions of an ADT are accessed in an application program.

Theory:

Postfix notation is a way of representing algebraic expressions without parentheses or operator precedence rules. In this notation, expressions are evaluated by scanning them from left to right and using a stack to perform the calculations. When an operand is encountered, it is pushed onto the stack, and when an operator is encountered, the last two operands from the stack are popped and used in the operation, with the result then pushed back onto the stack. This process continues until the entire postfix expression is parsed, and the result remains in the stack.

Conversion of infix to postfix expression



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Expression	Stack	Output
2	Empty	2
*	*	2
3	*	23
/	/	23*
(/(23*
2	/(23*2
-	/(-	23*2
1	/(-	23*21
)	/	23*21-
+	+	23*21-/
5	+	23*21-/5
*	+	23*21-/53
3	+	23*21-/53
	Empty	23*21-/53*+

Algorithm:

Conversion of infix to postfix

Step 1: Add ")" to the end of the infix expression

Step 2: Push "(" on to the stack

Step 3: Repeat until each character in the infix notation is scanned

IF a "(" is encountered, push it on the stack

IF an operand (whether a digit or a character) is encountered, add it to the postfix expression.

IF a ")" is encountered, then

a. Repeatedly pop from stack and add it to the postfix expression until a "(" is encountered.

b. Discard the "(" . That is, remove the "(" from stack and do not add it to the postfix expression

IF an operator o is encountered, then

a. Repeatedly pop from stack and add each operator (popped from the stack) to the postfix expression which has the same precedence or a higher precedence than o

b. Push the operator o to the stack

[END OF IF]



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Step 4: Repeatedly pop from the stack and add it to the postfix expression until the stack is empty

Step 5: EXIT

Code:

```
#include<stdio.h>

#include<ctype.h>

char stack[100];

int top = -1;

void push(char x)
{
    stack[++top] = x;
}

char pop()
{
    if(top == -1)
        return -1;
    else
        return stack[top--];
}

int priority(char x)
{
    if(x == '(')
        return 0;
    if(x == '+' || x == '-')
        return 1;
    if(x == '*' || x == '/')
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
return 2;

return 0;

}

int main()

{

char exp[100];

char *e, x;

printf("Enter the expression : ");

scanf("%s",exp);

printf("\n");

e = exp;

while(*e != '\0')

{

if(isalnum(*e))

printf("%c ",*e);

else if(*e == '(')

push(*e);

else if(*e == ')')

{

while((x = pop()) != '(')

printf("%c ", x);

}

else
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
{  
while(priority(stack[top]) >= priority(*e))  
printf("%c ",pop());  
push(*e);  
}  
e++;  
}  
  
while(top != -1)  
{  
printf("%c ",pop());  
}return 0;  
}
```

Output:



```
≡ File Edit Search Run Compile Debug
[■] _____ Output =
Enter the expression : (2+5)-1*2

2 5 + 1 2 * - _
```

Conclusion:

1) Convert the following infix expression to postfix $(A+(C/D))*B$

➤ The given infix expression " $A+(C/D)*B$ " is converted to postfix as follows: " $ACD/+B$ ".

2) How many push and pop operations were required for the above conversion?

➤ To convert the expression, you can count the push and pop operations:

- Push operations: 6
- Pop operations: 6

3) Where is the infix to postfix conversion used or applied?

➤ Infix to postfix conversion is used or applied in various computer science and programming areas, including:

- Compiler Design: It's used to convert mathematical expressions into a format that can be easily evaluated by a computer.

- Expression Parsing: Converting infix expressions to postfix makes it easier to perform operations and calculations in the correct order.

- Calculator Applications: In postfix notation, you don't need parentheses, making it suitable for calculator input.



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

- Stack-Based Algorithms: Postfix notation is well-suited for stack-based algorithms and data structures, making it useful in computer science and data processing.