00 (2025) 1–10

Hand Written Character Recognition Using CNN

Priyanshu Chauhan*, Aditya Pratap Singh, Arpit Sharma, Varnank Sharma, Ankush Gupta

Meerut Institute of Engineering and Technology,Meerut,250005, UP, India

Abstract

This article provides a comprehensive review of English character writing (HCR). Literacy is the process of converting written text into readable form. Handwritten characters are difficult to differentiate between different writers, and even when the same person writes the same character, there are differences in shape, size, and position of the characters. Recent research in this area has used a variety of different method s, classifications, and features to reduce the complexity of text recognition. Scientific Research. The tracking process increases detection accuracy by allowing the model to focus on important visual features. The integration of 3D CNN complements this approach by extracting physical and anatomical features from images, providing a more comprehensive analysis.

Keywords: CNN, Custom data set, MNSIT, IAM Dataset, Model

1. Introduction

One of the most important aspects of daily communication is writing. Despite the existence of modern writing instrument s, many people prefer to write old letters with pen and paper. However, writing also has some disadvantages[8]. The physical form is difficult to preserve, store and give to the people who need it. Physical data is difficult to store, access and process regularly. Data must be updated manually and efforts must be made to keep the data organized. As a result, many important documents have been lost or undetected because paper has not been converted to digital format[1]. We chose to solve this problem in the project because we believe that creating digital documents is easier than written documents; it will allow people to better access, search, share and analyze their information, while also allowing them to write in the style they want[9].

There are two types of handwriting: offline and online. Offline systems use text written on images, called optical character recognition (OCR). The online system uses a character list as a movable pen to represent written

*Corresponding author

Email addresses: priyanshuchauhan1123@gmail.com (Priyanshu Chauhan), priyanshu.chauhan.cse.2021@miet.ac.in (Priyanshu Chauhan), Meerut Institute of Engineering and Technology,Meerut,250005, UP, India (Priyanshu Chauhan), aditya.pratap.cse.2021@miet.ac.in (Aditya Pratap Singh), Meerut Institute of Engineering and Technology,Meerut,250005, UP, India (Aditya Pratap Singh), arpit.sharma.cse.2021@miet.ac.in (Arpit Sharma), Meerut Institute of Engineering and Technology,Meerut,250005, UP, India (Arpit Sharma), varnank.sharma.cse.2021@gmail.com (Varnank Sharma), Meerut Institute of Engineering and Technology,Meerut,250005, UP, India (Varnank Sharma), ankush.gupta@miet.ac.in (Ankush Gupta), Meerut Institute of Engineering and Technology,Meerut,250005, UP, India (Ankush Gupta)

characters[6]. The goal of this project is to further investigate the classification of manuscripts and the conversion of manuscripts into digital forms. Since writing is a broad concept, we want to narrow the scope of the project by defining what cursive means for our purposes. In this project, we competed in splitting the visual of the text[4].

The aim of this project is to analyze the problem of recognizing written text and converting it to digital representation[1]. Writing is a broad term and we plan to limit the scope of the work by defining writing according to our needs[8]. In this work, we have implemented the task of recognizing textual images and short-term (LSTM) network that can improve the detection process. This multimodal approach leverages the strengths of each technique; CNN for spatial features and LSTM for temporal dependencies[3].

Social and Ethical Implications: Human resource writing (HCR) has social and ethical implications, including concerns about privacy, injustice, accessibility, and cultural preservation[10].

HCR systems must prioritize information security to prevent unauthorized access when handling sensitive information, such as personal information and legal information[11]. Privacy risks increase when personal information is stored or shared without permission[2]. Bias is another concern, as labels vary widely across communities, and HCR's educational standards often include specific labels that may conflict with non-branded standards, create problems for some groups, and promote injustice[4].

Technology also raises job concerns through data entry processes that could change jobs in fields that rely on data transmission[7]. HCR can also help preserve words by digitizing rare or damaged text, but if not carefully designed, it can destroy important, relevant words related to culture[6]. While it is possible to increase accessibility by making text easier to navigate for the visually impaired, inadequate support for different texts can exclude those who use it[1]. A transparent, accountable HCR designed with strategic considerations such as accountability and participation is essential to ensuring that technology works for a fair and respectful society[7].

2. Related Work

2.1. Classical Machine Learning Methods

Early research on HCR focused on rule-based methods, statistical methods, and classical machine learning methods. Techniques such as K-nearest neighbor (KNN), support vector machine (SVM), and hidden Markov model (HMM) are widely used in character classification due to their good results in terms of knowledge about standards[5]. Preprocessing steps such as binarization, denoising, thinning, and feature extraction play an important role in improving the performance and accuracy of these models[1].Most of the features are manually generated and rely on annotations such as classification, visual search, and structural features, which limit their transferability to various types of writing[1] .Although these methods provide important information, they have difficulty generalizing across different writing styles and texts, highlighting the need for better and more flexible models[4].

2.2. Deep Learning

The introduction of deep learning models has revolutionized HCR, particularly using neural networks (CNN) and neural networks (RNN). CNNs are good at recognizing spatial patterns, making them ideal for capturing text from multiple convolutional techniques[1] .The introduction of LeNet-5, a CNN model that exhibits high accuracy in number recognition, by Lecun et al., forms the basis for subsequent models[1]. Nonlinear networks, particularly short-term temporal (LSTM) networks, are useful for predicting sequences, making them suitable for knowledge-based neural networks or speech[3]. Many studies have also investigated CNNRNN hybrids, where CNN extracts spatial features and RNN captures physical interactions, thus enhancing handwritten language [4].With the availability of large text databases such as MNIST, IAM, and EMNIST, deep learning models have achieved success and improved performance on a wide range of text types and languages[4].

2.3. Hybrid and Combination Techniques

Researchers are exploring hybrid techniques to increase the power of deep learning techniques. Integration techniques that combine multiple models, including decision trees, support vector machines, and neural networks have been widely studied to improve accuracy and robustness[4] .For example, combining CNNs with image-based models or HMMs has been used to process complex texts, such as speech or writing in multiple languages. The fusion process also allows models to be learned through a combination of manual and deep learning, providing greater flexibility and improving performance across databases[4].

2.4. Latest trends and advanced technologies

Recent research in HCR focuses on the use of Transformer models and tracking systems that are good at keeping the success and relationships away from symbols and words[2]. Transformer-based architectures such as VisionnTransformers (ViT) and their development for typing have achieved high accuracy and efficiency in behavior recognition tasks[2]. When adaptive learning and adaptive strategies proved to be effective in modifying the learned patterns of one language to recognize symbols in other languages, accepting multiple languages and multiple behaviors became important[2]. Additionally, models such as GANs (Generative Adversarial Networks) allow the model to learn from different types of writing by searching for additional information[7].

3. Methodology

This research used multiple methods using neural network (CNN) to recognize written characters. The main goal is to develop and evaluate deep learning models to accurately classify characters. Data collection behavior is primarily used to train and evaluate the model. This method can measure the effectiveness of CNN in character recognition. Example custom dataset creation. The file contains grayscale images of characters of various shapes and sizes. Behavioral annotations are added to the images. Use data enhancement techniques such as rotation, scaling, and transformation to expand the data and highlight differences. Preprocess the image collection. To reliably evaluate the performance of the model, the data is split into training, validation, and test equipment. Contains convolutional layers for feature extraction, pooling layers for dimensionality reduction, and density layers for classification.

Calculate performance metrics such as accuracy, precision, recall, and F1 score for training and testing. Cross-validation was used to ensure the generalizability of the model. The model may have a general problem with invisible labels, especially with populations not represented in the data. Usability in real-life scenarios. This may affect the sample performance when applied to grammars outside the database. Always complete in the book. These limitations will affect the accuracy and reliability of the prediction. The effect of feedback on expectations or current writing experience. Make a contribution. This research aims to improve character recognition using deep learning technology and solve the problems associated with different labels.

3.1. Flowchart




Figure 1. Flowchart for Handwritten Text Processing

This flowchart describes the handwritten text recognition process, which involves the following steps. The first step is loading an image, which is followed by a preprocessing stage to apply grayscale conversion, thresholding, and contour detection to improve the visibility of the text. Following preprocessing, it extracts the handwritten text and splits it into individual sentences for analysis. A machine learning model is trained using the dataset to ensure its effectiveness, and while training, the dataset is first preprocessed and then fed into a convolutional neural network (CNN). Once the model is trained, it is used for predicting text from new handwritten inputs. For prediction, each input image is resized, the trained model is applied, and the resulting output will be the predicted text. Finally, the output will be displayed depending on how the extracted text is output. The structure ensures the handwritten text is recognized quickly and accurately. This method allows for accurate and reliable handwritten text recognition for various applications in digitizing documents, automated systems for reading handwritten text, and text analysis. The preprocessing and segmentation of extracting handwritten text ultimately enable better usability by converting information into a machine-readable format with a high degree of accuracy.

3.2. Algorithm

Input: Image of shape (img_size_w, img_size_h, 1)
Output: Probability distribution over len(label_classes) classes
Initialize Input Layer
inp_ly ← Input(shape=(img_size_w, img_size_h, 1))

First Convolutional Block
$x \leftarrow$ Convu-2D(32, (3,3), padd='s', kernel_initializer=HeNormal())(inp_ly)
$x \leftarrow$ BatchNorm()(x)
$x \leftarrow$ Activ('relu')(x)
$x \leftarrow$ Convu-2D(32, (3,3), padd='s', kernel_initializer=HeNormal())(x)
$x \leftarrow$ BatchNorm()(x)
$x \leftarrow$ Activ('relu')(x)
$x \leftarrow$ MaxPooling2D((2,2))(x)
$x \leftarrow$ D(0.25)(x)
Second Convolutional Block
$x \leftarrow$ Convu-2D(64, (3,3), padd='s', kernel_initializer=HeNormal())(x)
$x \leftarrow$ BatchNorm()(x)
$x \leftarrow$ Activ('relu')(x)
$x \leftarrow$ Convu-2D(64, (3,3), padd='s', kernel_initializer=HeNormal())(x)
$x \leftarrow$ BatchNorm()(x)
$x \leftarrow$ Activ('relu')(x)
$x \leftarrow$ MaxPooling2D((2,2))(x)
$x \leftarrow$ D(0.25)(x)
Third Convolutional Block
$x \leftarrow$ Convu-2D(128, (3,3), padd='s', kernel_initializer=HeNormal())(x)
$x \leftarrow$ BatchNorm()(x)
$x \leftarrow$ Activ('relu')(x)
$x \leftarrow$ Convu-2D(128, (3,3), padd='s', kernel_initializer=HeNormal())(x)
$x \leftarrow$ BatchNorm()(x)
$x \leftarrow$ Activ('relu')(x)
$x \leftarrow$ MaxPooling2D((2,2))(x)
$x \leftarrow$ D(0.5)(x)
Global Feature Extraction
$x \leftarrow$ GlobalAveragePooling2D()(x)
Fully Connected Block
$x \leftarrow$ Dense(512, kernel_initializer=HeNormal())(x)
$x \leftarrow$ BatchNorm()(x)
$x \leftarrow$ Activ('relu')(x)
$x \leftarrow$ D(0.5)(x)
Output Layer
output $\leftarrow$ Dense(len(label_classes), activ='softmax')(x)
Model Compilation
model $\leftarrow$ Model(inp_ly, output)
Optional: Learning Rate Adjustment
End of Algorithm

4. Experimental results

The main presentation of findings from the study on the recognition of handwritten characters through Convolutional Neural Networks (CNNs) is organized to provide a clear understanding of model performance and how preprocessing and data augmentation contributed to some rigidities that came in experiments. The dataset used comprised grayscale images of handwritten characters. Each class of characters has its distinct handwritten style.

4.1. A summary of the dataset is given below

- Total Images : 1,000.
- Character Classes : 26 English alphabets (A-Z), 10 digits (0-9).

- Training Set : 70% of the dataset.
- Validation Set : 20% of the dataset.
- Testing Set : 10% of the dataset.

4.2. Preprocessing and Augmentation

- For sentence recognition, the images were adjusted to a resolution of 200×50 pixels to ensure consistency and accuracy.
- Pixel values were normalized between 0 and 1 to enhance training efficiency.
- Data augmentation was employed to improve model robustness, including:
  - Rotation : ±10 degrees.
  - Shifting : ±10% width/height.
  - Zooming : ±10%.
  - Shearing :±10%.

4.3. Model Performance

The CNN model achieved the following performance metrics:

Table 1. Performance Metrics of CNN-LSTM Model

Metric	**Training Set**	**Validation Set**	**Testing Set**
Accuracy	98.5%	96.7%	95.8%
Loss	0.021	0.045	0.052

The table shows the metrics of the performance of a CNN-LSTM (Convolutional Neural Network - Long Short-Term Memory) model on three different datasets: Training Set, Validation Set, and Testing Set. Accuracy:- Represents the percentage of predicted outputs that are correct.- The model has nearly perfect accuracy (98.5%) on the training set ,which is 70% of the dataset . The validation set accuracy is 96.7%,which consist of 20% of the dataset. Testing accuracy is 95.8% ,which consist of 10% of the dataset. Loss:- Loss represents the error shown in predictions, the lower the value, the better the performance.- The training loss is 0.021, validation loss is 0.045, and testing loss is 0.052.- There is a slight increase in loss from training to testing meaning that there is some overfitting taking place, but in general, the model demonstrates good generalization from seen to unseen data. In summary, the CNN-LSTM model performs good overall, it shows high accuracy and low loss across all datasets.

4.4. Survey of Challenges and Limitations

4.4.1. Misclassification

- Confusing Characters : Characters like ”O” and ”0,” or ”I” and ”1,” were occasionally misclassified.
- Noise Sensitivity : Images with overlapping characters or smudges showed reduced accuracy.
- To make accurate real-time predictions, it was essential to refine and optimize the preprocessing steps for handling large batches of images efficiently.

4.4.2. Insights from Data Augmentation

Augmented training data significantly improved model performance on unseen test samples. This demonstrates the effectiveness of introducing variability in training to enhance generalization capabilities.

4.4.3. User Testing Findings

When the model was applied to handwritten sentences for evaluation

- Ease of Use : Users found the system's prediction results satisfactory when tested on clear, isolated handwritten text.
- Error Cases : Sentences written in cursive or with overlapping words posed challenges for accurate recognition.
- Feedback : Simplifying the preprocessing for non-standard handwriting styles may improve accessibility and usability.

4.5. Conclusion of Findings

The study shows that CNNs for handwritten character recognition are feasible and can be extremely accurate. Preprocessing techniques with data augmentation have improved the performance taken to whole new heights. Future work may focus on solving the challenges posed by cursive handwriting and open discussion on the exploration of sequence-based models, RNNs or Transformers included, to solve connected handwriting problems. The research shows very well how deep learning can enhance the capability to automate handwriting recognition tasks, which will in turn open new doors to further improve optical character recognition technologies.

5. Discussion

5.1. Interpretation of Results

- This study found that in terms of handwritten character recognition, CNN-based models performed exceptionally well; users were keen on systems that recognized different styles of handwriting efficiently and accurately, with the results from the evaluation metrics, user feedback, and testing reflecting this. The accuracy on the test set coupled with user satisfaction during prototype testing provides further credence to the use of CNN architectures in addressing the variations that handwriting presents as a challenge.
- Users emphasized accuracy, robustness to noise, and ease of use as the most significant factors. The need to have the data set augmented prior to testing was pointed out, highlighting the great role played by this process in the increasing performance of the model. Other aspects that emerged from the study are those that deal with interface design and speed of prediction, both of which are claimed to directly influence user satisfaction.
- Moreover, feedback from the user testing phase underlines the necessity of error correction tools, especially in cases when such characters as 'O' and '0' are misclassified. In the end, the results point to an imperative trade-off between accuracy and user-friendly design that can be made to provide the utmost utility of handwriting recognition systems.
- Techniques for Recognition of Handwritten Characters: In its examination of handwriting recognition, commonly done through CNNs and RNNs, previous studies showed that CNNs outperform traditional SVM techniques in terms of accuracy because they extract hierarchical features from images (LeCun et al., 2015). In accession to these findings, this study attains over 95% accuracy on its test set.These Existing studies have highlighted the crucial role of preprocessing and data augmentation to improve model generalization (Simard et al., 2003). Thus, this study utilized rotation, zoom, and shift transformations, thereby strengthening the model against different variations of handwriting.
- Real-Time Recognition Systems: This research has emphasized the necessity for both the speed and the responsiveness of real-time handwriting recognition (Smith et al., 2020). Users generally voiced satisfaction with this prototype's real-time performance, reporting little if any lag when making their predictions.
- Error Correction and User Interaction: Research has also provided the theory of interactive systems allowing the user a means to manually fix recognition errors (Zhou et al., 2018). Here, the research corroborates such work when the users commented on their interest in error correction and customizable dictionaries to improve accuracy for domains of their own choosing.

5.2. Implications

- Theoretical Implications:This study demonstrates theories of pattern recognition and deep learning by showing how well Cnns can perform well by overcoming diversified noise in inputs using handwritten characters. Furthermore, data augmentation increases model generalization, especially in the applications of the area for which available labeled data is limited.

- Practical Implications for Application Development: Developers can use this study to build a successful handwriting recognition system that guarantees accuracy, usability, and tolerance to noise. Real-time feedback, offline mode, and customizable error correction tools are highly important for the acceptance of any tool. Implication for policy: Applications utilizing handwriting recognition have to face data privacy issues, especially if the user's input is saved for the sake of model improvement. Transparent data handling policies and options for offline mode are ways one can build user trust.

5.3. Limitations and Future Research

- Sample Size and Dataset Diversity: While comprehensive, the dataset utilized by this study may not fully capture all handwriting styles and languages. Future research may include collecting more diverse samples, such as handwritten cursive and multilingual samples, in order to improve the generalizability of the model.

- Prototype Testing: The prototype that was being implemented in this research may not entirely reflect what a production-level solution could deliver. Further work will have to focus on building a fully optimized application to assess its long-term usability and engagement.

- Real-World Testing: This study limited its scope to a controlled testing environment, but exposing the model to real-life testing with diverse user groups and devices could offer important insights on its robustness and scalability.

- Integration with Other Systems: Additional directions may include integration with educational tools, form-filling applications, or assistive technologies, expanding the usefulness of handwriting recognition systems. Future studies could look at the efficiency of these integrations.

5.4. Comparative Studies:

Comparing this approach with other handwriting recognition methods, such as hybrid RNN-CNN architectures, could offer valuable insights into the balance between accuracy, computational efficiency, and the complexity of implementation.

5.5. Conclusion

This study asserts the effectiveness of CNNs in handwriting character recognition and considers the importance of user-friendly design, robust preprocessing, and privacy concerns. While the findings are promising, further investigation is needed to enhance the generalization and usability of the model for the real world. The integration of handwriting recognition in the fields of education and assistive technologies has great potential for creating an easier and more efficient access tool to so many things.

6. Conclusion

This study was undertaken to look into the possibility of making use of Convolutional Neural Networks (CNNs) for handwritten character recognition. The results of the study proved that CNN-based models were quite good in recognizing handwritten characters, no doubt because of variability in handwriting style, noise,or other distortions. The performance of the model in terms of recognition and users' comments on its usability defines vast possibilities for real-life implementation.

6.1. Main Findings and Their Relevance to the Research Question

Key findings on the use of CNNs for handwritten character recognition include:

- High Accuracy of CNN Model: The CNN model demonstrated exceptional recognition accuracy, exceeding 95% on the test set. This result underscores the model's ability to effectively generalize across a wide range of handwriting styles
- Effectiveness of Data Augmentation: Preprocessing techniques like rotation, scaling, and noise addition significantly improved the model's robustness to variations in handwriting.
- Ease of Use: Prototype testing confirmed that users found the system easy to use, with real-time feedback and an intuitive interface being particularly appreciated.
- Challenges with Ambiguous Characters – The model encountered difficulties in distinguishing visually similar characters, such as 'O' vs. '0' or '1' vs. 'l'. This highlights the importance of integrating error-correction techniques or contextual recognition models to improve accuracy in such cases.

These findings directly address the research question, showing that CNN-based approaches are not only highly effective but also practical and user-friendly for handwritten character recognition tasks.

6.2. Contribution to the Field

This research provides insights into the application of CNNs to solve a given varying noisy handwriting problem associated with handwritten character recognition, hence extending the field. As CNNs learn from pixel data without any hard-made features, the complexity of use is increased and accuracy can be higher and more adaptable. The study also contributed insights to:

- Data Preprocessing: Demonstrating the critical role of augmentation techniques for improving model robustness.
- Usability Considerations: Highlighting the importance of designing systems that balance technical performance with user experience.
- Real-Time Applications: Validating the feasibility of CNN models for real-time handwriting recognition in practical scenarios.

By addressing the challenges of handwriting diversity and system usability, this research provides a foundation for future developments in character recognition technologies.

6.3. Final Thoughts and Recommendations

The findings of this study indicate a promising future for the use of CNNs in handwritten character recognition. To maximize the potential of these systems, the following recommendations are suggested:

- Robust Error Handling: Implement error correction features to address misclassifications, particularly for characters with similar visual structures.
- Expand Dataset Diversity: Future work should involve training models on datasets representing diverse handwriting styles, languages, and scripts to enhance generalization.
- Optimize Real-Time Performance: Focus on reducing latency and computational requirements to improve the system's responsiveness in real-time applications.
- User-Centric Design : Further improvements should focus on refining the interface to ensure the system remains accessible and easy to use for individuals with different levels of technical expertise.
- Integrate Contextual Recognition : Implement language models to enhance context-based predictions, helping to resolve ambiguities and improve overall recognition accuracy

The conclusion of this paper is that CNNs are effective for handwritten character recognition; hence, they can be widely adopted in applications like digital form processing, educational tools, and support systems for assistive devices. In this way, placing emphasis on user requirements in addressing the existing limitations shall enhance the accessibility and efficiency of handwriting recognition systems considerably.

References

[1] Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner, *Gradient-Based Learning Applied to Document Recognition*, Proceedings of the IEEE, Vol. 86, No. 11, pp. 2278–2324, 1998.

[2] Ian Goodfellow, Yoshua Bengio, and Aaron Courville, *Deep Learning*, MIT Press, Cambridge, MA, 2016.

[3] Ilya Sutskever, Oriol Vinyals, and Quoc V. Le, *Sequence to Sequence Learning with Neural Networks*, In Advances in Neural Information Processing Systems (NeurIPS), 2014.

[4] A. K. Bhunia, A. K. Bhunia, G. Kumar, et al., *Handwriting Recognition in Low-Resource Scripts Using Adversarial Learning*, In Proceedings of the IEEE/CVF International Conference on Computer Vision, 2019.

[5] Pierre-Yves Simard, David Steinkraus, and John C. Platt, *Best Practices for Convolutional Neural Networks Applied to Visual Document Analysis*, In Proceedings of the International Conference on Document Analysis and Recognition (ICDAR), 2003.

[6] Alex Graves and Jürgen Schmidhuber, *Offline Handwriting Recognition with Multidimensional Recurrent Neural Networks*, In Advances in Neural Information Processing Systems, 2009.

[7] Wei Zhou, Li Jin, and Xia Ding,*Recognizing Texts in Scene Images: A Comprehensive Survey.*, IEEE Transactions on Pattern Analysis and Machine Intelligence, 2018.

[8] Sudarchanan M S, Sujan G, Akila Devi R, *Handwritten Text Recognition Using Machine Learning and Deep Learning*, Proceedings of the International Conference on Advances in Computing, Communication and Control, 2023.

[9] Denis Coquenet, et al., *Advancements and Challenges in Handwritten Text Recognition* ,Journal of Imaging, 2023.

[10] King Yiu Suen, *Full Page Handwriting Recognition via Image to Sequence Extraction*, arXiv preprint arXiv:2103.06194, 2021.

[11] Dezhi Peng, Lianwen Jin, Yuliang Liu, Canjie Luo, Songxuan Lai, *PageNet: Towards End-to-End Weakly Supervised Page-Level Handwritten Chinese Text Recognition*, arXiv preprint arXiv:2207.14807, 2022.