```
PS C:\Users\pradeep tr\Downloads\L6_L7_03_coffee_shop_order-main\L6_L7_03_coffee_shop_order-main\Lab 7>    python -m pyt
est test_processor.py
============================================= test session starts =============================================
platform win32 -- Python 3.11.9, pytest-8.3.4, pluggy-1.5.0
rootdir: C:\Users\pradeep tr\Downloads
configfile: pyproject.toml
plugins: anyio-4.16.0, hypothesis-6.170.15
collected 3 items

test_processor.py ...                                                                                [100%]

============================================== 3 passed in 2.10s ==============================================
PS C:\Users\pradeep tr\Downloads\L6_L7_03_coffee_shop_order-main\L6_L7_03_coffee_shop_order-main\Lab 7>
```

```
PS C:\Users\pradeep tr\Downloads\L6_L7_03_coffee_shop_order-main\L6_L7_03_coffee_shop_order-main\Lab 7> python processor
.py
==== Running lookup_drink_code ====
Enter drink code prefix (e.g. LAT, CAP, ESP): xxx
Invalid or unknown drink code.

==== Running calculate_average_shot_cost ====
Enter CSV of shot prices (e.g. 1.0, 1.5, 2.0): yyy
Invalid shot prices.

==== Running parse_order_modifiers ====
Enter modifiers (e.g. milk:oat;syrup:vanilla): zzz
Invalid modifiers. Use key:value pairs separated by ; (e.g. milk:oat;syrup:vanilla).
PS C:\Users\pradeep tr\Downloads\L6_L7_03_coffee_shop_order-main\L6_L7_03_coffee_shop_order-main\Lab 7> python processor
.py
==== Running lookup_drink_code ====
Enter drink code prefix (e.g. LAT, CAP, ESP): LAT
Base Price: $ 4.5

==== Running calculate_average_shot_cost ====
Enter CSV of shot prices (e.g. 1.0, 1.5, 2.0): 4.0
Average Shot Price: $ 4.0

==== Running parse_order_modifiers ====
Enter modifiers (e.g. milk:oat;syrup:vanilla): milk:oat
Parsed Modifiers: {'milk': 'oat'}
PS C:\Users\pradeep tr\Downloads\L6_L7_03_coffee_shop_order-main\L6_L7_03_coffee_shop_order-main\Lab 7>
```