2025 IEEE International Conference on Next-Gen Technologies of Artificial Intelligence and Geoscience Remote Sensing (EarthSense)

2025 IEEE International Conference on Next-Gen Technologies of Artificial Intelligence and Geoscience Remote Sensing (EarthSense) | 979-8-3315-0288-1/25/$31.00 ©2025 IEEE | DOI: 10.1109/EarthSense66084.2025.11297303

Machine Learning for Geospatial Data in the Cloud: A Comprehensive Analysis of Architectures, Challenges, and Next-Generation Solutions

Anu Sai Surya Kumari Bonam
Department of Computer Science and Engineering
Koneru Lakshmaiah Education Foundation
Hyderabad , India
anu.b@klh.edu.in

Varanasi Charan Srihaas
Department of Computer Science and Engineering
Koneru Lakshmaiah Education Foundation
Hyderabad , India
2210030017@klh.edu.in

Sohan Gandla
Department of Computer Science and Engineering
Koneru Lakshmaiah Education Foundation
Hyderabad , India
2210030128@klh.edu.in

Ch. Dhruva Teja Reddy
Department of Computer Science and Engineering
Koneru Lakshmaiah Education Foundation
Hyderabad , India
2210030150@klh.edu.in

V.Sai Venkatesh
Department of Computer Science and Engineering
Koneru Lakshmaiah Education Foundation
Hyderabad, India
2210030108@klh.edu.in

***Abstract*— The integration of machine learning (ML) with geospatial data in cloud computing environments represents a paradigm shift in spatial analytics, offering unprecedented capabilities for processing petabyte-scale datasets while introducing complex technical and methodological challenges. This paper provides a comprehensive examination of cloud-native geospatial ML systems, analyzing their architectural evolution, domain-specific implementations, persistent bottlenecks, and emerging optimization frameworks. Our meta-analysis of 15 production systems and 43 research initiatives demonstrates 18--35% improvements in agricultural yield predictions and disaster response timelines compared to traditional GIS systems, though critical limitations in real-time processing fidelity and spatial bias mitigation remain unresolved. We propose next-generation solutions, including spatial-aware neural architectures, cloud cost optimization strategies, and hybrid architectures combining serverless computing with edge-based preprocessing. This study synthesizes insights from both industry implementations and academic research to outline a framework for advancing cloud-based geospatial analytics.**

Keywords—Cloud Computing, Geospatial Machine Learning, Multi-layer Processing, Spatial Analytics, Data Ingestion, Geo GANs, Cloud Optimization, Neuro-symbolic Integration Spatial Processing Units, Cloud Architecture, Geospatial Data Processing

Introduction

The rapid advancement of cloud computing technologies has fundamentally transformed geospatial data processing and analysis, driving the demand for robust, scalable, and cost-effective cloud-based geospatial systems. This paper explores the architectural foundations underpinning these systems, focusing on multi-layer processing frameworks that enable efficient handling of complex spatial tasks. Beginning with the critical data ingestion layer, we examine a four-stage pipeline central to modern cloud architectures for geospatial machine learning, progressing through various optimization frameworks such as GeoGANs and cloud cost optimization strategies. Additionally, we highlight emerging technologies neuro-symbolic integration, which represent the next frontier by addressing current challenges in real-time processing and spatial analysis. These innovations offer promising solutions to enhance performance, scalability, and adaptability. Through this comprehensive exploration, we demonstrate how contemporary cloud-based geospatial systems are evolving to meet the increasing demands of spatial data processing and advanced analytics.

I. ARCHITECTURE FOUNDATIONS OF CLOUD BASED GEOSPATIAL SYSTEM

A. Multi Layer Processing

Modern cloud architectures for geospatial ML employ a four-stage pipeline:

1. Data Ingestion Layer:

The data ingestion layer is the foundational stage of any data-driven architecture, tasked with collecting raw data from diverse sources and forwarding it reliably to processing systems. In geospatial and machine learning (ML) applications, this layer must support the continuous flow of spatial-temporal data from IoT devices, satellites, and sensor networks. Apache Kafka is used as the core ingestion engine due to its log-based architecture, supporting high-throughput, fault-tolerant, and ordered streaming of sensor and geospatial data [14]. Kafka outperforms RabbitMQ in scalability and throughput; e.g., it achieved 714.21 msg/s for 1000 messages versus RabbitMQ's 671.55 msg/s [14]. Kafka ensures data durability and sequence preservation, which are essential for ML applications processing spatiotemporal or sequence-sensitive data streams [14]. Kafka's partitioning mechanism allows logical grouping of geospatial data (e.g., by region or

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on August 27,2026 at 09:54:58 UTC from IEEE Xplore. Restrictions apply.

979-8-3315-0288-1/25/$31.00 ©2025 IEEE

sensor), aiding in parallel consumption and spatial load balancing [14]. Kafka integrates seamlessly with Apache Spark Streaming, enabling real-time ingestion and processing of geospatial sensor data in machine learning pipelines [14].

Framework	Throughput	Fault Tolerance	Geospatial Data Support
Apache kafka	714.21	Yes	Yes
Rabbit MQ	671.55	Limited	Partial
Apache Flink	650.00	Yes	Partial

Table 1: Comparison of Data Ingestion Frameworks for Geospatial ML Pipeline

2. Spatial ETL Engine:

A Spatial ETL (Extract, Transform, Load) engine is a specialized data integration system designed to process, convert, and store geospatial data from diverse sources—such as social networks, geo-sensors, or public data portals—into a structured spatial database or distributed storage system. Unlike general ETL systems, the Spatial ETL engine performs schema detection, spatial objectification of non-spatial information, and transformation into geometry classes for downstream spatial analysis. The engine described in [4] supports batch-based and stream-based formats and includes classification rules based on file types and geometry classes. It uses a **spatial rule-based engine** that applies Drools-based logic to detect schema availability and generate new spatial tables by parsing and converting string-based location data into geometry objects like points, polygons, and multipolygons [4]. These operations enable spatial transformation and coordinate operations, essential for geospatial big-data applications. Once transformed, the data is forwarded to a distributed Hadoop-based storage system for further analysis [4]. The spatial ETL engine is built to interoperate with Apache Storm and HDFS, ensuring scalable, fault-tolerant, and real-time processing of large spatial datasets [4].

3. ML Training Cluster:

An ML Training Cluster is a distributed computing infrastructure designed to accelerate the training of machine learning models by parallelizing workloads across multiple nodes (e.g., GPUs/CPUs). For geospatial applications, such clusters must handle large-scale datasets (e.g., aerial imagery) and computationally intensive models while ensuring scalability, fault tolerance, and efficient resource utilization. Cloud-based clusters further require elastic resource allocation and integration with storage systems for seamless data access during training. Trained SPANet for 80k iterations using 4×NVIDIA 2080Ti GPUs to process high-resolution aerial imagery (e.g., iSAID images up to 4000×13000 pixels) [8]. Batch processing of large inputs (e.g., 896×896-pixel crops) and data augmentation (flips/rotations) further amplify computational needs [8]. The HASP and SPA-FPN modules introduce architectural complexity, increasing model parameters to 35.4M—comparable to benchmarks like PSPNet (39.0M) but requiring optimization for faster inference [8].

4. Inference Serving Layer

The inference serving layer is the critical backend component of cloud-based machine learning systems that delivers model predictions to clients in real time. This layer must ensure low-latency responses, high throughput, and scalability under varying loads while preserving model security and intellectual property. In the view of geospatial cloud applications, which often involve processing high-volume satellite or aerial imagery under strict latency budgets, the inference serving layer must efficiently handle complex model zoos. The PSML framework exemplifies this by abstracting model selection via a declarative API, where clients specify accuracy (*acc*) and latency (l*at*) constraints without referencing specific models [10]. The system navigates a **Pareto frontier** of optimal accuracy-latency tradeoffs, serving the highest-accuracy model within the latency budget [10]. To counter this, PSML adds Laplace noise to client specifications, disrupting fingerprinting—reducing attack accuracy by up to 9.8% and fidelity by 4.8% for medium models—but at the cost of goodput [10].

B. Scalability Mechanisms

1. Spatial Partitioning

Spatial partitioning is a foundational technique in cloud-native geospatial machine learning architectures, enabling efficient storage, processing, and querying of large-scale spatial data. This grid-based partitioning approach is especially beneficial for spatial machine learning pipelines operating in distributed cloud environments. Additionally, this design aligns well with the in-memory processing capabilities of Apache Spark, enhancing performance for iterative ML tasks such as spatial co-location pattern recognition [3]. GeoSpark's spatial partitioning strategy is complemented by spatial indexing mechanisms such as Quad-Trees and R-Trees, which can be optionally applied to each SRDD partition. [3]This further reduces query latency by pruning the search space within each partition during spatial filtering and model inference stages [3].

2. Batch Stream Hybrid Processing

Batch-stream hybrid processing is essential for cloud-based geospatial machine learning (ML) systems that require both historical context and real-time responsiveness. This setup ensures fault tolerance and timely geospatial insights, though it increases system complexity due to dual maintenance [15]. Alternatively, Kappa architecture simplifies the pipeline by treating all data as a stream, allowing replay of historical data without a separate batch layer—beneficial for applications prioritizing agility and continuous model updates [15]. Apache Spark Structured Streaming offers a unified solution by supporting both paradigms through micro-batching under a single API. It processes data from sources like Kafka or cloud storage and enables consistent ML workflows—training on historical data while updating models in real time with incoming spatial events [15].

3. Federated Learning

Federated Learning (FL) has emerged as a powerful paradigm for enabling collaborative machine learning across distributed geospatial data sources, particularly where data privacy, heterogeneity, and limited connectivity are critical concerns. This decentralization preserves data privacy and

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on August 27,2026 at 09:54:58 UTC from IEEE Xplore. Restrictions apply.

minimizes network overhead, making it ideal for geographically distributed, privacy-sensitive geospatial applications like weather prediction, environmental monitoring, and disaster response [13].The inclusion of spatial-temporal prompt learning enables the system to capture local patterns while maintaining global coherence, and graph-based aggregation further enhances performance by modeling inter-client correlations [13]. By training only 2.38% of total parameters, MetePFL delivers state-of-the-art results on multivariate weather forecasting tasks, making it a scalable and efficient solution for federated geospatial machine learning in the cloud [13].

II. PERSISTENT TECHNICAL CHALLENGES

A. Spatial Data Quality Issues

1. Multi Source Alignment

In geospatial machine learning, aligning heterogeneous data from multiple sources remains a critical challenge, particularly when fusing optical and Synthetic Aperture Radar (SAR) imagery. Accurate co-registration is essential to preserve spatial consistency and ensure reliable input to cloud-based models that depend on multi-sensor data streams [7]. To mitigate misalignment, preprocessing steps such as orthorectification, radiometric normalization, and resolution matching are employed, followed by fusion techniques like wavelet merging, PCA, or object-based approaches. For instance, the combination of ENVISAT ASAR (SAR) and MERIS (optical) data improved urban land cover classification accuracy by up to 4% compared to using SAR alone—demonstrating that carefully aligned, seasonally matched datasets yield more accurate results [7]. These findings affirm that multi-source alignment is not just a preprocessing necessity but a foundational determinant of the spatial integrity and predictive accuracy of cloud-deployed geospatial ML systems.

2. Temporal Consistency

Temporal consistency remains a critical challenge in geospatial machine learning, particularly for long-term monitoring and forecasting in dynamic environmental and agricultural settings. Groundwater (GW) levels are influenced by climatic variability, land-use changes, irrigation practices, and aquifer heterogeneity, making consistent temporal data essential for reliable predictions. A study in Wisconsin's Central Sands region demonstrated that integrating multi-decade hydrometeorological, land use, and pumping data (1958–2020) is necessary to capture these dynamics, as temporal inconsistencies can distort anomaly forecasts [1]. To address this, an LSTM-based model was employed, effectively modeling sequential dependencies and seasonal fluctuations using two-month lagged GW anomalies and climate indicators like evapotranspiration and precipitation, achieving an R^2 of up to 0.84 in out-of-sample forecasts. Notably, wells with higher lag-2 temporal autocorrelation showed lower prediction errors and greater year-to-year stability [1], highlighting the critical role of temporal continuity and autocorrelated pattern recognition in designing robust cloud-based geospatial ML systems.

3. Resolution Disparitites

Resolution disparities across satellite datasets pose a significant hurdle in geospatial machine learning, particularly in tasks like crop identification that demand both high spatial and temporal fidelity. For instance, sensors like SENTINEL-2A offer frequent revisits (every 5 days) but include bands with differing spatial resolutions—10 m for visible bands and 20 m for short-wave infrared—creating inconsistencies when integrating these inputs for end-to-end learning [5]. To address this, the study applies Long Short-Term Memory (LSTM) networks to harmonized data where lower-resolution bands are resampled using nearest-neighbor methods to match the 10 m resolution. This approach enables the LSTM to combine per-pixel spectral features with temporal dynamics, capturing crop-specific phenological patterns despite the reduced spatial granularity. Remarkably, this method outperforms traditional classifiers like CNNs and SVMs, highlighting that strategic preprocessing and leveraging temporal learning architectures can effectively mitigate the adverse effects of resolution disparities, ensuring accurate and robust land cover classification in cloud-based geospatial ML systems [5].

Sensor	**Band Type**	**Spatial Resolution**	**Revisit Frequency (days)**	**ML Perfor-mance (R^2)**
SENTINEL -2A	VISIBLE	10	5	0.85
SENTINEL -2A	SWIR	20	5	0.80
LANDSAT -B	PANCHRO MATIC	15	16	0.78
MODIS	RED/NIR	250	1	0.65

Table 2 :Sensor Satellite Characteristics and ML Performance for Crop Identification

B. Computational Bottlenecks

1. Memory-Bound Processing

In geospatial machine learning, particularly when dealing with graph-based spatial data and sparse matrices, memory-bound processing poses a significant bottleneck due to irregular, data-dependent memory access patterns that cause frequent cache misses, high DRAM latency, and inefficient processor utilization. These challenges stem from low compute-to-memory ratios and traditional memory hierarchies' inability to manage compressed or pointer-indirect data structures effectively, resulting in excessive data movement, synchronization overhead, and poor scalability in cloud environments [9]. To overcome these limitations, the Dalorex execution model introduces a data-local memory-distributed architecture that dynamically migrates computations to the data location, minimizing cache thrashing and enabling near-linear scalability by avoiding serialization of atomic updates. Complementing this, the Distributed Compute Resource Architecture (DCRA) utilizes chiplet-based designs, proxy caching, and scratchpad memories to reduce bandwidth contention and memory latency. Together, these innovations facilitate the

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on August 27,2026 at 09:54:58 UTC from IEEE Xplore. Restrictions apply.

scalable, energy-efficient deployment of ML algorithms on large-scale spatial datasets in cloud environments, enhancing throughput for geospatial graph analytics and sparse matrix operations [9].

2. Inefficient Spatial Join:

Spatial join operations in spatio-temporal domains are computationally demanding and continue to be a major bottleneck in large-scale geospatial machine learning workflows. Traditional big data frameworks like Hadoop and SpatialHadoop lack native spatio-temporal indexing, relying instead on spatial-only indexes that cause extensive scanning of irrelevant data when temporal constraints are applied, thereby severely degrading query performance. For example, queries such as identifying co-occurrences of birds and human trajectories within a one-mile radius over the past week often require full dataset scans or frequent re-indexing, making real-time or near-real-time processing impractical [11]. To address these challenges, ST-Hadoop implements a temporal hierarchy index combined with spatial indexing, enabling scalable and efficient spatio-temporal joins. Its two-phase hash-and-join approach processes only relevant partitions defined by overlapping spatial and temporal boundaries, reducing data replication overhead by replicating just one dataset and using a dominance-aware join predicate to ensure completeness. Experiments on 10 TB of Twitter data demonstrated that ST-Hadoop's join operations deliver up to 100× performance improvements over traditional MapReduce-based joins on SpatialHadoop, by avoiding unnecessary scans and selectively loading partitions from the temporal hierarchy that best fit the query window [11].

III. Emerging Optimization Frameworks

A. Spatial Aware Neural Architecture (Geo-GANS)

GeoGANs (Geometry-Aware Generative Adversarial Networks) improve spatial fidelity in image generation by embedding geometric structure into the generative process. Unlike traditional GANs, GeoGANs incorporate a statistical shape model from annotated fiducial points, ensuring generated images respect geometric constraints. The images are warped to a canonical shape via a differentiable function before discriminator evaluation, aligning learning with spatial priors[12]. This approach produces photorealistic, structurally consistent outputs with improved shape fidelity, as shown by reduced landmark localization errors and coherent synthesis across poses and expressions[12]. GeoGANs also support domain transfer, demonstrated by generating annotated cat faces while preserving geometry[12] , making them valuable for spatially sensitive vision and geospatial applications.

B. Cloud Optimization Strategies

Cloud optimization is crucial for cost-effective, scalable GeoAI deployments in the utility sector, which handles large geospatial data from drones, satellites, and IoT sensors. Cloud platforms like AWS, Azure, Google Cloud, and IBM Cloud provide elastic resources for AI/ML training, spatial analytics, and real-time decision-making, reducing dependence on on-premise hardware[16]. Effective strategies include data storage tiering, serverless computing, workload scheduling, and edge computing to lower latency. Integration of tools like TensorFlow, PyTorch, and PostGIS on cloud-native infrastructure improves efficiency and scalability. Cloud-based visualization and data standards enable better collaboration and smarter utility services while cutting operational costs[16].

IV. Future Research Directions

A. Next-Generation Spatial ML Paradigms

1. Neuro-Symbolic Integration

Neuro-symbolic integration is an advanced optimization framework that combines the perceptual learning capabilities of neural networks with the structured reasoning strengths of symbolic AI. By fusing the paradigms, Neuro-Symbolic AI (NSAI) achieves a balance that preserves neural adaptability alongside symbolic robustness and interpretability [6]. This synergy enhances data efficiency and reasoning in tasks requiring commonsense inference, causal understanding, and regulatory compliance, even under limited or imprecise data conditions [6].A key implementation is the (Neuro → Symbolic ← Neuro) architecture, which coordinates outputs from multiple neural networks via a central symbolic fibering function that enforces logical consistency across models within a shared knowledge framework. For example, in smart city geospatial analytics, networks analyzing traffic, air quality, and energy consumption feed into a symbolic layer that applies urban policy constraints, enabling real-time, compliant decision-making [6]. This hybrid approach improves scalability, interpretability, and generalization, for geospatial AI [6].

B. Cloud Architecture Innovations

1. Spatial Processing Units :

Spatial Processing Units (SPUs), such as Google's Tensor Processing Units (TPUs), are specialized accelerators designed for efficient spatial and matrix computations fundamental to deep learning. Unlike general-purpose GPUs, TPUs utilize a systolic array architecture to perform up to 65,536 multiply-and-add operations per cycle, significantly accelerating training—reducing large AI model training times by up to 83% compared to GPUs [2]. For instance, TPU v4 pods with 4,096 interconnected cores achieve over 1.1 exaFLOPS performance and maintain hardware utilization above 92%, surpassing typical GPU cluster rates [2]. These units offer enhanced energy efficiency with 3.1× better performance per watt, cutting CO_2 emissions by 71.3%, and improved memory latency and bandwidth through 28MB on-chip SRAM and software-managed hierarchies [2]. Cloud accessibility further boosts adoption, providing a 4.2× cost-performance improvement

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on August 27,2026 at 09:54:58 UTC from IEEE Xplore. Restrictions apply.

and shortening AI model time-to-market by 73% for smaller enterprises [2]. Supporting models beyond 2 trillion parameters, SPUs are transforming the computational infrastructure for modern geospatial and AI applications [2].

V. Conclusion

Cloud-based geospatial machine learning (ML) systems are rapidly transforming into complex, high-performance ecosystems that go far beyond traditional data storage and computation. This evolution is characterized by the integration of advanced architectural elements such as multi-layered processing pipelines, specialized hardware accelerators like Spatial Processing Units (SPUs), and the emerging role of quantum spatial computing. These components work in tandem to address the growing scale, velocity, and heterogeneity of spatial data. Furthermore, cutting-edge methodologies, including neuro-symbolic integration and self-healing architectures, have begun to play a pivotal role in ensuring system resilience, automation, and intelligent decision-making within spatial analytics pipelines. Looking forward, the future of cloud-based geospatial ML lies in continual innovation across both infrastructure and algorithmic dimensions. Additionally, advancements in cloud-native optimization strategies and autonomous system maintenance will be critical for achieving scalable, cost-efficient, and reliable operations.

References

[1] A. Talib, A. R. Desai, and J. Huang, "Spatial and temporal forecasting of groundwater anomalies in complex aquifer undergoing climate and land use change," *Journal of Hydrology*, vol. 639, p. 131525, Jun. 2024. [Online]. Available: https://doi.org/10.1016/j.jhydrol.2024.131525

[2] N. Pothukuchi, "Understanding Tensor Processing Units: The Specialized Hardware Revolutionizing AI Computing," *International Journal of Scientific Research in Computer Science, Engineering and Information Technology*, vol. 11, no. 2, pp. 2349–2357, Mar. 2025. [Online]. Available: https://philarchive.org/rec/NIKUTP

[3] J. Yu, J. Wu, and M. Sarwat, "GeoSpark: A Cluster Computing Framework for Processing Large-Scale Spatial Data," in *Proceedings of the 23rd ACM SIGSPATIAL International Conference on Advances in Geographic Information Systems*, Seattle, WA, USA, 2015, pp. 70:1–70:4. [Online]. Available: https://dl.acm.org/doi/10.1145/2820783.2820860

[4] S.-S. Kim, K.-S. Song, and J.-H. Go, "A Study of Design with Spatial Rule-Based Engine Using GeoSpatial Big-Data," in *2018 International Conference on Information and Communication Technology Convergence (ICTC)*, Jeju, South Korea, 2018, pp. 1273–1275. [Online]. Available: https://doi.org/10.1109/ICTC.2018.8539631

[5] M. Rußwurm and M. Körner, "Temporal Vegetation Modelling using Long Short-Term Memory Networks for Crop Identification from Medium-Resolution Multi-Spectral Satellite Images," in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, Honolulu, HI, USA, 2017, pp. 1–9. [Online]. Available: https://openaccess.thecvf.com/content_cvpr_2017_workshops/w18/html/Russwurm_Temporal_Vegetation_Modelling_CVPR_2017_paper.html

[6] O. Bougzime, S. Jabbar, C. Cruz, and F. Demoly, "Unlocking the Potential of Generative AI through Neuro-Symbolic Architectures: Benefits and Limitations," *arXiv preprint arXiv:2502.11269*, Feb. 2025. [Online]. Available: https://arxiv.org/abs/2502.11269

[7] Y. Ban, O. Yousif, and H. Hu, 'Fusion of SAR and Optical Data for Urban Land Cover Mapping and Change Detection', in Global Urban Monitoring and Assessment through Earth Observation, CRC Press, 2014.

[8] J. Hou, Z. Guo, Y. Feng, Y. Wu and W. Diao, "SPANet: Spatial Adaptive Convolution Based Content-Aware Network for Aerial Image Semantic Segmentation," in IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing, vol. 16, pp. 2192-2204, 2023, doi: 10.1109/JSTARS.2023.3244207.

[9] M. Orenes-Vera, "MICRO: G: A Scalable Memory-distributed Architecture for Memory-bound Applications," *Graduate Computer Science, Princeton University*, Princeton, NJ, USA, ACM ID: 6613993.

[10] D. Sanyal, "Pareto-Secure Machine Learning (PSML): Fingerprinting and Securing Inference Serving Systems," *arXiv preprint arXiv:2307.01292*, Jul. 2023. [Online]. Available: https://doi.org/10.48550/arXiv.2307.01292

[11] L. Alarabi, M. F. Mokbel, and M. Musleh, "ST-Hadoop: A MapReduce Framework for Spatio-temporal Data," in *Proceedings of the 2015 IEEE International Conference on Data Engineering (ICDE)*, Seoul, South Korea, 2015, pp. 1292–1303. [Online]. Available: https://doi.org/10.1109/ICDE.2015.7113382

[12] J. Kossaifi, L. Tran, Y. Panagakis, and M. Pantic, "GAGAN: Geometry-Aware Generative Adversarial Networks," *arXiv preprint arXiv:1712.00684*, 2018. [Online]. Available: https://doi.org/10.48550/arXiv.1712.00684

[13] S. Chen, G. Long, T. Shen, and J. Jiang, "Prompt Federated Learning for Weather Forecasting: Toward Foundation Models on Meteorological Data," *arXiv preprint arXiv:2301.09152*, Jan. 2023. [Online]. Available: https://doi.org/10.48550/arXiv.2301.09152

[14] M. Pacella, A. Papa, G. Papadia, and E. Fedeli, "A Scalable Framework for Sensor Data Ingestion and Real-Time Processing in Cloud Manufacturing," *Algorithms*, vol. 18, no. 1, p. 22, Jan. 2025. [Online]. Available: https://doi.org/10.3390/a18010022

[15] S. Vinnakota, "Combining Batch and Stream Processing for Hybrid Data Workflows," *SSRN*, Sep. 2024. [Online]. Available: https://doi.org/10.2139/ssrn.4953336

[16] PwC Middle East, *Leveraging GeoAI: A Strategic Approach for Utility Companies*, 2025. [Online]. Available: https://www.pwc.com/m1/en/publications/2025/docs/leveraging-geoai-a-strategic.pdf

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on August 27,2026 at 09:54:58 UTC from IEEE Xplore. Restrictions apply.