

152. Tailwind का पूरा Mental Model

Level	क्या सीखना है	Example
Level 1	Basic utility	<code>p-4</code>
Level 2	CSS property	<code>p = padding</code>
Level 3	Value	<code>4 = spacing token</code>
Level 4	Responsive	<code>md:p-8</code>
Level 5	State	<code>hover:p-6</code>
Level 6	Multiple state	<code>dark:md:hover:p-8</code>
Level 7	Parent state	<code>group-hover:*</code>
Level 8	Sibling state	<code>peer-checked:*</code>
Level 9	Arbitrary value	<code>p-[27px]</code>



Level 9	Arbitrary value	<code>p-[27px]</code>
Level 10	Arbitrary property	<code>[mask-type:luminance]</code>
Level 11	CSS variable	<code>bg(--brand)</code>
Level 12	Theme	<code>@theme</code>
Level 13	Custom utility	<code>@utility</code>
Level 14	Custom variant	<code>@custom-variant</code>
Level 15	Advanced CSS	<code>@apply</code> , <code>@variant</code> , <code>--spacing()</code>

153. सबसे जरूरी बात: Tailwind की "ALL Properties" कैसे याद करें?

CSS Property	Tailwind Pattern	
<code>display</code>	<code>block</code> , <code>flex</code> , <code>grid</code> , <code>hidden</code>	
<code>position</code>	<code>static</code> , <code>relative</code> , <code>absolute</code> , <code>fixed</code> , <code>sticky</code>	
<code>width</code>	<code>w-*</code>	
<code>height</code>	<code>h-*</code>	
<code>margin</code>	<code>m-*</code> , <code>mx-*</code> , <code>my-*</code> , <code>mt-*</code>	
<code>padding</code>	<code>p-*</code> , <code>px-*</code> , <code>py-*</code> , <code>pt-*</code>	
<code>gap</code>	<code>gap-*</code> , <code>gap-x-*</code> , <code>gap-y-*</code>	
<code>flex-direction</code>	<code>flex-row</code> , <code>flex-col</code>	

Tailwind_css_part_1

<code>flex-direction</code>	<code>flex-row</code> , <code>flex-col</code>
<code>justify-content</code>	<code>justify-*</code>
<code>align-items</code>	<code>items-*</code>
<code>align-self</code>	<code>self-*</code>
<code>flex-grow</code>	<code>grow-*</code>
<code>flex-shrink</code>	<code>shrink-*</code>
<code>flex-basis</code>	<code>basis-*</code>
<code>grid-template-columns</code>	<code>grid-cols-*</code>
<code>grid-template-rows</code>	<code>grid-rows-*</code>
<code>grid-column</code>	<code>col-*</code>
<code>grid-row</code>	<code>row-*</code>



Tailwind_css_part_1

color	text-*
background-color	bg-*
background-image	bg-*
background-position	bg-*
font-family	font-*
font-size	text-*
font-weight	font-*
line-height	leading-*
letter-spacing	tracking-*
text-align	text-*

Tailwind_css_part_1

text-align	text-*
border	border-*
border-radius	rounded-*
box-shadow	shadow-*
opacity	opacity-*
overflow	overflow-*
object-fit	object-*
transform	scale-*, rotate-*, translate-*, skew-*
transition	transition-*
animation	animate-*
filter	blur-*, brightness-*, etc.
cursor	cursor-*
user-select	select-*
pointer-events	pointer-events-*
visibility	visible, invisible
z-index	z-*

1. Tailwind CSS का Basic Formula

Pattern	Example	मतलब	
<code>property-value</code>	<code>text-center</code>	CSS property + value	
<code>property-size</code>	<code>p-4</code>	spacing value	
<code>breakpoint:utility</code>	<code>md:p-8</code>	md+ पर लागू	
<code>state:utility</code>	<code>hover:bg-blue-700</code>	hover पर लागू	
<code>variant:variant:utility</code>	<code>dark:md:hover:bg-black</code>	तीन conditions	
<code>[value]</code>	<code>w-[347px]</code>	Custom/arbitrary value	
<code>[property:value]</code>	<code>[mask-type:luminance]</code>	Arbitrary CSS property	
<code>(--variable)</code>	<code>bg(--my-color)</code>	CSS variable	
<code>@container</code>	<code>@md:flex-row</code> 	Parent container के size पर responsive	
<code>@container</code>	<code>@md:flex-row</code>	Parent container के size पर responsive	
<code>group-*</code>	<code>group-hover:text-blue-500</code>	Parent की state पर child style	
<code>peer-*</code>	<code>peer-checked:block</code>	Sibling की state पर style	

Tailwind में arbitrary values और arbitrary properties सीधे class syntax में लिखे जा सकते हैं।

2. Responsive Breakpoints

Tailwind v4 में default breakpoints `sm` से `2xl` तक हैं। ये **minimum width** हैं, यानी `sm` का अर्थ "छोटा करना" नहीं बल्कि उस width से ऊपर utility लागू करना है।  Tailwind CSS

Prefix	Default Minimum	Pixels	मतलब
कोई prefix नहीं	<code>0rem</code>	<code>0px</code>	सभी screens
<code>sm:</code>	<code>40rem</code>	<code>640px</code>	640px+
<code>md:</code>	<code>48rem</code>	<code>768px</code>	768px+
<code>lg:</code>	<code>64rem</code>	<code>1024px</code>	1024px+
<code>xl:</code>	<code>80rem</code>	<code>1280px</code>	1280px+
<code>2xl:</code>	<code>96rem</code>	<code>1536px</code>	1536px+
Example	Result ↓		
<code>w-full</code>	हर screen पर 100%		

Example	Result
<code>w-full</code>	हर screen पर 100%
<code>sm:w-1/2</code>	640px+ पर 50%
<code>md:w-1/2</code>	768px+ पर 50%
<code>lg:w-1/3</code>	1024px+ पर 33.33%
<code>xl:w-1/4</code>	1280px+ पर 25%
<code>2xl:w-1/5</code>	1536px+ पर 20%

3. Arbitrary Breakpoints

Class	Meaning
<code>min-[500px]:bg-red-500</code>	500px+
<code>max-[600px]:text-center</code>	600px से नीचे
<code>min-[900px]:grid-cols-3</code>	900px+
<code>max-[1200px]:p-4</code>	1200px से नीचे

4. Container

Class	काम
<code>container</code>	Responsive <code>max-width</code> वाला container
<code>mx-auto</code>	Container को horizontally center
<code>container mx-auto</code>	सबसे common centered container pattern
<code>max-w-sm</code>	Maximum width small
<code>max-w-md</code>	Maximum width medium
<code>max-w-lg</code>	Maximum width large
<code>max-w-xl</code>	Extra large
<code>max-w-2xl</code>	2xl
<code>max-w-4xl</code>	↓
<code>max-w-4xl</code>	4xl
<code>max-w-7xl</code>	बहुत wide
<code>max-w-full</code>	100%
<code>max-w-screen-sm</code>	Screen breakpoint तक
<code>max-w-screen-md</code>	md screen
<code>max-w-screen-lg</code>	lg screen
<code>max-w-screen-xl</code>	xl screen
<code>max-w-screen-2xl</code>	2xl screen

5. Display

Tailwind का `display` utility सीधे CSS `display` property को control करता है। 

Class	CSS	काम
<code>block</code>	<code>display:block</code>	पूरी line/block
<code>inline</code>	<code>display:inline</code>	Inline element
<code>inline-block</code>	<code>display:inline-block</code>	Inline + width/height
<code>flex</code>	<code>display:flex</code>	Flex container
<code>inline-flex</code>	<code>display:inline-flex</code>	Inline flex
<code>grid</code>	<code>display:grid</code>	Grid container
<code>inline-grid</code>	<code>display:inline-grid</code>	Inline grid
<code>flow-root</code>	<code>display:flow-root</code>	New formatting context
<code>contents</code>	<code>display:contents</code>	Wrapper box हटता है

<code>contents</code>	<code>display:contents</code>	Wrapper box မှီငဲ့ပါ မှီ
<code>table</code>	<code>display:table</code>	Table layout
<code>inline-table</code>	<code>display:inline-table</code>	Inline table
<code>table-row</code>	<code>display:table-row</code>	Table row
<code>table-cell</code>	<code>display:table-cell</code>	Table cell
<code>table-caption</code>	<code>display:table-caption</code>	Caption
<code>list-item</code>	<code>display:list-item</code>	List item
<code>hidden</code>	<code>display:none</code>	Completely hide

6. Accessibility Display

Class	काम
<code>sr-only</code>	Screen पर visually hide, लेकिन screen reader के लिए available
<code>not-sr-only</code>	<code>sr-only</code> effect हटाता है

7. Position

Class	CSS	काम
<code>static</code>	<code>position:static</code>	Normal document flow
<code>relative</code>	<code>position:relative</code>	खुद की position relative
<code>absolute</code>	<code>position:absolute</code>	nearest positioned ancestor के relative
<code>fixed</code>	<code>position:fixed</code>	viewport से fixed



`fixed``position:fixed`

viewport से fixed

`sticky``position:sticky`

scroll पर sticky

`absolute` child को parent के relative position करना हो तो सामान्य pattern `relative` parent + `absolute` child होता है।  Tailwind CSS

8. Position Offset

Class Pattern	CSS	Example	
<code>inset-*</code>	<code>inset</code>	<code>inset-0</code>	
<code>inset-x-*</code>	left + right	<code>inset-x-0</code>	
<code>inset-y-*</code>	top + bottom	<code>inset-y-0</code>	
<code>top-*</code>	top	<code>top-0</code>	
<code>right-*</code>	right	<code>right-0</code>	



<code>right-*</code>	right	<code>right-0</code>
<code>bottom-*</code>	bottom	<code>bottom-0</code>
<code>left-*</code>	left	<code>left-0</code>
<code>start-*</code>	logical start	<code>start-0</code>
<code>end-*</code>	logical end	<code>end-0</code>

9. Position Examples

Class	Result
<code>top-0</code>	top = 0
<code>top-1/2</code>	top = 50%
<code>left-1/2</code>	left = 50%



<code>top-1/2</code>	<code>top = 50%</code>
<code>left-1/2</code>	<code>left = 50%</code>
<code>right-0</code>	<code>right = 0</code>
<code>bottom-0</code>	<code>bottom = 0</code>
<code>inset-0</code>	चारों तरफ 0
<code>inset-x-0</code>	left/right 0
<code>inset-y-0</code>	top/bottom 0
<code>top-[117px]</code>	<code>top = 117px</code>
<code>left-[30%]</code>	<code>left = 30%</code>

10. Z-Index

Class	काम
<code>z-0</code>	z-index 0
<code>z-10</code>	z-index 10
<code>z-20</code>	z-index 20
<code>z-30</code>	z-index 30
<code>z-40</code>	z-index 40
<code>z-50</code>	z-index 50
<code>z-auto</code>	auto
<code>-z-10</code>	negative z-index
<code>z-[999]</code>	 custom z-index

11. Width

Class	CSS/Meaning
<code>w-0</code>	0
<code>w-px</code>	1px
<code>w-1</code>	theme spacing
<code>w-4</code>	1rem
<code>w-8</code>	2rem
<code>w-16</code>	4rem
<code>w-32</code>	8rem
<code>w-1/2</code>	50%
<code>w-1/3</code>	33.333%

w-1/3	33.333%
w-2/3	66.667%
w-1/4	25%
w-3/4	75%
w-full	100%
w-screen	100vw
w-auto	auto
w-fit	fit-content
w-min	min-content
w-max	max-content
w-[350px]	Custom width

12. Min/Max Width

Class	काम
<code>min-w-0</code>	minimum width 0
<code>min-w-full</code>	minimum 100%
<code>min-w-fit</code>	fit-content
<code>min-w-min</code>	min-content
<code>min-w-max</code>	max-content
<code>max-w-none</code>	No max-width
<code>max-w-xs</code>	Small max-width
<code>max-w-sm</code>	Small
<code>max-w-md</code>	Medium
<code>max-w-lg</code>	Large



Tailwind_css_part_1

max-w-lg		Large
max-w-xl		XL
max-w-2xl		2XL
max-w-3xl		3XL
max-w-4xl		4XL
max-w-5xl		5XL
max-w-6xl		6XL
max-w-7xl		7XL
max-w-full		100%
max-w-screen-lg		screen max
	↓	
max-w-[800px]		Custom

13. Height

Class	Meaning
<code>h-0</code>	0
<code>h-px</code>	1px
<code>h-4</code>	1rem
<code>h-8</code>	2rem
<code>h-16</code>	4rem
<code>h-1/2</code>	50%
<code>h-1/3</code>	33.33%
<code>h-full</code>	100%
<code>h-screen</code>	100vh
<code>h-auto</code>	auto



<code>h-auto</code>	auto
<code>h-fit</code>	fit-content
<code>h-min</code>	min-content
<code>h-max</code>	max-content
<code>h-[500px]</code>	custom

14. Min/Max Height

Class	काम
<code>min-h-0</code>	min-height 0
<code>min-h-full</code>	100%
<code>min-h-screen</code>	100vh
<code>min-h-screen</code>	100vh
<code>min-h-dvh</code>	dynamic viewport height
<code>min-h-svh</code>	small viewport height
<code>min-h-lvh</code>	large viewport height
<code>max-h-full</code>	max 100%
<code>max-h-screen</code>	max 100vh
<code>max-h-[500px]</code>	custom

15. Margin

Tailwind spacing utilities theme spacing scale से values लेती हैं।

Class	CSS
<code>m-0</code>	margin 0
<code>m-1</code>	small margin
<code>m-2</code>	0.5rem
<code>m-4</code>	1rem
<code>m-8</code>	2rem
<code>m-auto</code>	margin auto
<code>mx-4</code>	left + right
<code>my-4</code>	top + bottom
<code>mt-4</code>	top
<code>mt-4</code>	top
<code>mr-4</code>	right
<code>mb-4</code>	bottom
<code>ml-4</code>	left
<code>ms-4</code>	logical start
<code>me-4</code>	logical end

16. Negative Margin

Class	काम
<code>-m-4</code>	negative all margin
<code>-mt-4</code>	negative top
<code>-mr-4</code>	negative right
<code>-mb-4</code>	negative bottom
<code>-ml-4</code>	negative left
<code>-mx-4</code>	negative horizontal
<code>-my-4</code>	negative vertical

17. Padding

Class	Meaning
<code>p-0</code>	all padding 0
<code>p-1</code>	small
<code>p-2</code>	0.5rem
<code>p-4</code>	1rem
<code>p-8</code>	2rem
<code>px-4</code>	left/right
<code>py-4</code>	top/bottom
<code>pt-4</code>	top
<code>pr-4</code>	right
<code>pb-4</code>	bottom

<code>pb-4</code>	bottom
<code>pl-4</code>	left
<code>ps-4</code>	logical start
<code>pe-4</code>	logical end

18. Space Between Children

Class	काम
<code>space-x-4</code>	Horizontal children के बीच
<code>space-y-4</code>	Vertical children के बीच
<code>space-x-reverse</code>	Horizontal direction reverse
<code>space-y-reverse</code>	Vertical direction reverse

Difference:

<code>gap-4</code>	<code>space-y-4</code>
Grid/Flex <code>gap</code>	Children के बीच margin-based spacing
Modern preferred	Nested layouts में behavior अलग हो सकता है

19. Gap

Class	Meaning
<code>gap-0</code>	No gap
<code>gap-1</code>	small
<code>gap-2</code>	0.5rem
<code>gap-4</code>	1rem

<code>gap-4</code>	1rem
<code>gap-8</code>	2rem
<code>gap-x-4</code>	column gap
<code>gap-y-4</code>	row gap
<code>gap-[30px]</code>	custom

20. Flexbox — Container

Class	CSS	काम
<code>flex</code>	<code>display:flex</code>	Flex container
<code>inline-flex</code>	<code>inline-flex</code>	Inline flex

21. Flex Direction

Class	CSS
<code>flex-row</code>	row
<code>flex-row-reverse</code>	row-reverse
<code>flex-col</code>	column
<code>flex-col-reverse</code>	column-reverse

22. Flex Wrap

Class	CSS	काम
<code>flex-wrap</code>	wrap	अगली line allowed
<code>flex-nowrap</code>	nowrap	same line
<code>flex-wrap-reverse</code>	wrap-reverse	reverse wrap

23. Justify Content

Class	CSS	Meaning
<code>justify-normal</code>	normal	default
<code>justify-start</code>	flex-start	शुरुआत
<code>justify-end</code>	flex-end	अंत
<code>justify-center</code>	center	center
<code>justify-between</code>	space-between	बीच में space
<code>justify-around</code>	space-around	आसपास space
<code>justify-evenly</code>	space-evenly	बराबर space
<code>justify-stretch</code>	stretch	stretch

24. Align Items

Class	CSS	काम
<code>items-start</code>	flex-start	ऊपर/start
<code>items-end</code>	flex-end	end
<code>items-center</code>	center	center
<code>items-baseline</code>	baseline	text baseline
<code>items-stretch</code>	stretch	stretch

25. Align Self

Class	Meaning
<code>self-auto</code>	parent alignment
<code>self-start</code>	start
<code>self-end</code>	end
<code>self-center</code>	center
<code>self-stretch</code>	stretch
<code>self-baseline</code>	baseline

26. Align Content

Class	Meaning
<code>content-normal</code>	normal
<code>content-center</code>	center
<code>content-start</code>	start
<code>content-end</code>	end
<code>content-between</code>	between
<code>content-around</code>	around
<code>content-evenly</code>	evenly
<code>content-baseline</code>	baseline
<code>content-stretch</code>	stretch



27. Flex Gr

Class

27. Flex Grow/Shrink

Class	Meaning
<code>grow</code>	<code>flex-grow:1</code>
<code>grow-0</code>	grow बंद
<code>shrink</code>	shrink allowed
<code>shrink-0</code>	shrink बंद
<code>flex-1</code>	flexible remaining space
<code>flex-auto</code>	auto
<code>flex-initial</code>	initial
<code>flex-none</code>	grow/shrink नहीं

28. Flex Basis

Class	Meaning
<code>basis-0</code>	basis 0
<code>basis-full</code>	100%
<code>basis-1/2</code>	50%
<code>basis-1/3</code>	33.33%
<code>basis-auto</code>	auto
<code>basis-[300px]</code>	custom

29. Order

Class	Meaning
<code>order-first</code>	सबसे पहले
<code>order-last</code>	सबसे बाद
<code>order-none</code>	default
<code>order-1</code>	order 1
<code>order-2</code>	order 2
<code>order-3</code>	order 3
<code>order-[10]</code>	custom

4d52a88c7e4

30. Grid Container

Class	Meaning
<code>grid</code>	display grid
<code>inline-grid</code>	inline grid

31. Grid Columns

Class	Meaning
<code>grid-cols-1</code>	1 column
<code>grid-cols-2</code>	2
<code>grid-cols-3</code>	3
<code>grid-cols-4</code>	4



<code>grid-cols-5</code>	5
<code>grid-cols-6</code>	6
<code>grid-cols-7</code>	7
<code>grid-cols-8</code>	8
<code>grid-cols-9</code>	9
<code>grid-cols-10</code>	10
<code>grid-cols-11</code>	11
<code>grid-cols-12</code>	12
<code>grid-cols-none</code>	none
<code>grid-cols-[200px_1fr_200px]</code>	custom

32. Grid Rows

Class	Meaning
<code>grid-rows-1</code>	1 row
<code>grid-rows-2</code>	2
<code>grid-rows-3</code>	3
<code>grid-rows-4</code>	4
<code>grid-rows-6</code>	6
<code>grid-rows-none</code>	none
<code>grid-rows-[auto_1fr_auto]</code>	custom

33. Column Span

Class	Meaning
<code>col-span-1</code>	1 column
<code>col-span-2</code>	2
<code>col-span-3</code>	3
<code>col-span-4</code>	4
<code>col-span-6</code>	6
<code>col-span-12</code>	12
<code>col-span-full</code>	full
<code>col-span-[5]</code>	custom

34. Column Start/End

Class	काम
<code>col-start-1</code>	column line 1
<code>col-start-3</code>	line 3
<code>col-end-4</code>	line 4
<code>col-end-13</code>	line 13
<code>col-start-auto</code>	auto
<code>col-end-auto</code>	auto

35. Row Span

Class	Meaning
<code>row-span-1</code>	1 row
<code>row-span-2</code>	2
<code>row-span-3</code>	3
<code>row-span-full</code>	full

36. Grid Flow

Class	CSS
<code>grid-flow-row</code>	row
<code>grid-flow-col</code>	column
<code>grid-flow-dense</code>	dense packing
<code>grid-flow-row-dense</code>	row + dense
<code>grid-flow-col-dense</code>	column + dense

37. Auto Columns/Rows

Class	Meaning
<code>auto-cols-auto</code>	auto
<code>auto-cols-min</code>	min-content
<code>auto-cols-max</code>	max-content
<code>auto-cols-fr</code>	fraction
<code>auto-rows-auto</code>	auto
<code>auto-rows-min</code>	min-content
<code>auto-rows-max</code>	max-content
<code>auto-rows-fr</code>	fraction



38. Place Content

Class	Meaning
<code>place-content-center</code>	दोनों axes center
<code>place-content-start</code>	start
<code>place-content-end</code>	end
<code>place-content-between</code>	between
<code>place-content-around</code>	around
<code>place-content-evenly</code>	evenly
<code>place-content-stretch</code>	stretch

39. Place Items

Class	Meaning
<code>place-items-start</code>	start
<code>place-items-end</code>	end
<code>place-items-center</code>	center
<code>place-items-baseline</code>	baseline
<code>place-items-stretch</code>	stretch

40. Place Self

Class	Meaning
<code>place-self-auto</code>	auto
<code>place-self-start</code>	start
<code>place-self-end</code>	end
<code>place-self-center</code>	center
<code>place-self-stretch</code>	stretch

41. Typography — Font Family

Class	Meaning
<code>font-sans</code>	Sans-serif
<code>font-serif</code>	Serif
<code>font-mono</code>	Monospace
<code>font-[Inter]</code>	Custom font
<code>font-(--font-body)</code>	CSS variable font

Theme variables जैसे `--font-*` font-family utilities generate करते हैं। 

42. Font Size

Class	Typical Meaning
<code>text-xs</code>	Extra small
<code>text-sm</code>	Small
<code>text-base</code>	Base
<code>text-lg</code>	Large
<code>text-xl</code>	XL
<code>text-2xl</code>	2XL
<code>text-3xl</code>	3XL
<code>text-4xl</code>	4XL
<code>text-5xl</code>	5XL
<code>text-6xl</code>	6XL
<code>text-6xl</code>	6XL
<code>text-7xl</code>	7XL
<code>text-8xl</code>	8XL
<code>text-9xl</code>	9XL
<code>text-[22px]</code>	Custom

43. Font Weight

Class	CSS Meaning
<code>font-thin</code>	100
<code>font-extralight</code>	200
<code>font-light</code>	300
<code>font-normal</code>	400
<code>font-medium</code>	500
<code>font-semibold</code>	600
<code>font-bold</code>	700
<code>font-extrabold</code>	800
<code>font-black</code>	900



44. Font Style

Class	CSS
<code>italic</code>	<code>italic</code>
<code>not-italic</code>	<code>normal</code>

45. Text Alignment

Class	CSS
<code>text-left</code>	<code>left</code>
<code>text-center</code>	<code>center</code>
<code>text-right</code>	<code>right</code>
<code>text-justify</code>	<code>justify</code>



text-start	logical start
------------	---------------

text-end	logical end
----------	-------------

46. Line Height

Class	Meaning
leading-none	very tight
leading-tight	tight
leading-snug	snug
leading-normal	normal
leading-relaxed	relaxed
leading-loose	loose



TABLE 4000104		
leading-loose		loose
leading-6	leading-6	spacing value
leading-[1.8]	leading-	custom

47. Letter Spacing

Class		Meaning
tracking-tighter		कम spacing
tracking-tight		थोड़ा कम
tracking-normal		normal
tracking-wide		ज्यादा
tracking-wider	↓	और ज्यादा

<code>tracking-widest</code>	बहुत ज्यादा
------------------------------	-------------

<code>tracking-[2px]</code>	custom
-----------------------------	--------

48. Text Transform

Class	CSS
<code>uppercase</code>	uppercase
<code>lowercase</code>	lowercase
<code>capitalize</code>	Capitalize
<code>normal-case</code>	normal