

95. Transform — Scale

Class	Meaning
<code>scale-50</code>	50%
<code>scale-75</code>	75%
<code>scale-90</code>	90%
<code>scale-95</code>	95%
<code>scale-100</code>	normal
<code>scale-105</code>	105%
<code>scale-110</code>	110%
<code>scale-125</code>	125%
<code>scale-150</code>	150%
<code>scale-[1.35]</code>	custom



96. Transform — Rotate

Class	Meaning
<code>rotate-0</code>	0°
<code>rotate-1</code>	1°
<code>rotate-45</code>	45°
<code>rotate-90</code>	90°
<code>rotate-180</code>	180°
<code>-rotate-45</code>	-45°
<code>rotate-[30deg]</code>	custom

97. Transform — Translate

Class	Meaning
<code>translate-x-0</code>	0
<code>translate-x-4</code>	+spacing
<code>translate-x-1/2</code>	+50%
<code>-translate-x-4</code>	negative
<code>translate-y-4</code>	Y positive
<code>-translate-y-4</code>	Y negative
<code>translate-x-[20px]</code>	custom

98. Transform — Skew

Class	Meaning
<code>skew-x-0</code>	0
<code>skew-x-6</code>	X 6°
<code>skew-x-12</code>	X 12°
<code>-skew-x-6</code>	negative
<code>skew-y-6</code>	Y 6°

99. Transform Origin

Class	Meaning
<code>origin-center</code>	center
<code>origin-top</code>	top
<code>origin-top-right</code>	top-right
<code>origin-right</code>	right
<code>origin-bottom-right</code>	bottom-right
<code>origin-bottom</code>	bottom
<code>origin-bottom-left</code>	bottom-left
<code>origin-left</code>	left
<code>origin-top-left</code>	top-left
<code>origin-[50%_20%]</code>	custom



100. Animation

Class	काम
<code>animate-none</code>	animation none
<code>animate-spin</code>	continuous rotation
<code>animate-ping</code>	expanding pulse
<code>animate-pulse</code>	fade pulse
<code>animate-bounce</code>	bounce
<code>animate-[wiggle_1s_ease-in-out]</code>	custom animation

101. Filters — Blur

Class	Meaning
<code>blur-none</code>	none
<code>blur-xs</code>	extra small
<code>blur-sm</code>	small
<code>blur</code>	default
<code>blur-md</code>	medium
<code>blur-lg</code>	large
<code>blur-xl</code>	XL
<code>blur-2xl</code>	2XL
<code>blur-3xl</code>	3XL
<code>blur-[5px]</code>	custom

102. Brightness

Class	Meaning
<code>brightness-50</code>	50%
<code>brightness-75</code>	75%
<code>brightness-90</code>	90%
<code>brightness-100</code>	normal
<code>brightness-110</code>	brighter
<code>brightness-125</code>	more
<code>brightness-150</code>	much more
<code>brightness-200</code>	 2x

103. Contrast

Class	Meaning
<code>contrast-0</code>	0
<code>contrast-50</code>	50%
<code>contrast-75</code>	75%
<code>contrast-100</code>	normal
<code>contrast-125</code>	125%
<code>contrast-150</code>	150%
<code>contrast-200</code>	200%

104. Grayscale

Class	Meaning
<code>grayscale-0</code>	normal
<code>grayscale</code>	grayscale

105. Hue Rotate

Class	Meaning
<code>hue-rotate-0</code>	0
<code>hue-rotate-15</code>	15°
<code>hue-rotate-30</code>	30°
<code>hue-rotate-60</code>	60°
<code>hue-rotate-90</code>	90°



hue-rotate-90	90°
---------------	-----

hue-rotate-180	180°
----------------	------

106. Invert

Class	Meaning
invert	invert
invert-0	normal

107. Saturate

Class	Meaning
saturate-0	0
saturate-50	50%
saturate-100	normal
saturate-150	150%
saturate-200	200%

108. Sepia

Class	Meaning
<code>sepia</code>	sepia
<code>sepia-0</code>	none

109. Drop Shadow

Class	Meaning
<code>drop-shadow-xs</code>	small
<code>drop-shadow-sm</code>	small
<code>drop-shadow</code>	default
<code>drop-shadow-md</code>	medium
<code>drop-shadow-lg</code>	large



drop-shadow-xl	XL
drop-shadow-2xl	2XL
drop-shadow-none	none

110. Backdrop Blur

Class	Meaning
backdrop-blur-none	none
backdrop-blur-xs	small
backdrop-blur-sm	small
backdrop-blur	normal
backdrop-blur-md	medium



<code>backdrop-blur-md</code>	medium
<code>backdrop-blur-lg</code>	large
<code>backdrop-blur-xl</code>	XL
<code>backdrop-blur-2xl</code>	2XL
<code>backdrop-blur-3xl</code>	3XL

111. Backdrop Brightness/Contrast

Pattern	Example
<code>backdrop-brightness-*</code>	<code>backdrop-brightness-75</code>
<code>backdrop-contrast-*</code>	<code>backdrop-contrast-125</code>
<code>backdrop-grayscale</code>	 grayscale

<code>backdrop-invert</code>	invert
<code>backdrop-opacity-*</code>	opacity
<code>backdrop-saturate-*</code>	saturation
<code>backdrop-sepia</code>	sepia
<code>backdrop-blur-*</code>	blur

112. List Style

Class	Meaning
<code>list-none</code>	no marker
<code>list-disc</code>	bullets
<code>list-decimal</code>	numbers
<code>list-[square]</code>	custom
<code>list-inside</code>	marker inside
<code>list-outside</code>	marker outside

113. Placeholder

Class	Meaning
<code>placeholder:text-gray-500</code>	placeholder color
<code>placeholder:opacity-50</code>	opacity
<code>placeholder:italic</code>	italic
<code>placeholder:text-sm</code>	size

114. Caret

Class	काम
<code>caret-blue-500</code>	typing cursor color
<code>caret-transparent</code>	cursor invisible
<code>caret-current</code>	current color
<code>caret-[red]</code>	custom

115. Tables

Class	Meaning
<code>border-collapse</code>	borders collapse
<code>border-separate</code>	separate borders
<code>border-spacing-0</code>	spacing 0
<code>border-spacing-2</code>	spacing
<code>caption-top</code>	caption top
<code>caption-bottom</code>	caption bottom
<code>table-auto</code>	automatic table layout
<code>table-fixed</code>	fixed table layout

116. SVG

Class	Meaning
<code>fill-current</code>	SVG fill <code>currentColor</code>
<code>fill-none</code>	no fill
<code>fill-blue-500</code>	fill color
<code>stroke-current</code>	stroke <code>currentColor</code>
<code>stroke-blue-500</code>	stroke color
<code>stroke-0</code>	stroke width 0
<code>stroke-1</code>	stroke width 1
<code>stroke-2</code>	stroke width 2

117. Accessibility Variants

Variant	Meaning
<code>aria-checked:</code>	ARIA checked
<code>aria-disabled:</code>	ARIA disabled
<code>aria-expanded:</code>	expanded
<code>aria-hidden:</code>	hidden
<code>aria-pressed:</code>	pressed
<code>aria-selected:</code>	selected
<code>aria-[sort=ascending]:</code>	custom ARIA value

118. Important state variants

Tailwind का सबसे powerful हिस्सा variants हैं—लगभग किसी भी utility के आगे variant लगाकर उसे conditional बनाया जा सकता है। 

Variant	CSS State/Condition
hover:	:hover
focus:	:focus
focus-within:	descendant focused
focus-visible:	keyboard-visible focus
active:	pressed
visited:	visited link
target:	URL target
disabled:	disabled
enabled:	enabled

Tailwind_css_part_3

enabled:	enabled
checked:	checked
indeterminate:	indeterminate
default:	default option
required:	required
valid:	valid
invalid:	invalid
in-range:	range valid
out-of-range:	range invalid
placeholder-shown:	placeholder visible
autofill:	autofill



<code>autofill:</code>	autofill
<code>read-only:</code>	readonly
<code>empty:</code>	empty element

119. Structural Variants

Variant	Meaning
<code>first:</code>	first child
<code>last:</code>	last child
<code>only:</code>	only child
<code>odd:</code>	odd child
<code>even:</code>	even child



<code>even:</code>	even child
<code>first-of-type:</code>	first of type
<code>last-of-type:</code>	last of type
<code>only-of-type:</code>	only of type
<code>nth-3:</code>	nth child
<code>nth-last-3:</code>	nth from end
<code>nth-of-type-3:</code>	nth type
<code>empty:</code>	no children

Tailwind nth-child और अन्य structural pseudo-class variants भी support करता है।

120. Group Variant

Code	काम
Parent: <code>group</code>	Parent को group mark करता है
Child: <code>group-hover:text-blue-500</code>	Parent hover होने पर child blue
<code>group-focus:</code>	Parent focus
<code>group-active:</code>	Parent active
<code>group-disabled:</code>	Parent disabled
<code>group-hover:scale-110</code>	Parent hover → child scale

Example

HTML

```
<div class="group">
```

Result

Parent

```
<span class="group-hover:text-red-500">
```

Parent hover पर red

121. Named Group

Class

Meaning

```
group/item
```

Named group

```
group-hover/item:*
```

उसी named group की hover state

```
group/edit
```

दूसरा group



```
group-focus/edit:*
```

edit group focus

122. Peer Variant

Class

Meaning

```
peer
```

Element को peer बनाओ

```
peer-checked:*
```

peer checked होने पर

```
peer-focus:*
```

peer focused

```
peer-invalid:*
```

peer invalid

```
peer-placeholder-shown:*
```

peer placeholder state

123. Dark Mode

Class	Meaning
<code>dark:bg-black</code>	dark mode में black
<code>dark:text-white</code>	dark mode में white
<code>dark:border-gray-700</code>	dark mode border

Tailwind dark variant को color-scheme/media या custom selector strategy के साथ use कर सकता है।  Tailwind CSS

126. Container Queries

Tailwind viewport के अलावा **parent container के size** के आधार पर भी responsive styling करता है।  Tailwind CSS

Class	Meaning	
<code>@container</code>	Parent को query container	
<code>@sm:</code>	container $\geq 24\text{rem}$	
<code>@md:</code>	container $\geq 28\text{rem}$	
<code>@lg:</code>	container $\geq 32\text{rem}$	
<code>@xl:</code>	container $\geq 36\text{rem}$	
<code>@2xl:</code>	container $\geq 42\text{rem}$	
<code>@3xl:</code>	container $\geq 48\text{rem}$	
<code>@4xl:</code>	container $\geq 56\text{rem}$	



@4xl:	container ≥ 56rem
@5xl:	container ≥ 64rem
@6xl:	container ≥ 72rem
@7xl:	container ≥ 80rem

127. Container Query Example

Code	Meaning
@container	parent container query
flex flex-col @md:flex-row	container 28rem+ होने पर row
@max-md:block	container md से छोटा
@min-[475px]:flex-row	↓ custom container width

128. Child Variants

Variant	Meaning
*:	direct children
**:	all descendants
*: + utility	direct child styling
** + utility	nested descendants

Tailwind * और ** variants से parent से descendants को style कर सकता है।

129. Data Attribute Variants

Class	Meaning
<code>data-active:*</code>	<code>data-active</code> exists
<code>data-[size=large]:p-8</code>	specific data value
<code>group-data-active:*</code>	parent data state
<code>peer-data-active:*</code>	peer data state

130. Arbitrary Variants

Class	Meaning
<code>[&:hover]:bg-red-500</code>	custom hover selector
<code>[&_p]:mt-4</code>	descendants <code>p</code>
<code>[&>div]:p-4</code>	direct div children
<code>[&.active]:text-red-500</code>	<code>.active</code> state
<code>[@supports(display:grid)]:grid</code>	supports query

Arbitrary variants custom CSS selectors/at-rules को सीधे class में लिखने देते हैं।

131. Arbitrary Values — सबसे Powerful Feature

Syntax	Example	Meaning
<code>[value]</code>	<code>w-[347px]</code>	custom width
<code>#[hex]</code>	<code>bg-#[1da1f2]</code>	custom color
<code>[calc(...)]</code>	<code>w-[calc(100%-20px)]</code>	calculation
<code>[url(...)]</code>	<code>bg-[url('/a.jpg')]</code>	custom image
<code>(--var)</code>	<code>bg-(--brand)</code>	CSS variable
<code>[var(...)]</code>	<code>bg-[var(--brand)]</code>	explicit variable
<code>[property:value]</code>	<code>[mask-type:luminance]</code>	arbitrary CSS property

132. Arbitrary CSS Properties

अगर Tailwind में किसी CSS property की built-in utility नहीं है:

CSS	Tailwind
<code>mask-type:luminance</code>	<code>[mask-type:luminance]</code>
<code>content-visibility:auto</code>	<code>[content-visibility:auto]</code>
<code>text-wrap:balance</code>	<code>[text-wrap:balance]</code>
<code>scrollbar-color:red</code>	<code>[scrollbar-color:red]</code>
<code>writing-mode:vertical-rl</code>	<code>[writing-mode:vertical-rl]</code>

इसका मतलब Tailwind आपको framework की predefined utility list तक सीमित नहीं करता।

133. CSS Variables

Syntax	Meaning
<code>bg(--color)</code>	<code>background-color:var(--color)</code>
<code>text(--color)</code>	text color variable
<code>w(--width)</code>	width variable
<code>p(--spacing)</code>	padding variable
<code>[--my-value:20px]</code>	element पर custom variable
<code>bg-[var(--my-color)]</code>	variable explicitly

134. Tailwind Theme Variables

Tailwind v4 में `@theme` design tokens define करता है और उन्हीं tokens से utility classes generate हो सकती हैं। 

Namespace	क्या control करता है
<code>--color-*</code>	Colors
<code>--font-*</code>	Font family
<code>--text-*</code>	Font sizes
<code>--font-weight-*</code>	Font weights
<code>--tracking-*</code>	Letter spacing
<code>--leading-*</code>	Line height
<code>--breakpoint-*</code>	Responsive breakpoints
<code>--container-*</code>	Container queries/max sizes

<code>--container-*</code>	Container queries/max sizes
<code>--spacing-*</code>	Spacing/sizing
<code>--radius-*</code>	Border radius
<code>--shadow-*</code>	Box shadows
<code>--inset-shadow-*</code>	Inset shadows
<code>--drop-shadow-*</code>	Drop shadows
<code>--blur-*</code>	Blur
<code>--perspective-*</code>	Perspective
<code>--zoom-*</code>	Zoom
<code>--aspect-*</code>	Aspect ratio
<code>--ease-*</code>	Timing functions



`--ease-*`

Timing functions

`--animate-*`

Animations

135. @theme

Syntax

काम

`@theme { ... }`

Theme variables define

`--color-brand: ...`

Custom brand color

`--font-display: ...`

Custom font

`--breakpoint-tablet: ...`

Custom breakpoint

`--radius-card: ...`

Custom radius

`--shadow-card: ...`

Custom shadow

Example

CSS

```
@theme { --color-brand: #ff6600; }
```

फिर HTML में `bg-brand` / `text-brand` जैसे utilities use कर सकते हो।

136. @import

Code	काम
<code>@import "tailwindcss";</code>	Tailwind को CSS में import
<code>@import "../custom.css";</code>	CSS file import

137. @utility

Custom utility बनाने के लिए:

Syntax	काम
<code>@utility content-auto { ... }</code>	custom utility
<code>content-auto</code>	HTML में usable
<code>hover:content-auto</code>	variants भी काम करेंगे

Official docs के अनुसार custom utilities built-in utilities के साथ utilities layer में add होती हैं।

 Tailwind CSS