

1. Text properties — PDF ke alawa complete important properties

Property / Method	Kya kaam karta hai?	Example	Deep explanation	 Share
<code>text-align</code>	Text ko horizontal direction me align karta hai	<code>text-align: center;</code>	<code>left</code> , <code>right</code> , <code>center</code> , <code>justify</code> , <code>start</code> , <code>end</code> se text ki position/line alignment control hoti hai.	
<code>text-align-last</code>	Last line ko alag align karta hai	<code>text-align-last: center;</code>	Jab paragraph <code>justify</code> ho, tab last line ko separately control kar sakte ho.	
<code>text-indent</code>	First line ko indent karta hai	<code>text-indent: 40px;</code>	Paragraph ki first line 40px andar se start hogi.	
<code>text-transform</code>	Letters ka case change karta hai	<code>text-transform: uppercase;</code>	<code>uppercase</code> , <code>lowercase</code> , <code>capitalize</code> etc. se displayed text ka case control hota hai.	
<code>text-decoration</code>	Text decoration shorthand 	<code>text-decoration: underline;</code>	Underline, overline, line-through ko ek property se set kar sakte ho.	
<code>text-decoration-line</code>	Decoration ka type	<code>text-decoration-line: underline;</code>	Sirf underline/overline/line-through decide karta hai.	
<code>text-decoration-color</code>	Decoration ka color	<code>text-decoration-color: red;</code>	Text black ho sakta hai lekin underline red ho sakti hai.	
<code>text-decoration-style</code>	Decoration ka style	<code>text-decoration-style: wavy;</code>	<code>solid</code> , <code>double</code> , <code>dotted</code> , <code>dashed</code> , <code>wavy</code> etc.	
<code>text-decoration-thickness</code>	Decoration ki thickness	<code>text-decoration-thickness: 3px;</code>	Underline ko thin/thick kar sakte ho.	
<code>text-underline-offset</code>	Underline ki distance	<code>text-underline-offset: 5px;</code>	Text aur underline ke beech gap control karta hai.	
<code>text-shadow</code>	Text par shadow	<code>text-shadow: 2px 2px 5px gray;</code>	Horizontal offset, vertical offset, blur aur color se text shadow banata hai.	

Css part 1

<code>text-overflow</code>	Overflow text ka visual behavior	<code>text-overflow: ellipsis;</code>	Commonly <code>overflow: hidden</code> + <code>white-space: nowrap</code> ke saath <code>...</code> dikhane ke liye use hota hai.
<code>white-space</code>	Spaces aur wrapping control	<code>white-space: nowrap;</code>	Text ko next line me jane se rok sakta hai ya whitespace preserve kar sakta hai.
<code>word-spacing</code>	Words ke beech distance	<code>word-spacing: 10px;</code>	Do words ke beech extra horizontal spacing deta hai.
<code>letter-spacing</code>	Characters ke beech distance	<code>letter-spacing: 2px;</code>	Har character ke beech spacing increase/decrease karta hai.
<code>word-break</code>	Words ko break karne ka rule	<code>word-break: break-all;</code>	Long words ko container ke andar fit karne ke liye break kar sakta hai.
			
<code>overflow-wrap</code>	Long word ko wrap karna	<code>overflow-wrap: anywhere;</code>	Bahut long URL/word container se bahar na nikle, isme useful hai.
<code>hyphens</code>	Word breaking me hyphen	<code>hyphens: auto;</code>	Browser language information ke according words ko hyphen ke saath break kar sakta hai.
<code>direction</code>	Text direction	<code>direction: rtl;</code>	Left-to-right ya right-to-left text direction control karta hai.
<code>vertical-align</code>	Inline/table-cell vertical alignment	<code>vertical-align: middle;</code>	Inline elements ya table cells ke vertical alignment ko control karta hai.
<code>line-height</code>	Lines ke beech vertical distance	<code>line-height: 1.5;</code>	Paragraph/readability me bahut important hai.

2. Font properties — PDF ke topic ka complete expansion

Property	Kya kaam karta hai?	Example	Deep explanation
<code>font-family</code>	Font choose karta hai	<code>font-family: Arial;</code>	Text kis font me render hoga decide karta hai.
<code>font-size</code>	Font ka size	<code>font-size: 20px;</code>	Characters ka visual size control karta hai.
<code>font-weight</code>	Font thickness	<code>font-weight: 700;</code>	<code>100-900</code> numeric weights ya <code>normal/bold</code> use kar sakte ho.
<code>font-style</code>	Font style	<code>font-style: italic;</code>	<code>normal</code> , <code>italic</code> , <code>oblique</code> etc.
<code>font-variant</code>	Font variant	<code>font-variant: small-caps;</code>	Characters ke alternate typographic form ko control karta hai.
<code>font-stretch</code>	Font width	<code>font-stretch: expanded;</code>	Supported variable fonts me glyphs ko wider/narrower style me render kar sakta hai.

<code>font-size-adjust</code>	Font size adjustment	<code>font-size-adjust: 0.5;</code>	Different fallback fonts ke visual size ko more consistent rakhne me help karta hai.
<code>font-kerning</code>	Character-pair spacing	<code>font-kerning: normal;</code>	Particular character pairs ke beech natural typographic spacing control karta hai.
<code>font-feature-settings</code>	Advanced font features	<code>font-feature-settings: "liga";</code>	OpenType font features ko control karne ke liye.
<code>font-variation-settings</code>	Variable font axes	<code>font-variation-settings: "wght" 700;</code>	Variable fonts ke custom axes control kar sakta hai.
<code>font</code>	Font shorthand	<code>font: bold 20px Arial;</code>	Multiple font properties ko ek declaration me likhne ka shorthand.



3. Selectors — PDF ke selectors ke alawa important selectors

Selector / Method	Kya select karta hai?	Example	Deep explanation	
<code>*</code>	Sabhi elements	<code>* { margin: 0; }</code>	Universal selector page ke all elements ko target karta hai.	
<code>element</code>	Specific HTML element	<code>p { color: red; }</code>	Saare <code><p></code> elements select honge.	
<code>.class</code>	Class wale elements	<code>.box { ... }</code>	Same class wale multiple elements select ho sakte hain.	
<code>#id</code>	Specific ID	<code>#header { ... }</code>	Specific ID wale element ko target karta hai.	
<code>A B</code>	Descendant	<code>div p { ... }</code>	<code>div</code> ke andar kahin bhi present <code>p</code> select hota hai.	
<code>A > B</code>	Direct child	 <code>> p { ... }</code>	Sirf direct child <code><p></code> select hota hai.	

Css part 1

<code>A + B</code>	Adjacent sibling	<code>h2 + p { ... }</code>	<code>h2</code> ke immediately baad wala <code>p</code> .
<code>A ~ B</code>	General sibling	<code>h2 ~ p { ... }</code>	<code>h2</code> ke baad same parent ke sibling <code>p</code> elements.
<code>[attr]</code>	Attribute exists	<code>input[required]</code>	Jinke paas <code>required</code> attribute hai.
<code>[attr="value"]</code>	Exact attribute value	<code>input[type="text"]</code> <code>]</code>	Attribute exactly <code>text</code> hona chahiye.
<code>[attr^="value"]</code>	Starts with	<code>[class^="btn"]</code>	Attribute value <code>btn</code> se start honi chahiye.
<code>[attr\$="value"]</code>	Ends with	<code>[class\$="box"]</code>	Attribute value <code>box</code> par end honi chahiye.
<code>[attr*="value"]</code>	Contains	<code>[class*="card"]</code> 	Attribute ke andar <code>card</code> kahin bhi ho.

Css part 1

<code>[attr~="value"]</code>	Space-separated word	<code>[class~="active"]</code>	Attribute value me <code>active</code> ek complete space-separated token ho.
<code>`[attr</code>	<code>= "value"]`</code>	Exact/prefix with <code>-</code>	<code>`[lang</code>
<code>A, B</code>	Group selector	<code>h1, h2 { ... }</code>	Multiple selectors par same CSS apply karta hai.
<code>:not()</code>	Exclude	<code>p:not(.active)</code>	<code>.active</code> ko chhodkar matching <code><p></code> select karta hai.
<code>:is()</code>	Selector group	<code>:is(h1,h2,p)</code>	Multiple alternatives ko short form me group karta hai.
<code>:where()</code>	Zero-specificity group	<code>:where(h1,h2)</code>	Grouping karta hai lekin specificity ko low/zero rakhta hai.
<code>:has()</code>	Relational/parent-like selection	<code>.card:has(img)</code> 	Aise <code>.card</code> ko select karta hai jiske andar <code>img</code> hai.

4. Pseudo-classes — PDF me diye gaye `:hover` , `:active` , `:checked` , `:nth-of-type()` ke alawa



Pseudo-class	Kya kaam karta hai?	Example	Deep explanation
<code>:link</code>	Unvisited link	<code>a:link</code>	Aise <code><a></code> links ko target karta hai jo visit nahi hue.
<code>:visited</code>	Visited link	<code>a:visited</code>	Browser history ke according visited link target karta hai.
<code>:hover</code>	Mouse hover	<code>button:hover</code>	Cursor element ke upar aane par CSS apply hota hai.
<code>:active</code>	Active/clicking state	<code>button:active</code>	User click/press kar raha ho tab state apply hoti hai.
<code>:focus</code>	Focused element	<code>input:focus</code>	Input select/focus hone par style apply hota hai.
<code>:focus-visible</code>	Visible focus state	<code>button:focus-visible</code>	Usually keyboard navigation jaise cases me useful.

Css part 1

<code>:focus-visible</code>	Visible focus state	<code>button:focus-visible</code>	Usually keyboard navigation jai  cases me useful.
<code>:focus-within</code>	Parent contains focus	<code>.form:focus-within</code>	Form ke kisi child par focus ho to parent select hota hai.
<code>:checked</code>	Checked control	<code>input:checked</code>	Checkbox/radio checked hone par.
<code>:disabled</code>	Disabled element	<code>button:disabled</code>	Disabled controls ko target karta hai.
<code>:enabled</code>	Enabled element	<code>input:enabled</code>	Enabled controls ko target karta hai.
<code>:required</code>	Required input	<code>input:required</code>	<code>required</code> attribute wale controls.
<code>:optional</code>	Optional input	<code>input:optional</code> 	Required nahi wale form controls.

Css part 1

<code>:optional</code>	Optional input	<code>input:optional</code>	Required nahi wale form controls.	
<code>:valid</code>	Valid input	<code>input:valid</code>	Validation rules satisfy hone par.	
<code>:invalid</code>	Invalid input	<code>input:invalid</code>	Validation fail hone par.	
<code>:read-only</code>	Read-only control	<code>input:read-only</code>	User edit nahi kar sakta.	
<code>:read-write</code>	Editable control	<code>input:read-write</code>	User edit kar sakta hai.	
<code>:first-child</code>	Parent ka first child	<code>li:first-child</code>	Parent ke andar first child agar <code>li</code> hai to select hoga.	
<code>:last-child</code>	Last child	<code>li:last-child</code>	Parent ka last child.	
<code>:only-child</code>	Only child	<code>p:only-child</code>	Parent ka ek hi child ho aur wo <code>p</code> ho.	
<code>:nth-child(n)</code>	Child position	 <code>li:nth-child(2)</code>	Parent ke children me position ke basis par select karta hai.	

Css part 1

<code>:nth-child(n)</code>	Child position	<code>li:nth-child(2)</code>	Parent ke children me position ke basis par select karta hai. 
<code>:nth-last-child(n)</code>	Reverse child position	<code>li:nth-last-child(2)</code>	Last se counting karta hai.
<code>:first-of-type</code>	First same-type element	<code>p:first-of-type</code>	Parent ke andar first <code><p></code> .
<code>:last-of-type</code>	Last same-type element	<code>p:last-of-type</code>	Parent ke andar last <code><p></code> .
<code>:only-of-type</code>	Only same-type	<code>p:only-of-type</code>	Parent ke andar sirf ek <code><p></code> ho.
<code>:nth-of-type(n)</code>	Same type ki position	<code>p:nth-of-type(2)</code>	Sirf <code><p></code> elements ko count karke second select karta hai.
<code>:nth-last-of-type(n)</code>	Reverse type position	<code>p:nth-last-of-type(2)</code>	Same type ko last se count karta hai.
<code>:empty</code>	Empty element	 <code>div:empty</code>	Jiske andar text/child content nahi hai.

Css part 1

<code>:empty</code>	Empty element	<code>div:empty</code>	Jiske andar text/child content nahi hai.	 S
<code>:root</code>	Document root	<code>:root</code>	HTML document me normally <code><html></code> ko target karta hai.	
<code>:not()</code>	Condition exclude	<code>p:not(.red)</code>	<code>.red</code> ko exclude karta hai.	
<code>:is()</code>	Alternatives group	<code>:is(h1,h2,h3)</code>	Multiple selectors ko ek selector me group karta hai.	
<code>:where()</code>	Low-specificity group	<code>:where(h1,h2)</code>	Grouping with zero specificity.	
<code>:has()</code>	Related element check	<code>.card:has(button)</code>	Button-containing cards ko select kar sakta hai.	

5. Pseudo-elements — PDF ke `::first-letter` / `::first-line` ke alawa

Pseudo-element	Kya kaam karta hai?	Example	Deep explanation	 Share 
<code>::before</code>	Element ke content se pehle generated content	<code>.box::before</code>	<code>content</code> property ke saath decorative content add karne me use hota hai.	
<code>::after</code>	Element ke content ke baad generated content	<code>.box::after</code>	Icons, decorations, overlays etc. me useful.	
<code>::first-letter</code>	First letter	<code>p::first-letter</code>	Paragraph ki first letter ko separately style kar sakta hai.	
<code>::first-line</code>	First line	<code>p::first-line</code>	Paragraph ki currently rendered first line ko style karta hai.	
<code>::selection</code>	Selected text	<code>p::selection</code>	User text select kare to selected area ka color/background change kar sakte ho.	
<code>::marker</code>	List marker	 <code>li::marker</code>	<code></code> ke bullet/number ko style karta hai.	

Css part 1

<code>::marker</code>	List marker	<code>li::marker</code>	<code></code> ke bullet/number ko style karta hai.
<code>::placeholder</code>	Input placeholder	<code>input::placeholder</code>	Placeholder text ko style karta hai.
<code>::file-selector-button</code>	File input button	<code>input::file-selector-button</code>	<code><input type="file"></code> ke button ko style karta hai.
<code>::backdrop</code>	Fullscreen/dialog backdrop	<code>dialog::backdrop</code>	Dialog/modal ke peeche wale backdrop ko style karne ke liye.

6. Specificity / Cascade — PDF ke topic ko complete karne ke liye

Concept	Kya kaam karta hai?	Priority / Meaning
Universal selector <code>*</code>	All elements target	Specificity contribution normally <code>0</code>
Element selector	<code>p</code> , <code>div</code>	Low specificity
Class selector	<code>.box</code>	Element se higher
Attribute selector	<code>[type="text"]</code>	Class-level specificity
Pseudo-class	<code>:hover</code>	Class-level specificity
ID selector	<code>#box</code>	Class/element se higher
Inline style	<code>style="color:red"</code>	Normal author rules se higher
<code>!important</code>	Declaration ko higher priority deta hai	Normal cascade ko override kar sakta hai; unnecessary use avoid karo
Source order	Same specificity me later	Jo matching rule baad me aata hai,

7. Inheritance — PDF ke inherit ke alawa

Value / Method	Kya karta hai?	Example	Deep explanation	
inherit	Parent ki computed value leta hai	color: inherit;	Child explicitly parent ki property value use karta hai.	
initial	Property ki initial specification value	color: initial;	Browser/user styles par depend karne ke bajay property's initial value apply karta hai.	
unset	Context ke according inherit/initial	color: unset;	Agar property naturally inherited hai to inherit, otherwise initial behavior.	
revert	Earlier cascade behavior par return	color: revert;	Current author rule ko undo karke earlier cascade/user-agent behavior use karne me help karta hai.	
revert-layer	Previous cascade layer par revert	color: revert-layer;	Current cascade layer ki styling ko undo karke previous layer ki value use karta hai.	

8. Width / Height — PDF ke `width / height` ka complete expansion

Property	Kya kaam karta hai?	Example	Deep explanation	
<code>width</code>	Element ki width	<code>width: 300px;</code>	Default box model me content width set karta hai.	
<code>height</code>	Element ki height	<code>height: 200px;</code>	Default box model me content height set karta hai.	
<code>min-width</code>	Minimum width	<code>min-width: 200px;</code>	Element isse chhota nahi hoga, subject to layout constraints.	
<code>max-width</code>	Maximum width	<code>max-width: 1000px;</code>	Element isse bada nahi hoga. Responsive layouts me very useful.	
<code>min-height</code>	Minimum height	<code>min-height: 200px;</code>	Element ki minimum height maintain karta hai.	
<code>max-height</code>	Maximum height	<code>max-height: 500px;</code>	Element ki maximum height limit karta hai.	
<code>min-height</code>	Minimum height	<code>min-height: 200px;</code>	Element ki minimum height maintain karta hai.	
<code>max-height</code>	Maximum height	<code>max-height: 500px;</code>	Element ki maximum height limit karta hai.	
<code>aspect-ratio</code>	Width/height ratio	<code>aspect-ratio: 16 / 9;</code>	Box ko particular ratio maintain karne me help karta hai.	

9. Border — PDF me diye properties ke alawa complete important properties

Property	Kya kaam karta hai?	Example	Deep explanation
<code>border-top-width</code>	Top border thickness	<code>border-top-width: 5px;</code>	Sirf top border ki width.
<code>border-right-width</code>	Right border thickness	<code>border-right-width: 5px;</code>	Sirf right border.
<code>border-bottom-width</code>	Bottom border thickness	<code>border-bottom-width: 5px;</code>	Sirf bottom border.
<code>border-left-width</code>	Left border thickness	<code>border-left-width: 5px;</code>	Sirf left border.
<code>border-top-style</code>	Top border style	<code>border-top-style: dashed;</code>	Top border solid/dashed/dotted etc.
<code>border-right-style</code>	Right style	<code>border-right-style: dotted;</code>	Right border style.

Css part 1

<code>border-right-style</code>	Right style	<code>border-right-style: dotted;</code>	Right border style.
<code>border-bottom-style</code>	Bottom style	<code>border-bottom-style: double;</code>	Bottom border style.
<code>border-left-style</code>	Left style	<code>border-left-style: dashed;</code>	Left border style.
<code>border-top-color</code>	Top color	<code>border-top-color: red;</code>	Sirf top border ka color.
<code>border-right-color</code>	Right color	<code>border-right-color: blue;</code>	Sirf right border ka color.
<code>border-bottom-color</code>	Bottom color	<code>border-bottom-color: green;</code>	Sirf bottom border ka color.
<code>border-left-color</code>	Left color	 <code>border-left-color: orange;</code>	Sirf left border ka color.

Css part 1

<code>border-left-color</code>	Left color	<code>border-left-color: orange;</code>	Sirf left border ka color.	
<code>border-top-left-radius</code>	Top-left corner rounding	<code>border-top-left-radius: 20px;</code>	Sirf top-left corner round karta hai.	
<code>border-top-right-radius</code>	Top-right rounding	<code>border-top-right-radius: 20px;</code>	PDF me ye already example ke roop me hai.  CSS	
<code>border-bottom-right-radius</code>	Bottom-right rounding	<code>border-bottom-right-radius: 20px;</code>	Bottom-right corner.	
<code>border-bottom-left-radius</code>	Bottom-left rounding	<code>border-bottom-left-radius: 20px;</code>	Bottom-left corner.	
<code>border-image</code>	Image/gradient ko border ki tarah use	<code>border-image: url(x.png) 30;</code>	Normal solid border ki jagah image-based border bana sakta hai.	

<code>border-image-source</code>	Border image source	<code>border-image-source: url(x.png);</code>	Border image kaha se aayegi.
<code>border-image-slice</code>	Image ko slices me divide	<code>border-image-slice: 30;</code>	Border image ke portions define karta hai.
<code>border-image-width</code>	Image border width	<code>border-image-width: 10px;</code>	Border image ki displayed thickness.
<code>border-image-repeat</code>	Image repeat/stretch	<code>border-image-repeat: stretch;</code>	Border image edges ka repeat/stretch behavior.
<code>border-image-outset</code>	Border image outward extend	<code>border-image-outset: 5px;</code>	Border image border box se bahar extend kar sakti hai.
<code>border-collapse</code>	Table borders merge	<code>border-collapse: collapse;</code>	Table cells ke adjacent borders ko collapse karta hai.

`border-spacing`

Table cells ke beech
gap

`border-spacing:
10px;`

Separate table borders me cells
ke beech spacing.

10. Padding — PDF ke shorthand ke alawa

Property	Kya kaam karta hai?	Example	Deep explanation 
<code>padding</code>	Four sides ka shorthand	<code>padding: 10px 20px 30px 40px;</code>	Order: top → right → bottom → left. PDF me ye 4-value method shown hai.  CSS
<code>padding-top</code>	Top inner space	<code>padding-top: 20px;</code>	Content aur top border ke beech gap.
<code>padding-right</code>	Right inner space	<code>padding-right: 20px;</code>	Content aur right border ke beech gap.
<code>padding-bottom</code>	Bottom inner space	<code>padding-bottom: 20px;</code> 	Content aur bottom border ke beech gap.

<code>padding-left</code>	Left inner space	<code>padding-left: 20px;</code>	Content aur left border ke beech gap.
---------------------------	------------------	----------------------------------	---------------------------------------

11. Margin — PDF ke shorthand ke alawa

Property	Kya kaam karta hai?	Example	Deep explanation 
<code>margin</code>	Four-side outer space	<code>margin: 10px 20px 30px 40px;</code>	Top/right/bottom/left outer spacing. PDF me iska 4-value form shown hai.  CSS
<code>margin-top</code>	Top outer space	<code>margin-top: 20px;</code>	Element ke upar external gap.
<code>margin-right</code>	Right outer space	<code>margin-right: 20px;</code>	Element ke right side external gap.
<code>margin-bottom</code>	Bottom outer space	<code>margin-bottom: 20px;</code> 	Element ke neeche external gap.

<code>margin-bottom</code>	Bottom outer space	<code>margin-bottom: 20px;</code>	Element ke neeche external gap.
<code>margin-left</code>	Left outer space	<code>margin-left: 20px;</code>	Element ke left side external gap.
<code>margin: auto</code>	Automatic available-space distribution	<code>margin: 0 auto;</code>	Fixed/max-width block ko horizontally center karne me commonly use hota hai.

12. Box Model — PDF ke box model ke andar aur important properties

Property	Kya kaam karta hai?	Example	Deep explanation	
<code>box-sizing: content-box</code>	Width/height mainly content box ko refer karta hai	<code>box-sizing: content-box;</code>	<code>width + padding + border</code> se actual outer size badh sakta hai.	
<code>box-sizing: border-box</code>	Width/height border box ko include karta hai 	<code>box-sizing: border-box;</code>	Given width ke andar padding + border included hote hain; responsive layouts me very	
<code>overflow</code>	Extra content ka behavior	<code>overflow: auto;</code>	Content box se bahar nikle to visible/hidden/scroll/auto decide karta hai.	
<code>overflow-x</code>	Horizontal overflow	<code>overflow-x: auto;</code>	Horizontal extra content ko control karta hai.	
<code>overflow-y</code>	Vertical overflow	<code>overflow-y: auto;</code>	Vertical extra content ko control karta hai.	
<code>overflow-wrap</code>	Long content wrapping	<code>overflow-wrap: anywhere;</code>	Long URLs/words ko box se bahar jaane se rokne me useful.	

Css part 1

<code>overflow</code>	Extra content ka behavior	<code>overflow: auto;</code>	Content box se bahar nikle to visible/hidden/scroll/auto decide karta hai.
<code>overflow-x</code>	Horizontal overflow	<code>overflow-x: auto;</code>	Horizontal extra content ko control karta hai.
<code>overflow-y</code>	Vertical overflow	<code>overflow-y: auto;</code>	Vertical extra content ko control karta hai.
<code>overflow-wrap</code>	Long content wrapping	<code>overflow-wrap: anywhere;</code>	Long URLs/words ko box se bahar jaane se rokne me useful.

13. Display — PDF ke `block`, `inline`, `inline-block`, `none` ke alawa

[Share](#)

Display value	Kya kaam karta hai?	Example	Deep explanation
<code>block</code>	Full block formatting	<code>display: block;</code>	New line se start hota hai aur available horizontal space generally occupy karta hai.
<code>inline</code>	Inline formatting	<code>display: inline;</code>	Same line me content ke saath flow karta hai; width/height ka behavior block jaisa nahi hota.
<code>inline-block</code>	Inline + box dimensions	<code>display: inline-block;</code>	Same line me reh sakta hai aur width/height/padding/border effectively control kar sakte ho.
<code>none</code>	Element ko layout se remove	<code>display: none;</code>	Element visible nahi hota aur uski layout space bhi nahi rehti. PDF Page 22 me ye directly shown hai. CSS
<code>flex</code>	Flex container	<code>display: flex;</code>	Children ko one-dimensional row/column layout me arrange karne ka system.



Css part 1

flex	Flex container	display: flex;	Children ko one-dimensional row/column me arrange karne ka system.	Share
inline-flex	Inline flex container	display: inline-flex;	Flex container itself inline flow me participate karta hai.	
grid	Grid container	display: grid;	Rows aur columns based two-dimensional layout.	
inline-grid	Inline grid	display: inline-grid;	Grid container inline flow me behave karta hai.	
flow-root	New block formatting context	display: flow-root;	Container apna independent block formatting context create karta hai.	
contents	Element ka own box remove	display: contents;	Element ka box layout me nahi hota, lekin children layout me remain karte hain.	
list-item	List item behavior	display: list-item;	Element ko list-item jaise marker behavior de sakta hai.	
table	Table-like layout	display: table;	Element table formatting context me behave kar sakta hai.	

list-item	List item behavior	display: list-item;	Element ko list-item jaise marker behavior de sakta hai.	Share
table	Table-like layout	display: table;	Element table formatting context me behave kar sakta hai.	
table-row	Table-row behavior	display: table-row;	Table row jaise layout behavior.	
table-cell	Table-cell behavior	display: table-cell;	Table cell jaise layout behavior.	

14. CSS Units — PDF ke px , % , em , rem ke alawa

Unit	Relative kis se?	Example	Deep explanation	Share
px	CSS pixel	width: 200px;	CSS me common fixed-length unit.	
%	Relevant parent/property ke reference se	width: 50%;	Width, height, margin, padding etc. me reference context property ke according change hota hai.	
em	Current/parent font-size context	font-size: 2em;	PDF me nested example diya hai jahan em parent font size ke relative change hota hai. CSS	
rem	Root (html) font-size	font-size: 2rem;	PDF ke last pages me rem ko immediate parent ke bajay root font-size ke relative explain kiya gaya hai. CSS	
vw	Viewport width	width: 50vw;	Browser viewport ki width ka percentage.	
vh	Viewport height	height: 50vh;	Browser viewport ki height ka percentage.	
vmin	Viewport ki smaller dimension	width: 50vmin;	Width/height me jo smaller dimension hai uske relative.	

Css part 1

vh	Viewport height	height: 50vh;	Browser viewport ki height ka percentage	 Share
vmin	Viewport ki smaller dimension	width: 50vmin;	Width/height me jo smaller dimension hai uske relative.	
vmax	Viewport ki larger dimension	width: 50vmax;	Viewport ki larger dimension ke relative.	
svw	Small viewport width	width: 100svw;	Mobile browser UI changes ke context me small viewport dimension.	
svh	Small viewport height	height: 100svh;	Small viewport height.	
lvw	Large viewport width	100lvw	Large viewport width.	
lvh	Large viewport height	100lvh	Large viewport height.	
dvw	Dynamic viewport width	100dvw	Current dynamic viewport width.	

Css part 1

<code>dvw</code>	Dynamic viewport width	<code>100dvw</code>	Current dynamic viewport width.	Share
<code>dvh</code>	Dynamic viewport height	<code>100dvh</code>	Mobile layouts me current viewport height ke saath useful.	
<code>ch</code>	Approx. <code>0</code> character width	<code>width: 60ch;</code>	Text-based widths, jaise readable paragraph width, me useful.	
<code>ex</code>	x-height	<code>2ex</code>	Font ke lowercase x-height ke relative unit.	
<code>cap</code>	Capital height	<code>2cap</code>	Font ke capital-letter height ke relative.	
<code>lh</code>	Current line-height	<code>2lh</code>	Element ki line-height ke relative length.	
<code>rlh</code>	Root line-height	<code>2rlh</code>	Root element ki line-height ke relative.	
<code>cm</code>	Centimeter	<code>2cm</code>	Physical length unit; screens par actual physical size device/browser se vary kar sakta hai.	
<code>mm</code>	Millimeter	<code>10mm</code>	Physical length unit.	
<code>mm</code>	Millimeter	<code>10mm</code>	Physical length unit.	Share
<code>in</code>	Inch	<code>1in</code>	CSS physical-length unit.	
<code>pt</code>	Point	<code>12pt</code>	Print/typography contexts me common.	
<code>pc</code>	Pica	<code>1pc</code>	Typographic unit.	

15. Background — PDF me background-color ke alawa isi topic ke properties

Property	Kya kaam karta hai?	Example	Deep explanation
background-color	Background color	background-color: yellow;	PDF me multiple pages par use hua hai. 
background-image	Background image	background-image: url("bg.jpg");	Element ke background me image lagata hai.
background-repeat	Image repeat	background-repeat: no-repeat;	Image repeat hogi ya nahi aur kis direction me hogi.
background-position	Image position	background-position: center;	Background image ko top/center/bottom/left/right ya exact position par place karta hai.
background-size	Image size	background-size: cover;	cover box ko cover karta hai; contain image ko fit karta hai.
background-attachment	Background scrolling	background-attachment: fixed;	Background viewport/element ke scroll behavior ko control karta hai.
background-origin	Background positioning area	background-origin: border-box;	Background image ka positioning reference box decide karta hai.
background-clip	Background painting area	background-clip: padding-box;	Background ko kis box boundary tak paint karna hai decide karta hai.
background-blend-mode	Background layers blend	background-blend-mode: multiply;	Background color/image ko blending mode ke through combine karta hai.
background	Shorthand	background: red url(x) center/cover no-repeat;	Multiple background properties ko ek declaration me set karta hai.

16. Colors — PDF me use hue color methods ka complete expansion

Method / Format	Example	Kya karta hai?	Deep explanation
Named color	<code>color: red;</code>	Color name se color set	PDF me <code>red</code> , <code>yellow</code> , <code>green</code> , <code>purple</code> , <code>orange</code> , <code>black</code> etc. examples hain. 
HEX	<code>color: #ff0000;</code>	Hexadecimal color	<code>#RRGGBB</code> format; web development me extremely common.
3-digit HEX	<code>color: #f00;</code>	Short HEX	<code>#ff0000</code> ka short form.
<code>rgb()</code>	<code>color: rgb(255,0,0);</code>	RGB channels	Red, green, blue values se color banata hai.
<code>rgba()</code>	<code>color: rgba(255,0,0,.5);</code>	RGB + alpha	Alpha transparency control karta hai.
<code>hsl()</code>	<code>color: hsl(0,100%,50%);</code>	 Saturation/Lightness	Color ko HSL model se define karta hai.

Css part 1

hsl()	color: hsl(0,100%,50%);	Hue/Saturation/Lightness	Color ko HSL model se define karta hai.
hsla()	color: hsla(0,100%,50%,.5);	HSL + alpha	HSL ke saath transparency.
hwb()	color: hwb(0 0% 0%);	Hue/Whiteness/Blackness	Alternative color representation.
lab()	color: lab(50% 40 30);	Lab color space	More perceptual color representation ke liye.
lch()	color: lch(50% 80 40);	Lightness/Chroma/Hue	Perceptual color representation.

17. CSS Functions — in topics ke saath important methods

Function	Example	Kya kaam karta hai?	Deep explanation
<code>calc()</code>	<code>width: calc(100% - 40px);</code>	Mathematical calculation	Different units ko combine karke dynamic value calculate kar sakta hai.
<code>min()</code>	<code>width: min(500px, 100%);</code>	Smaller value choose	Responsive width ke liye useful.
<code>max()</code>	<code>width: max(300px, 50%);</code>	Larger value choose	Minimum effective size maintain karne me useful.
<code>clamp()</code>	<code>font-size: clamp(16px, 3vw, 32px);</code>	Min + preferred + max	Responsive typography ka powerful method.
<code>var()</code>	<code>color: var(--primary);</code>	CSS variable read	Reusable CSS values ke liye.
<code>url()</code>	<code>background-image: url("/assets/...");</code>	Resource reference	Image/font etc. resource ko CSS me reference karta hai.

Css part 1

<code>url()</code>	<code>background-image: url("a.jpg");</code>	Resource reference	Image/font etc. resource ko CSS me reference karta hai.
<code>rgb()</code>	<code>rgb(0 0 255)</code>	RGB color	RGB channels se color.
<code>hsl()</code>	<code>hsl(220 80% 50%)</code>	HSL color	Hue, saturation, lightness se color.
<code>linear-gradient()</code>	<code>linear- gradient(red, blue)</code>	Linear gradient	Ek direction me colors smoothly transition karta hai.
<code>radial-gradient()</code>	<code>radial- gradient(red, blue)</code>	Radial gradient	Center se outward circular/elliptical gradient.
<code>conic-gradient()</code>	<code>conic- gradient(red, blue)</code>	Conical gradient	Center ke around angular gradient.



18. Extra properties jo isi basic CSS/box/display foundation ke baad directly related hain



Property	Kya kaam karta hai?	Example	Deep explanation	
<code>opacity</code>	Element transparency	<code>opacity: 0.5;</code>	<code>0</code> fully transparent aur <code>1</code> fully opaque.	
<code>visibility</code>	Visibility control	<code>visibility: hidden;</code>	Element hide ho sakta hai lekin <code>display:none</code> ke unlike layout space generally retain karta hai.	
<code>cursor</code>	Mouse cursor shape	<code>cursor: pointer;</code>	User ko clickable/disabled/etc. visual indication dene me useful.	
<code>outline</code>	Outer focus/outline line	<code>outline: 2px solid blue;</code>	Border ke bahar outline draw karta hai; focus states me important.	
<code>outline-width</code>	Outline thickness	<code>outline-width: 2px;</code>	Outline ki width.	



Css part 1

<code>outline-style</code>	Outline style	<code>outline-style: solid;</code>	Outline ka style.
<code>outline-color</code>	Outline color	<code>outline-color: red;</code>	Outline ka color.
<code>outline-offset</code>	Outline distance	<code>outline-offset: 4px;</code>	Element aur outline ke beech gap.
<code>box-shadow</code>	Box shadow	<code>box-shadow: 0 4px 10px gray;</code>	Box ke around shadow/elevation effect.
<code>content</code>	Generated content	<code>content: "Hello";</code>	Mainly <code>::before</code> / <code>::after</code> jaise pseudo-elements ke saath generated content create karta hai.
<code>box-decoration-break</code>	Box decoration fragmentation	<code>box-decoration-break: clone;</code>	Line/page fragmentation me border, padding, background etc. ka behavior control karta hai.

<code>object-fit</code>	Replaced element content fit	<code>object-fit: cover;</code>	<code></code> / <code><video></code> ko given box me fit karne ka behavior control karta hai. 
<code>object-position</code>	Replaced content position	<code>object-position: center;</code>	Image/video ko box ke andar kis position par place karna hai.

19. CSS Variables — modern CSS me isi foundation ka important extension

Property / Method	Example	Kya kaam karta hai?	Deep explanation 
Custom property	<code>--primary: blue;</code>	Apni CSS value store	Reusable value define karte ho.
<code>var()</code>	<code>color: var(--primary);</code>	Variable use	Ek value ko multiple places par reuse kar sakte ho.
<code>var()</code> fallback	<code>color: var(--primary, blue);</code>	Backup value	Variable available na ho to fallback <code>blue</code> use hota hai.
<code>:root</code>	<code>:root { --primary: blue; }</code>	 Global variables	Usually global CSS variables define karne ke liye.