

EXP NO:4

DATE:

RSA

Aim : To implement an encryption algorithm using Rsa.

Algorithm:

- Step 1: Select two large prime numbers, p and q. ● Step 2: Calculate the modulus, $n = p * q$.
- Step 3: Compute Euler's totient function, $\phi(n) = (p - 1) * (q - 1)$.
- Step 4: Choose a public exponent, e, such that $1 < e < \phi(n)$ and $\gcd(e, \phi(n)) = 1$.
- Step 5: Compute the private exponent, d, such that $(d * e) \bmod \phi(n) = 1$.
- Step 6: Convert the plaintext message into a numerical representation, usually using ASCII values or Unicode.
- Step 7: Encrypt the message by computing ciphertext, c, using the formula $c = (msg^e) \bmod n$.
- Step 8: Print the encrypted data.
- Step 9: Decrypt the ciphertext by computing the original message, m, using the formula $m = (c^d) \bmod n$.
- Step 10: Print the original message.
- Step 11: Return 0 for successful execution and program termination.

Program:

```
import java.io.*;
import java.math.*;
import java.util.*;
public class GFG { public static double
    gcd(double a, double h)
    { double temp;
      while (true) {
        temp = a % h;
        if (temp == 0)
```

```

return h;

a = h;

h = temp;
    }
    } public static void
main(String[] args)
    { double p = 9;
      double q = 5; double n = p *
      q; double e = 2; double phi
      = (p - 1) * (q - 1); while (e <
      phi) { if (gcd(e, phi) == 1)
      break;
          else e++; } int k = 2;
      double d = (1 + (k * phi)) / e;

      double msg = 12;

      System.out.println("Message data = " + msg);

      double c = Math.pow(msg, e);
      c = c % n;
      System.out.println("Encrypted data = " + c);
      double m = Math.pow(c, d);
      m = m % n;
      System.out.println("Original Message Sent = " + m);
    }
}

```

Output:

```
java -cp /tmp/RgOMJoXiEh/GFG  
Message data = 12.0  
Encrypted data = 18.0  
Original Message Sent = 29.0  
  
=== Code Execution Successful ===
```

Result: