

**EXP NO:5**

**DATE:**

## **DIFFIE-HELLMAN KEY EXCHANGE**

**Aim:** To implement Diffie-Hellman key exchange using C.

### **Algorithm:**

- Step 1: Choose a large prime number  $P$  and a primitive root modulo ( $P$ ), denoted as ( $G$ ). Both parties agree on these values.
- Step 2: Alice chooses a private key ( $a$ ), while Bob chooses a private key ( $b$ ). These private keys are kept secret.
- Step 3: Alice calculates her public key ( $x$ ) using ( $x = G^a \bmod P$ ), and Bob calculates his public key ( $y$ ) using ( $y = G^b \bmod P$ ).
- Step 4: Alice sends her public key ( $x$ ) to Bob, and Bob sends his public key ( $y$ ) to Alice.
- Step 5: Using the received public keys, Alice computes the secret key ( $k_a$ ) using ( $k_a = y^a \bmod P$ ), and Bob computes the secret key ( $k_b$ ) using ( $k_b = x^b \bmod P$ ).
- Step 6: Both Alice and Bob now have the same shared secret key.
- Step 7: They can now communicate securely using the shared secret key for encryption and decryption.
- Step 8: The security of the Diffie-Hellman Key Exchange relies on the difficulty of calculating discrete logarithms in finite fields.

### **Program:**

```
#include <math.h>
#include <stdio.h>
long long int power(long long int a, long long int b, long long int P)
{ if (b == 1)
    return a;
  else return (((long long int)pow(a, b)) % P);
} int
main()
```

```

{ long long int P, G, x, a, y, b, ka, kb; P =
    23;
    printf("The value of P : %lld\n", P);
    G = 9;
printf("The value of G : %lld\n\n", G); a = 4; printf("The
    private key a for Alice : %lld\n", a);
x    = power(G, a, P); b = 3;
    printf("The private key b for Bob : %lld\n\n", b);
y    = power(G, b, P);
    ka = power(y, a, P);
    kb = power(x, b, P);
    printf("Secret key for the Alice is : %lld\n", ka);
printf("Secret Key for the Bob is : %lld\n", kb); return 0;
}

```

### Output:

```

/tmp/6Ex6MzCUmw.o
The value of P : 21
The value of G : 7

The private key a for Alice : 3
The private key b for Bob : 3

Secret key for the Alice is : 7
Secret Key for the Bob is : 7

=== Code Execution Successful ===

```

### Result: