Imperial College London


Design and Professional Practice 2

Product Specification Document

Dr Ian Radcliffe









Imperial College London



Product Development Process

User Requirements

4.0 System Features

- 4.1 The system will consist of two handheld devices, differing only by the size and arrangement of the electrodes. The primary device will consist of a more extensive number of electrodes and will be used to produce planes of coagulated tissue in highly vascular organs. The secondary device will be used to coagulate small vessels or areas of tissue that have not been coagulated by the primary device.
- 4.2 Each device's handle will be constructed from a medical grade polymer which will provide thermal and electrical insulation. The handle design will be comfortable and practical.
- 4.3 For the primary device, multiple electrodes will issue from the handle in an array that will be designed to coagulate a volume of tissue at depths of up to 20cm, with a length of more than 2cm and widths of 1 cm. Each volume of tissue will be coagulated in less than 5 minutes.
- 4.4 For the secondary device, electrodes will issue from the handle in an array that will be designed to coagulate tissue at depths of up to 5 cm., lengths of 2 cm and widths of 1 cm. Each volume of coagulated tissue will be achieved in 3 minutes.
- 4.5 Both devices will be supplied sterile and for single use only.
- 4.6 Each alternate electrode on a device will act as the ground return for the active electrode; hence the RF energy will be delivered bipolar. This substantially reduces the measured impedance, allowing for a more efficient power delivery, and eliminating the risk of ground electrode burns.
- 4.7 The electrodes on each device will be made from a material that will provide mechanical strength compatible with multiple insertions into soft tissue without significant deformation of the electrodes. The electrodes will have suitable conductive properties. The electrodes will have a non-stick surface preparation to facilitate insertion and removal from the liver or other soft vascular tissue. The electrodes will be designed to allow easy insertion into soft tissue.
- 4.8 The devices will have cables and connectors for connection to an RF generator outside of the sterile field. The RF generator will supply the RF energy in the frequency range 200-800kHz to the electrodes. The device will operate with 200W generators such as the Radionic's RF generator.

Technical Specification


Device		A: Long Probe	B: Short Probe
Total Number of Needles		4	4
Needle Diameter	mm	2.0	1.5
Total Length	mm	210	70
Useable Needle Length below plate	mm	190	50
Insulated Length	mm	150	0
Non insulated (active) length (distal portion)	mm	40	50 (full length)
Arrangement of needle array		2 x 2 (2 pairs)	2 x 2 (2 pairs)
Separation to sideways neighbour (centre-centre)	mm	6.0	6.0
Separation to next pair (centre-centre)	mm	7.0	7.0







Product Development Process



The PSD provides criteria to assess the product against.

Validation against the User Requirements:

Are we building the right product?

Verification against the Technical Requirements:

Are we building the product right?















Product·Specification·Document¶

1

Project-Name:¤	п	п
Date:¤		п
Release-Number:¤	п	п

1

(4)			2.002		
No.	Aspects	Objectives	Specification	Test-Method=	п
				a a	п
	y and				п
в	unctionality Performan	н			12
	Funct				11
п					п
	丑				п
10.	d-Weights				13
	É		u	a	13
п	Size			n	п









Product·Specification·Document¶

1

Project-Name:¤	 Use the shortened project name (and number) 	IX
Date:¤	■The date	п
Release-Number:¤	Allows you to keep track of changes you make (1, 2, 3, A etc.)	п

1

No,¤	Aspectu	Objectives	Specifications	Test-Method=	D
#					п
ш	y and				10
	Functionality an Performances	п			13
п	Funct				
n		n			
н	異				п
ж.	and-Weights	(B)	(#)	u u	п
п	Size-and	n :		ш	
m	Ø.		(m)		п









Product·Specification·Document¶

1

Project-Name:¤	•Use the shortened project name (and number)	m
Date:¤	The date	13
Release-Number:¤	Allows you to keep track of changes you make (1, 2, 3, A etc.)	п

(P)	<u> </u>		J 11.77		
No.¤	Aspectu	Objectives	Specifications	Test-Methods	п
#	7.00				10
	y and				10
	nctionality and Performances				10
	Functionality and Performances				D
n		a			b
	4	в .			1
ж.	3-Weights	(B)		u	10
	ze-and	B)		ш	10
pt.	Sign		(8)		









Product·Specification·Document¶

Project-Name:¤	•Use the shortened project name (and number)	K
Date:¤	The date	1
Release·Number:¤	"Allows you to keep track of changes you make (1, 2, 3, A etc.)	

Aspects	Objectives	Specifications	Test-Method=	E
	A chart line which			E
2 0	describes what this			E
	particular			E
Funct	specification is.			£
	(e.a.: weight.			
丑	maximum load,			E
Weig	energy			E
ze-anc	· · · · · · · · · · · · · · · · · · ·		а	
ii.	fire retardant.)			
	Size-and-Weights Functionality-and de	A short line which describes what this particular specification is. (e.g.: weight, maximum load, energy consumption, power supply, cost,	A short line which describes what this particular specification is. (e.g.: weight, maximum load, energy consumption, power supply, cost,	A short line which describes what this particular specification is. (e.g.: weight, maximum load, energy consumption, power supply, cost,











Product·Specification·Document¶

1

Project-Name:¤	use the shortened project name (and number)	
Date:¤	The date	
Release·Number:¤	Allows you to keep track of changes you make (1, 2, 3, A etc.)	

No.¤	Aspects	Objectives	Specifications	Test-Method=	
28	-	A short line which	Detail technical aspects of		
ш	ty and	describes what this	this objective including if		
в	forma	particular	possible a reference to any		
11	Funct	specification is.	relevant guidelines or		
n		(e.g.: weight,	regulations.	u	
п	華	maximum load,	(e.g.: fire retardant – burn		
n	d-Weig	energy	rate must be below burn	u	
11	Ze-an	consumption, power supply, cost,	slower than 10 mm per second (BS EN 71-	α	
п	95	fire retardant.)	2:2011+A1:2014))	u u	











Product-Specification-Document¶

Project-Name:¤	"Use the shortened project name (and number)	n
Date:¤	The date	п
Release-Number:¤	Allows you to keep track of changes you make (1, 2, 3, A etc.)	a

Numbering is important for documenting future Verification and Validation

No,¤	Aspects
#	-
п	ty and
в	form
11	Func
п	
н	节
и.	e and Wei
111	ze-an
m	SS.

A short line which describes what this particular specification is. (e.g.: weight, maximum load, energy consumption, power supply, cost, fire retardant.)

Objectives

Detail technical aspects of this objective including if possible a reference to any relevant guidelines or regulations.

Specifications

(e.g.: fire retardant – burn rate must be below burn slower than 10 mm per second (BS EN 71-2:2011+A1:2014))

Information on how you will test that the design meets this particular requirement.

Test-Method#

(e.g.: fire retardant – testing in accordance to the methods set out in BS EN 71-2:2011+A1:2014)











Product·Specification·Document¶

Project-Name:¤	use the shortened project name (and number)	п
Date:¤	The date	п
Release-Number:¤	Allows you to keep track of changes you make (1, 2, 3, A etc.)	п

No.¤	Aspects	Objectives	Specifications	Test-Method=		
11	onality and ormances					
10			u .	в		
11	Funct					
п				n n		
н	五			u u		
m	Weig	(8)	я (u		
ш	ze-an	100	10	α		
ш	65		*			











Product·Specification·Document¶

Project-Name:¤	use the shortened project name (and number)	п
Date:¤	The date	п
Release-Number:¤	Allows you to keep track of changes you make (1, 2, 3, A etc.)	n

No,¤	Aspectu	Objective¤	Specifications	Test-Method¤		
#	ė.	Functional requirement - detail the intended behaviour of the device, such as				
п	ality an	services, tasks or functions it is required to perform.			4	
	form	n n	B		=[
11	Func					
п		s				
	B					
n	The physical attributes that the device needs to have, size, weight also potentially material and strength characteristics				1	
e:	Ze-an			а		
п	SS.		m)			



