Profile Summary

Generated 20-May-2020 14:19:23 using performance time.

Function Name	Calls	Total Time	Self Time*	Total Time Plot (dark band = self time)
main	1	11.426 s	0.566 s	
fn_UT0	514	5.317 s	3.367 s	
fn_UT1	511	5.284 s	3.345 s	
kron	10754	3.956 s	3.956 s	
fn_QuImg	7	0.198 s	0.071 s	
fn_LSBext	5	0.198 s	0.005 s	
fn_qureg	15361	0.060 s	0.060 s	
bi2de	5	0.036 s	0.034 s	
de2bi	5	0.009 s	0.008 s	
close	1	0.005 s	0.001 s	
close>safegetchildren	1	0.003 s	0.000 s	
allchild	1	0.003 s	0.001 s	
bi2de>validateInputs	5	0.002 s	0.002 s	
clearvars	1	0.002 s	0.002 s	
fn_QtoC	1	0.002 s	0.001 s	
fn_expand	1	0.001 s	0.001 s	

[fn_ket](#)	7	0.001 s	0.001 s	
[fn_shrink](#)	1	0.001 s	0.001 s	
[onCleanup>onCleanup.delete](#)	1	0.001 s	0.000 s	
[ind2sub](#)	1	0.001 s	0.001 s	
[onCleanup>onCleanup.onCleanup](#)	1	0.000 s	0.000 s	
[clearvars>parseArgs](#)	1	0.000 s	0.000 s	
[fliplr](#)	5	0.000 s	0.000 s	
[close>getEmptyHandleList](#)	1	0.000 s	0.000 s	
[...set(rootobj,'ShowHiddenHandles',Temp)](#)	1	0.000 s	0.000 s	
[allchild>getchildren](#)	1	0.000 s	0.000 s	
[uitools\private\allchildRootHelper](#)	1	0.000 s	0.000 s	
[clearvars>createPattern](#)	1	0.000 s	0.000 s	
[close>checkfigs](#)	1	0.000 s	0.000 s	
[close>request_close](#)	1	0.000 s	0.000 s	

Self time is the time spent in a function excluding the time spent in its child functions.
Self time also includes overhead resulting from the process of profiling.