

Lecture 3

C++ Data Types

In this tutorial, we will learn about basic data types such as int, float, char, etc. in C++ programming with the help of examples.

In C++, data types are declarations for variables. This determines the type and size of data associated with variables. For example,

```
int age = 13;
```

Here, `age` is a variable of type `int`. Meaning, the variable can only store integers of either 2 or 4 bytes.

C++ Fundamental Data Types

The table below shows the fundamental data types, their meaning, and their sizes (in bytes):

Data Type	Meaning	Size (in Bytes)
<code>int</code>	Integer	2 or 4
<code>float</code>	Floating-point	4
<code>double</code>	Double Floating-point	8
<code>char</code>	Character	1
<code>wchar_t</code>	Wide Character	2
<code>bool</code>	Boolean	1
<code>void</code>	Empty	0

Now, let us discuss these fundamental data types in more detail.

1. C++ int

- The `int` keyword is used to indicate integers.
- Its size is usually 4 bytes. Meaning, it can store values from **-2147483648 to 2147483647**.
- For example,

```
int salary = 85000;
```

2. C++ float and double

- `float` and `double` are used to store floating-point numbers (decimals and exponentials).
- The size of `float` is 4 bytes and the size of `double` is 8 bytes. Hence, `double` has two times the precision of `float`. To learn more, visit [C++ float and double](#).
- For example,

```
float area = 64.74;  
double volume = 134.64534;
```

As mentioned above, these two data types are also used for exponentials. For example,

```
double distance = 45E12    // 45E12 is equal to 45*10^12
```

3. C++ char

- Keyword `char` is used for characters.
- Its size is 1 byte.
- Characters in C++ are enclosed inside single quotes `' '`.
- For example,

```
char test = 'h';
```

4. C++ wchar_t

- Wide character `wchar_t` is similar to the `char` data type, except its size is 2 bytes instead of 1.
- It is used to represent characters that require more memory to represent them than a single `char`.
- For example,

```
#include <iostream>
using namespace std;

int main()
{
    wchar_t w = L'A';
    cout << "Wide character value:: " << w << endl ;
    cout << "Size of the wide char is:: " << sizeof(w)<<endl;

    char caname[] = "Object Oriented" ;
    cout << caname << endl ;

    // wide-char type array string
    wchar_t waname[] = L" Object Oriented" ;
    wcout << waname << endl;
    return 0;
}
```

L is the prefix for wide character literals and wide-character string literals which tells the compiler that that the char or string is of type wide-char.

w is prefixed in operations like scanning (wcin) or printing (wcout) while operating wide-char type.

5. C++ bool

- The `bool` data type has one of two possible values: `true` or `false`.
- Booleans are used in conditional statements and loops (which we will learn in later chapters).
- For example,

```
bool cond = false;
```

6. C++ void

- The `void` keyword indicates an absence of data. It means "nothing" or "no value".
- We will use void when we learn about functions and pointers.

Note: We cannot declare variables of the `void` type.

C++ Type Modifiers

We can further modify some of the fundamental data types by using type modifiers.

There are 4 type modifiers in C++. They are:

1. `signed`
2. `unsigned`
3. `short`
4. `long`

We can modify the following data types with the above modifiers:

- `int`
- `double`
- `char`

C++ Modified Data Types List

Data Type	Size (in Bytes)	Meaning
<code>signed int</code>	4	used for integers (equivalent to <code>int</code>)
<code>unsigned int</code>	4	can only store positive integers
<code>short</code>	2	used for small integers (range -32768 to 32767)
<code>unsigned short</code>	2	used for small positive integers (range 0 to 65,535)
<code>long</code>	at least 4	used for large integers (equivalent to <code>long int</code>)
<code>unsigned long</code>	4	used for large positive integers or 0 (equivalent to <code>unsigned long int</code>)
<code>long long</code>	8	used for very large integers (equivalent to <code>long long int</code>).
<code>unsigned long long</code>	8	used for very large positive integers or 0 (equivalent to <code>unsigned long long int</code>)
<code>long double</code>	12	used for large floating-point numbers
<code>signed char</code>	1	used for characters (guaranteed range -127 to 127)
<code>unsigned char</code>	1	used for characters (range 0 to 255)

Let's see a few examples.

```
long b = 4523232;  
long int c = 2345342;  
long double d = 233434.56343;  
short d = 3434233; // Error! out of range  
unsigned int a = -5;    // Error! can only store positive numbers or 0
```

Derived Data Types

Data types that are derived from fundamental data types are derived types. For example: arrays, pointers, function types, structures, etc.