

## Lecture 14

# C++ Public, Protected and Private Inheritance

In C++ inheritance, we can derive a child class from the base class in different access modes. For example,

```
class Base {  
    ....  
};  
  
class Derived : public Base {  
    ....  
};
```

Notice the keyword `public` in the code

```
class Derived : public Base
```

This means that we have created a derived class from the base class in **public mode**.

Alternatively, we can also derive classes in **protected** or **private** modes.

These 3 keywords (`public`, `protected`, and `private`) are known as **access specifiers** in C++ inheritance.

## public, protected and private inheritance in C++

**public**, **protected**, and **private** inheritance have the following features:

- **public inheritance** makes `public` members of the base class `public` in the derived class, and the `protected` members of the base class remain `protected` in the derived class.
- **protected inheritance** makes the `public` and `protected` members of the base class `protected` in the derived class.

- **private inheritance** makes the `public` and `protected` members of the base class `private` in the derived class.

**Note:** `private` members of the base class are inaccessible to the derived class.

```
class Base {
    public:
        int x;
    protected:
        int y;
    private:
        int z;
};

class PublicDerived: public Base {
    // x is public
    // y is protected
    // z is not accessible from PublicDerived
};

class ProtectedDerived: protected Base {
    // x is protected
    // y is protected
    // z is not accessible from ProtectedDerived
};

class PrivateDerived: private Base {
    // x is private
    // y is private
    // z is not accessible from PrivateDerived
};
```

## Example 1: C++ public Inheritance

```
// C++ program to demonstrate the working of public inheritance

#include <iostream>
using namespace std;
```

```

class Base {
private:
    int pvt = 1;

protected:
    int prot = 2;

public:
    int pub = 3;

    // function to access private member
    int getPVT() {
        return pvt;
    }
};

class PublicDerived : public Base {
public:
    // function to access protected member from Base
    int getProt() {
        return prot;
    }
};

int main() {
    PublicDerived object1;
    cout << "Private = " << object1.getPVT() << endl;
    cout << "Protected = " << object1.getProt() << endl;
    cout << "Public = " << object1.pub << endl;
    return 0;
}

```

## Output

```

Private = 1
Protected = 2
Public = 3

```

Here, we have derived `PublicDerived` from `Base` in **public mode**.

As a result, in `PublicDerived`:

- `prot` is inherited as **protected**.
- `pub` and `getPVT()` are inherited as **public**.
- `pvt` is inaccessible since it is **private** in `Base`.

Since **private** and **protected** members are not accessible from `main()`, we need to create public functions `getPVT()` and `getProt()` to access them:

```
// Error: member "Base::pvt" is inaccessible
cout << "Private = " << object1.pvt;

// Error: member "Base::prot" is inaccessible
cout << "Protected = " << object1.prot;
```

Notice that the `getPVT()` function has been defined inside `Base`. But the `getProt()` function has been defined inside `PublicDerived`.

This is because `pvt`, which is **private** in `Base`, is inaccessible to `PublicDerived`.

However, `prot` is accessible to `PublicDerived` due to public inheritance.

So, `getProt()` can access the protected variable from within `PublicDerived`.

## Accessibility in public Inheritance

Accessibility	private members	protected members	public members
Base Class	Yes	Yes	Yes
Derived Class	No	Yes	Yes

## Example 2: C++ protected Inheritance

```
// C++ program to demonstrate the working of protected inheritance
#include <iostream>
using namespace std;

class Base {
private:
    int pvt = 1;
```

```

protected:
    int prot = 2;

public:
    int pub = 3;

    // function to access private member
    int getPVT() {
        return pvt;
    }
};

class ProtectedDerived : protected Base {
public:
    // function to access protected member from Base
    int getProt() {
        return prot;
    }

    // function to access public member from Base
    int getPub() {
        return pub;
    }
};

int main() {
    ProtectedDerived object1;
    cout << "Private cannot be accessed." << endl;
    cout << "Protected = " << object1.getProt() << endl;
    cout << "Public = " << object1.getPub() << endl;
    return 0;
}

```

## Output

```

Private cannot be accessed.
Protected = 2
Public = 3

```

Here, we have derived `ProtectedDerived` from `Base` in **protected mode**.

As a result, in `ProtectedDerived`:

- `prot`, `pub` and `getPVT()` are inherited as **protected**.
- `pvt` is inaccessible since it is **private** in `Base`.

As we know, **protected** members cannot be directly accessed from outside the class.

As a result, we cannot use `getPVT()` from `ProtectedDerived`.

That is also why we need to create the `getPub()` function in `ProtectedDerived` in order to access the `pub` variable.

```
// Error: member "Base::getPVT()" is inaccessible
cout << "Private = " << object1.getPVT();

// Error: member "Base::pub" is inaccessible
cout << "Public = " << object1.pub;
```

## Accessibility in protected Inheritance

Accessibility	private members	protected members	public members
Base Class	Yes	Yes	Yes
Derived Class	No	Yes	Yes (inherited as protected variables)

## Example 3: C++ private Inheritance

```
// C++ program to demonstrate the working of private inheritance
#include <iostream>
using namespace std;

class Base {
private:
    int pvt = 1;
```

```

protected:
    int prot = 2;

public:
    int pub = 3;

    // function to access private member
    int getPVT() {
        return pvt;
    }
};

class PrivateDerived : private Base {
public:
    // function to access protected member from Base
    int getProt() {
        return prot;
    }

    // function to access private member
    int getPub() {
        return pub;
    }
};

int main() {
    PrivateDerived object1;
    cout << "Private cannot be accessed." << endl;
    cout << "Protected = " << object1.getProt() << endl;
    cout << "Public = " << object1.getPub() << endl;
    return 0;
}

```

## Output

```

Private cannot be accessed.
Protected = 2
Public = 3

```

Here, we have derived `PrivateDerived` from `Base` in **private mode**.

As a result, in `PrivateDerived`:

- `prot`, `pub` and `getPVT()` are inherited as **private**.
- `pvt` is inaccessible since it is **private** in `Base`.

As we know, private members cannot be directly accessed from outside the class. As a result, we cannot use `getPVT()` from `PrivateDerived`.

That is also why we need to create the `getPub()` function in `PrivateDerived` in order to access the `pub` variable.

```
// Error: member "Base::getPVT()" is inaccessible
cout << "Private = " << object1.getPVT();

// Error: member "Base::pub" is inaccessible
cout << "Public = " << object1.pub;
```

## Accessibility in private Inheritance

Accessibility	private members	protected members	public members
Base Class	Yes	Yes	Yes
Derived Class	No	Yes (inherited as private variables)	Yes (inherited as private variables)