

Date: Oct 2, 2025

HOVER AND CLICK MENU

Playwright + TypeScript

Many websites have dropdown menus that appear only when you hover your mouse over them! Playwright makes it super easy with the `hover` method.

IMPORTANT!

`hover()` simulates mouse movement over an element, making hidden submenus visible. Perfect for dropdown navigation menus!

Understanding Hover Menus

How it works:

Before Hover:

Add-ons Menu

Mouse Hover

After Hover:

Add-ons Menu

Taxi

Hotels

Meals

Seat Selection

The hover Method

Playwright provides the hover method to simulate mouse movement!

Syntax

```
await locator.hover();
```

What hover does:

Moves mouse cursor to the element

Triggers CSS hover effects

Makes hidden dropdown menus visible

Waits for element to be ready

Real Example - SpiceJet

Let's hover over Add-ons menu and click on Taxi submenu!

Complete Code

```
import { Browser, chromium, Page } from "playwright";

let page: Page;

(async () => {
  const browser: Browser = await chromium.launch({
    headless: false,
    channel: "chrome",
  });

  page = await browser.newPage();
  await page.goto("https://www.spicejet.com/");

  // Step 1: Hover over parent menu
  await page.getByText('Add-ons', { exact: true }).hover();

  // Step 2: Click on submenu item
  await page.getByTestId('test-id-Taxi').click();
})();
```

Breaking it down:

Step 1: Find Add-ons menu using text

Step 2: Hover over it to reveal submenu

Step 3: Click on Taxi submenu using test ID

Different Ways to Hover

Method 1: Using getByText

```
await page.getByText('Add-ons', { exact: true }).hover();  
await page.getByText('Taxi').click();
```

Method 2: Using CSS Selector

```
await page.locator('.menu-item').hover();  
await page.locator('.submenu-taxi').click();
```

Method 3: Using XPath

```
await page.locator("//a[text()='Add-ons']").hover();  
await page.locator("//div[@data-testid='test-id-Taxi']").click();
```

Multi-Level Menus

Some websites have menus within menus! You need to hover multiple times!

Nested Hover Example

```
// Level 1: Hover on main menu
await page.getByText('Products').hover();

// Level 2: Hover on submenu
await page.getByText('Electronics').hover();

// Level 3: Click on final item
await page.getByText('Laptops').click();
```

REMEMBER!

hover makes hidden elements visible

Always hover BEFORE clicking submenu items

Playwright waits for element to be ready

No need for manual waits or Thread.sleep!

COMMON MISTAKES

Clicking without hovering first

Adding unnecessary waits (Playwright auto-waits!)

Not using exact: true for ambiguous text

Hovering on wrong element

PRO TIPS!

Use exact: true to avoid matching partial text

Prefer getByRole or getByText over CSS/XPath

No need for Thread.sleep - Playwright waits automatically!

Chain multiple hovers for nested menus

KEY TAKEAWAYS

Use hover to reveal hidden dropdown menus

Always hover BEFORE clicking submenu items

Playwright auto-waits - no manual waits needed!

Chain multiple hovers for multi-level menus

Perfect for navigation menus, tooltips, and flyouts!

NAVEEN AUTOMATION LABS

Your Journey to Test Automation Excellence