

Date: Oct 2, 2025

RIGHT CLICK / CONTEXT CLICK

Playwright + TypeScript

Right-click (also called context click) opens a context menu with options like Copy, Paste, Edit, Delete, etc. In Playwright, we can simulate right-click using the click method with button option!

IMPORTANT!

To perform right-click, use: click with button: 'right' option. This simulates the context menu that appears when you right-click on an element!

Understanding Right Click

How it works:

Before Right Click:

Element

Right Click

After Right Click:

Element

Edit

Copy

Paste

Delete

Quit

Right Click Syntax

Use click method with button: 'right' option to perform right-click!

Basic Syntax

```
// Right click on element  
await locator.click({ button: 'right' });
```

Mouse Button Options:

button: 'left' - Normal click (default)

button: 'right' - Right click / Context click

button: 'middle' - Middle mouse button click

Real Example - Context Menu

Let's right-click on an element and select an option from the context menu!

Complete Code

```
import { Browser, chromium, Page } from "playwright";

let page: Page;

(async () => {
  const browser: Browser = await chromium.launch({
    headless: false,
    channel: "chrome",
  });

  page = await browser.newPage();
  await page.goto('https://swisnl.github.io/jquery-contextMenu/demo.html');

  // Step 1: Right click on element
  await page.locator('span.context-menu-one').click({ button: 'right' });
```

```
// Step 2: Get all menu options
let allOptions: string[] = await page.locator(`ul.context-menu-list span`).allInnerTexts();
console.log(allOptions);

// Step 3: Click on Copy option
await page.getByText('Copy', { exact: true }).click();
})();
```

Breaking it down:

Step 1: Perform right-click on element

Step 2: Get all menu options (optional)

Step 3: Click on desired menu option

Different Button Clicks

Left Click (Default)

```
// Normal left click
await page.locator('button').click();

// OR explicitly specify left button
await page.locator('button').click({ button: 'left' });
```

Right Click (Context Click)

```
// Right click to open context menu  
await page.locator('element').click({ button: 'right' });
```

Middle Click

```
// Middle mouse button click  
await page.locator('link').click({ button: 'middle' });
```

Complete Workflow

Right Click Flow:

- 1. Locate the element to right-click*
- 2. Perform right-click with button: 'right'*
- 3. Wait for context menu to appear*
- 4. Locate menu option*
- 5. Click on menu option*

Getting All Menu Options

You can fetch all available options from the context menu using `allInnerTexts`:

Get Menu Options

```
// Right click to open menu
await page.locator('element').click({ button: 'right' });

// Get all menu options
let allOptions: string[] = await page.locator(`ul.context-menu-list span`).allInnerTexts();
console.log(allOptions);

// Output: ['Edit', 'Copy', 'Paste', 'Delete', 'Quit']
```

Why get all options?

To verify all expected options are present

To check if a specific option exists

For debugging and logging

To validate context menu behavior

REMEMBER!

Use click with button: 'right' for right-click

Context menu appears after right-click

Use allInnerTexts to get all menu options

Playwright waits for elements automatically!

COMMON MISTAKES

Using regular click instead of click with button: 'right'

Not waiting for context menu to appear

Using wrong locator for menu options

Forgetting exact: true when clicking menu items with common text

PRO TIPS!

Always use button: 'right' for context click

Use exact: true to avoid partial text matches

allInnerTexts is great for verifying menu options

Test right-click behavior on different browsers

Real-World Use Cases

1. File managers - Right-click to delete, rename files

2. Text editors - Right-click for copy, paste, format
3. Image galleries - Right-click for download, share
4. Tables - Right-click rows for edit, delete options
5. Custom context menus - Application-specific actions

KEY TAKEAWAYS

Right-click = click with button: 'right'

Opens context menu with options

Use `allInnerTexts` to get all menu items

Then click on desired option

Simple and powerful for context menus!

NAVEEN AUTOMATION LABS

Your Journey to Test Automation Excellence