

AI Meets Declarative Process Mining: A Concrete Initiative to Move from Theory to Practice



Fabrizio M. Maggi
maggi@inf.unibz.it


Process Intelligence

Process mining: Application of **data science** to discover, validate and improve processes. **By combining data mining and process analytics**, organizations can mine log data from their information systems to **understand the performance** of their processes, **revealing bottlenecks** and other **areas of improvement**.

Wil M. P. van der Aalst: ***Process Mining - Data Science in Action, Second Edition***. Springer 2016, ISBN 978-3-662-49850-7

Process Intelligence: Application of **AI for developing process mining techniques** to **strengthen** *designing, monitoring* and *diagnosis* of BPs during their **life-cycle**.

Process Intelligence in the BPM Lifecycle





```

graph LR
    subgraph Front_Office [Front Office]
        Start(( )) --> OR[Order Received]
        OR --> DO[Document the Order]
        DO --> CRO[Check for Related Products on Special Offers]
        CRO --> D1{Other products required?}
        D1 -- Yes --> CTC[Calculate Totals and Confirm]
    end

    subgraph Back_Office [Back Office]
        CTC --> RI[Raise an Invoice]
        RI --> J1(( ))
        J1 --> TP[Take Payment]
        J1 --> UCHO[Update Customer Order History]
        TP --> J2(( ))
        UCHO --> J2
    end

    subgraph Warehouse [Warehouse]
        J2 --> SO[Ship the Order]
        SO --> End((Process Order Complete))
    end
  
```



Declare

- *A is always eventually followed by B*
- RESPONSE
- Graphical representation


Maja Pesic, Helen Schonenberg, Wil M. P. van der Aalst: **DECLARE: Full Support for Loosely-Structured Processes**. EDOC 2007: 287-300



- Semantics specified through LTL (for finite traces)

$$\Box(A \Rightarrow \Diamond B)$$

- LTL rules can be translated into automata



Giuseppe De Giacomo, Moshe Y. Vardi: **Linear Temporal Logic and Linear Dynamic Logic on Finite Traces**. IJCAI 2013: 854-860

Roadmap


*Automated **Process Discovery***

Compliance Monitoring

Conformance Checking

Log Generation


Imperative Process Discovery




Imperative Process Discovery




Declarative Process Discovery



Declarative Process Discovery




Declarative Process Discovery



Discovery algorithm

$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$




- finite number of constraint types
- finite set of activities

Fabrizio M. Maggi, R. P. Jagadeesh
Chandra Bose, Wil M. P. van der
Aalst: ***Efficient Discovery of
Understandable Declarative
Process Models from Event
Logs***. CAiSE 2012: 270-285


Discovery algorithm

$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$



Discovery algorithm


$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$



$\Box(A \Rightarrow \Diamond B)$

Discovery algorithm

$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$




Discovery algorithm

$W = [\langle A C B C \rangle, \langle C B A C \rangle, \langle A C A C A C B \rangle]$




$\Box(A \Rightarrow \Diamond B)$




Discovery algorithm

$W = [\langle A C B C \rangle, \langle C B A C \rangle, \langle A C A C A C B \rangle]$




Discovery algorithm

$W = [<\textcolor{red}{A} C B C>, <C B A C>, <A C A C A C B>]$




Discovery algorithm

$W = [<A \text{ C } B \text{ C}>, <C \text{ B } A \text{ C}>, <A \text{ C } A \text{ C } A \text{ C } B>]$




Discovery algorithm

$W = [<A\ C\ \textcolor{red}{B}\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$




Discovery algorithm

$W = [<A\ C\ B\ \textcolor{red}{C}>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$




Discovery algorithm

$W = [\langle A C B C \rangle, \langle C B A C \rangle, \langle A C A C A C B \rangle]$




Discovery algorithm

$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$




Discovery algorithm

$W = [<A\ C\ B\ C>, <\textcolor{red}{C}\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$




Discovery algorithm

$W = [<A\ C\ B\ C>, <C\ \textcolor{red}{B}\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$




Discovery algorithm

$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$



Discovery algorithm

$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$





Discovery algorithm

$W = [<A C B C>, <C B A C>, <A C A C A C B>]$




$\Box(A \Rightarrow \Diamond B)$




Discovery algorithm: Pruning

$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$




Discovery algorithm: Pruning

$W = [\boxed{\langle A C B C \rangle}, \langle C B A C \rangle, \langle A C A C A C B \rangle]$




Discovery algorithm: Pruning

$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$




Discovery algorithm: Pruning

$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$



Discovery algorithm: Pruning

$W = [<A\ C\ B\ C>, <C\ B\ A\ C>, <A\ C\ A\ C\ A\ C\ B>]$



Process Discovery



rulemining.org

Roadmap

Automated Process Discovery

Compliance Monitoring



Conformance Checking

Log Generation





Compliance







Compliance Models





Compliance Models



Compliance Models



Compliance Models







RV-LTL Semantics



Andreas Bauer, Martin Leucker, Christian Schallhart: ***The Good, the Bad, and the Ugly, But How Ugly Is Ugly?*** RV 2007: 126-138



RV-LTL Semantics




“the good” (permanently sat)





RV-LTL Semantics




“the bad” (permanently viol)



RV-LTL Semantics



“inconclusive” (possibly sat)






“inconclusive” (possibly viol)



Monitoring Approach

Fabrizio M. Maggi, Marco Montali, Michael Westergaard, Wil M. P. van der Aalst:
Monitoring Business Constraints with Linear Temporal Logic: An Approach Based on Colored Automata. BPM 2011: 132-147



M



S

E





Monitoring Approach

Fabrizio M. Maggi, Marco Montali, Michael Westergaard, Wil M. P. van der Aalst:
Monitoring Business Constraints with Linear Temporal Logic: An Approach Based on Colored Automata. BPM 2011: 132-147






Monitoring Approach

Fabrizio M. Maggi, Marco Montali, Michael Westergaard, Wil M. P. van der Aalst:
Monitoring Business Constraints with Linear Temporal Logic: An Approach Based on Colored Automata. BPM 2011: 132-147





Monitoring Approach

Fabrizio M. Maggi, Marco Montali, Michael Westergaard, Wil M. P. van der Aalst:
Monitoring Business Constraints with Linear Temporal Logic: An Approach Based on Colored Automata. BPM 2011: 132-147



Monitoring Approach

Fabrizio M. Maggi, Marco Montali, Michael Westergaard, Wil M. P. van der Aalst:
Monitoring Business Constraints with Linear Temporal Logic: An Approach Based on Colored Automata. BPM 2011: 132-147




↑
start

M


S

E



Monitoring Approach

Fabrizio M. Maggi, Marco Montali, Michael Westergaard, Wil M. P. van der Aalst:
Monitoring Business Constraints with Linear Temporal Logic: An Approach Based on Colored Automata. BPM 2011: 132-147




start

↑
M



S

E





Monitoring Approach

Fabrizio M. Maggi, Marco Montali, Michael Westergaard, Wil M. P. van der Aalst:
Monitoring Business Constraints with Linear Temporal Logic: An Approach Based on Colored Automata. BPM 2011: 132-147



Monitoring Approach

Fabrizio M. Maggi, Marco Montali, Michael Westergaard, Wil M. P. van der Aalst:
Monitoring Business Constraints with Linear Temporal Logic: An Approach Based on Colored Automata. BPM 2011: 132-147



start

M

S

E



Compliance Monitoring



rulemining.org

Roadmap

Automated Process Discovery

Compliance Monitoring

Conformance Checking


Log Generation

Conformance Checking with Trace Alignment



Trace Alignment

<A A D F C D E>




Massimiliano de Leoni, Fabrizio M. Maggi, Wil M. P. van der Aalst:
Aligning Event Logs and Declarative Process Models for Conformance Checking. BPM
2012: 82-97





Trace Alignment

<**A** A D F C D E>



Trace Alignment

<A A D F C D E>





<A A D F C D E B>



in Alignment

Trace Alignment

<A A D F C D E>





<A A D F C D E **B**>



in Alignment

Trace Alignment

<A A D F C D E>



<A A D F C D E B>



in Alignment


Trace Alignment

<A A D F C D E>





Trace Alignment

<**A** A D F C D E>



Trace Alignment

<A A D F C D E>





<A A D F C D E>



in Alignment

Trace Alignment

<A A D F C D E>





<A A D F C D E>



in Alignment

Trace Alignment

<A A D F C D E>




<A A D F C D E>



in Alignment

Trace Alignment

<A A D F C D E>



<A A D F C D E>



in Alignment

Optimal Alignments

Modifications have a cost!



Trace Alignment as a Planning Problem

- ❑ Trace Alignment can be formulated as a cost-optimal planning problem
 - **Domain:**
 - ✓ Addition and Deletion modeled by actions with positive costs
 - ✓ Domain dynamics encodes synchronous execution of a trace and all constraint automata
 - **Problem:**
 - ✓ Initial state: all automata in their initial state
 - ✓ Goal state: all automata in a final state
 - **Solution:**
 - ✓ Optimal (i.e., minimal-cost) plan to reach the goal state
- ❑ To find the minimum cost trace alignment, any planner can be used
 - e.g., **Fast-Downward**, **SymBA*-2**

Giuseppe De Giacomo, Fabrizio M. Maggi, Andrea Marrella, Fabio Patrizi: ***On the Disruptive Effectiveness of Automated Planning for LTLf-Based Trace Alignment.*** AAAI 2017: 3555-3561

Conformance Checking



rulemining.org

Roadmap


Automated Process Discovery

Compliance Monitoring


Conformance Checking

Log Generation


Log Generation




Log Generation



Log Generation



Log Generation



#traces in the log
#events in a trace
...



Log Generation with ASP

- ❑ Log generation can be encoded in Answer Set Programming (ASP) using predicates and rules to define:
 - Each constraint automaton of the input model
 - The length of a trace to be generated
 - The requirement that every automaton ends up in a final state in the last time point of the generated trace
- ❑ Predicate ***trace*** is the guessed predicate and contains a sequence of activities satisfying all the input constraints
- ❑ To generate a solution for the guessed predicate, an ASP solver can be used
 - e.g., **Clingo**


Francesco Chiariello, Fabrizio M. Maggi, Fabio Patrizi: ***ASP-Based Declarative Process Mining***. AAAI 2022: 5539-5547

Log Generation



rulemining.org

For Python Users...



<https://github.com/francxx96/declare4py>

***Thank you
for your attention!***