

Optimizing Vector Particle-In-Cell (VPIC) for Memory Constrained Systems Using Half-Precision

Nigel Tan, Robert Bird, Michela

Taufer



Particle Simulations

0.374 Pflop/s Trillion-Particle Kinetic Modeling of Laser Plasma Interaction on Roadrunner

K. J. Bowers, *Member, IEEE*, B. J. Albright, *Member, IEEE*, B. Bergen, *Member, IEEE*,
L. Yin, K. J. Barker and D. J. Kerbyson, *Member, IEEE*

2 trillion particles = 58.21 TB
(2008)

Tuning Parallel I/O on Blue Waters for Writing 10 Trillion Particles

Surendra Byna*, Robert Sisneros[†], Kalyana Chadalavada[‡], and Quincey Koziol[§]


10 trillion particles = 291.04 TB
(2015)

- Simulation scale more limited by memory than compute
- Accelerators add more memory constraints
 - Max CPU memory: **4TB**, Max GPU memory: **32GB**
 - PCIe 4.0 x16 Bandwidth: **32 GB/s** in one direction

Vector Particle-In-Cell (VPIC)


- High performance particle-in-cell code for plasma simulations:
 - Simulates magnetic reconnection, fusion, solar weather, and particle acceleration amongst other plasma phenomena
 - One of the fastest plasma codes in the world
 - Is well optimized for modern CPUs
 - Was **NOT** optimized for accelerators (e.g., GPUs)

VPIC Algorithm



Spatial domain: Particles are distributed across an n -D space that is decomposed into a n -D grid

Iterative process: Four key steps define a VPIC iteration




Particle Storage

- The larger the number of particles, the more physically accurate the simulations and the greater the memory usage

```
struct particle {  
    float dx, dy, dz; // Position  
    int i;           // Cell index  
    float ux, uy, uz; // Momentum  
    float w;         // Weight  
};
```

VPIC Memory Usage




Particle Storage

- The larger the number of particles, the more physically accurate the simulations and the greater the memory usage

```
struct particle {  
    float dx, dy, dz; // Position  
    int i;             // Cell index  
    float ux, uy, uz; // Momentum  
    float w;           // Weight  
};
```

VPIC Memory Usage




Particle Storage: Weight

- The larger the number of particles, the more physically accurate the simulations and the greater the memory usage


```
struct particle {  
    float dx, dy, dz; // Position  
    int i;           // Cell index  
    float ux, uy, uz; // Momentum  
    float w;         // Weight  
};
```

VPIC Memory Usage



Particle Weight


- Each simulated particle is a macroparticle
- Weight defines the number of real particles modeled by each macroparticle
- **Weight generally does not change during a simulation**



Example of macroparticle modeling
55 real particles


Optimizing Particle Weight Storage (I)

- Assume particle weights may vary but have a limited range of values
 - Weights have a common divisor
- Replace weight with 16-bit short integer (**SW**)
- Reduce particle memory usage by at most **6.25%** over default VPIC




Optimizing Particle Weight Storage (II)

- Assume all particles in a species share the same constant weight (**CW**)
- Remove weight field and use a per species constant weight
- Reduce particle storage cost by at most **12.5%** over default VPIC



Single Precision
Weight




Constant
Weight **CW**

Particle Storage: Position

- The larger the number of particles, the more physically accurate the simulations and the greater the memory usage


```
struct particle {  
    float dx, dy, dz; // Position  
    int i;             // Cell index  
    float ux, uy, uz; // Momentum  
    float w;           // Weight  
};
```

VPIC Memory Usage




Half-Precision Particle Position

Half-Precision Position




Half-Precision Particle Position

Half-Precision Position




Half-Precision Position + Constant Weight



Results: Memory Usage and Runtime


VPIC Memory Usage Comparison




Constant Weight + Half Precision
enables a **40%** increase in
number of particles

Results: Memory Usage and Runtime

VPIC Memory Usage Comparison




VPIC Execution Time Comparison



Results: Accuracy

- Perform as well as the original single precision VPIC with a sufficiently fine grid
- Weight kept constant and does not affect overall accuracy



1D problem modeling 2 particles with a known analytical solution. Simulation space is split into 10,000 cells.

Next Steps

- Add half-precision support for CPUs
- Develop model for automatically determining whether to use half-precision based on simulation settings
- Investigate alternative formats for position
- Develop optimizations for particle momentum