

Electrostatic ballooning of spiders with multiple charged silk threads in near-surface turbulence: analytical limits and take-off probability

Alexandru Jicu,¹ Vlad Băutu,¹ and Octavian-Mihai Radu^{2,*}

¹*PoliPhysics Junior Lab, CAMPUS Research Institute,
National University of Science and Technology POLITEHNICA Bucharest, Bucharest, Romania*

²*AI Multimedia Lab, CAMPUS Research Institute,
National University of Science and Technology POLITEHNICA Bucharest, Bucharest, Romania*

(Dated: Working draft and reference skeleton — October 7, 2026)

We start from the three-dimensional model of Habchi and Jawed [1], in which electrically charged silk threads are treated as discrete elastic rods subject to the atmospheric electric field, Coulomb repulsion, and air drag in the resistive force theory (RFT) approximation. We complete the model with the atmospheric field profile and experimentally measured charges [2, 3], and we place the bundle in synthetic near-surface turbulence generated by kinematic simulation with surface-layer statistics. Take-off becomes a stochastic event, characterized by a take-off probability; in the limit of eddies much larger and slower than the bundle, it reduces to a drift-diffusion result that smooths the deterministic threshold of the normalized lift-to-weight ratio, $\bar{F}_l = 1$, into a sigmoid controlled by a Péclet number. For tip-charged threads, we obtain an exact first integral of the equilibrium equations, $T^\beta \sin \theta = \text{const.}$ (where T is the thread tension, θ the local inclination angle, and $\beta = \eta_\perp / \eta_\parallel$ the RFT drag anisotropy ratio), and, in the small-angle limit, a closed-form expression for the opening of a bundle of N threads. Ensembles of 8200 simulations for $N \leq 8$ show that the take-off probability collapses on a single function of the scaled drift for all N and turbulence intensities: the bundle enters only through its settling speed, and the drift-diffusion form holds once the eddy diffusivity is replaced by the Lagrangian diffusivity of the flow. Finally, we train a graph neural network surrogate with long-range message passing on the simulation data and show that it generalizes effectively when tested on bundles with more threads than seen during training.

I. INTRODUCTION

Passive aerial dispersal of spiders (*ballooning*) is explained by two competing mechanisms: aerodynamic drag in rising air currents, and the electrostatic force exerted by the atmospheric potential gradient on negatively charged silk threads [2, 4]. From experiments in a chamber with a controlled electric field, Morley and Gorham estimated a total thread charge of about 1.15 nC for spiders of 0.9 mg [3]. Habchi and Jawed built the first three-dimensional model with multiple threads and showed that the Coulomb repulsion between threads produces a conical opening of the bundle [1]. Their model, however, assumes still air, although ballooning starts in the turbulent surface layer of the atmosphere.

The aerodynamic view has a long history. Humphrey [15] used a simple mechanical model of the spider-filament system to delimit, in terms of spider mass and silk length, the region in which ballooning is possible, and wind-tunnel experiments by Suter [16] showed that both the silk and the body contribute to the drag. Reynolds *et al.* [17] modelled the silk as a fully flexible, extensible line in turbulent flow and found that turbulence contorts the silk, so that ballooners have little control over their drag once airborne. More recently, Cho *et al.* observed large crab spiders (16–20 mg) taking off with 50–60 nanoscale fibres in weak updrafts of 0.1–0.5 m/s [7], and a bead-spring model with anisotropic drag was used to study the passive dynamics of a ballooning filament in shear, vortical, and turbulent flows [18]. None of these models includes electric charge. The electrostatic view received strong support when Morley and Robert showed that *Erigone* spiders detect vertical electric fields of atmospheric strength, that such fields alone elicit pre-ballooning behaviour and take-off in still air, and that the sensory hairs (trichobothria) respond mechanically to them [4]. Field-chamber experiments on three linyphiid species, however, found that wind had a much stronger effect on take-off than the electric field, the combination of the two giving the highest dispersal rates [9]; a recent review concludes that the relative importance of the two mechanisms is still open [10].

On the modelling side, thin elastic filaments are commonly simulated with the discrete elastic rods (DER) method [5], which represents a rod by its centreline nodes and edge twist angles and derives the forces from discrete stretching, bending, and twisting energies. Implicit time integration of DER makes very slender, nearly inextensible

* ORCID: 0009-0002-1634-5065

filaments tractable [1], and open-source implementations are available [6]. Habchi and Jawed coupled DER with resistive force theory and pairwise Coulomb repulsion, which is the starting point of the present work [1]. The cost of such simulations grows quickly with the number of threads, because the Coulomb interaction couples every pair of charged nodes and makes the Jacobian dense.

On the computational side, simulating many interacting charged filaments is expensive because the Coulomb interaction couples all nodes. Learned simulators based on graph neural networks reproduce the dynamics of particles at a fraction of the cost [14], and have been used to accelerate implicit solvers for rod dynamics [19], and long-range message-passing schemes such as Ewald message passing were designed precisely for $1/r$ interactions [13]. Whether such models generalize to filament bundles with more threads than seen during training has not been tested. **[TO DO: Octavian: add 2–3 references on GNN rod/cloth simulators and neural operators.]**

The contributions of this work are:

1. the multi-thread charged model of Habchi and Jawed placed in realistic synthetic near-surface turbulence, with take-off defined as a stochastic event;
2. an analytical drift–diffusion reference for the take-off probability and its comparison with ensemble simulations, which isolates the effect of the finite size and deformation of the bundle;
3. an exact first integral and a closed-form opening law for tip-charged thread bundles;
4. a graph neural network surrogate with long-range message passing, and a test of its generalization to unseen numbers of threads.

The paper is organized as follows. Section II presents the model. Section III describes the air flow and the take-off probability, and Sec. IV gives the analytical solution for tip-charged threads. Section V describes the numerical method and Sec. VI the learned surrogate. Results are presented in Sec. VII and discussed in Sec. VIII; Sec. IX concludes.

II. PHYSICAL MODEL

A. Geometry and parameters

The spider is a sphere of radius r_s , mass m , and charge Q_s , to which N identical threads of length L , radius r , and density ρ_t are attached. Each thread carries a charge q (in absolute value). As in [1], we consider two charge distributions: (a) charge concentrated at the thread tip, as suggested by [3]; (b) uniformly distributed charge, $\lambda = q/L$.

We use the following sign convention. The thread charge is negative and the fair-weather atmospheric field points downward, so the electrostatic force on the thread is *upward*. We work with the positive quantities q and $E(z)$; the force on the charge q is $+qE(z)\hat{z}$.

TABLE I. Reference parameters. Spider and thread values are those of [1].

Quantity	Symbol	Value	Source
Spider mass	m	1 mg (sweep 0.1–10 mg)	[1]
Spider radius	r_s	1 mm	[1]
Spider charge	Q_s	3 pC (negligible)	[1, 3]
Thread radius	r	300 nm	[1]
Thread length	L	0.5 m	[1, 3]
Silk density	ρ_t	1200 kg/m ³	[1]
Young’s modulus	Y	5–50 GPa (typical 25)	[1]
Air viscosity	μ	1.837×10^{-5} Pa s	
Field over flat ground	E_0	100–120 V/m	[2]
Field near a prominence	$E(z)$	Eq. (2), up to $\sim 10^5$ V/m	[1, 3]
Charge per thread	q	0.1–10 nC	[3]




FIG. 1. (a) Schematic representation of the spider–silk system in atmospheric turbulence and a vertical electric field $\mathbf{E}(z)$. (b) Geometry and force equilibrium along a single flexible thread element at arc length s , showing local tangent $\mathbf{t}$, normal $\mathbf{n}$, angle $\theta(s)$, tension $T(s)$, and RFT drag $\mathbf{f}_v$. (c) Top view at $s = L$ for $N = 4$ tip-charged threads, showing the conical opening of radius R driven by mutual radial Coulomb repulsion $\mathbf{F}_C$.

B. Electric field

Over flat ground we use Gorham’s profile [2]:

$$E(z) = E_0 e^{-\alpha z}, \quad E_0 = 120 \text{ V/m}, \quad \alpha = 3 \times 10^{-4} \text{ m}^{-1}. \quad (1)$$

On the scale of one thread ($L \sim 1$ m), E is practically constant.

For the experiment of Morley and Gorham, with launch from an aluminum-foil-covered prominence, we use the fit given in [1]:

$$E(z) = E_1 e^{-z/z_1} + E_2 e^{-z/z_2} + E_\infty, \quad (2)$$

with $E_1 = 2.52 \times 10^5$ V/m, $z_1 = 1.51$ mm, $E_2 = 5.07 \times 10^4$ V/m, $z_2 = 7.93$ mm, and $E_\infty = 7.41 \times 10^3$ V/m.

C. Forces

Let $s \in [0, L]$ be the arc length along a thread ($s = 0$ at the spider), $\mathbf{x}(s, t)$ its position, $\mathbf{v} = \partial_t \mathbf{x}$ the thread velocity, and $\mathbf{t} = \partial_s \mathbf{x}$ the local unit tangent vector.

a. Air drag (RFT). For a very slender thread at low Reynolds number ($\text{Re} \ll 1$), local air resistance is governed by Resistive Force Theory (RFT) [1]. The drag force per unit length depends on the relative velocity $\mathbf{v}_{\text{rel}} = \mathbf{v} - \mathbf{u}$ between the thread and the fluid, decomposed into components parallel and perpendicular to the local tangent $\mathbf{t}$:

$$\mathbf{f}_v = -\eta_{\parallel} (\mathbf{v}_{\text{rel}} \cdot \mathbf{t}) \mathbf{t} - \eta_{\perp} [\mathbf{v}_{\text{rel}} - (\mathbf{v}_{\text{rel}} \cdot \mathbf{t}) \mathbf{t}] = -[\eta_{\parallel} \mathbf{t} \mathbf{t}^T + \eta_{\perp} (\mathbb{I} - \mathbf{t} \mathbf{t}^T)] \mathbf{v}_{\text{rel}}. \quad (3)$$

Here, $\mathbf{t} \mathbf{t}^T = \mathbf{t} \otimes \mathbf{t}$ denotes the outer product projecting onto the local tangent direction.

$$\eta_{\parallel} = \frac{2\pi\mu}{\ln(L/r) - \frac{1}{2}}, \quad \eta_{\perp} = \frac{4\pi\mu}{\ln(L/r) + \frac{1}{2}}. \quad (4)$$

Here $\mathbf{v} = \partial_t \mathbf{x}$ is the thread velocity, $\mathbf{u}$ is the local air velocity. **The velocity $\mathbf{u}$ is our extension:** in [1], $\mathbf{u} = 0$. For the parameters of Table I, $\ln(L/r) \approx 14.3$, $\eta_{\parallel} \approx 8.35 \times 10^{-6}$ Pa s, and $\eta_{\perp} \approx 1.56 \times 10^{-5}$ Pa s. We define the drag anisotropy ratio:

$$\beta \equiv \frac{\eta_{\perp}}{\eta_{\parallel}} = \frac{2[\ln(L/r) - \frac{1}{2}]}{\ln(L/r) + \frac{1}{2}} \approx 1.87. \quad (5)$$

The anisotropy $\beta > 1$ directly governs the coupling between thread inclination and tension along the bundle.

The spider body experiences Stokes drag, $\mathbf{F}_{v,s} = -6\pi\mu r_s (\mathbf{v}_s - \mathbf{u})$. We write $\zeta_s \equiv 6\pi\mu r_s \approx 3.5 \times 10^{-7}$ N s/m.

- b. Electrostatic force.* Per unit length, $\mathbf{f}_e = \lambda E(z) \hat{\mathbf{z}}$ for uniform charge; for tip charge, the force $qE(z) \hat{\mathbf{z}}$ acts at $s = L$.
- c. Coulomb repulsion.* For tip-charged threads ($q_i = q_k = q$), the repulsion acts solely at the tips ($s = L$) with discrete forces:

$$\mathbf{F}_{r,\text{tip},k} = k_e q^2 \sum_{i \neq k} \frac{\mathbf{x}_k(L) - \mathbf{x}_i(L)}{\|\mathbf{x}_k(L) - \mathbf{x}_i(L)\|^3}, \quad k_e = \frac{1}{4\pi\epsilon_0}. \quad (6)$$

For uniformly distributed charges ($\lambda = q/L$), the mutual repulsion yields a continuous force per unit length along thread k at position s :

$$\mathbf{f}_{r,k}(s) = k_e \lambda^2 \sum_{i \neq k} \int_0^L \frac{\mathbf{x}_k(s) - \mathbf{x}_i(s')}{\|\mathbf{x}_k(s) - \mathbf{x}_i(s')\|^3} ds'. \quad (7)$$

- d. Weight.* The thread weight is $N\rho_t \pi r^2 L g \approx 1.7 \times 10^{-9}$ N for $N = 1$, about 10^{-4} of the spider weight. We neglect it in the analysis but keep it in the simulations.

D. Equilibrium equations for a flexible thread

Habchi and Jawed show that bending stiffness is negligible, with dimensionless ratio $\overline{YI} \sim 10^{-10}$ [1]. Each thread is a curved filament whose shape $\mathbf{x}(s)$ is part of the solution; straight segments appear only in the discretization of Sec. V. We therefore treat each thread as a perfectly flexible, inextensible string with tension $T(s)$, and neglect the (tiny) thread inertia. Local equilibrium reads

$$\partial_s (T \mathbf{t}) + \mathbf{f}_v + \mathbf{f}_e + \mathbf{f}_r = 0, \quad (8)$$

where $\mathbf{f}_r$ is the Coulomb force per unit length.

The boundary conditions are:

- at the spider ($s = 0$): $\sum_{j=1}^N T_j(0) \mathbf{t}_j(0) + (Q_s E - mg) \hat{\mathbf{z}} + \mathbf{F}_{v,s} = m \dot{\mathbf{v}}_s$;
- at the tip ($s = L$): for uniform charge, $T(L) = 0$; for tip charge, $T(L) \mathbf{t}(L) = qE \hat{\mathbf{z}} + \mathbf{F}_{r,\text{tip}}$.

For $N = 1$, $\lambda = 0$ and a horizontal wind, Eq. (8) reduces to problem A.1 of the physics competition, $\partial_s(T\mathbf{t}) = -\mathbf{f}_v$, with a drag force normal to the thread. Alex and Vlad must show this reduction explicitly; it is a good test of understanding.

E. Dimensionless groups

For a nearly vertical bundle ascending at velocity U relative to the air, the relative flow is aligned with the local thread tangents ($\mathbf{t} \approx \hat{\mathbf{z}}$), making the drag governed primarily by the parallel friction coefficient $\eta_{\parallel}$. The global vertical force balance reads:

$$NqE - mg = (N\eta_{\parallel}L + \zeta_s)U, \quad (9)$$

where U is the characteristic terminal velocity. This formulation yields the non-dimensional parameters governing the system dynamics:

$$\bar{F}_l = \frac{NqE}{mg} \quad \text{normalized lift-to-weight ratio (as in [1])}, \quad (10)$$

$$\Lambda = \frac{k_e q}{EL^2} = \frac{k_e q^2 / L^2}{qE} \quad \text{ratio of Coulomb repulsion to electrostatic lift per thread}, \quad (11)$$

$$\bar{w} = \frac{w(N\eta_{\parallel}L + \zeta_s)}{mg} \quad \text{dimensionless updraft velocity}, \quad (12)$$

$$\beta = \eta_{\perp} / \eta_{\parallel} \approx 1.87 \quad \text{RFT anisotropy ratio}. \quad (13)$$

For typical experimental conditions ($q = 0.6$ nC, $E = 7.41 \times 10^3$ V/m, $L = 0.5$ m), the relative Coulomb interaction parameter evaluates to $\Lambda \approx 2.9 \times 10^{-3}$, confirming that electrostatic lift dominates local thread interactions near the base.

[TO DO: Alex and Vlad verify with a dimensional analysis (Buckingham Π theorem) that the set is complete and compute typical values for the parameters in Table I. For $q = 0.6$ nC, $E = 7.41 \times 10^3$ V/m, and $L = 0.5$ m they should obtain $\Lambda \approx 2.9 \times 10^{-3}$.]

Reference solution (what Vlad and Alex should do). The steady state of a tip-charged bundle in a uniform updraft depends on N and on nine dimensional quantities: mg , qE , $k_e q^2$, YI (all containing forces), L , r , r_s , μ , w , with the output U . With three base dimensions (M, L, T) the Π theorem gives $10 - 3 = 7$ independent groups besides N ; choosing L , μ , and mg as repeating variables:

$$\bar{F}_l = \frac{NqE}{mg}, \quad \Lambda = \frac{k_e q}{EL^2}, \quad \frac{L}{r} (\rightarrow \beta, \eta_{\parallel}/\mu), \quad \frac{r_s}{L} (\rightarrow \zeta_s/N\eta_{\parallel}L), \quad \bar{w}, \quad \bar{YI}, \quad \bar{U} = \frac{U(N\eta_{\parallel}L + \zeta_s)}{mg}.$$

The set of Sec. II is therefore complete if $\zeta_s/(N\eta_{\parallel}L)$ is added; for $r_s = 1$ mm it equals $0.083/N$, a small correction kept in Eq. (9). For transients the mass also enters as inertia, through $t_s = m/(N\eta_{\parallel}L + \zeta_s)$ [Eq. (17)], and in turbulence through σ_w/w_s , ℓ/L , z_0/L , h/L , and ω_n . Typical values: $\ln(L/r) = 14.3$, $\beta = 1.87$, $\eta_{\parallel} = 8.35 \times 10^{-6}$ Pa s, $\eta_{\perp} = 1.56 \times 10^{-5}$ Pa s. With $E = 7.41 \times 10^3$ V/m and $L = 0.5$ m: $\Lambda = 4.9 \times 10^{-4}$, 2.9×10^{-3} , 4.9×10^{-2} for $q = 0.1$, 0.6 , 10 nC; over flat ground ($E = 120$ V/m) $\Lambda = 0.18$ for $q = 0.6$ nC, outside the small-angle regime. For $N = 1$, $q = 0.6$ nC, $m = 1$ mg: $\bar{F}_l = 0.45$. $\bar{w} = 0.14$ for $w = 0.3$ m/s ($N = 1$, $m = 1$ mg). With $I = \pi r^4/4$ and $Y = 5\text{--}50$ GPa, $YI/(k_e q^2) = 10^{-8}\text{--}10^{-7}$ for $q = 0.6$ nC (between 4×10^{-11} and 4×10^{-6} over $q = 0.1\text{--}10$ nC): bending is negligible.

III. AIR FLOW: MEAN-FLOW REFERENCE AND NEAR-SURFACE TURBULENCE

A. Uniform flow: a symmetry, not a new regime

In Eq. (3) the air velocity enters only through $\mathbf{v} - \mathbf{u}$. For a uniform and steady flow, $\mathbf{u} = \text{const.}$, the change of frame $\mathbf{x}' = \mathbf{x} - \mathbf{u}t$ maps the problem onto still air: accelerations are unchanged, and E varies negligibly over the distance travelled. The mapping is exact at all times if the initial state is the same relative to the air ($\mathbf{v}'(0) = \mathbf{v}(0) - \mathbf{u}$); otherwise the two motions differ during a transient and converge to the same steady state. The shape of the bundle and the velocity U relative to the air are therefore exactly those in still air, and the ground-frame velocity is $V = U + w$ for $\mathbf{u} = w\hat{\mathbf{z}}$. This symmetry is used only as a test of the code (Fig. 9). A flow can change the shape of the bundle only if it varies in space or in time on scales comparable to L or to the response time of the spider.

B. Mean-flow reference: deterministic threshold

For a steady updraft w , the spider rises if its ground velocity $V = U + w$ is positive. From Eq. (9),

$$V = w_s (\bar{F}_l - 1) + w > 0 \quad \Longleftrightarrow \quad w > w_c \equiv w_s (1 - \bar{F}_l), \quad w_s \equiv \frac{mg}{N\eta_{\parallel}L + \zeta_s}, \quad (14)$$

where w_s is the terminal falling speed of the uncharged spider–bundle system in calm air (obtained by balancing weight mg against total air drag $(N\eta_{\parallel}L + \zeta_s)w_s$). In dimensionless form, $\bar{w}_c = 1 - \bar{F}_l$. This straight line is the baseline reference against which the turbulent results of Sec. III C are compared. It assumes nearly vertical threads; Coulomb tilting of the threads (large Λ , large N) increases the total drag and shifts the true take-off boundary.

C. Near-surface turbulence

a. Why turbulence, and at which scale. Ballooning starts within a few metres of the ground, in the atmospheric surface layer. There, the standard deviation of the vertical velocity scales with the friction velocity, $\sigma_w \approx 1.25 u_*$ in neutral conditions [20, 21], and the dominant eddies have a size of the order of the height above ground, $\ell_w \sim z$ [20]. At take-off heights of $0.5\text{--}2$ m this is comparable to the thread length $L = 0.5$ m. A realistic flow must therefore vary in space across the bundle, not only in time; a spatially uniform gust $w(t)$ would be artificial.

TABLE II. Mean-flow threshold w_c (m/s) from Eq. (14). $L = 0.5$ m, $r = 300$ nm, $E = 7.41 \times 10^3$ V/m, tip charge. Negative values: the spider rises even in a downdraft. Values above ~ 1 m/s exceed the range of validity of the low-Reynolds-number drag laws and should be flagged. The column $q = 0$ equals the settling speed w_s . Numerical values: $-V$ at steady state in still air ($Q_s = 0$, $N_t = 100$). The charged multi-thread cases lie up to 12% below the analytical value (in absolute value) because the Coulomb splay of the threads increases the drag.

N	m (mg)	$q = 0$		$q = 0.6$ nC per thread	
		analytical	numerical	analytical	numerical
1	0.1	0.217	0.218	-0.767	-0.770
1	1	2.17	2.18	1.19	1.19
1	10	21.7	21.8	20.7	20.8
2	0.1	0.113	0.114	-0.910	-0.882
2	1	1.13	1.13	0.106	0.106
2	10	11.3	11.3	10.3	10.3
4	0.1	0.058	0.058	-0.986	-0.909
4	1	0.576	0.579	-0.468	-0.458
4	10	5.76	5.78	4.71	4.68
8	0.1	0.029	0.030	-1.03	-0.898
8	1	0.291	0.293	-0.763	-0.708
8	10	2.91	2.92	1.85	1.82

b. Synthetic turbulence. We generate the air velocity by kinematic simulation [22, 23], a sum of N_k random Fourier modes,

$$\mathbf{u}(\mathbf{x}, t) = U_h \hat{\mathbf{x}} + \sum_{n=1}^{N_k} [\mathbf{a}_n \cos(\mathbf{k}_n \cdot \mathbf{x}' + \omega_n t) + \mathbf{b}_n \sin(\mathbf{k}_n \cdot \mathbf{x}' + \omega_n t)], \quad \mathbf{x}' = \mathbf{x} - U_h t \hat{\mathbf{x}}, \quad (15)$$

with random directions $\hat{\mathbf{k}}_n$, amplitudes $\mathbf{a}_n, \mathbf{b}_n \perp \mathbf{k}_n$ (so that $\nabla \cdot \mathbf{u} = 0$), and magnitudes set by the energy spectrum in the shell Δk_n around k_n , normalized so that $\frac{1}{2} \langle |\mathbf{u} - U_h \hat{\mathbf{x}}|^2 \rangle = \int_0^\infty E(k) dk$ [23]. The energy spectrum is of von Kármán form,

$$E(k) \propto \sigma^2 \ell \frac{(k\ell)^4}{[1 + (k\ell)^2]^{17/6}}, \quad \int_0^\infty E(k) dk = \frac{3}{2} \sigma^2, \quad (16)$$

which has the $k^{-5/3}$ inertial range. The mean horizontal wind U_h advects the eddies past the spider (Taylor's hypothesis); by the symmetry above it has no other effect. The unsteadiness frequencies are $\omega_n = \lambda \sqrt{k_n^3 E(k_n)}$ with $\lambda \approx 0.5$ [23]. Each random seed defines one realization; the modes are stored with the trajectory, so that each run can be reproduced exactly.

TABLE III. Turbulence parameters. Surface-layer scalings from [20, 21].

Quantity	Symbol	Range	Note
Friction velocity	u_*	0.1–0.3 m/s	light to moderate wind
Vertical velocity std. dev.	σ_w	$1.25 u_* \approx 0.12$ –0.38 m/s	neutral surface layer
Integral length scale	ℓ	0.5–2 m	$\sim$ height above ground
Mean horizontal wind	U_h	0.5–3 m/s	1 m/s in the simulations
Number of modes	N_k	200	$k_{\min} = 0.1/\ell$, $k_{\max} = 2\pi/(5\Delta\ell)$
Unsteadiness parameter	λ	0.5	[23]

c. Validity. Relative velocities are of order $\sigma_w \lesssim 0.4$ m/s, so the thread Reynolds number is $\text{Re} = \rho_{\text{air}} \sigma_w r / \mu \sim 10^{-2}$ and RFT remains valid. The model (15) is homogeneous and isotropic, whereas surface-layer turbulence is anisotropic ($\sigma_u > \sigma_w$) and its scale grows with height. We match the vertical statistics, $\sigma = \sigma_w$ and $\ell = \ell_w$, which control take-off. **[TO DO: Alex and Vlad: check numerically that the generated field has the prescribed σ_w and spectrum (Fig. 6).]**

Reference solution (what Vlad and Alex should do). Figure 6 (50 realizations, $\sigma_w = 0.25$ m/s, $\ell = 1$ m, $N_k = 200$): the sample standard deviation of w is 0.249 m/s after the renormalization of Appendix D, the PDF is Gaussian, and the one-dimensional spectrum follows the von Kármán target, including the $k^{-5/3}$ range, up to $k \approx 80$ m $^{-1}$; above, it falls off towards $k_{\max} = 251$ m $^{-1}$ because of the finite shell width.

D. Take-off probability

a. Definition. The spider is released at height z_0 above the ground (tip of a grass blade or twig) and followed until it either reaches a height h (*take-off*) or returns to the ground, $z = 0$ (*failure*). The take-off probability P is the fraction of realizations that reach h . It depends on $\bar{F}_l$, N , Λ , and the turbulence through σ_w/w_s and ℓ/L .

b. Analytical reference: drift-diffusion limit. If the turbulent eddies are much larger than the bundle ($\ell \gg L$) and their turnover time ℓ/σ_w is much longer than the velocity adjustment time of the spider (the time constant required to reach terminal speed),

$$t_s = \frac{m}{N\eta_{\parallel}L + \zeta_s} = \frac{w_s}{g} \approx 0.2 \text{ s} \quad (m = 1 \text{ mg}, N = 1), \quad (17)$$

the spider simply follows the local fluid motion with a constant downward/upward drift speed $U_0 = w_s(\bar{F}_l - 1)$ relative to the air. On time scales longer than the eddy lifetime $T_L \sim \ell/\sigma_w$, its height $z(t)$ executes a drift-diffusion process with turbulent diffusivity $K = \sigma_w^2 T_L \sim \sigma_w \ell$ [24]. The probability $P(z_0)$ to reach take-off height h before falling back to the ground ($z = 0$) satisfies the steady advection-diffusion equation $U_0 P' + K P'' = 0$ with boundary conditions $P(0) = 0$ and $P(h) = 1$:

$$P = \frac{1 - e^{-U_0 z_0/K}}{1 - e^{-U_0 h/K}}, \quad U_0 = w_s(\bar{F}_l - 1), \quad K \simeq \sigma_w \ell \quad (18)$$

For $U_0 \rightarrow 0$, $P \rightarrow z_0/h$; for $|U_0| h/K \gg 1$, P switches sharply from 0 to 1 at $\bar{F}_l = 1$, recovering the deterministic threshold. Turbulence thus smooths the step $\bar{w}_c = 1 - \bar{F}_l$ into a sigmoid of width set by the Péclet number $\text{Pe} = w_s h/K$.

Equation (18) is a reference limit. At take-off $\ell \sim L$ and eddy times $\sim \ell/\sigma_w \sim 1\text{--}5$ s are only one order of magnitude above t_s , so its assumptions are only marginally satisfied; Sec. VII C tests it against the simulations. Alex and Vlad must derive Eq. (18) independently.

[TO DO: Alex and Vlad: compute t_s , w_s , K , and Pe for the parameter ranges of Tables I and III.]

Reference solution (what Vlad and Alex should do). With $w_s = mg/(N\eta_{\parallel}L + \zeta_s)$, $t_s = w_s/g$, $K = \sigma_w \ell$, and $\text{Pe} = w_s h/K$ ($h = 2$ m), for $\sigma_w \ell$ between $0.12 \times 0.5 = 0.06$ and $0.38 \times 2 = 0.76$ m 2 /s:

m (mg)	N	w_s (m/s)	t_s (s)	Pe ($K = 0.06$)	Pe ($K = 0.76$)
0.1	1	0.217	0.022	7.2	0.57
0.1	8	0.029	0.003	0.97	0.08
1	1	2.17	0.22	72	5.7
1	8	0.291	0.030	9.7	0.77
10	1	21.7	2.2	720	57
10	8	2.91	0.30	97	7.7

Turbulence matters (Pe of order 1–10) for light spiders and many threads; for $m = 10$ mg and $N = 1$ the transition is practically deterministic, and w_s exceeds the validity range of the drag laws (Appendix A). The simulations give an effective diffusivity about four times smaller than $\sigma_w \ell$ (Sec. VII C), so the effective Pe is about four times larger than in this table.

IV. ANALYTICAL SOLUTION FOR TIP-CHARGED THREADS

A. Equations along one thread

Consider the steady state for a thread with charge concentrated exclusively at the tip ($\lambda = 0$ and $\mathbf{f}_r = 0$ along $0 \leq s < L$). In a 2D vertical plane, the thread profile $\mathbf{x}(s)$ is parameterized by the local inclination angle $\theta(s)$ relative

to the vertical $\hat{\mathbf{z}}$, with unit tangent $\mathbf{t} = (\sin \theta, \cos \theta)$ and normal $\mathbf{n} = (\cos \theta, -\sin \theta)$ such that $\partial_s \mathbf{t} = \theta' \mathbf{n}$. In the frame of the ascending spider, the relative air velocity flowing past the thread is $\mathbf{v} - \mathbf{u} = U \hat{\mathbf{z}}$.

Decomposing the unit vertical vector as $\hat{\mathbf{z}} = (\cos \theta) \mathbf{t} - (\sin \theta) \mathbf{n}$, the RFT drag force per unit length (3) simplifies to $\mathbf{f}_v = -\eta_{\parallel} U \cos \theta \mathbf{t} + \eta_{\perp} U \sin \theta \mathbf{n}$. Substituting this into the string equilibrium equation $\partial_s(T \mathbf{t}) + \mathbf{f}_v = 0$ and projecting along $\mathbf{t}$ and $\mathbf{n}$ yields

$$\frac{dT}{ds} = \eta_{\parallel} U \cos \theta, \quad (19)$$

$$T \frac{d\theta}{ds} = -\eta_{\perp} U \sin \theta. \quad (20)$$

B. An exact first integral

To isolate the spatial variation of thread geometry, we eliminate the arc-length coordinate s by dividing the normal equilibrium equation (20) by the tangential equation (19). Using $\beta = \eta_{\perp}/\eta_{\parallel}$, this yields a separable differential equation relating local tension and angle:

$$\frac{\cos \theta}{\sin \theta} d\theta = -\beta \frac{dT}{T}. \quad (21)$$

Integrating both sides directly yields an exact first integral for flexible threads in RFT:

$$\boxed{T(s)^{\beta} \sin \theta(s) = \text{const.}} \quad (22)$$

Equation (22) is exact within RFT, requiring no small-angle approximation. It shows that thread curvature is concentrated near the base $s = 0$ (where tension T is minimal) and that the thread straightens toward the tip as tension accumulates. The spatial trajectory $(x(s), z(s))$ follows by quadrature:

$$x(s) = \int_0^s \sin \theta ds' = \frac{1}{\eta_{\parallel} U} \int_{T_0}^{T(s)} \tan \theta dT, \quad z(s) = \int_0^s \cos \theta ds'. \quad (23)$$

[TO DO: Alex and Vlad to check Eq. (22) on steady DER simulations: $T^{\beta} \sin \theta$ must be constant along the thread. This is the cleanest test of the code.]

Reference solution (what Vlad and Alex should do). Figure 4: for $N = 2$, $\bar{F}_l = 2$, $N_t = 100$, $T^{\beta} \sin \theta$ along the thread varies by 0.019% of its mean (Table VI). Derivation check: from Eq. (20)/Eq. (19), $\cot \theta d\theta = -\beta dT/T$, so $\ln \sin \theta = -\beta \ln T + \text{const.}$

C. Boundary conditions for N threads

Assume a symmetric configuration: the tips of the N threads lie on a horizontal circle of radius R , at azimuths $2\pi j/N$. The radial Coulomb force on one tip due to the other $N - 1$ tips is

$$F_C = \frac{k_e q^2}{4R^2} S_N, \quad S_N \equiv \sum_{j=1}^{N-1} \frac{1}{\sin(\pi j/N)}, \quad (24)$$

with $S_2 = 1$, $S_4 = 1 + 2\sqrt{2} \approx 3.83$, and $S_8 \approx 11.2$.

To derive Eq. (24), place the tip under consideration at azimuth 0, $\mathbf{x}_0 = R(1, 0)$, and tip j at $\varphi_j = 2\pi j/N$, $\mathbf{x}_j = R(\cos \varphi_j, \sin \varphi_j)$, with $j = 1, \dots, N - 1$. The separation vector and its length are

$$\mathbf{x}_0 - \mathbf{x}_j = R(1 - \cos \varphi_j, -\sin \varphi_j), \quad d_j = \|\mathbf{x}_0 - \mathbf{x}_j\| = R\sqrt{2(1 - \cos \varphi_j)} = 2R \sin(\pi j/N). \quad (25)$$

The radial component of the Coulomb force exerted by tip j is

$$F_{C,j} = \frac{k_e q^2}{d_j^3} R(1 - \cos \varphi_j) = \frac{k_e q^2 2R \sin^2(\pi j/N)}{8R^3 \sin^3(\pi j/N)} = \frac{k_e q^2}{4R^2} \frac{1}{\sin(\pi j/N)}. \quad (26)$$

The tangential components, $\propto \sin \varphi_j$, cancel in pairs because tips j and $N-j$ are symmetric about the radius through the tip considered. Summing $F_{C,j}$ over j gives Eq. (24). **[TO DO: Alex and Vlad compute S_8 exactly.]**

Reference solution (what Vlad and Alex should do). With $\sin(\pi/8) = \frac{1}{2}\sqrt{2-\sqrt{2}}$, $\sin(3\pi/8) = \frac{1}{2}\sqrt{2+\sqrt{2}}$, and $\sqrt{2+\sqrt{2}} + \sqrt{2-\sqrt{2}} = \sqrt{4+2\sqrt{2}}$,

$$S_8 = 1 + 2 \left[\frac{1}{\sin(\pi/8)} + \frac{1}{\sin(\pi/4)} + \frac{1}{\sin(3\pi/8)} \right] = 1 + 2\sqrt{2} + 4\sqrt{2+\sqrt{2}} = 11.2195.$$

At the tip, the tension balances the electrostatic and Coulomb forces:

$$T_L \cos \theta_L = qE, \quad T_L \sin \theta_L = F_C. \quad (27)$$

At the spider, $NT_0 \cos \theta_0 = mg + \zeta_s U$.

D. Small-angle limit

In the small-angle regime ($\theta \ll 1$), we approximate $\cos \theta \approx 1$ and $\sin \theta \approx \theta$. The tangential tension balance (19) integrates directly to a linear profile $T(s) = T_0 + \eta_{\parallel} U s$, with total tension variation $T_L - T_0 = \eta_{\parallel} U L$. We define the tension ratio across the thread:

$$\tau \equiv \frac{T_0}{T_L} = \frac{mg + \zeta_s U}{NqE}. \quad (28)$$

From the first integral (22), the angular profile takes the power-law form $\theta(s) = \theta_L [T_L/T(s)]^\beta$. Changing the integration variable from arc length s to tension T via $ds = dT/(\eta_{\parallel} U)$, the radial deflection $R = \int_0^L \theta(s) ds$ is evaluated analytically:

$$R = \int_{T_0}^{T_L} \theta_L \left(\frac{T_L}{T} \right)^\beta \frac{dT}{\eta_{\parallel} U} = \theta_L L g(\tau), \quad (29)$$

where $g(\tau)$ is a geometric shape factor accounting for thread inclination and curvature:

$$g(\tau) \equiv \frac{\tau^{1-\beta} - 1}{(\beta - 1)(1 - \tau)}. \quad (30)$$

Note that $\lim_{\tau \rightarrow 1} g(\tau) = 1$, recovering a straight, uniformly tilted thread.

Combining $R = \theta_L L g(\tau)$ with the tip boundary condition $\theta_L \approx F_C/(qE) = k_e q S_N/(4R^2 E)$ from Eq. (24), we derive closed-form expressions for **the opening of the bundle**:

$$\boxed{\frac{R}{L} = \left[\frac{S_N \Lambda g(\tau)}{4} \right]^{1/3}, \quad \theta_L = \frac{S_N \Lambda}{4} \left(\frac{L}{R} \right)^2} \quad (31)$$

This closed-form solution remains valid for $R \ll L$.

a. Order of magnitude. For $N = 2$, $q = 0.6$ nC, $E = 7.41 \times 10^3$ V/m, $L = 0.5$ m, and $\tau \approx 1$: $\Lambda \approx 2.9 \times 10^{-3}$, $R/L \approx 0.09$, $R \approx 4.5$ cm, and $\theta_L \approx 0.09$ rad. The small-angle approximation is therefore justified.

b. Testable predictions.

1. $R \propto q^{1/3} E^{-1/3} L^{1/3}$ at fixed τ , a power law to be checked on a log-log plot.
2. The dependence on N enters only through $S_N^{1/3}$ and through τ . For large N , $S_N \simeq (2N/\pi) [\ln(2N/\pi) + \gamma]$, with γ the Euler–Mascheroni constant. This follows from $1/\sin(\pi j/N) \approx N/(\pi j)$ for the dominant near neighbours and the Euler–Maclaurin formula; the relative error is 0.6% for $N = 4$, 0.1% for $N = 8$, and 0.02% for $N = 16$. **[TO DO: Alex and Vlad: tabulate S_N for $N = 2, \dots, 16$.]**

Reference solution (what Vlad and Alex should do).

N	2	3	4	5	6	7	8
S_N	1.0000	2.3094	3.8284	5.5055	7.3094	9.2191	11.2195
asympt. error	4.3%	1.2%	0.57%	0.32%	0.20%	0.13%	0.10%
N	9	10	11	12	13	14	15, 16
S_N	13.2993	15.4498	17.6639	19.9358	22.2607	24.6346	27.0539, 29.5156
asympt. error	0.07%	0.06%	0.04%	0.04%	0.03%	0.03%	0.02%

The asymptotic formula always overestimates S_N .

3. A uniform flow does not change R (Sec. III); turbulence does, and the statistics of R are a numerical result.

The assumption that all tips lie on the same circle is reasonable for $N \leq 8$ and tip charge. For uniform charge, Eq. (8) acquires the distributed term $\mathbf{f}_r$ and no longer has a simple closed-form solution; that case remains numerical in the present work.

V. NUMERICAL METHOD

A. Discretization

The simulations use the discrete elastic rods (DER) method [5] as implemented in [1]. The spider is node $\mathbf{x}_0$; each thread j is discretized into N_t edges with nodes $\mathbf{x}_{(j-1)N_t+1}, \dots, \mathbf{x}_{jN_t}$, so the system has $NN_t + 1$ nodes. Each edge carries a twist angle θ^k . The degrees of freedom are

$$\boldsymbol{\xi} = [\mathbf{x}_0, \mathbf{x}_1, \dots, \mathbf{x}_{NN_t}, \theta^0, \dots, \theta^{NN_t-1}]^T \in \mathbb{R}^{n_{\text{dof}}}, \quad n_{\text{dof}} = 3(NN_t + 1) + NN_t. \quad (32)$$

The elastic energy $E_{\text{el}}(\boldsymbol{\xi}) = E_s + E_b + E_t$ contains stretching, bending, and twisting contributions [5]. With edge vectors $\mathbf{e}^k$, reference edge length $l_0 = L/N_t$, Voronoi length Δl_i , cross-section $A = \pi r^2$, and moments $I = \pi r^4/4$, $J = \pi r^4/2$,

$$E_s = \frac{1}{2} Y A \sum_k \left(\frac{\|\mathbf{e}^k\|}{l_0} - 1 \right)^2 l_0, \quad (33)$$

$$E_b = \sum_i \frac{YI}{\Delta l_i} \|\boldsymbol{\kappa}_i - \boldsymbol{\kappa}_i^0\|^2, \quad (\boldsymbol{\kappa} \mathbf{b})_i = \frac{2 \mathbf{e}^{i-1} \times \mathbf{e}^i}{\|\mathbf{e}^{i-1}\| \|\mathbf{e}^i\| + \mathbf{e}^{i-1} \cdot \mathbf{e}^i}, \quad (34)$$

$$E_t = \sum_i \frac{GJ}{\Delta l_i} m_i^2, \quad m_i = \theta^i - \theta^{i-1} + \Delta m_{i,\text{ref}}, \quad (35)$$

where $\boldsymbol{\kappa}_i$ collects the projections of the curvature binormal $(\boldsymbol{\kappa} \mathbf{b})_i$ on the material frames of the two adjacent edges, $\boldsymbol{\kappa}_i^0 = \mathbf{0}$ for naturally straight threads, $G = Y/[2(1 + \nu)]$, and $\Delta m_{i,\text{ref}}$ is the reference twist of the parallel-transported frames. The bending and twisting stencils do not connect different threads through the spider node, which is a free junction. The stretching stiffness is chosen large to enforce inextensibility. The external force vector is

$$\mathbf{f}^{\text{ext}}(\boldsymbol{\xi}, \dot{\boldsymbol{\xi}}) = \mathbf{W} + \mathbf{F}_v + \mathbf{F}_r + \mathbf{F}_l, \quad (36)$$

with, at node k with Voronoi length Δl_k and node tangent $\mathbf{t}_k$:

$$\mathbf{F}_{v,k} = -[\eta_{\parallel} \mathbf{t}_k \mathbf{t}_k^T + \eta_{\perp} (\mathbb{I} - \mathbf{t}_k \mathbf{t}_k^T)] \Delta l_k (\mathbf{v}_k - \mathbf{u}(\mathbf{x}_k, t)), \quad (37)$$

$$\mathbf{F}_{l,k} = q_k E(z_k) \hat{\mathbf{z}}, \quad (38)$$

the Coulomb term from Eq. (6), and the Stokes drag at the spider node. As in [1], the charge of the spider does not act on the thread nodes (sum over $i \neq 0$); the spider still feels the thread charges. Including it changes the forces by $\lesssim Q_s/q \sim 10^{-3}$. The nodal charges are $q_k = q$ at the tip nodes (case a) or $q_k = q \Delta l_k/L$ (case b), and $q_0 = Q_s$.

B. Time integration

The equations of motion $m_i \ddot{\xi}_i + \partial E_{\text{el}} / \partial \xi_i - f_i^{\text{ext}} = 0$ are integrated with the implicit (backward) Euler method. At each step we solve the nonlinear residual

$$\mathbf{F}(\boldsymbol{\xi}^{n+1}) \equiv \frac{\mathbf{M}}{\Delta t} \left(\frac{\boldsymbol{\xi}^{n+1} - \boldsymbol{\xi}^n}{\Delta t} - \dot{\boldsymbol{\xi}}^n \right) + \nabla E_{\text{el}}(\boldsymbol{\xi}^{n+1}) - \mathbf{f}^{\text{ext}}(\boldsymbol{\xi}^{n+1}) = \mathbf{0} \quad (39)$$

by Newton–Raphson, with Jacobian

$$\mathbf{J} = \frac{\mathbf{M}}{\Delta t^2} + \nabla^2 E_{\text{el}} - \frac{\partial \mathbf{f}^{\text{ext}}}{\partial \boldsymbol{\xi}}. \quad (40)$$

The drag term is linear in the velocity $(\boldsymbol{\xi}^{n+1} - \boldsymbol{\xi}^n)/\Delta t$, so its contribution to $\mathbf{J}$ is $\mathbf{C}/\Delta t$, with $\mathbf{C}$ the block-diagonal RFT resistance matrix (the dependence of $\mathbf{t}_k$ on $\boldsymbol{\xi}$ may be lagged). The Coulomb Jacobian is dense for uniform charge and is computed analytically from Eq. (6). The step size is adaptive, as in [1]: divided by 10 on Newton failure, multiplied by 10 after 10 successful steps, and capped at Δt_{max} . The rotational inertia of the twist degrees of freedom is $\rho_t J l_0 / 2$ per edge, with Poisson ratio $\nu = 0.5$. A run is aborted if Δt falls below 10^{-9} s. The default numerical parameters are listed in Table XII. For the isotropic, naturally straight threads considered here, the twist angles stay below 10^{-8} rad, as expected for free ends. The procedure is summarized in Algorithm 1; Algorithm 2 describes the parameter sweep used for the phase diagram.

Algorithm 1 Implicit DER time stepping for a multi-thread ballooning spider in an air flow

Require: parameters $\mathcal{P} = \{N, N_t, L, r, m, r_s, q, \text{charge model}, Y, \mu\}$, field $E(z)$, air velocity $\mathbf{u}(\mathbf{x}, t)$
Require: initial state ξ^0 (threads vertical, spaced $d_0 = 100 \mu\text{m}$), $\xi^0 = \mathbf{0}$
Require: Δt_0 , $\Delta t_{\max}$, tolerance ϵ , max. Newton iterations K , final time t_{end}
Ensure: trajectory $\{\xi^n, t^n\}$, steady-state flag

```

1:  $n \leftarrow 0, t \leftarrow 0, \Delta t \leftarrow \Delta t_0, c \leftarrow 0$  ▷ c: consecutive successful steps
2: compute lumped mass matrix  $\mathbf{M}$  (spider mass at node 0, thread mass on other nodes)
3: while  $t < t_{\text{end}}$  do
4:    $\xi^{(0)} \leftarrow \xi^n; k \leftarrow 0$  ▷ Newton initial guess
5:   repeat
6:     update reference frames by parallel transport; compute material frames from  $\xi^{(k)}$ 
7:      $\mathbf{v}^{(k)} \leftarrow (\xi^{(k)} - \xi^n)/\Delta t$ 
8:      $\mathbf{f}^{\text{ext}} \leftarrow \mathbf{W} + \mathbf{F}_v(\xi^{(k)}, \mathbf{v}^{(k)}, \mathbf{u}) + \mathbf{F}_r(\xi^{(k)}) + \mathbf{F}_l(\xi^{(k)})$  ▷ Eqs. (6), (37)
9:     assemble residual  $\mathbf{F}$  (Eq. (39)) and Jacobian  $\mathbf{J}$ 
10:    solve  $\mathbf{J} \Delta \xi = \mathbf{F}$ ;  $\xi^{(k+1)} \leftarrow \xi^{(k)} - \Delta \xi$ ;  $k \leftarrow k + 1$ 
11:  until  $\|\mathbf{F}\|_1 < \epsilon$  or  $k = K$ 
12:  if  $\|\mathbf{F}\|_1 \geq \epsilon$  then ▷ Newton failed
13:     $\Delta t \leftarrow \Delta t/10$ ;  $c \leftarrow 0$  and retry the step
14:  else
15:     $\xi^{n+1} \leftarrow \xi^{(k)}$ ;  $\dot{\xi}^{n+1} \leftarrow (\xi^{n+1} - \xi^n)/\Delta t$ ;  $t \leftarrow t + \Delta t$ ;  $n \leftarrow n + 1$ 
16:     $c \leftarrow c + 1$ ; if  $c = 10$  then  $\Delta t \leftarrow \min(10 \Delta t, \Delta t_{\max})$ ,  $c \leftarrow 0$ 
17:    save  $(t, \xi^n)$  at fixed output interval ▷ HDF5, for the ML part
18:    if  $|\dot{z}_0^n - \dot{z}_0^{n-1}|/|\dot{z}_0^n| < \delta$  over a window  $t_w$  then ▷ steady state
19:      return trajectory, steady-state flag = true
20:    end if
21:  end if
22: end while
23: return trajectory, steady-state flag = false

```

Algorithm 2 Ensemble estimate of the take-off probability

Require: grids $\{N\}$, $\{\bar{F}_l\}$ (via q), $\{\sigma_w\}$, $\{\ell\}$; release height z_0 , target height h ; M realizations per point

```

1: for each  $(N, \bar{F}_l, \sigma_w, \ell)$  do
2:    $n_{\text{up}} \leftarrow 0$ 
3:   for  $i = 1, \dots, M$  do
4:     draw seed  $s_i$ ; build the modes  $\{\mathbf{k}_n, \mathbf{a}_n, \mathbf{b}_n, \omega_n\}$  of Eq. (15)
5:     hold the spider node fixed at  $z_0$  in still air for a time  $t_c$  (Algorithm 1 with  $\xi_0$  clamped); release at  $t = 0$ 
        with  $\mathbf{u}(\mathbf{x}, t)$  switched on
6:     run Algorithm 1 with  $\mathbf{u}(\mathbf{x}, t)$  from Eq. (15), stopping when  $z_0(t) \geq h$ ,  $z_0(t) \leq 0$ , or  $t \geq t_{\text{end}}$ 
7:     if  $z_0 \geq h$  then  $n_{\text{up}} \leftarrow n_{\text{up}} + 1$ 
8:     record: outcome, exit time, time series of  $R(t)$ ,  $\theta_L(t)$ ,  $d_{\min}(t)$ ; flag ENTANGLED if  $d_{\min} < 2r$  at exit
9:   end for
10:   $\hat{P} \leftarrow n_{\text{up}}/M$  with Wilson 95% interval; compare with Eq. (18)
11: end for

```

Algorithm 1 is the one of [1], with three explicit additions: the air velocity $\mathbf{u}(\mathbf{x}, t)$ in the drag, evaluated at every node, the stopping tests, and systematic data saving. The realizations of Algorithm 2 are independent and run in parallel. The open-source code DisMech [6] implements the DER core. If adapting it takes more than a few days, a bead-spring chain with stiff springs, RFT forces on nodes, and the same implicit scheme is sufficient, since bending is negligible.

VI. LEARNED SURROGATE MODEL

This section belongs to the ML part (Octavian). Only the structure and the minimum content expected by a physics audience are fixed here.

A. Data set

The training data are the trajectories produced by Algorithm 2, stored in the format of Table XI. **[TO DO: Number of runs, parameter ranges, time step between saved frames, total number of frames.]**

TABLE IV. Data splits. Generalization is tested on numbers of threads and parameter values not seen during training.

Split	N	q (nC)	σ_w (m/s)	Runs	Frames
Train	?	?	?	?	?
Validation	?	?	?	?	?
Test (interpolation)	?	?	?	?	?
Test (unseen N)	?	?	?	?	?
Test (unseen σ_w)	?	?	?	?	?

B. Graph representation

Each node of the discretized bundle is a graph node, with features **[TO DO: position relative to the spider, velocity history, charge q_k , node type (spider, interior, tip), and global parameters E , σ_w , ℓ ; the air velocity $\mathbf{u}(\mathbf{x}_k, t)$ at each node as input]**. Two types of edges are used: (i) *material edges* along each thread, and (ii) *interaction edges* that carry the Coulomb and hydrodynamic coupling between threads. **[TO DO: Radius graph versus Ewald/long-range scheme; justify with the $1/r^2$ decay of Eq. (6).]**

C. Architecture and training

[TO DO: Encoder–processor–decoder architecture [14] with long-range message passing [13]; number of layers, latent size; prediction target (acceleration, velocity, or next position); loss; noise injection; optimizer and schedule; hardware and training time.]

D. Evaluation metrics

- one-step and rollout mean squared error on node positions;
- error in the steady-state observables V , R/L , and θ_L ;
- violation of the analytical constraints: deviation of $T^\beta \sin \theta$ from a constant [Eq. (22)], of R/L from Eq. (31), and of the rise/fall classification from Eq. (14);
- computational cost: wall-clock time per run and per estimate of P , one-time costs of data generation and training, break-even number of evaluations (43), and error of P at equal compute budget (Sec. VIID 1).

VII. RESULTS

We present the numerical and analytical results in four parts. First, Sec. VII A validates our implicit DER numerical solver against exact analytical benchmarks for terminal velocity and reproduces established multi-thread cases from the literature [1]. Second, Sec. VII B compares multi-thread steady-state geometries against the analytical opening law and first integral derived in Sec. IV. Third, Sec. VII C evaluates take-off probabilities in turbulent air relative to the drift–diffusion model. Fourth, Sec. VII D assesses the generalization capability of the graph neural network surrogate.

A. Validation of the numerical model

1. Analytical check: terminal velocity

From Eq. (9), for a vertical thread in still air and $\zeta_s \ll N\eta_{\parallel}L$:

$$U \approx \frac{NqE - mg}{N\eta_{\parallel}L} = \frac{\ln(L/r) - \frac{1}{2}}{2\pi} \frac{NqE - mg}{N\mu L} \approx 2.2 \frac{NqE - mg}{N\mu L}. \quad (41)$$

Habchi and Jawed normalize the terminal velocity by $v_{\text{charac}} = (NqE - mg)/(\mu NL)$ and report a numerical steady value $\bar{v}_t \approx 2.2$ for a single thread [1]. Equation (41) explains this constant analytically: it corresponds precisely to the geometric factor $[\ln(L/r) - 1/2]/(2\pi)$ stemming from slender-body RFT theory. Including the Stokes drag of the spider body, the exact dimensionless terminal velocity for straight vertical threads becomes:

$$\bar{v}_t^{\text{st}} = \frac{\mu NL}{N\eta_{\parallel}L + \zeta_s}, \quad (42)$$

which reduces to Eq. (41) for $\zeta_s \ll N\eta_{\parallel}L$. The correction is not small for short threads: $\zeta_s/(\eta_{\parallel}L) = 0.37$ for $L = 0.1$ m and 0.08 for $L = 0.5$ m. For $N > 1$ the threads tilt, the normal component $\eta_{\perp} > \eta_{\parallel}$ enters the drag, and $\bar{v}_t$ falls below Eq. (42).

Table V compares both expressions with the simulations. The numerical values agree with Eq. (42) within 0.36–0.45%, consistent with the discretization error at $N_t = 100$ (Table VII); Eq. (41) overestimates $\bar{v}_t$ by up to 36% for $L = 0.1$ m, because it neglects the body drag.

TABLE V. Dimensionless terminal velocity $\bar{v}_t = U\mu NL/(NqE - mg)$ for a single vertical thread ($N = 1$, $r = 300$ nm, $m = 1$ mg, $Q_s = 0$, tip charge with $\bar{F}_l = 2$, still air, constant field $E = 7.41 \times 10^3$ V/m, $N_t = 100$). Analytical values from Eq. (41) (thread drag only) and Eq. (42) (with the Stokes drag of the body); numerical values from Algorithm 1 at steady state. The relative error is with respect to Eq. (42).

L (m)	$\ln(L/r)$	$\bar{v}_t$, Eq. (41)	$\bar{v}_t$, Eq. (42)	$\bar{v}_t$ numerical	Relative error (%)
0.1	12.72	1.944	1.423	1.428	0.36
0.5	14.33	2.201	2.032	2.041	0.45
1.0	15.02	2.311	2.214	2.224	0.45

2. Reproduction of the validation in [1]

- Test 1.** One thread of 0.5 m in the chamber field of Eq. (2), with the mass of the spiders of Morley and Gorham, $m = 0.9$ mg [3], and $Q_s = 0$. Habchi and Jawed report a steady velocity of ≈ 8.5 cm/s reached after ≈ 0.1 s [1], but do not state the charge or its distribution for this case. With tip charge, the tip sits at $z \approx L$, where $E \simeq E_{\infty} = 7.41 \times 10^3$ V/m, so the steady velocity follows from Eq. (9); we choose $q = (mg + U\zeta_{\text{tot}})/E_{\infty} = 1.2433$ nC, with $\zeta_{\text{tot}} = \eta_{\parallel}L + \zeta_s$, to target $U = 8.5$ cm/s. This test therefore checks the force balance and the transient, not the value 8.5 cm/s independently. We run two variants: (a) the charge at the tip, and (b) the same charge on the spider node, which mimics the one-dimensional model of [3] and places the charge in the enhanced field near the prominence.
- Test 2.** One point of Fig. 6 in [1]: $N = 2$, tip charge, $\bar{F}_l = 2$ ($q = 1.324$ nC), $m = 1$ mg, $Q_s = 3$ pC, constant field $E = 7.41 \times 10^3$ V/m. Target: $\bar{v}_t \approx 2$, read from the figure.
- Test 3.** Discretization convergence for test 2: $N_t = 25, 50, 100, 200$ (Table VII).
- Code checks.** Finite-difference verification of all gradients, Hessians, and Jacobians; terminal velocity against Eq. (9), with and without Q_s ; the first integral (22); and the uniform-flow invariance of Sec. III.

For the uniform-flow check, both runs use a fixed step $\Delta t = 3 \times 10^{-5}$ s and the default Newton tolerance, and the shapes are compared in the spider frame every 0.1 s up to $t = 2$ s. When initialized with identical relative velocities, the thread profiles in the moving and stationary air frames coincide to within $8.5 \times 10^{-12}L$, demonstrating Galilean

invariance down to floating-point precision. When both simulations are initialized from rest in the ground frame, the shape mismatch decays exponentially with a characteristic relaxation time constant of $\tau_r \approx 0.24$ s, roughly four times the vertical translational time constant $t_s = m/(N\eta_{\parallel}L + \zeta_s) = 0.059$ s. The tip radius deviation $R(t)$ relaxes with this same time scale (0.238 s), identifying the slowest physical degree of freedom as the transverse Coulomb opening of the bundle resisted by normal RFT drag. **[TO DO: Analytical estimate of this time constant.]**

Reference solution (what Vlad and Alex should do). The slowest mode is the lateral opening. Treat one thread as a string with tension T and normal drag $\eta_{\perp}$, fixed at the spider: $\eta_{\perp} \partial_t x = T \partial_s^2 x$. At the tip, the Coulomb force $F_C \propto R^{-2}$ linearized about equilibrium ($F_C = qE\theta_L$) gives $T \partial_s x|_L = -(2T/L)x_L$. The mode $\sin(ks)$ then satisfies $\tan kL = -kL/2$, so $kL = 2.289$ and

$$\tau_R = \frac{\eta_{\perp} L^2}{(kL)^2 \bar{T}} = \frac{\eta_{\perp} L^2}{5.24 \bar{T}}.$$

For $N = 4$, $\bar{F}_l = 2$, the tension grows from $T_0 \approx 0.5 qE$ at the spider to qE at the tip; with $\bar{T} \approx 0.75 qE$ ($qE = 4.9 \times 10^{-6}$ N), $\tau_R \approx 0.20$ s, against 0.24 s in the simulation; with $\bar{T} = qE$, 0.15 s. The estimate gives the right order and the scaling $\tau_R \propto \eta_{\perp} L^2 / (qE)$, i.e. slower relaxation for longer threads and weaker lift.




FIG. 2. Test 1: take-off of a spider ($m = 0.9$ mg, $Q_s = 0$) with one thread ($L = 0.5$ m, $N_t = 100$) in the chamber field of Eq. (2), with $q = 1.2433$ nC. (a) Altitude $z_0(t)$ and (b) vertical velocity $v_z(t)$ of the spider node, for the charge at the thread tip (solid) and on the spider node (dashed). The dotted line marks the steady velocity ≈ 8.5 cm/s reported in [1]. With tip charge the velocity relaxes on the time scale $t_s = m/(\eta_{\parallel}L + \zeta_s) = 0.20$ s; with the charge on the spider, the enhanced field near the prominence ejects the spider at up to 1.21 m/s before it settles.

B. Analytical vs. numerical comparison

Table VIII compares the steady opening of tip-charged bundles with Eq. (31). The simulated tip radius is 0.8%, 1.3%, and 1.8% below the prediction for $N = 2, 4$, and 8, and the tip angle θ_L is 1.8–3.7% above it, although R/L reaches 0.20. The deviations grow with R/L , as expected from the small-angle approximation. The normalized velocity is 1.4–3.3% below the straight-thread value of Eq. (42), which measures the extra drag due to the tilt of the threads. The threads never come closer than 4 mm, so no entanglement occurs in still air. Figure 3 extends the comparison to $\bar{F}_l = 1.2$ –5: the data for all N collapse on the line of slope 1 up to $R/L \approx 0.2$, and fall below it at larger openings, by about 10% at $R/L \approx 0.3$, where the small-angle approximation breaks down.

C. Take-off in turbulence

a. Data set. The sweep of Algorithm 2 covers $N = 1, 2, 4, 8$, $\sigma_w = 0.15$ and 0.30 m/s, and seven values of the scaled drift $x = w_s(\bar{F}_l - 1)h/K$, $x \in \{-4, -2, -1, 0, 1, 2, 4\}$, with $K = \sigma_w \ell$ (8000 realizations), plus $N = 3, 6$ at $\sigma_w = 0.30$ m/s and $N = 2, 4$ at $\sigma_w = 0.22$ m/s for $|x| \leq 1$ (600 realizations). Four grid points with large $N\sigma_w$ and

TABLE VI. Reproduction of the validation cases of [1].

Test	Configuration	Reference value	This work	Error (%)
1a	$N = 1$, $m = 0.9$ mg, tip charge, Eq. (2)	$U \approx 8.5$ cm/s [1]	8.502 cm/s	0.02
1a	same	$t_{95} = 3t_s = 0.597$ s (theory)	0.604 s	1.1
1a	same	time to steady state ≈ 0.1 s [1]	0.604 s (t_{95})	—
1b	same, charge on the spider node	$U \approx 8.5$ cm/s [1]	8.516 cm/s	0.19
1b	same	—	peak 1.21 m/s; within 5% of U after 1.14 s	—
2	$N = 2$, tip charge, $\bar{F}_l = 2$, $N_t = 100$	$\bar{v}_t \approx 2$ (read from Fig. 6 of [1])	2.088	4.4
check	$N = 1$, constant E , $Q_s = 0$	Eq. (9): 9.513 cm/s	9.520 cm/s	0.076
check	$N = 1$, constant E , $Q_s = 3$ pC	Eq. (9) with $Q_s E$: 10.044 cm/s	10.050 cm/s	0.066
check	$N = 2$, first integral (22)	$T^\beta \sin \theta = \text{const.}$	spread 0.019%	—
check	$N = 4$, uniform flow $w = 0.5$ m/s, same initial state relative to the air	$\Delta V = 0.5$ m/s; same shape at all t	$\Delta V = 0.50000000005$ m/s; max. shape deviation $8.5 \times 10^{-12} L$ over $t \leq 2$ s	10^{-8}
check	same, both runs started at rest in the ground frame	transient, same steady state	deviation $2.3 \times 10^{-3} L$ at $t = 0.1$ s, $9 \times 10^{-7} L$ at $t = 2$ s; decay time 0.24 s	—
check	gradients, Hessians, Jacobians	finite differences	agreement to $\sim 10^{-10}$	—

TABLE VII. Discretization convergence for test 2 ($N = 2$, tip charge, $\bar{F}_l = 2$, $Q_s = 3$ pC). Δ is the relative difference with respect to the finest mesh, $N_t = 200$. The differences halve with each refinement (first-order convergence); Richardson extrapolation gives $\bar{v}_t \rightarrow 2.078$. CPU time: one core of an Apple M4 Pro.

N_t (edges/thread)	$\bar{v}_t$	$\Delta \bar{v}_t$ (%)	R/L	$\Delta(R/L)$ (%)	CPU time (s)
25	2.1196	1.75	0.14287	0.48	5.6
50	2.0986	0.74	0.14248	0.20	11.5
100	2.0883	0.25	0.14229	0.067	25.7
200	2.0832	—	0.14220	—	51.6

$x \leq -2$ have $\bar{F}_l \leq 0$, i.e. no electrostatic lift; they lie outside the model (the threads fold onto the spider) and are excluded (387 realizations; all 13 solver failures of the sweep occurred there). Of the remaining 8200 realizations, 56 (0.7%) reached $t_{\text{end}} = 60$ s without exit and are excluded from P ; no thread entanglement was detected (in 3 of 8200 realizations the threads approach to $0.5\text{--}0.6$ μm , about $2r$, a few centimetres from the spider within 0.15 s after release, and then separate).

b. Collapse on the scaled drift. Figure 7(a) shows that the transition from failure to take-off widens with N when plotted against $\bar{F}_l$, because the settling speed w_s decreases with N and the same turbulence then competes with a smaller drift. In the scaled variable x , Fig. 7(b), all 64 grid points collapse on a single curve, independently of N and σ_w . This is the structure predicted by Eq. (18), which depends on the parameters only through x . The width of the curve, however, is not the one of Eq. (18) with $K = \sigma_w \ell$: the simulated transition is about four times sharper. A maximum-likelihood fit of Eq. (18) with an effective diffusivity $K_{\text{eff}} = K/a$ and an effective start fraction p_0 in place of z_0/h gives $a = 4.2$ and $p_0 = 0.34$, with $\chi^2 = 48$ for 62 degrees of freedom. Separate fits for each (N, σ_w) give $a = 3.7\text{--}4.5$ and $p_0 = 0.32\text{--}0.38$, without a systematic trend with N .

c. Interpretation. Both corrections are properties of the flow, not of the bundle. The diffusivity of Taylor's theory is $K = \sigma_w^2 T_L$, with T_L the Lagrangian integral time; $K = \sigma_w \ell$ assumes $T_L = \ell/\sigma_w$, whereas $a = 4.2$ corresponds to $T_L \approx 0.24 \ell/\sigma_w$. At $x = 0$, a massless tracer in the same fields reaches h with probability 0.33 ([0.20, 0.48], 40 fields), consistent with $p_0 = 0.34$; the excess over $z_0/h = 0.25$ reflects the finite correlation time of the velocity seen during the ascent. A tracer study in the same fields confirms both values: with an imposed drift $U_0 = xK/h$, massless tracers ($M = 2000$ per point) give $a = 4.20$, $p_0 = 0.34$ for $\sigma_w = 0.15$ m/s and $a = 4.12$, $p_0 = 0.36$ for $\sigma_w = 0.30$ m/s, identical within the uncertainties to the fit for the bundles, and the Lagrangian integral time of w along tracer paths

TABLE VIII. Steady-state observables for tip-charged bundles in still air ($L = 0.5$ m, $m = 1$ mg, $Q_s = 0$, $\bar{F}_l = 2$, constant $E = 7.41 \times 10^3$ V/m, $N_t = 100$). τ uses the simulated U . Λ , τ , and $(R/L)_{\text{an}}$ from Eqs. (30)–(31); the remaining columns from simulation. d_{min} : minimum distance between threads.

N	q (nC)	Λ	τ	$(R/L)_{\text{an}}$	$(R/L)_{\text{num}}$	θ_L (rad)	$\bar{v}_t$	d_{min} (μm)
2	1.324	6.42×10^{-3}	0.520	0.1433	0.1422	0.0796	2.084	7497
4	0.662	3.21×10^{-3}	0.510	0.1790	0.1766	0.0987	2.103	6584
8	0.331	1.61×10^{-3}	0.505	0.2039	0.2003	0.1123	2.106	4021




FIG. 3. Opening of the bundle. (a) Tip radius from simulation, $(R/L)_{\text{num}}$, versus the small-angle prediction of Eq. (31), for $N = 2$ (circles), 4 (squares), and 8 (triangles), and $\bar{F}_l = 1.2, 1.5, 2, 3, 5$ (tip charge, still air, $m = 1$ mg, $Q_s = 0$, constant $E = 7.41 \times 10^3$ V/m). The solid line has slope 1. (b) Relative deviation from the prediction: below 1% for small openings, growing to about -17% at the largest opening ($N = 8$, $\bar{F}_l = 5$), which marks the breakdown of the small-angle approximation.

gives $a = \sigma_w \ell / (\sigma_w^2 T_L) = 3.0\text{--}5.8$, depending on the integration limit of the autocorrelation. The bundle therefore enters the take-off probability only through its settling speed w_s , i.e. through x : within the statistical resolution of the sweep (± 0.07 in P at the transition), the deformation of the threads and their Coulomb opening have no further effect. Equation (18) remains the correct form, provided K is the Lagrangian diffusivity $\sigma_w^2 T_L$ of the flow and z_0/h is replaced by the effective start fraction of the same flow.

d. Deformation. Turbulence opens the bundle on average: for $N = 4$, $\bar{F}_l = 1$, $\sigma_w = 0.30$ m/s, the time-averaged tip radius is $R/L = 0.165 \pm 0.018$ over the realizations, with temporal fluctuations of 0.039 within a run, against 0.115 in still air [Fig. 8(b)]. The mean opening over all realizations grows with N : $R/L = 0.042, 0.112, 0.149$, and 0.204 for $N = 1, 2, 4$, and 8 (for $N = 1$, the tilt of the single thread). The closest approach between threads is $0.5 \mu\text{m}$. Clamped in still air for $t \geq 1.4$ s, the bundle reaches $R/L = 0.093, 0.115$, and 0.127 for $N = 2, 4$, and 8 , within 0.2, 0.2, and 3.2% of Eq. (31); in turbulence the run-averaged opening is larger by 26, 43, and 83%. The sweep releases the bundle after a clamp time $t_c = 0.05$ s, before the Coulomb opening is complete ($R/L \approx 0.07$ at release). A control run with $t_c = 3$ s, for $N = 4, 8$, $\sigma_w = 0.30$ m/s, $x = 0, 1$, and the same 200 seeds per point, gives take-off probabilities within 0.017 of the sweep (two-proportion test $p \geq 0.73$) and run-averaged openings within 2%: the results above do not depend on the initial opening.




FIG. 4. Numerical check of the first integral of Eq. (22). The quantity $T^\beta \sin \theta$, normalized by its mean value, along one thread at steady state ($N = 2$, tip charge, $q = 1.324$ nC, $\bar{F}_l = 2$, $Q_s = 0$), for $N_t = 100$. Shown is the deviation from the mean in percent; the exact RFT result is zero (dashed line). The spread over the interior edges is 0.019%.




FIG. 5. Steady shapes of tip-charged bundles in still air ($L = 0.5$ m, $m = 1$ mg, $Q_s = 0$, $\bar{F}_l = 2$, constant $E = 7.41 \times 10^3$ V/m, $N_t = 100$; parameters of Table VIII). (a)–(c) Side view of the threads in the frame of the spider for $N = 2, 4$, and 8 . (d) Top view of the tips, which lie on a circle of radius R , as assumed in Sec. IV.

D. Learned surrogate

[TO DO: Octavian: results text.]

TABLE IX. Surrogate accuracy on the test splits of Table IV. Rollout errors after ? steps. Baselines: ? (e.g. local-only GNN without long-range edges).

Model	Split	Rollout MSE	$\Delta V/V$ (%)	$\Delta(R/L)$ (%)	$ \Delta P $	Speed-up
Local GNN	interp.	?	?	?	?	?
Local GNN	unseen N	?	?	?	?	?
Long-range GNN	interp.	?	?	?	?	?
Long-range GNN	unseen N	?	?	?	?	?
Local GNN	unseen σ_w	?	?	?	?	?
Long-range GNN	unseen σ_w	?	?	?	?	?




FIG. 6. Validation of the synthetic turbulence of Eq. (15), for $\sigma_w = 0.25$ m/s, $\ell = 1$ m, and $N_k = 200$ modes (average over 50 realizations). (a) Longitudinal one-dimensional spectrum of w along a vertical line versus the spectrum implied by Eq. (16); the generated spectrum is shown up to the cut-off $k_{\max} = 2\pi/(5 \times 5 \text{ mm}) = 251 \text{ m}^{-1}$ and falls below the target above $k \approx 80 \text{ m}^{-1}$ because of the finite shell width near $k_{\max}$. (b) Probability density of w with the Gaussian of standard deviation σ_w ; the sample standard deviation is 0.249 m/s. Mode amplitudes renormalized as in Appendix D.




FIG. 7. Take-off probability in synthetic turbulence ($\ell = 1$ m, $U_h = 1$ m/s, $z_0 = 0.5$ m, $h = 2$ m, tip charge, $m = 1$ mg, $Q_s = 0$, $N_t = 50$). Markers: ensemble estimates from Algorithm 2 with 95% Wilson intervals ($M = 200$ for $|x| \leq 1$, $M = 100$ otherwise; $M = 50$ for $N = 3, 6$ and $\sigma_w = 0.22$ m/s). (a) P versus $\bar{F}_l$ for $\sigma_w = 0.30$ m/s; the vertical dashed line marks the deterministic threshold $\bar{F}_l = 1$. (b) All valid grid points versus the scaled drift $x = w_s(\bar{F}_l - 1)h/K$, $K = \sigma_w\ell$; open markers $\sigma_w = 0.15$, grey 0.22, filled 0.30 m/s, small horizontal offsets for readability. Dashed: Eq. (18) with $K = \sigma_w\ell$; solid: Eq. (18) with $K_{\text{eff}} = \sigma_w\ell/a$ and start fraction p_0 fitted to all points ($a = 4.2$, $p_0 = 0.34$).

1. Computational cost

a. Protocol. The surrogate and the simulator are compared on the same tasks: (i) one complete run, from release until the spider reaches h or the ground, and (ii) one estimate of the take-off probability P from M realizations. Wall-clock times are reported for both methods in their optimized setting: the simulator with independent realizations run in parallel on all CPU cores, the surrogate with realizations batched on the GPU. Hardware: ? (CPU, cores, GPU, memory).

b. Total cost and break-even. Let c_{sim} and c_{sur} be the costs of one estimate of P with the simulator and with the surrogate, and C_{data} and C_{train} the one-time costs of generating the training data and training the network. The




FIG. 8. Deformation of the bundle by turbulence ($N = 4$, $q = 0.331$ nC, $\bar{F}_l = 1$, $\sigma_w = 0.30$ m/s, $\ell = 1$ m). (a) One rising realization at three instants, side view in the frame of the spider (panels offset horizontally); nodes coloured by the vertical air velocity w at the node. (b) Distribution over the $M = 200$ realizations of the time-averaged tip radius R/L , compared with the still-air value of Eq. (31) at $\bar{F}_l = 1$ ($\tau = 1$, $g = 1$).




FIG. 9. Code test: shape invariance under a uniform updraft ($N = 4$, tip charge, $q = 0.662$ nC, $\bar{F}_l = 2$, $Q_s = 0$, constant $E = 7.41 \times 10^3$ V/m, $N_t = 100$). (a) Steady-state configurations in the frame of the spider for $w = 0$ (solid) and $w = 0.5$ m/s (dashed); the curves should coincide. (b) Ground-frame altitude $z_0(t)$; the slopes differ by exactly w . (c) Both runs started at rest in the ground frame: maximum shape difference and tip-radius difference, normalized by L ; both decay exponentially with time constant 0.24 s.

surrogate is cheaper overall after

$$Q^* = \frac{C_{\text{data}} + C_{\text{train}}}{c_{\text{sim}} - c_{\text{sur}}} \quad (43)$$

evaluations of P . Q^* must be compared with the number of evaluations actually needed, for example the number of points in Fig. 7, or in a finer sweep or an inverse problem.

c. Accuracy at equal cost. The reference value P_{ref} is estimated with the simulator using $M_{\text{ref}} = ?$ realizations. For a given compute budget B , the simulator affords $M_{\text{sim}}(B)$ realizations and the surrogate $M_{\text{sur}}(B) \gg M_{\text{sim}}(B)$. The error of the surrogate estimate contains a statistical part, $\propto M_{\text{sur}}^{-1/2}$, and a systematic part (model bias) that does not decrease with M . The surrogate is useful only where its bias is smaller than the statistical error of the simulator at the same budget.




FIG. 10. Surrogate performance. (a) Rollout error of the node positions versus time, for interpolation and unseen- N test sets, with and without long-range message passing. (b) Steady-state tip radius predicted by the surrogate versus the DER simulation and the analytical law of Eq. (31).

TABLE X. Computational cost of the simulator (Algorithm 1) and of the surrogate, for $N = ?$, $\sigma_w = ?$ m/s. $|\Delta P|$: mean absolute error of P with respect to P_{ref} , over the points of Fig. 7, at a fixed budget $B = ?$ s per point. Hardware as stated in the text.

Method	Hardware	Time per run (s)	Time per P ($M = ?$) (s)	C_{data} (h)	C_{train} (h)	Q^*	$ \Delta P $ at budget B
Simulator	CPU, ? cores	?	?	—	—	—	?
Surrogate	GPU, ?	?	?	?	?	?	?




FIG. 11. Accuracy versus computational cost for the estimate of the take-off probability ($N = ?$, $\bar{F}_l = ?$, $\sigma_w = ?$ m/s). Mean absolute error $|P - P_{\text{ref}}|$ as a function of wall-clock time per point, for the simulator (circles) and the surrogate (squares), obtained by varying the number of realizations M . The dashed line has slope $-1/2$ (statistical error). The error of the surrogate saturates at its systematic bias; the crossing of the two curves marks the budget above which the simulator is preferable.

VIII. DISCUSSION

Alex and Vlad should rewrite this section in their own words.

A. What this work adds

Compared with [1], the present work (i) places the charged multi-thread bundle in realistic near-surface turbulence and treats take-off as a stochastic event; (ii) gives an analytical drift-diffusion reference, Eq. (18), in which the electrostatic lift enters through $\bar{F}_l$ and the turbulence through a Péclet number; and (iii) provides an exact first integral and a closed-form opening law, $R/L \propto (S_N \Lambda)^{1/3}$, for tip-charged threads. Turbulent ballooning has been simulated before only for single, uncharged filaments [17, 18]. Earlier work treated the two lift mechanisms mostly separately: aerodynamic models without charge [7, 8], and electrostatic models in still air [1, 2]. Field and laboratory studies indicate that both play a role [9, 10]. Equation (18) makes this quantitative: electrostatic lift shifts the drift U_0 , while turbulence sets the width of the transition. The simulations (Sec. VII C) confirm the structure of Eq. (18) but not its parameters. For $N = 1-8$ and two turbulence intensities, P depends only on the scaled drift x ; the bundle enters only through w_s , so at fixed $\bar{F}_l$ adding threads lowers w_s , brings x closer to zero, and widens the transition [Fig. 7(a)], while thread deformation and Coulomb opening have no measurable further effect. With $K = \sigma_w \ell$, Eq. (18) underestimates the steepness of the transition by a factor of about four and the probability at $x = 0$ by 0.09; both corrections are reproduced by massless tracers in the same fields and are therefore properties of the flow: the relevant diffusivity is the Lagrangian one, $\sigma_w^2 T_L$, and the finite correlation time raises the effective start fraction from $z_0/h = 0.25$ to 0.34. For predictions in the atmosphere, T_L should be taken from surface-layer measurements rather than from the synthetic field.

B. What the learned surrogate adds

[TO DO: Octavian: interpret the results of Sec. VIID. Does the surrogate respect the analytical limits (first integral, opening law, threshold)? Where does it fail (large Λ , entanglement, unseen N)? What speed-up does it offer for parameter sweeps and inverse problems, given the break-even Q^* and the bias found in Sec. VIID 1?]

C. Order-of-magnitude assessment of the mechanism

Over flat ground ($E_0 \approx 120$ V/m), a spider of 1 mg carrying a total charge of 1 nC receives an electrostatic force of $\sim 1.2 \times 10^{-7}$ N, about 1% of its weight ($\sim 10^{-5}$ N). Electrostatic lift alone therefore requires either a field enhanced by a prominence (grass tips, twigs), where E reaches 10^4 – 10^5 V/m [1, 3], or charges about two orders of magnitude larger than those measured. In the language of the model, take-off from flat ground is essentially aerodynamic ($\bar{F}_l \ll 1$, w_c close to the settling speed), whereas take-off from an elevated point can be electrostatic or mixed. As the spider moves away from the prominence, E decays towards E_0 and $\bar{F}_l$ drops. Electrostatic forces are therefore most relevant *at take-off and in the first centimetres to metres of flight*, and much less during long-distance transport. For the chamber profile of Eq. (2), the enhanced part of the field decays on the scales $z_1 = 1.5$ mm and $z_2 = 7.9$ mm: at $z = 3$ cm above the prominence it is below 2% of E_∞ , so a bundle with $\bar{F}_l$ close to 1 at the prominence loses most of its electrostatic lift within the first centimetres of flight, a distance much shorter than the thread length.

D. Potential applications

- **Dispersal ecology.** Combined with routinely measured meteorological quantities (u_* , and hence σ_w ; atmospheric potential gradient), the take-off probability predicts under which weather conditions ballooning is likely, and how it depends on spider mass and number of threads.
- **Charged filament bundles.** The opening law (31) applies to any set of thin charged filaments in a viscous medium, for example electrospinning jets, charged fibres in filtration, and electrostatically interacting hair or fibre arrays [12].

- **Passive bio-inspired fliers.** The analysis gives design rules for ultralight passive fliers or airborne sensors lifted by drag on filaments, with or without charge. The number and length of the filaments set the sink speed, and hence the updraft required to stay aloft.
- **Atmospheric electricity.** The opening of a charged bundle scales as $E^{-1/3}$ [Eq. (31)], which suggests a passive indicator of the local field. The weak exponent and the sensitivity to charge leakage make this a qualitative rather than a practical measurement principle.
- **Benchmark for learned simulators.** The simulations form a controlled data set with known analytical limits, suitable for testing graph-based surrogate models of filament dynamics with long-range interactions [13, 14].

E. Limitations

a. Of the model.

- RFT neglects hydrodynamic interactions between threads, although the threads are very close near the spider [1]. A slender-body treatment would reduce the drag of the bundle near the spider.
- The charge distribution along the thread is unknown; only two limiting cases are treated.
- The charge is constant in time. Silk conductivity increases roughly exponentially with relative humidity [11], so in humid air the charge may leak within the flight time.
- The turbulence is synthetic, homogeneous, and isotropic, with statistics matched only for the vertical component; the growth of the eddy size with height, mean shear, and convective plumes are not included.
- Values of w_c above ~ 1 m/s (Table II) lie outside the range of validity of the low-Reynolds-number drag laws.
- The drift-diffusion reference (18) assumes a height-independent diffusivity; near the ground K grows with z .
- The fitted Lagrangian correction ($a \approx 4$, $p_0 \approx 0.34$) is a property of the kinematic-simulation field, which does not sweep small eddies with the large ones; the collapse on x is expected to hold more generally, but the values of a and p_0 need not carry over to real surface-layer turbulence.

b. Of the mechanism. The electrostatic mechanism depends on field enhancement near objects and on nanocoulomb charges whose origin (triboelectric charging during spinning, or induction) is not established. The measured charges [3] are indirect, inferred from the motion in a known field. The mechanism thus explains take-off in calm air from elevated points, but it cannot on its own explain long-distance transport at altitudes of hundreds of metres.

F. Future work

1. Anisotropic, height-dependent surface-layer turbulence (e.g. from large-eddy simulation), mean shear, and convective plumes.
2. Time-dependent charge, with a leakage rate depending on humidity [11].
3. An analytical or asymptotic solution for uniformly charged threads.
4. Hydrodynamic interactions between threads (slender-body theory or regularized Stokeslets).
5. Comparison with laboratory measurements of the opening angle versus applied field.
6. Learned surrogate simulators (graph neural networks with long-range message passing) trained on the present data, tested on unseen N and parameters, and checked against the analytical results of Secs. III–IV.

IX. CONCLUSIONS

We placed the charged multi-thread ballooning model of Habchi and Jawed [1] in synthetic near-surface turbulence with surface-layer statistics. A uniform flow leaves the bundle unchanged, so the relevant effect of the air is its spatial and temporal variability on the scale of the bundle. Take-off then becomes a stochastic event; in the limit of large, slow eddies its probability follows a drift-diffusion law that smooths the deterministic threshold $\bar{F}_l = 1$ into a sigmoid set by a Péclet number. For tip-charged threads we derived the exact first integral $T^\beta \sin \theta = \text{const.}$ and the closed-form opening law $R/L = [S_N \Lambda g(\tau)/4]^{1/3}$. The simulations reproduce the validation cases of [1] within 4.4% (the target read from a figure) and analytical terminal velocities within 0.08%, and confirm the opening law within 2% for $R/L \leq 0.2$. In turbulence, the take-off probability of 8200 simulated bundles with $N = 1-8$ collapses on a single function of the scaled drift $x = w_s(\bar{F}_l - 1)h/K$: the bundle enters only through its settling speed. The drift-diffusion law has the right form, but its width is set by the Lagrangian diffusivity of the flow, about four times smaller than $\sigma_w \ell$ in the synthetic field, as confirmed with massless tracers. An order-of-magnitude assessment indicates that electrostatic lift matters at take-off from elevated points, whereas over flat ground the aerodynamic mechanism dominates. Finally, a graph neural network surrogate trained on bundles with $N \leq ?$ threads predicts ? for $N = ?$ with an error of ?%, at a cost ? times lower than the full simulation.

TABLE XI. HDF5 layout: one file per run.

Dataset / attribute	Shape	Content
/params (attributes)	—	N, N_t, L, r, m, r_s, q , charge model, Y, μ , field model, z_0, h
/turb (attributes, arrays)	$(N_k, \cdot)$	$\sigma_w, \ell, U_h, \lambda$, seed; $\mathbf{k}_n, \mathbf{a}_n, \mathbf{b}_n, \omega_n$
/t	(n_t)	output times (s)
/x	$(n_t, NN_t + 1, 3)$	node positions (m); node 0 = spider
/v	$(n_t, NN_t + 1, 3)$	node velocities (m/s)
/edges	$(NN_t, 2)$	node connectivity
/thread_id	$(NN_t + 1)$	thread index per node (−1 for spider)
/q_node	$(NN_t + 1)$	nodal charges (C)
/outcome (attributes)	—	rise/fall/timeout, exit time, entangled flag; still-air V, R, θ_L

ACKNOWLEDGMENTS

[TO DO:]

AUTHOR CONTRIBUTIONS

[TO DO: .]

DATA AVAILABILITY

[TO DO: .]

Appendix A: Resistive force coefficients

For a slender filament of length L and radius $r \ll L$ at low Reynolds number, the drag coefficients per unit length of Eq. (4) follow from slender-body theory to leading order in $1/\ln(L/r)$. [TO DO: Give the reference used and check the validity condition on the thread Reynolds number, $\text{Re} = \rho_{\text{air}}|\mathbf{v} - \mathbf{u}|r/\mu$, for the velocities in Table II.]

Reference solution (what Vlad and Alex should do). The coefficients of Eq. (4) are the leading-order slender-body (Cox) coefficients for a straight cylinder of length L and radius r ; they appear in exactly this form in the review

of Hosoi and Goldman, *Annu. Rev. Fluid Mech.* (2015), and derive from R. G. Cox, *J. Fluid Mech.* 44, 791 (1970). Reynolds number of the thread, $\text{Re} = \rho_{\text{air}} v r / \mu$ ($\rho_{\text{air}} = 1.2 \text{ kg/m}^3$): 0.006 at $v = 0.29 \text{ m/s}$ ($N = 8$), 0.04 at 2.2 m/s ($N = 1$), 0.4 at 21.7 m/s ($m = 10 \text{ mg}$, $N = 1$); RFT is valid except at the largest w_c of Table II. The spider body is the weaker point: its Reynolds number $\rho_{\text{air}} v 2r_s / \mu$ is 38 at 0.29 m/s and 280 at 2.2 m/s , so Stokes drag underestimates its drag by a factor of about 3 and 8 (Schiller–Naumann correction $1 + 0.15 \text{Re}^{0.687}$). Because $\zeta_s \ll N\eta_{\parallel} L$, this changes w_s by about 2% for $N = 8$ but by about 40% for $N = 1$ at $m = 1 \text{ mg}$.

Appendix B: Derivation of the opening law

With $T(s) = T_0 + \eta_{\parallel} U s$ and $\theta(s) = \theta_L [T_L / T(s)]^{\beta}$,

$$R = \int_0^L \theta \, ds = \frac{\theta_L T_L^{\beta}}{\eta_{\parallel} U} \int_{T_0}^{T_L} T^{-\beta} \, dT = \theta_L L \frac{\tau^{1-\beta} - 1}{(\beta - 1)(1 - \tau)}, \quad (\text{B1})$$

using $\eta_{\parallel} U L = T_L(1 - \tau)$. Combining with $\theta_L = F_C / (qE)$ and Eq. (24) gives Eq. (31). **[TO DO: Alex and Vlad: add the first correction in θ^2 and estimate the error for $\Lambda \sim 10^{-2}$.]**

Reference solution (what Vlad and Alex should do). In the limit $\tau \rightarrow 1$ ($U \rightarrow 0$) the threads are straight and the tip balance is exact: $R/L = \sin \theta_L$ and $\tan \theta_L = F_C / (qE) = S_N \Lambda / [4(R/L)^2]$. With $\rho = R/L$ and $\rho_0^3 = S_N \Lambda / 4$ (Eq. (31) at $g = 1$), $\tan \theta_L = \rho(1 + \rho^2/2 + \dots)$ gives $\rho^3(1 + \rho^2/2) = \rho_0^3$, i.e.

$$\frac{R}{L} = \rho_0 \left(1 - \frac{\rho_0^2}{6} \right) + O(\rho_0^5).$$

The small-angle law overestimates R by $\rho_0^2/6$: 0.3% for $N = 2$ and 1.5% for $N = 8$ at $\Lambda = 10^{-2}$. Check against the clamped still-air runs ($\bar{F}_l = 1$): predicted 0.14, 0.22, 0.29%, simulated 0.12, 0.20, 3.2% for $N = 2, 4, 8$. The correction explains $N = 2$ and 4; the 3% for $N = 8$ is not a small-angle effect (possibly tips not exactly on one circle, or interactions near the spider) and remains open. For $\tau < 1$ the curvature of the thread adds corrections of the same order through $g(\tau)$.

Appendix C: Simulation parameters

TABLE XII. Numerical parameters used in all simulations.

Parameter	Symbol	Value
Edges per thread	N_t	100 (convergence study: 25–200)
Initial / maximum / minimum time step	$\Delta t_0, \Delta t_{\text{max}}, \Delta t_{\text{min}}$	$10^{-4} \text{ s}, 10^{-2} \text{ s}, 10^{-9} \text{ s}$
Newton tolerance	ϵ	10^{-10} N (on $\ \mathbf{F}\ _1$)
Maximum Newton iterations	K	20
Steady-state tolerance and window	δ, t_w	$10^{-6}, 0.05 \text{ s}$
Clamp time before release (Alg. 2)	t_c	0.05 s (sweep), 3 s (check)
Initial thread spacing	d_0	100 μm
Poisson ratio; twist inertia	ν ; —	0.5; $\rho_t J l_0 / 2$
Tangent dependence of $\mathbf{C}$ in $\mathbf{J}$	—	lagged
Output interval	Δt_{out}	10^{-2} s (10^{-3} s for test 1)
Code and version	—	Python 3.14, NumPy 2.5, SciPy 1.18; commit 88246c2
Hardware	—	Apple M4 Pro, 10 performance cores, CPU only

Appendix D: Reproducibility of the ensemble simulations

The turbulence ensembles (Sec. VII C) use $N_t = 50$ edges per thread; for test 2 this changes $\bar{v}_t$ by 0.5% and R/L by 0.13% relative to $N_t = 100$ (Table VII). They were run from commit 507637e (clean working tree) on two Google

Cloud **c2-standard-30** instances, with resume from per-run outputs; the control run of Sec. VII C with $t_c = 3$ s used commit **e57dd01**. Before production we checked: (i) the synthetic field, renormalized so that the sample standard deviation of w equals σ_w (correction factor 1.019), with the spectrum of Fig. 6; (ii) that the trajectories do not depend on the mesh through the turbulence ($k_{\max}$ fixed at $2\pi/(5 \times 5 \text{ mm}) = 251 \text{ m}^{-1}$; spider positions for $N_t = 50$ and 100 within 0.6 cm after the same flight); (iii) the time-step cap $\Delta t_{\max} = 10^{-2}$ s (difference 0.65 cm against $\Delta t_{\max} = 10^{-3}$ s); (iv) that a run interrupted and resumed reproduces the uninterrupted one; and (v) that massless tracers in the same fields give the same take-off probability at $x = 0$ as the bundles. A regression test compared the production code with the version used for Secs. VII A–VII B: on the same machine the outputs are identical, and between the cloud and the laptop of Table XII the largest relative difference is 1.4×10^{-6} (in θ_L), apart from quantities at round-off level. Newton’s method failed to converge at 5 time steps in total over the 8200 valid runs, all of which completed. Each run is stored as an HDF5 file (Sec. VI) with the commit hash, the seed, and all parameters as attributes.

Appendix E: List of symbols

TABLE XIII. Main symbols.

N	number of threads	$\eta_{\parallel}, \eta_{\perp}$	RFT drag coefficients
L, r	thread length, radius	β	$\eta_{\perp}/\eta_{\parallel}$
m, r_s	spider mass, radius	ζ_s	Stokes drag coefficient of the spider
q	charge per thread	$T(s)$	tension
$E(z)$	atmospheric electric field	$\theta(s)$	angle from the vertical
$\mathbf{u}, w$	air velocity, updraft speed	R	radius of the tip circle
U	velocity relative to air	S_N	Coulomb sum, Eq. (24)
V	ground-frame velocity	τ	tension ratio T_0/T_L
$\bar{F}_l$	lift-to-weight ratio	Λ	Coulomb-to-lift ratio
$\bar{w}$	dimensionless updraft	w_c, w_s	mean-flow threshold, settling speed
σ_w, ℓ	turbulence intensity, scale	P, K	take-off probability, diffusivity

-
- [1] C. Habchi and M. K. Jawed, Ballooning in spiders using multiple silk threads, *Phys. Rev. E* **105**, 034401 (2022); preprint arXiv:2112.10981.
- [2] P. W. Gorham, Ballooning spiders: The case for electrostatic flight, arXiv:1309.4731 (2013).
- [3] E. L. Morley and P. W. Gorham, Evidence for nanocoulomb charges on spider ballooning silk, *Phys. Rev. E* **102**, 012403 (2020); preprint arXiv:1912.02335.
- [4] E. L. Morley and D. Robert, Electric fields elicit ballooning in spiders, *Curr. Biol.* **28**, 2324 (2018).
- [5] M. Bergou, M. Wardetzky, S. Robinson, B. Audoly, and E. Grinspun, Discrete elastic rods, *ACM Trans. Graph.* **27**, 63 (2008).
- [6] DisMech: A discrete differential geometry-based physical simulator for soft robots and structures, arXiv:2311.18126; code: <https://github.com/StructuresComp/dismech-rods>.
- [7] M. Cho, P. Neubauer, C. Fahrenson, and I. Rechenberg, An observational study of ballooning in large spiders: Nanoscale multifibers enable large spiders’ soaring flight, *PLOS Biol.* **16**, e2004405 (2018).
- [8] Ballooning spiders: modeling of take-off, MIT Mathematical Biology report (2017), <https://bpb-us-e1.wpmucdn.com/sites.mit.edu/dist/a/1194/files/2014/10/2017-MathBio-Ballooning-LBLB-2.pdf>.
- [9] N. Narimanov *et al.*, Disentangling the roles of electric fields and wind in spider dispersal experiments, *J. Arachnol.* **49**, 380 (2021).
- [10] M. Montes and R. M. Gleiser, Why do spiders balloon? A review of recent evidence, *J. Insect Conserv.* **29** (2025), <https://ri.conicet.gov.ar/handle/11336/263802>.
- [11] Humidity dependence of the electrical conductivity of silk, <https://pmc.ncbi.nlm.nih.gov/articles/PMC5074434/>.
- [12] Electrostatic interactions in arrays of sensory hairs, *J. R. Soc. Interface*, doi:10.1098/rsif.2022.0053 (2022).
- [13] A. Kosmala, J. Gasteiger, N. Gao, and S. Günnemann, Ewald-based long-range message passing for molecular graphs, *Proc. ICML, PMLR* **202** (2023).
- [14] A. Sanchez-Gonzalez *et al.*, Learning to simulate complex physics with graph networks, arXiv:2002.09405 (2020).

- [15] J. A. C. Humphrey, Fluid mechanic constraints on spider ballooning, *Oecologia* **73**, 469 (1987).
- [16] R. B. Suter, Ballooning in spiders: results of wind tunnel experiments, *Ethol. Ecol. Evol.* **3**, 13 (1991).
- [17] A. M. Reynolds, D. A. Bohan, and J. R. Bell, Ballooning dispersal in arthropod taxa with convergent behaviours: dynamic properties of ballooning silk in turbulent flows, *Proc. R. Soc. B* (2006).
- [18] M. Cho, M. N. Cruz Bournazou, P. Neubauer, and I. Rechenberg, Passive dynamics of a ballooning spider, *bioRxiv* 10.1101/2020.06.06.137505 (2020).
- [19] H. Shao, T. Kugelstadt, T. Hädrich, W. Pałubicki, J. Bender, S. Pirk, and D. L. Michels, Accurately solving rod dynamics with graph learning, *Adv. Neural Inf. Process. Syst.* **34**, 4829 (2021).
- [20] J. C. Kaimal, J. C. Wyngaard, Y. Izumi, and O. R. Coté, Spectral characteristics of surface-layer turbulence, *Q. J. R. Meteorol. Soc.* **98**, 563 (1972).
- [21] NASA Marshall Space Flight Center, Earth Global Reference Atmospheric Model (Earth-GRAM) 2024, User Guide, <https://ntrs.nasa.gov/api/citations/20240008432/downloads/Earth-GRAM%202024%20User%20Guide.pdf>.
- [22] R. H. Kraichnan, Diffusion by a random velocity field, *Phys. Fluids* **13**, 22 (1970).
- [23] J. C. H. Fung, J. C. R. Hunt, N. A. Malik, and R. J. Perkins, Kinematic simulation of homogeneous turbulence by unsteady random Fourier modes, *J. Fluid Mech.* **236**, 281 (1992).
- [24] G. I. Taylor, Diffusion by continuous movements, *Proc. London Math. Soc.* **s2-20**, 196 (1922).