



Reborn RBJ-350

Acabadora digital para embellecimiento de etiquetas.

Aplicaciones

- Embosado
- Hot Stamping
- Serigrafía
- Y más

| Configuración | |
|---|--------------------------------|
| Constant tension unwinder | 1 set |
| Auto. web guide | 2 sets |
| Printing station (semi-rotary) | 2 sets |
| Printing station (full-rotary) | 1 set |
| Flatbed screen printing | 1 set |
| Hot rotary anvils device (circularing oil heating roller) | 1 set |
| Rotary die cut (semi-rotary & full rotary) | 1 set |
| Anilox roller | 300LPI 2pcs |
| Full varnish roller | 88T 1pcs |
| Printing cylinder | 70T-170 (customatized) 2pcs |
| Magnetic cylinder | 120T 1pcs |
| Tooling | 1 set |
| UV glue lamination/cold foil stamping | 1 set |

Beneficios

- Etiquetas de alto valor agregado
- Máquina troqueladora rotativa
- Equipos modulares que se adaptan a tus necesidades.
- Rápida y automátizada y fácil de usar.

| Especificaciones | | |
|--------------------------------------|--------------------------------|--|
| Max web width | 350mm | |
| Unwind roll diameter | ф 650mm | |
| Rewind roll diameter | ф 650mm | |
| Max speed for semi - rotary | 50 m/min | |
| Max repeat length for semi-rotary | 330mm | |
| Air requiment | 0.6 Mpa | |
| Voltage | 3PH+N+PE 380V | |
| Applicable material | Roll-fed material | |
| UV current | 50A | |
| UV power | 21KW | |
| Rated current | 100A | |
| Gross power | 40KW | |
| Dimension (L*W*H) | (L)11300mm*(W)1460mm*(H)1860mm | |
| Weight | About 8T | |