STUDY TIME TRACKER

Complete Source Code

Generated: 3/28/2026

Total Files: 62

TABLE OF CONTENTS

1. App.tsx
2. components/ui/accordion.tsx
3. components/ui/alert-dialog.tsx
4. components/ui/alert.tsx
5. components/ui/aspect-ratio.tsx
6. components/ui/avatar.tsx
7. components/ui/badge.tsx
8. components/ui/breadcrumb.tsx
9. components/ui/button.tsx
10. components/ui/calendar.tsx
11. components/ui/card.tsx
12. components/ui/carousel.tsx
13. components/ui/chart.tsx
14. components/ui/checkbox.tsx
15. components/ui/collapsible.tsx
16. components/ui/command.tsx
17. components/ui/context-menu.tsx
18. components/ui/dialog.tsx
19. components/ui/drawer.tsx
20. components/ui/dropdown-menu.tsx
21. components/ui/form.tsx
22. components/ui/hover-card.tsx
23. components/ui/input-otp.tsx
24. components/ui/input.tsx
25. components/ui/label.tsx

26. components/ui/menubar.tsx
27. components/ui/navigation-menu.tsx
28. components/ui/pagination.tsx
29. components/ui/popover.tsx
30. components/ui/progress.tsx
31. components/ui/radio-group.tsx
32. components/ui/resizable.tsx
33. components/ui/scroll-area.tsx
34. components/ui/select.tsx
35. components/ui/separator.tsx
36. components/ui/sheet.tsx
37. components/ui/sidebar.tsx
38. components/ui/skeleton.tsx
39. components/ui/slider.tsx
40. components/ui/sonner.tsx
41. components/ui/switch.tsx
42. components/ui/table.tsx
43. components/ui/tabs.tsx
44. components/ui/textarea.tsx
45. components/ui/toast.tsx
46. components/ui/toaster.tsx
47. components/ui/toggle-group.tsx
48. components/ui/toggle.tsx
49. components/ui/tooltip.tsx
50. components/ui/use-toast.ts
51. hooks/use-mobile.tsx
52. hooks/use-toast.ts
53. integrations/supabase/client.ts
54. integrations/supabase/types.ts
55. lib/utils.ts
56. main.tsx
57. pages/Auth.tsx
58. pages/Home.tsx
59. pages/NotFound.tsx
60. pages/Progress.tsx
61. pages/Summary.tsx
62. vite-env.d.ts

1. App.tsx

Path: src/App.tsx

```
import { Toaster } from "@/components/ui/toaster";
import { Toaster as Sonner } from "@/components/ui/sonner";
import { TooltipProvider } from "@/components/ui/tooltip";
import { QueryClient, QueryClientProvider } from "@tanstack/react-query";
import { BrowserRouter, Routes, Route } from "react-router-dom";
import Home from "./pages/Home";
import Summary from "./pages/Summary";
import Progress from "./pages/Progress";
import Auth from "./pages/Auth";
import NotFound from "./pages/NotFound";

const queryClient = new QueryClient();

const App = () => (
  <QueryClientProvider client={queryClient}>
    <TooltipProvider>
      <Toaster />
      <Sonner />
      <BrowserRouter>
        <Routes>
          <Route path="/" element={<Home />} />
          <Route path="/summary" element={<Summary />} />
          <Route path="/progress" element={<Progress />} />
          <Route path="/auth" element={<Auth />} />
          {/* ADD ALL CUSTOM ROUTES ABOVE THE CATCH-ALL "*" ROUTE */}
          <Route path="*" element={<NotFound />} />
        </Routes>
      </BrowserRouter>
    </TooltipProvider>
  </QueryClientProvider>
);

export default App;

```

2. components/ui/accordion.tsx

Path: src/components/ui/accordion.tsx

```
import * as React from "react";
import * as AccordionPrimitive from "@radix-ui/react-accordion";
import { ChevronDown } from "lucide-react";

import { cn } from "@/lib/utils";

const Accordion = AccordionPrimitive.Root;

const AccordionItem = React.forwardRef<
  React.ElementRef<typeof AccordionPrimitive.Item>,
```

```
  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Item>
>(({ className, ...props }, ref) => (
  <AccordionPrimitive.Item ref={ref} className={cn("border-b", className)} {...props} />
));
AccordionItem.displayName = "AccordionItem";

const AccordionTrigger = React.forwardRef<
  React.ElementRef<typeof AccordionPrimitive.Trigger>,
  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Trigger>
>(({ className, children, ...props }, ref) => (
  <AccordionPrimitive.Header className="flex">
    <AccordionPrimitive.Trigger
      ref={ref}
      className={cn(
        "flex flex-1 items-center justify-between py-4 font-medium transition-all hover:underline [&[data-state=o
        className,
      )}
      {...props}
    >
      {children}
      <ChevronDown className="h-4 w-4 shrink-0 transition-transform duration-200" />
    </AccordionPrimitive.Trigger>
  </AccordionPrimitive.Header>
));
AccordionTrigger.displayName = AccordionPrimitive.Trigger.displayName;

const AccordionContent = React.forwardRef<
  React.ElementRef<typeof AccordionPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof AccordionPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <AccordionPrimitive.Content
    ref={ref}
    className="overflow-hidden text-sm transition-all data-[state=closed]:animate-accordion-up data-[state=open]:
    {...props}
  >
    <div className={cn("pb-4 pt-0", className)}>{children}</div>
  </AccordionPrimitive.Content>
));

AccordionContent.displayName = AccordionPrimitive.Content.displayName;

export { Accordion, AccordionItem, AccordionTrigger, AccordionContent };

```

3. components/ui/alert-dialog.tsx

Path: src/components/ui/alert-dialog.tsx

```
import * as React from "react";
import * as AlertDialogPrimitive from "@radix-ui/react-alert-dialog";

import { cn } from "@/lib/utils";
import { buttonVariants } from "@/components/ui/button";
```

```
 6 |
 7 | const AlertDialog = AlertDialogPrimitive.Root;
 8 |
 9 | const AlertDialogTrigger = AlertDialogPrimitive.Trigger;
10 |
11 | const AlertDialogPortal = AlertDialogPrimitive.Portal;
12 |
13 | const AlertDialogOverlay = React.forwardRef<
14 |   React.ElementRef<typeof AlertDialogPrimitive.Overlay>,
15 |   React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Overlay>
16 | >(({ className, ...props }, ref) => (
17 |   <AlertDialogPrimitive.Overlay
18 |     className={cn(
19 |       "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=cl
20 |       className,
21 |     )}
22 |     {...props}
23 |     ref={ref}
24 |   />
25 | ));
26 | AlertDialogOverlay.displayName = AlertDialogPrimitive.Overlay.displayName;
27 |
28 | const AlertDialogContent = React.forwardRef<
29 |   React.ElementRef<typeof AlertDialogPrimitive.Content>,
30 |   React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Content>
31 | >(({ className, ...props }, ref) => (
32 |   <AlertDialogPortal>
33 |     <AlertDialogOverlay />
34 |     <AlertDialogPrimitive.Content
35 |       ref={ref}
36 |       className={cn(
37 |         "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 border
38 |         className,
39 |       )}
40 |       {...props}
41 |     />
42 |   </AlertDialogPortal>
43 | ));
44 | AlertDialogContent.displayName = AlertDialogPrimitive.Content.displayName;
45 |
46 | const AlertDialogHeader = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
47 |   <div className={cn("flex flex-col space-y-2 text-center sm:text-left", className)} {...props} />
48 | );
49 | AlertDialogHeader.displayName = "AlertDialogHeader";
50 |
51 | const AlertDialogFooter = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
52 |   <div className={cn("flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2", className)} {...props} />
53 | );
54 | AlertDialogFooter.displayName = "AlertDialogFooter";
55 |
56 | const AlertDialogTitle = React.forwardRef<
57 |   React.ElementRef<typeof AlertDialogPrimitive.Title>,
58 |   React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Title>
59 | >(({ className, ...props }, ref) => (
```

```
  <AlertDialogPrimitive.Title ref={ref} className={cn("text-lg font-semibold", className)} {...props} />
));
AlertDialogTitle.displayName = AlertDialogPrimitive.Title.displayName;

const AlertDialogDescription = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Description>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Description>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Description ref={ref} className={cn("text-sm text-muted-foreground", className)} {...prop
));
AlertDialogDescription.displayName = AlertDialogPrimitive.Description.displayName;

const AlertDialogAction = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Action>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Action>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Action ref={ref} className={cn(buttonVariants(), className)} {...props} />
));
AlertDialogAction.displayName = AlertDialogPrimitive.Action.displayName;

const AlertDialogCancel = React.forwardRef<
  React.ElementRef<typeof AlertDialogPrimitive.Cancel>,
  React.ComponentPropsWithoutRef<typeof AlertDialogPrimitive.Cancel>
>(({ className, ...props }, ref) => (
  <AlertDialogPrimitive.Cancel
    ref={ref}
    className={cn(buttonVariants({ variant: "outline" }), "mt-2 sm:mt-0", className)}
    {...props}
  />
));
AlertDialogCancel.displayName = AlertDialogPrimitive.Cancel.displayName;

export {
  AlertDialog,
  AlertDialogPortal,
  AlertDialogOverlay,
  AlertDialogTrigger,
  AlertDialogContent,
  AlertDialogHeader,
  AlertDialogFooter,
  AlertDialogTitle,
  AlertDialogDescription,
  AlertDialogAction,
  AlertDialogCancel,
};

```

4. components/ui/alert.tsx

Path: src/components/ui/alert.tsx

```
import * as React from "react";
import { cva, type VariantProps } from "class-variance-authority";
```

```
 3 |
 4 | import { cn } from "@/lib/utils";
 5 |
 6 | const alertVariants = cva(
 7 |   "relative w-full rounded-lg border p-4 [&>svg~*]:pl-7 [&>svg+div]:translate-y-[-3px] [&>svg]:absolute [&>svg]:l
 8 |   {
 9 |     variants: {
10 |       variant: {
11 |         default: "bg-background text-foreground",
12 |         destructive: "border-destructive/50 text-destructive dark:border-destructive [&>svg]:text-destructive",
13 |       },
14 |     },
15 |     defaultVariants: {
16 |       variant: "default",
17 |     },
18 |   },
19 | );
20 |
21 | const Alert = React.forwardRef<
22 |   HTMLDivElement,
23 |   React.HTMLAttributes<HTMLDivElement> & VariantProps<typeof alertVariants>
24 | >(({ className, variant, ...props }, ref) => (
25 |   <div ref={ref} role="alert" className={cn(alertVariants({ variant }), className)} {...props} />
26 | ));
27 | Alert.displayName = "Alert";
28 |
29 | const AlertTitle = React.forwardRef<HTMLParagraphElement, React.HTMLAttributes<HTMLHeadingElement>>(
30 |   ({ className, ...props }, ref) => (
31 |     <h5 ref={ref} className={cn("mb-1 font-medium leading-none tracking-tight", className)} {...props} />
32 |   ),
33 | );
34 | AlertTitle.displayName = "AlertTitle";
35 |
36 | const AlertDescription = React.forwardRef<HTMLParagraphElement, React.HTMLAttributes<HTMLParagraphElement>>(
37 |   ({ className, ...props }, ref) => (
38 |     <div ref={ref} className={cn("text-sm [&_p]:leading-relaxed", className)} {...props} />
39 |   ),
40 | );
41 | AlertDescription.displayName = "AlertDescription";
42 |
43 | export { Alert, AlertTitle, AlertDescription };
44 |
```

5. components/ui/aspect-ratio.tsx

Path: src/components/ui/aspect-ratio.tsx

```
 1 | import * as AspectRatioPrimitive from "@radix-ui/react-aspect-ratio";
 2 |
 3 | const AspectRatio = AspectRatioPrimitive.Root;
 4 |
 5 | export { AspectRatio };
 6 |
```

6. components/ui/avatar.tsx

Path: src/components/ui/avatar.tsx

```
1 | import * as React from "react";
2 | import * as AvatarPrimitive from "@radix-ui/react-avatar";
3 |
4 | import { cn } from "@/lib/utils";
5 |
6 | const Avatar = React.forwardRef<
7 |   React.ElementRef<typeof AvatarPrimitive.Root>,
8 |   React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Root>
9 | >(({ className, ...props }, ref) => (
10 |   <AvatarPrimitive.Root
11 |     ref={ref}
12 |     className={cn("relative flex h-10 w-10 shrink-0 overflow-hidden rounded-full", className)}
13 |     {...props}
14 |   />
15 | ));
16 | Avatar.displayName = AvatarPrimitive.Root.displayName;
17 |
18 | const AvatarImage = React.forwardRef<
19 |   React.ElementRef<typeof AvatarPrimitive.Image>,
20 |   React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Image>
21 | >(({ className, ...props }, ref) => (
22 |   <AvatarPrimitive.Image ref={ref} className={cn("aspect-square h-full w-full", className)} {...props} />
23 | ));
24 | AvatarImage.displayName = AvatarPrimitive.Image.displayName;
25 |
26 | const AvatarFallback = React.forwardRef<
27 |   React.ElementRef<typeof AvatarPrimitive.Fallback>,
28 |   React.ComponentPropsWithoutRef<typeof AvatarPrimitive.Fallback>
29 | >(({ className, ...props }, ref) => (
30 |   <AvatarPrimitive.Fallback
31 |     ref={ref}
32 |     className={cn("flex h-full w-full items-center justify-center rounded-full bg-muted", className)}
33 |     {...props}
34 |   />
35 | ));
36 | AvatarFallback.displayName = AvatarPrimitive.Fallback.displayName;
37 |
38 | export { Avatar, AvatarImage, AvatarFallback };
39 |
```

7. components/ui/badge.tsx

Path: src/components/ui/badge.tsx

```
1 | import * as React from "react";
2 | import { cva, type VariantProps } from "class-variance-authority";
```

```
 3 |
 4 | import { cn } from "@/lib/utils";
 5 |
 6 | const badgeVariants = cva(
 7 |   "inline-flex items-center rounded-full border px-2.5 py-0.5 text-xs font-semibold transition-colors focus:outli
 8 |   {
 9 |     variants: {
10 |       variant: {
11 |         default: "border-transparent bg-primary text-primary-foreground hover:bg-primary/80",
12 |         secondary: "border-transparent bg-secondary text-secondary-foreground hover:bg-secondary/80",
13 |         destructive: "border-transparent bg-destructive text-destructive-foreground hover:bg-destructive/80",
14 |         outline: "text-foreground",
15 |       },
16 |     },
17 |     defaultVariants: {
18 |       variant: "default",
19 |     },
20 |   },
21 | );
22 |
23 | export interface BadgeProps extends React.HTMLAttributes<HTMLDivElement>, VariantProps<typeof badgeVariants> {}
24 |
25 | function Badge({ className, variant, ...props }: BadgeProps) {
26 |   return <div className={cn(badgeVariants({ variant }), className)} {...props} />;
27 | }
28 |
29 | export { Badge, badgeVariants };
30 |
```

8. components/ui/breadcrumb.tsx

Path: src/components/ui/breadcrumb.tsx

```
 1 | import * as React from "react";
 2 | import { Slot } from "@radix-ui/react-slot";
 3 | import { ChevronRight, MoreHorizontal } from "lucide-react";
 4 |
 5 | import { cn } from "@/lib/utils";
 6 |
 7 | const Breadcrumb = React.forwardRef<
 8 |   HTMLElement,
 9 |   React.ComponentPropsWithoutRef<"nav"> & {
10 |     separator?: React.ReactNode;
11 |   }
12 | >(({ ...props }, ref) => <nav ref={ref} aria-label="breadcrumb" {...props} />);
13 | Breadcrumb.displayName = "Breadcrumb";
14 |
15 | const BreadcrumbList = React.forwardRef<HTMLOListElement, React.ComponentPropsWithoutRef<"ol">>(
16 |   ({ className, ...props }, ref) => (
17 |     <ol
18 |       ref={ref}
19 |       className={cn(
20 |         "flex flex-wrap items-center gap-1.5 break-words text-sm text-muted-foreground sm:gap-2.5",
```

```
21 |         className,
22 |       )}
23 |       {...props}
24 |     />
25 |   ),
26 | );
27 | BreadcrumbList.displayName = "BreadcrumbList";
28 |
29 | const BreadcrumbItem = React.forwardRef<HTMLLIElement, React.ComponentPropsWithoutRef<"li">>(
30 |   ({ className, ...props }, ref) => (
31 |     <li ref={ref} className={cn("inline-flex items-center gap-1.5", className)} {...props} />
32 |   ),
33 | );
34 | BreadcrumbItem.displayName = "BreadcrumbItem";
35 |
36 | const BreadcrumbLink = React.forwardRef<
37 |   HTMLAnchorElement,
38 |   React.ComponentPropsWithoutRef<"a"> & {
39 |     asChild?: boolean;
40 |   }
41 | >(({ asChild, className, ...props }, ref) => {
42 |   const Comp = asChild ? Slot : "a";
43 |
44 |   return <Comp ref={ref} className={cn("transition-colors hover:text-foreground", className)} {...props} />;
45 | });
46 | BreadcrumbLink.displayName = "BreadcrumbLink";
47 |
48 | const BreadcrumbPage = React.forwardRef<HTMLSpanElement, React.ComponentPropsWithoutRef<"span">>(
49 |   ({ className, ...props }, ref) => (
50 |     <span
51 |       ref={ref}
52 |       role="link"
53 |       aria-disabled="true"
54 |       aria-current="page"
55 |       className={cn("font-normal text-foreground", className)}
56 |       {...props}
57 |     />
58 |   ),
59 | );
60 | BreadcrumbPage.displayName = "BreadcrumbPage";
61 |
62 | const BreadcrumbSeparator = ({ children, className, ...props }: React.ComponentProps<"li">) => (
63 |   <li role="presentation" aria-hidden="true" className={cn("[&>svg]:size-3.5", className)} {...props}>
64 |     {children ?? <ChevronRight />}
65 |   </li>
66 | );
67 | BreadcrumbSeparator.displayName = "BreadcrumbSeparator";
68 |
69 | const BreadcrumbEllipsis = ({ className, ...props }: React.ComponentProps<"span">) => (
70 |   <span
71 |     role="presentation"
72 |     aria-hidden="true"
73 |     className={cn("flex h-9 w-9 items-center justify-center", className)}
74 |     {...props}
```

```
75 |   >
76 |     <MoreHorizontal className="h-4 w-4" />
77 |     <span className="sr-only">More</span>
78 |   </span>
79 | );
80 | BreadcrumbEllipsis.displayName = "BreadcrumbElipssis";
81 |
82 | export {
83 |   Breadcrumb,
84 |   BreadcrumbList,
85 |   BreadcrumbItem,
86 |   BreadcrumbLink,
87 |   BreadcrumbPage,
88 |   BreadcrumbSeparator,
89 |   BreadcrumbEllipsis,
90 | };
91 |
```

9. components/ui/button.tsx

Path: src/components/ui/button.tsx

```
1 | import * as React from "react";
2 | import { Slot } from "@radix-ui/react-slot";
3 | import { cva, type VariantProps } from "class-variance-authority";
4 |
5 | import { cn } from "@/lib/utils";
6 |
7 | const buttonVariants = cva(
8 |   "inline-flex items-center justify-center gap-2 whitespace-nowrap rounded-md text-sm font-medium ring-offset-bac
9 |   {
10 |     variants: {
11 |       variant: {
12 |         default: "bg-primary text-primary-foreground hover:bg-primary/90",
13 |         destructive: "bg-destructive text-destructive-foreground hover:bg-destructive/90",
14 |         outline: "border border-input bg-background hover:bg-accent hover:text-accent-foreground",
15 |         secondary: "bg-secondary text-secondary-foreground hover:bg-secondary/80",
16 |         ghost: "hover:bg-accent hover:text-accent-foreground",
17 |         link: "text-primary underline-offset-4 hover:underline",
18 |       },
19 |       size: {
20 |         default: "h-10 px-4 py-2",
21 |         sm: "h-9 rounded-md px-3",
22 |         lg: "h-11 rounded-md px-8",
23 |         icon: "h-10 w-10",
24 |       },
25 |     },
26 |     defaultVariants: {
27 |       variant: "default",
28 |       size: "default",
29 |     },
30 |   },
31 | );
```

```
32 |
33 | export interface ButtonProps
34 |   extends React.ButtonHTMLAttributes<HTMLButtonElement>,
35 |     VariantProps<typeof buttonVariants> {
36 |   asChild?: boolean;
37 | }
38 |
39 | const Button = React.forwardRef<HTMLButtonElement, ButtonProps>(
40 |   ({ className, variant, size, asChild = false, ...props }, ref) => {
41 |     const Comp = asChild ? Slot : "button";
42 |     return <Comp className={cn(buttonVariants({ variant, size, className }))} ref={ref} {...props} />;
43 |   },
44 | );
45 | Button.displayName = "Button";
46 |
47 | export { Button, buttonVariants };
48 |
```

10. components/ui/calendar.tsx

Path: src/components/ui/calendar.tsx

```
1 | import * as React from "react";
2 | import { ChevronLeft, ChevronRight } from "lucide-react";
3 | import { DayPicker } from "react-day-picker";
4 |
5 | import { cn } from "@/lib/utils";
6 | import { buttonVariants } from "@/components/ui/button";
7 |
8 | export type CalendarProps = React.ComponentProps<typeof DayPicker>;
9 |
10 | function Calendar({ className, classNames, showOutsideDays = true, ...props }: CalendarProps) {
11 |   return (
12 |     <DayPicker
13 |       showOutsideDays={showOutsideDays}
14 |       className={cn("p-3", className)}
15 |       classNames={{
16 |         months: "flex flex-col sm:flex-row space-y-4 sm:space-x-4 sm:space-y-0",
17 |         month: "space-y-4",
18 |         caption: "flex justify-center pt-1 relative items-center",
19 |         caption_label: "text-sm font-medium",
20 |         nav: "space-x-1 flex items-center",
21 |         nav_button: cn(
22 |           buttonVariants({ variant: "outline" }),
23 |           "h-7 w-7 bg-transparent p-0 opacity-50 hover:opacity-100",
24 |         ),
25 |         nav_button_previous: "absolute left-1",
26 |         nav_button_next: "absolute right-1",
27 |         table: "w-full border-collapse space-y-1",
28 |         head_row: "flex",
29 |         head_cell: "text-muted-foreground rounded-md w-9 font-normal text-[0.8rem]",
30 |         row: "flex w-full mt-2",
31 |         cell: "h-9 w-9 text-center text-sm p-0 relative [&:has([aria-selected].day-range-end)]:rounded-r-md [&:ha
```

```
32 |         day: cn(buttonVariants({ variant: "ghost" }), "h-9 w-9 p-0 font-normal aria-selected:opacity-100"),
33 |         day_range_end: "day-range-end",
34 |         day_selected:
35 |           "bg-primary text-primary-foreground hover:bg-primary hover:text-primary-foreground focus:bg-primary foc
36 |         day_today: "bg-accent text-accent-foreground",
37 |         day_outside:
38 |           "day-outside text-muted-foreground opacity-50 aria-selected:bg-accent/50 aria-selected:text-muted-foreg
39 |         day_disabled: "text-muted-foreground opacity-50",
40 |         day_range_middle: "aria-selected:bg-accent aria-selected:text-accent-foreground",
41 |         day_hidden: "invisible",
42 |         ...classNames,
43 |       }}
44 |       components={{
45 |         IconLeft: ({ ..._props }) => <ChevronLeft className="h-4 w-4" />,
46 |         IconRight: ({ ..._props }) => <ChevronRight className="h-4 w-4" />,
47 |       }}
48 |       {...props}
49 |     />
50 |   );
51 | }
52 | Calendar.displayName = "Calendar";
53 |
54 | export { Calendar };
55 |
```

11. components/ui/card.tsx

Path: src/components/ui/card.tsx

```
1 | import * as React from "react";
2 |
3 | import { cn } from "@/lib/utils";
4 |
5 | const Card = React.forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>(({ className, ...props }, ref
6 |   <div ref={ref} className={cn("rounded-lg border bg-card text-card-foreground shadow-sm", className)} {...props}
7 | ));
8 | Card.displayName = "Card";
9 |
10 | const CardHeader = React.forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>(
11 |   ({ className, ...props }, ref) => (
12 |     <div ref={ref} className={cn("flex flex-col space-y-1.5 p-6", className)} {...props} />
13 |   ),
14 | );
15 | CardHeader.displayName = "CardHeader";
16 |
17 | const CardTitle = React.forwardRef<HTMLParagraphElement, React.HTMLAttributes<HTMLHeadingElement>>(
18 |   ({ className, ...props }, ref) => (
19 |     <h3 ref={ref} className={cn("text-2xl font-semibold leading-none tracking-tight", className)} {...props} />
20 |   ),
21 | );
22 | CardTitle.displayName = "CardTitle";
23 |
24 | const CardDescription = React.forwardRef<HTMLParagraphElement, React.HTMLAttributes<HTMLParagraphElement>>(
```

```
25 |   ({ className, ...props }, ref) => (
26 |     <p ref={ref} className={cn("text-sm text-muted-foreground", className)} {...props} />
27 |   ),
28 | );
29 | CardDescription.displayName = "CardDescription";
30 |
31 | const CardContent = React.forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>(
32 |   ({ className, ...props }, ref) => <div ref={ref} className={cn("p-6 pt-0", className)} {...props} />,
33 | );
34 | CardContent.displayName = "CardContent";
35 |
36 | const CardFooter = React.forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>(
37 |   ({ className, ...props }, ref) => (
38 |     <div ref={ref} className={cn("flex items-center p-6 pt-0", className)} {...props} />
39 |   ),
40 | );
41 | CardFooter.displayName = "CardFooter";
42 |
43 | export { Card, CardHeader, CardFooter, CardTitle, CardDescription, CardContent };
44 |
```

12. components/ui/carousel.tsx

Path: src/components/ui/carousel.tsx

```
1 | import * as React from "react";
2 | import useEmblaCarousel, { type UseEmblaCarouselType } from "embla-carousel-react";
3 | import { ArrowLeft, ArrowRight } from "lucide-react";
4 |
5 | import { cn } from "@/lib/utils";
6 | import { Button } from "@/components/ui/button";
7 |
8 | type CarouselApi = UseEmblaCarouselType[1];
9 | type UseCarouselParameters = Parameters<typeof useEmblaCarousel>;
10 | type CarouselOptions = UseCarouselParameters[0];
11 | type CarouselPlugin = UseCarouselParameters[1];
12 |
13 | type CarouselProps = {
14 |   opts?: CarouselOptions;
15 |   plugins?: CarouselPlugin;
16 |   orientation?: "horizontal" | "vertical";
17 |   setApi?: (api: CarouselApi) => void;
18 | };
19 |
20 | type CarouselContextProps = {
21 |   carouselRef: ReturnType<typeof useEmblaCarousel>[0];
22 |   api: ReturnType<typeof useEmblaCarousel>[1];
23 |   scrollPrev: () => void;
24 |   scrollNext: () => void;
25 |   canScrollPrev: boolean;
26 |   canScrollNext: boolean;
27 | } & CarouselProps;
28 |
```

```
29 | const CarouselContext = React.createContext<CarouselContextProps | null>(null);
30 |
31 | function useCarousel() {
32 |   const context = React.useContext(CarouselContext);
33 |
34 |   if (!context) {
35 |     throw new Error("useCarousel must be used within a <Carousel />");
36 |   }
37 |
38 |   return context;
39 | }
40 |
41 | const Carousel = React.forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement> & CarouselProps>(
42 |   ({ orientation = "horizontal", opts, setApi, plugins, className, children, ...props }, ref) => {
43 |     const [carouselRef, api] = useEmblaCarousel(
44 |       {
45 |         ...opts,
46 |         axis: orientation === "horizontal" ? "x" : "y",
47 |       },
48 |       plugins,
49 |     );
50 |     const [canScrollPrev, setCanScrollPrev] = React.useState(false);
51 |     const [canScrollNext, setCanScrollNext] = React.useState(false);
52 |
53 |     const onSelect = React.useCallback((api: CarouselApi) => {
54 |       if (!api) {
55 |         return;
56 |       }
57 |
58 |       setCanScrollPrev(api.canScrollPrev());
59 |       setCanScrollNext(api.canScrollNext());
60 |     }, []);
61 |
62 |     const scrollPrev = React.useCallback(() => {
63 |       api?.scrollPrev();
64 |     }, [api]);
65 |
66 |     const scrollNext = React.useCallback(() => {
67 |       api?.scrollNext();
68 |     }, [api]);
69 |
70 |     const handleKeyDown = React.useCallback(
71 |       (event: React.KeyboardEvent<HTMLDivElement>) => {
72 |         if (event.key === "ArrowLeft") {
73 |           event.preventDefault();
74 |           scrollPrev();
75 |         } else if (event.key === "ArrowRight") {
76 |           event.preventDefault();
77 |           scrollNext();
78 |         }
79 |       },
80 |       [scrollPrev, scrollNext],
81 |     );
82 |
```

```
83 |     React.useEffect(() => {
84 |       if (!api || !setApi) {
85 |         return;
86 |       }
87 |
88 |       setApi(api);
89 |     }, [api, setApi]);
90 |
91 |     React.useEffect(() => {
92 |       if (!api) {
93 |         return;
94 |       }
95 |
96 |       onSelect(api);
97 |       api.on("reInit", onSelect);
98 |       api.on("select", onSelect);
99 |
100 |       return () => {
101 |         api?.off("select", onSelect);
102 |       };
103 |     }, [api, onSelect]);
104 |
105 |     return (
106 |       <CarouselContext.Provider
107 |         value={{
108 |           carouselRef,
109 |           api: api,
110 |           opts,
111 |           orientation: orientation || (opts?.axis === "y" ? "vertical" : "horizontal"),
112 |           scrollPrev,
113 |           scrollNext,
114 |           canScrollPrev,
115 |           canScrollNext,
116 |         }}
117 |       >
118 |         <div
119 |           ref={ref}
120 |           onKeyDownCapture={handleKeyDown}
121 |           className={cn("relative", className)}
122 |           role="region"
123 |           aria-roledescription="carousel"
124 |           {...props}
125 |         >
126 |           {children}
127 |         </div>
128 |       </CarouselContext.Provider>
129 |     );
130 |   },
131 | );
132 | Carousel.displayName = "Carousel";
133 |
134 | const CarouselContent = React.forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>(
135 |   ({ className, ...props }, ref) => {
136 |     const { carouselRef, orientation } = useCarousel();
```

```
137 |
138 |     return (
139 |       <div ref={carouselRef} className="overflow-hidden">
140 |         <div
141 |           ref={ref}
142 |           className={cn("flex", orientation === "horizontal" ? "-ml-4" : "-mt-4 flex-col", className)}
143 |           {...props}
144 |         />
145 |       </div>
146 |     );
147 |   },
148 | );
149 | CarouselContent.displayName = "CarouselContent";
150 |
151 | const CarouselItem = React.forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>(
152 |   ({ className, ...props }, ref) => {
153 |     const { orientation } = useCarousel();
154 |
155 |     return (
156 |       <div
157 |         ref={ref}
158 |         role="group"
159 |         aria-roledescription="slide"
160 |         className={cn("min-w-0 shrink-0 grow-0 basis-full", orientation === "horizontal" ? "pl-4" : "pt-4", class
161 |         {...props}
162 |       />
163 |     );
164 |   },
165 | );
166 | CarouselItem.displayName = "CarouselItem";
167 |
168 | const CarouselPrevious = React.forwardRef<HTMLButtonElement, React.ComponentProps<typeof Button>>(
169 |   ({ className, variant = "outline", size = "icon", ...props }, ref) => {
170 |     const { orientation, scrollPrev, canScrollPrev } = useCarousel();
171 |
172 |     return (
173 |       <Button
174 |         ref={ref}
175 |         variant={variant}
176 |         size={size}
177 |         className={cn(
178 |           "absolute h-8 w-8 rounded-full",
179 |           orientation === "horizontal"
180 |             ? "-left-12 top-1/2 -translate-y-1/2"
181 |             : "-top-12 left-1/2 -translate-x-1/2 rotate-90",
182 |           className,
183 |         )}
184 |         disabled={!canScrollPrev}
185 |         onClick={scrollPrev}
186 |         {...props}
187 |       >
188 |         <ArrowLeft className="h-4 w-4" />
189 |         <span className="sr-only">Previous slide</span>
190 |       </Button>
```

```
191 |     );
192 |   },
193 | );
194 | CarouselPrevious.displayName = "CarouselPrevious";
195 |
196 | const CarouselNext = React.forwardRef<HTMLButtonElement, React.ComponentProps<typeof Button>>(
197 |   ({ className, variant = "outline", size = "icon", ...props }, ref) => {
198 |     const { orientation, scrollNext, canScrollNext } = useCarousel();
199 |
200 |     return (
201 |       <Button
202 |         ref={ref}
203 |         variant={variant}
204 |         size={size}
205 |         className={cn(
206 |           "absolute h-8 w-8 rounded-full",
207 |           orientation === "horizontal"
208 |             ? "-right-12 top-1/2 -translate-y-1/2"
209 |             : "-bottom-12 left-1/2 -translate-x-1/2 rotate-90",
210 |           className,
211 |         )}
212 |         disabled={!canScrollNext}
213 |         onClick={scrollNext}
214 |         {...props}
215 |       >
216 |         <ArrowRight className="h-4 w-4" />
217 |         <span className="sr-only">Next slide</span>
218 |       </Button>
219 |     );
220 |   },
221 | );
222 | CarouselNext.displayName = "CarouselNext";
223 |
224 | export { type CarouselApi, Carousel, CarouselContent, CarouselItem, CarouselPrevious, CarouselNext };
225 |
```

13. components/ui/chart.tsx

Path: src/components/ui/chart.tsx

```
1 | import * as React from "react";
2 | import * as RechartsPrimitive from "recharts";
3 |
4 | import { cn } from "@/lib/utils";
5 |
6 | // Format: { THEME_NAME: CSS_SELECTOR }
7 | const THEMES = { light: "", dark: ".dark" } as const;
8 |
9 | export type ChartConfig = {
10 |   [k in string]: {
11 |     label?: React.ReactNode;
12 |     icon?: React.ComponentType;
13 |   } & ({ color?: string; theme?: never } | { color?: never; theme: Record<keyof typeof THEMES, string> });
```

```
14 | };
15 |
16 | type ChartContextProps = {
17 |   config: ChartConfig;
18 | };
19 |
20 | const ChartContext = React.createContext<ChartContextProps | null>(null);
21 |
22 | function useChart() {
23 |   const context = React.useContext(ChartContext);
24 |
25 |   if (!context) {
26 |     throw new Error("useChart must be used within a <ChartContainer />");
27 |   }
28 |
29 |   return context;
30 | }
31 |
32 | const ChartContainer = React.forwardRef<
33 |   HTMLDivElement,
34 |   React.ComponentProps<"div"> & {
35 |     config: ChartConfig;
36 |     children: React.ComponentProps<typeof RechartsPrimitive.ResponsiveContainer>["children"];
37 |   }
38 | >(({ id, className, children, config, ...props }, ref) => {
39 |   const uniqueId = React.useId();
40 |   const chartId = `chart-${id || uniqueId.replace(/:/g, "")}`;
41 |
42 |   return (
43 |     <ChartContext.Provider value={{ config }}>
44 |       <div
45 |         data-chart={chartId}
46 |         ref={ref}
47 |         className={cn(
48 |           "flex aspect-video justify-center text-xs [&_.recharts-cartesian-axis-tick_text]:fill-muted-foreground
49 |           className,
50 |         )}
51 |         {...props}
52 |       >
53 |         <ChartStyle id={chartId} config={config} />
54 |         <RechartsPrimitive.ResponsiveContainer>{children}</RechartsPrimitive.ResponsiveContainer>
55 |       </div>
56 |     </ChartContext.Provider>
57 |   );
58 | });
59 | ChartContainer.displayName = "Chart";
60 |
61 | const ChartStyle = ({ id, config }: { id: string; config: ChartConfig }) => {
62 |   const colorConfig = Object.entries(config).filter(([_, config]) => config.theme || config.color);
63 |
64 |   if (!colorConfig.length) {
65 |     return null;
66 |   }
67 |
```

```
68 |   return (
69 |     <style
70 |       dangerouslySetInnerHTML={{
71 |         __html: Object.entries(THEMES)
72 |           .map(
73 |             ([theme, prefix]) => `
74 | ${prefix} [data-chart=${id}] {
75 | ${colorConfig
76 |   .map(([key, itemConfig]) => {
77 |     const color = itemConfig.theme?.[theme as keyof typeof itemConfig.theme] || itemConfig.color;
78 |     return color ? `  --color-${key}: ${color};` : null;
79 |   })
80 |   .join("\n")}
81 | }
82 | `,
83 |           )
84 |           .join("\n"),
85 |       }}
86 |     />
87 |   );
88 | };
89 |
90 | const ChartTooltip = RechartsPrimitive.Tooltip;
91 |
92 | const ChartTooltipContent = React.forwardRef<
93 |   HTMLDivElement,
94 |   React.ComponentProps<typeof RechartsPrimitive.Tooltip> &
95 |     React.ComponentProps<"div"> & {
96 |       hideLabel?: boolean;
97 |       hideIndicator?: boolean;
98 |       indicator?: "line" | "dot" | "dashed";
99 |       nameKey?: string;
100 |       labelKey?: string;
101 |     }
102 | >(
103 |   (
104 |     {
105 |       active,
106 |       payload,
107 |       className,
108 |       indicator = "dot",
109 |       hideLabel = false,
110 |       hideIndicator = false,
111 |       label,
112 |       labelFormatter,
113 |       labelClassName,
114 |       formatter,
115 |       color,
116 |       nameKey,
117 |       labelKey,
118 |     },
119 |     ref,
120 |   ) => {
121 |     const { config } = useChart();
```

```
122 |
123 |   const tooltipLabel = React.useMemo(() => {
124 |     if (hideLabel || !payload?.length) {
125 |       return null;
126 |     }
127 |
128 |     const [item] = payload;
129 |     const key = `${labelKey || item.dataKey || item.name || "value"}`;
130 |     const itemConfig = getPayloadConfigFromPayload(config, item, key);
131 |     const value =
132 |       !labelKey && typeof label === "string"
133 |         ? config[label as keyof typeof config]?.label || label
134 |         : itemConfig?.label;
135 |
136 |     if (labelFormatter) {
137 |       return <div className={cn("font-medium", labelClassName)}>{labelFormatter(value, payload)}</div>;
138 |     }
139 |
140 |     if (!value) {
141 |       return null;
142 |     }
143 |
144 |     return <div className={cn("font-medium", labelClassName)}>{value}</div>;
145 |   }, [label, labelFormatter, payload, hideLabel, labelClassName, config, labelKey]);
146 |
147 |   if (!active || !payload?.length) {
148 |     return null;
149 |   }
150 |
151 |   const nestLabel = payload.length === 1 && indicator !== "dot";
152 |
153 |   return (
154 |     <div
155 |       ref={ref}
156 |       className={cn(
157 |         "grid min-w-[8rem] items-start gap-1.5 rounded-lg border border-border/50 bg-background px-2.5 py-1.5 t
158 |         className,
159 |       )}
160 |     >
161 |       {!nestLabel ? tooltipLabel : null}
162 |       <div className="grid gap-1.5">
163 |         {payload.map((item, index) => {
164 |           const key = `${nameKey || item.name || item.dataKey || "value"}`;
165 |           const itemConfig = getPayloadConfigFromPayload(config, item, key);
166 |           const indicatorColor = color || item.payload.fill || item.color;
167 |
168 |           return (
169 |             <div
170 |               key={item.dataKey}
171 |               className={cn(
172 |                 "flex w-full flex-wrap items-stretch gap-2 [&>svg]:h-2.5 [&>svg]:w-2.5 [&>svg]:text-muted-foreg
173 |                 indicator === "dot" && "items-center",
174 |               )}
175 |             >
```

```
176 |                {formatter && item?.value !== undefined && item.name ? (
177 |                  formatter(item.value, item.name, item, index, item.payload)
178 |                ) : (
179 |                  <>
180 |                    {itemConfig?.icon ? (
181 |                      <itemConfig.icon />
182 |                    ) : (
183 |                      !hideIndicator && (
184 |                        <div
185 |                          className={cn("shrink-0 rounded-[2px] border-[--color-border] bg-[--color-bg]", {
186 |                            "h-2.5 w-2.5": indicator === "dot",
187 |                            "w-1": indicator === "line",
188 |                            "w-0 border-[1.5px] border-dashed bg-transparent": indicator === "dashed",
189 |                            "my-0.5": nestLabel && indicator === "dashed",
190 |                          })}
191 |                          style={
192 |                            {
193 |                              "--color-bg": indicatorColor,
194 |                              "--color-border": indicatorColor,
195 |                            } as React.CSSProperties
196 |                          }
197 |                        />
198 |                      )
199 |                    )}
200 |                    <div
201 |                      className={cn(
202 |                        "flex flex-1 justify-between leading-none",
203 |                        nestLabel ? "items-end" : "items-center",
204 |                      )}
205 |                    >
206 |                      <div className="grid gap-1.5">
207 |                        {nestLabel ? tooltipLabel : null}
208 |                        <span className="text-muted-foreground">{itemConfig?.label || item.name}</span>
209 |                      </div>
210 |                      {item.value && (
211 |                        <span className="font-mono font-medium tabular-nums text-foreground">
212 |                          {item.value.toLocaleString()}
213 |                        </span>
214 |                      )}
215 |                    </div>
216 |                  </>
217 |                )}
218 |              </div>
219 |            );
220 |          })}
221 |        </div>
222 |      </div>
223 |    );
224 |  },
225 | );
226 | ChartTooltipContent.displayName = "ChartTooltip";
227 |
228 | const ChartLegend = RechartsPrimitive.Legend;
229 |
```

```
230 | const ChartLegendContent = React.forwardRef<
231 |   HTMLDivElement,
232 |   React.ComponentProps<"div"> &
233 |     Pick<RechartsPrimitive.LegendProps, "payload" | "verticalAlign"> & {
234 |       hideIcon?: boolean;
235 |       nameKey?: string;
236 |     }
237 | >(({ className, hideIcon = false, payload, verticalAlign = "bottom", nameKey }, ref) => {
238 |   const { config } = useChart();
239 |
240 |   if (!payload?.length) {
241 |     return null;
242 |   }
243 |
244 |   return (
245 |     <div
246 |       ref={ref}
247 |       className={cn("flex items-center justify-center gap-4", verticalAlign === "top" ? "pb-3" : "pt-3", classNam
248 |     >
249 |       {payload.map((item) => {
250 |         const key = `${nameKey || item.dataKey || "value"}`;
251 |         const itemConfig = getPayloadConfigFromPayload(config, item, key);
252 |
253 |         return (
254 |           <div
255 |             key={item.value}
256 |             className={cn("flex items-center gap-1.5 [&>svg]:h-3 [&>svg]:w-3 [&>svg]:text-muted-foreground")}
257 |           >
258 |             {itemConfig?.icon && !hideIcon ? (
259 |               <itemConfig.icon />
260 |             ) : (
261 |               <div
262 |                 className="h-2 w-2 shrink-0 rounded-[2px]"
263 |                 style={{
264 |                   backgroundColor: item.color,
265 |                 }}
266 |               />
267 |             )}
268 |             {itemConfig?.label}
269 |           </div>
270 |         );
271 |       })}
272 |     </div>
273 |   );
274 | });
275 | ChartLegendContent.displayName = "ChartLegend";
276 |
277 | // Helper to extract item config from a payload.
278 | function getPayloadConfigFromPayload(config: ChartConfig, payload: unknown, key: string) {
279 |   if (typeof payload !== "object" || payload === null) {
280 |     return undefined;
281 |   }
282 |
283 |   const payloadPayload =
```

```
    "payload" in payload && typeof payload.payload === "object" && payload.payload !== null
      ? payload.payload
      : undefined;

  let configLabelKey: string = key;

  if (key in payload && typeof payload[key as keyof typeof payload] === "string") {
    configLabelKey = payload[key as keyof typeof payload] as string;
  } else if (
    payloadPayload &&
    key in payloadPayload &&
    typeof payloadPayload[key as keyof typeof payloadPayload] === "string"
  ) {
    configLabelKey = payloadPayload[key as keyof typeof payloadPayload] as string;
  }

  return configLabelKey in config ? config[configLabelKey] : config[key as keyof typeof config];
}

export { ChartContainer, ChartTooltip, ChartTooltipContent, ChartLegend, ChartLegendContent, ChartStyle };

```

14. components/ui/checkbox.tsx

Path: src/components/ui/checkbox.tsx

```
import * as React from "react";
import * as CheckboxPrimitive from "@radix-ui/react-checkbox";
import { Check } from "lucide-react";

import { cn } from "@/lib/utils";

const Checkbox = React.forwardRef<
  React.ElementRef<typeof CheckboxPrimitive.Root>,
  React.ComponentPropsWithoutRef<typeof CheckboxPrimitive.Root>
>(({ className, ...props }, ref) => (
  <CheckboxPrimitive.Root
    ref={ref}
    className={cn(
      "peer h-4 w-4 shrink-0 rounded-sm border border-primary ring-offset-background data-[state=checked]:bg-prim
      className,
    )}
    {...props}
  >
    <CheckboxPrimitive.Indicator className={cn("flex items-center justify-center text-current")}>
      <Check className="h-4 w-4" />
    </CheckboxPrimitive.Indicator>
  </CheckboxPrimitive.Root>
));
Checkbox.displayName = CheckboxPrimitive.Root.displayName;

export { Checkbox };

```

15. components/ui/collapsible.tsx

Path: src/components/ui/collapsible.tsx

```
 1 | import * as CollapsiblePrimitive from "@radix-ui/react-collapsible";
 2 |
 3 | const Collapsible = CollapsiblePrimitive.Root;
 4 |
 5 | const CollapsibleTrigger = CollapsiblePrimitive.CollapsibleTrigger;
 6 |
 7 | const CollapsibleContent = CollapsiblePrimitive.CollapsibleContent;
 8 |
 9 | export { Collapsible, CollapsibleTrigger, CollapsibleContent };
10 |
```

16. components/ui/command.tsx

Path: src/components/ui/command.tsx

```
 1 | import * as React from "react";
 2 | import { type DialogProps } from "@radix-ui/react-dialog";
 3 | import { Command as CommandPrimitive } from "cmdk";
 4 | import { Search } from "lucide-react";
 5 |
 6 | import { cn } from "@/lib/utils";
 7 | import { Dialog, DialogContent } from "@/components/ui/dialog";
 8 |
 9 | const Command = React.forwardRef<
10 |   React.ElementRef<typeof CommandPrimitive>,
11 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive>
12 | >(({ className, ...props }, ref) => (
13 |   <CommandPrimitive
14 |     ref={ref}
15 |     className={cn(
16 |       "flex h-full w-full flex-col overflow-hidden rounded-md bg-popover text-popover-foreground",
17 |       className,
18 |     )}
19 |     {...props}
20 |   />
21 | ));
22 | Command.displayName = CommandPrimitive.displayName;
23 |
24 | interface CommandDialogProps extends DialogProps {}
25 |
26 | const CommandDialog = ({ children, ...props }: CommandDialogProps) => {
27 |   return (
28 |     <Dialog {...props}>
29 |       <DialogContent className="overflow-hidden p-0 shadow-lg">
30 |         <Command className="[&_[cmdk-group-heading]]:px-2 [&_[cmdk-group-heading]]:font-medium [&_[cmdk-group-hea
31 |           {children}
```

```
32 |         </Command>
33 |       </DialogContent>
34 |     </Dialog>
35 |   );
36 | };
37 |
38 | const CommandInput = React.forwardRef<
39 |   React.ElementRef<typeof CommandPrimitive.Input>,
40 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.Input>
41 | >(({ className, ...props }, ref) => (
42 |   <div className="flex items-center border-b px-3" cmdk-input-wrapper="">
43 |     <Search className="mr-2 h-4 w-4 shrink-0 opacity-50" />
44 |     <CommandPrimitive.Input
45 |       ref={ref}
46 |       className={cn(
47 |         "flex h-11 w-full rounded-md bg-transparent py-3 text-sm outline-none placeholder:text-muted-foreground d
48 |         className,
49 |       )}
50 |       {...props}
51 |     />
52 |   </div>
53 | ));
54 |
55 | CommandInput.displayName = CommandPrimitive.Input.displayName;
56 |
57 | const CommandList = React.forwardRef<
58 |   React.ElementRef<typeof CommandPrimitive.List>,
59 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.List>
60 | >(({ className, ...props }, ref) => (
61 |   <CommandPrimitive.List
62 |     ref={ref}
63 |     className={cn("max-h-[300px] overflow-y-auto overflow-x-hidden", className)}
64 |     {...props}
65 |   />
66 | ));
67 |
68 | CommandList.displayName = CommandPrimitive.List.displayName;
69 |
70 | const CommandEmpty = React.forwardRef<
71 |   React.ElementRef<typeof CommandPrimitive.Empty>,
72 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.Empty>
73 | >((props, ref) => <CommandPrimitive.Empty ref={ref} className="py-6 text-center text-sm" {...props} />);
74 |
75 | CommandEmpty.displayName = CommandPrimitive.Empty.displayName;
76 |
77 | const CommandGroup = React.forwardRef<
78 |   React.ElementRef<typeof CommandPrimitive.Group>,
79 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.Group>
80 | >(({ className, ...props }, ref) => (
81 |   <CommandPrimitive.Group
82 |     ref={ref}
83 |     className={cn(
84 |       "overflow-hidden p-1 text-foreground [&_[cmdk-group-heading]]:px-2 [&_[cmdk-group-heading]]:py-1.5 [&_[cmdk
85 |       className,
```

```
 86 |     )}
 87 |     {...props}
 88 |   />
 89 | ));
 90 |
 91 | CommandGroup.displayName = CommandPrimitive.Group.displayName;
 92 |
 93 | const CommandSeparator = React.forwardRef<
 94 |   React.ElementRef<typeof CommandPrimitive.Separator>,
 95 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.Separator>
 96 | >(({ className, ...props }, ref) => (
 97 |   <CommandPrimitive.Separator ref={ref} className={cn("-mx-1 h-px bg-border", className)} {...props} />
 98 | ));
 99 | CommandSeparator.displayName = CommandPrimitive.Separator.displayName;
100 |
101 | const CommandItem = React.forwardRef<
102 |   React.ElementRef<typeof CommandPrimitive.Item>,
103 |   React.ComponentPropsWithoutRef<typeof CommandPrimitive.Item>
104 | >(({ className, ...props }, ref) => (
105 |   <CommandPrimitive.Item
106 |     ref={ref}
107 |     className={cn(
108 |       "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none data-[di
109 |       className,
110 |     )}
111 |     {...props}
112 |   />
113 | ));
114 |
115 | CommandItem.displayName = CommandPrimitive.Item.displayName;
116 |
117 | const CommandShortcut = ({ className, ...props }: React.HTMLAttributes<HTMLSpanElement>) => {
118 |   return <span className={cn("ml-auto text-xs tracking-widest text-muted-foreground", className)} {...props} />;
119 | };
120 | CommandShortcut.displayName = "CommandShortcut";
121 |
122 | export {
123 |   Command,
124 |   CommandDialog,
125 |   CommandInput,
126 |   CommandList,
127 |   CommandEmpty,
128 |   CommandGroup,
129 |   CommandItem,
130 |   CommandShortcut,
131 |   CommandSeparator,
132 | };
133 |
```

17. components/ui/context-menu.tsx

Path: src/components/ui/context-menu.tsx

```
 1 | import * as React from "react";
 2 | import * as ContextMenuPrimitive from "@radix-ui/react-context-menu";
 3 | import { Check, ChevronRight, Circle } from "lucide-react";
 4 |
 5 | import { cn } from "@/lib/utils";
 6 |
 7 | const ContextMenu = ContextMenuPrimitive.Root;
 8 |
 9 | const ContextMenuTrigger = ContextMenuPrimitive.Trigger;
10 |
11 | const ContextMenuGroup = ContextMenuPrimitive.Group;
12 |
13 | const ContextMenuPortal = ContextMenuPrimitive.Portal;
14 |
15 | const ContextMenuSub = ContextMenuPrimitive.Sub;
16 |
17 | const ContextMenuRadioGroup = ContextMenuPrimitive.RadioGroup;
18 |
19 | const ContextMenuSubTrigger = React.forwardRef<
20 |   React.ElementRef<typeof ContextMenuPrimitive.SubTrigger>,
21 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.SubTrigger> & {
22 |     inset?: boolean;
23 |   }
24 | >(({ className, inset, children, ...props }, ref) => (
25 |   <ContextMenuPrimitive.SubTrigger
26 |     ref={ref}
27 |     className={cn(
28 |       "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none data-[state=open]
29 |       inset && "pl-8",
30 |       className,
31 |     )}
32 |     {...props}
33 |   >
34 |     {children}
35 |     <ChevronRight className="ml-auto h-4 w-4" />
36 |   </ContextMenuPrimitive.SubTrigger>
37 | ));
38 | ContextMenuSubTrigger.displayName = ContextMenuPrimitive.SubTrigger.displayName;
39 |
40 | const ContextMenuSubContent = React.forwardRef<
41 |   React.ElementRef<typeof ContextMenuPrimitive.SubContent>,
42 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.SubContent>
43 | >(({ className, ...props }, ref) => (
44 |   <ContextMenuPrimitive.SubContent
45 |     ref={ref}
46 |     className={cn(
47 |       "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-md data-
48 |       className,
49 |     )}
50 |     {...props}
51 |   />
52 | ));
53 | ContextMenuSubContent.displayName = ContextMenuPrimitive.SubContent.displayName;
54 |
```

```
55 | const ContextMenuContent = React.forwardRef<
56 |   React.ElementRef<typeof ContextMenuPrimitive.Content>,
57 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Content>
58 | >(({ className, ...props }, ref) => (
59 |   <ContextMenuPrimitive.Portal>
60 |     <ContextMenuPrimitive.Content
61 |       ref={ref}
62 |       className={cn(
63 |         "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-md ani
64 |         className,
65 |       )}
66 |       {...props}
67 |     />
68 |   </ContextMenuPrimitive.Portal>
69 | ));
70 | ContextMenuContent.displayName = ContextMenuPrimitive.Content.displayName;
71 |
72 | const ContextMenuItem = React.forwardRef<
73 |   React.ElementRef<typeof ContextMenuPrimitive.Item>,
74 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Item> & {
75 |     inset?: boolean;
76 |   }
77 | >(({ className, inset, ...props }, ref) => (
78 |   <ContextMenuPrimitive.Item
79 |     ref={ref}
80 |     className={cn(
81 |       "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none data-[di
82 |       inset && "pl-8",
83 |       className,
84 |     )}
85 |     {...props}
86 |   />
87 | ));
88 | ContextMenuItem.displayName = ContextMenuPrimitive.Item.displayName;
89 |
90 | const ContextMenuCheckboxItem = React.forwardRef<
91 |   React.ElementRef<typeof ContextMenuPrimitive.CheckboxItem>,
92 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.CheckboxItem>
93 | >(({ className, children, checked, ...props }, ref) => (
94 |   <ContextMenuPrimitive.CheckboxItem
95 |     ref={ref}
96 |     className={cn(
97 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none dat
98 |       className,
99 |     )}
100 |     checked={checked}
101 |     {...props}
102 |   >
103 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
104 |       <ContextMenuPrimitive.ItemIndicator>
105 |         <Check className="h-4 w-4" />
106 |       </ContextMenuPrimitive.ItemIndicator>
107 |     </span>
108 |     {children}
```

```
109 |   </ContextMenuPrimitive.CheckboxItem>
110 | ));
111 | ContextMenuCheckboxItem.displayName = ContextMenuPrimitive.CheckboxItem.displayName;
112 |
113 | const ContextMenuRadioItem = React.forwardRef<
114 |   React.ElementRef<typeof ContextMenuPrimitive.RadioItem>,
115 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.RadioItem>
116 | >(({ className, children, ...props }, ref) => (
117 |   <ContextMenuPrimitive.RadioItem
118 |     ref={ref}
119 |     className={cn(
120 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none dat
121 |       className,
122 |     )}
123 |     {...props}
124 |   >
125 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
126 |       <ContextMenuPrimitive.ItemIndicator>
127 |         <Circle className="h-2 w-2 fill-current" />
128 |       </ContextMenuPrimitive.ItemIndicator>
129 |     </span>
130 |     {children}
131 |   </ContextMenuPrimitive.RadioItem>
132 | ));
133 | ContextMenuRadioItem.displayName = ContextMenuPrimitive.RadioItem.displayName;
134 |
135 | const ContextMenuLabel = React.forwardRef<
136 |   React.ElementRef<typeof ContextMenuPrimitive.Label>,
137 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Label> & {
138 |     inset?: boolean;
139 |   }
140 | >(({ className, inset, ...props }, ref) => (
141 |   <ContextMenuPrimitive.Label
142 |     ref={ref}
143 |     className={cn("px-2 py-1.5 text-sm font-semibold text-foreground", inset && "pl-8", className)}
144 |     {...props}
145 |   />
146 | ));
147 | ContextMenuLabel.displayName = ContextMenuPrimitive.Label.displayName;
148 |
149 | const ContextMenuSeparator = React.forwardRef<
150 |   React.ElementRef<typeof ContextMenuPrimitive.Separator>,
151 |   React.ComponentPropsWithoutRef<typeof ContextMenuPrimitive.Separator>
152 | >(({ className, ...props }, ref) => (
153 |   <ContextMenuPrimitive.Separator ref={ref} className={cn("-mx-1 my-1 h-px bg-border", className)} {...props} />
154 | ));
155 | ContextMenuSeparator.displayName = ContextMenuPrimitive.Separator.displayName;
156 |
157 | const ContextMenuShortcut = ({ className, ...props }: React.HTMLAttributes<HTMLSpanElement>) => {
158 |   return <span className={cn("ml-auto text-xs tracking-widest text-muted-foreground", className)} {...props} />;
159 | };
160 | ContextMenuShortcut.displayName = "ContextMenuShortcut";
161 |
162 | export {
```

```
163 |   ContextMenu,
164 |   ContextMenuTrigger,
165 |   ContextMenuContent,
166 |   ContextMenuItem,
167 |   ContextMenuCheckboxItem,
168 |   ContextMenuRadioItem,
169 |   ContextMenuLabel,
170 |   ContextMenuSeparator,
171 |   ContextMenuShortcut,
172 |   ContextMenuGroup,
173 |   ContextMenuPortal,
174 |   ContextMenuSub,
175 |   ContextMenuSubContent,
176 |   ContextMenuSubTrigger,
177 |   ContextMenuRadioGroup,
178 | };
179 |
```

18. components/ui/dialog.tsx

Path: src/components/ui/dialog.tsx

```
 1 | import * as React from "react";
 2 | import * as DialogPrimitive from "@radix-ui/react-dialog";
 3 | import { X } from "lucide-react";
 4 |
 5 | import { cn } from "@/lib/utils";
 6 |
 7 | const Dialog = DialogPrimitive.Root;
 8 |
 9 | const DialogTrigger = DialogPrimitive.Trigger;
10 |
11 | const DialogPortal = DialogPrimitive.Portal;
12 |
13 | const DialogClose = DialogPrimitive.Close;
14 |
15 | const DialogOverlay = React.forwardRef<
16 |   React.ElementRef<typeof DialogPrimitive.Overlay>,
17 |   React.ComponentPropsWithoutRef<typeof DialogPrimitive.Overlay>
18 | >(({ className, ...props }, ref) => (
19 |   <DialogPrimitive.Overlay
20 |     ref={ref}
21 |     className={cn(
22 |       "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=cl
23 |       className,
24 |     )}
25 |     {...props}
26 |   />
27 | ));
28 | DialogOverlay.displayName = DialogPrimitive.Overlay.displayName;
29 |
30 | const DialogContent = React.forwardRef<
31 |   React.ElementRef<typeof DialogPrimitive.Content>,
```

```
32 |   React.ComponentPropsWithoutRef<typeof DialogPrimitive.Content>
33 | >(({ className, children, ...props }, ref) => (
34 |   <DialogPortal>
35 |     <DialogOverlay />
36 |     <DialogPrimitive.Content
37 |       ref={ref}
38 |       className={cn(
39 |         "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-50%] gap-4 border
40 |         className,
41 |       )}
42 |       {...props}
43 |     >
44 |       {children}
45 |       <DialogPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background trans
46 |         <X className="h-4 w-4" />
47 |         <span className="sr-only">Close</span>
48 |       </DialogPrimitive.Close>
49 |     </DialogPrimitive.Content>
50 |   </DialogPortal>
51 | ));
52 | DialogContent.displayName = DialogPrimitive.Content.displayName;
53 |
54 | const DialogHeader = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
55 |   <div className={cn("flex flex-col space-y-1.5 text-center sm:text-left", className)} {...props} />
56 | );
57 | DialogHeader.displayName = "DialogHeader";
58 |
59 | const DialogFooter = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
60 |   <div className={cn("flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2", className)} {...props} />
61 | );
62 | DialogFooter.displayName = "DialogFooter";
63 |
64 | const DialogTitle = React.forwardRef<
65 |   React.ElementRef<typeof DialogPrimitive.Title>,
66 |   React.ComponentPropsWithoutRef<typeof DialogPrimitive.Title>
67 | >(({ className, ...props }, ref) => (
68 |   <DialogPrimitive.Title
69 |     ref={ref}
70 |     className={cn("text-lg font-semibold leading-none tracking-tight", className)}
71 |     {...props}
72 |   />
73 | ));
74 | DialogTitle.displayName = DialogPrimitive.Title.displayName;
75 |
76 | const DialogDescription = React.forwardRef<
77 |   React.ElementRef<typeof DialogPrimitive.Description>,
78 |   React.ComponentPropsWithoutRef<typeof DialogPrimitive.Description>
79 | >(({ className, ...props }, ref) => (
80 |   <DialogPrimitive.Description ref={ref} className={cn("text-sm text-muted-foreground", className)} {...props} />
81 | ));
82 | DialogDescription.displayName = DialogPrimitive.Description.displayName;
83 |
84 | export {
85 |   Dialog,
```

```
  DialogPortal,
  DialogOverlay,
  DialogClose,
  DialogTrigger,
  DialogContent,
  DialogHeader,
  DialogFooter,
  DialogTitle,
  DialogDescription,
};

```

19. components/ui/drawer.tsx

Path: src/components/ui/drawer.tsx

```
import * as React from "react";
import { Drawer as DrawerPrimitive } from "vaul";

import { cn } from "@/lib/utils";

const Drawer = ({ shouldScaleBackground = true, ...props }: React.ComponentProps<typeof DrawerPrimitive.Root>) =>
  <DrawerPrimitive.Root shouldScaleBackground={shouldScaleBackground} {...props} />
);
Drawer.displayName = "Drawer";

const DrawerTrigger = DrawerPrimitive.Trigger;

const DrawerPortal = DrawerPrimitive.Portal;

const DrawerClose = DrawerPrimitive.Close;

const DrawerOverlay = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Overlay>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Overlay>
>(({ className, ...props }, ref) => (
  <DrawerPrimitive.Overlay ref={ref} className={cn("fixed inset-0 z-50 bg-black/80", className)} {...props} />
));
DrawerOverlay.displayName = DrawerPrimitive.Overlay.displayName;

const DrawerContent = React.forwardRef<
  React.ElementRef<typeof DrawerPrimitive.Content>,
  React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Content>
>(({ className, children, ...props }, ref) => (
  <DrawerPortal>
    <DrawerOverlay />
    <DrawerPrimitive.Content
      ref={ref}
      className={cn(
        "fixed inset-x-0 bottom-0 z-50 mt-24 flex h-auto flex-col rounded-t-[10px] border bg-background",
        className,
      )}
      {...props}
```

```
38 |     >
39 |       <div className="mx-auto mt-4 h-2 w-[100px] rounded-full bg-muted" />
40 |       {children}
41 |     </DrawerPrimitive.Content>
42 |   </DrawerPortal>
43 | ));
44 | DrawerContent.displayName = "DrawerContent";
45 |
46 | const DrawerHeader = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
47 |   <div className={cn("grid gap-1.5 p-4 text-center sm:text-left", className)} {...props} />
48 | );
49 | DrawerHeader.displayName = "DrawerHeader";
50 |
51 | const DrawerFooter = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
52 |   <div className={cn("mt-auto flex flex-col gap-2 p-4", className)} {...props} />
53 | );
54 | DrawerFooter.displayName = "DrawerFooter";
55 |
56 | const DrawerTitle = React.forwardRef<
57 |   React.ElementRef<typeof DrawerPrimitive.Title>,
58 |   React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Title>
59 | >(({ className, ...props }, ref) => (
60 |   <DrawerPrimitive.Title
61 |     ref={ref}
62 |     className={cn("text-lg font-semibold leading-none tracking-tight", className)}
63 |     {...props}
64 |   />
65 | ));
66 | DrawerTitle.displayName = DrawerPrimitive.Title.displayName;
67 |
68 | const DrawerDescription = React.forwardRef<
69 |   React.ElementRef<typeof DrawerPrimitive.Description>,
70 |   React.ComponentPropsWithoutRef<typeof DrawerPrimitive.Description>
71 | >(({ className, ...props }, ref) => (
72 |   <DrawerPrimitive.Description ref={ref} className={cn("text-sm text-muted-foreground", className)} {...props} />
73 | ));
74 | DrawerDescription.displayName = DrawerPrimitive.Description.displayName;
75 |
76 | export {
77 |   Drawer,
78 |   DrawerPortal,
79 |   DrawerOverlay,
80 |   DrawerTrigger,
81 |   DrawerClose,
82 |   DrawerContent,
83 |   DrawerHeader,
84 |   DrawerFooter,
85 |   DrawerTitle,
86 |   DrawerDescription,
87 | };
88 |
```

20. components/ui/dropdown-menu.tsx

Path: src/components/ui/dropdown-menu.tsx

```
 1 | import * as React from "react";
 2 | import * as DropdownMenuPrimitive from "@radix-ui/react-dropdown-menu";
 3 | import { Check, ChevronRight, Circle } from "lucide-react";
 4 |
 5 | import { cn } from "@/lib/utils";
 6 |
 7 | const DropdownMenu = DropdownMenuPrimitive.Root;
 8 |
 9 | const DropdownMenuTrigger = DropdownMenuPrimitive.Trigger;
10 |
11 | const DropdownMenuGroup = DropdownMenuPrimitive.Group;
12 |
13 | const DropdownMenuPortal = DropdownMenuPrimitive.Portal;
14 |
15 | const DropdownMenuSub = DropdownMenuPrimitive.Sub;
16 |
17 | const DropdownMenuRadioGroup = DropdownMenuPrimitive.RadioGroup;
18 |
19 | const DropdownMenuSubTrigger = React.forwardRef<
20 |   React.ElementRef<typeof DropdownMenuPrimitive.SubTrigger>,
21 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubTrigger> & {
22 |     inset?: boolean;
23 |   }
24 | >(({ className, inset, children, ...props }, ref) => (
25 |   <DropdownMenuPrimitive.SubTrigger
26 |     ref={ref}
27 |     className={cn(
28 |       "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none data-[state=open]
29 |       inset && "pl-8",
30 |       className,
31 |     )}
32 |     {...props}
33 |   >
34 |     {children}
35 |     <ChevronRight className="ml-auto h-4 w-4" />
36 |   </DropdownMenuPrimitive.SubTrigger>
37 | ));
38 | DropdownMenuSubTrigger.displayName = DropdownMenuPrimitive.SubTrigger.displayName;
39 |
40 | const DropdownMenuSubContent = React.forwardRef<
41 |   React.ElementRef<typeof DropdownMenuPrimitive.SubContent>,
42 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.SubContent>
43 | >(({ className, ...props }, ref) => (
44 |   <DropdownMenuPrimitive.SubContent
45 |     ref={ref}
46 |     className={cn(
47 |       "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-lg data-
48 |       className,
49 |     )}
50 |     {...props}
```

```
51 |   />
52 | ));
53 | DropdownMenuSubContent.displayName = DropdownMenuPrimitive.SubContent.displayName;
54 |
55 | const DropdownMenuContent = React.forwardRef<
56 |   React.ElementRef<typeof DropdownMenuPrimitive.Content>,
57 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Content>
58 | >(({ className, sideOffset = 4, ...props }, ref) => (
59 |   <DropdownMenuPrimitive.Portal>
60 |     <DropdownMenuPrimitive.Content
61 |       ref={ref}
62 |       sideOffset={sideOffset}
63 |       className={cn(
64 |         "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-md dat
65 |         className,
66 |       )}
67 |       {...props}
68 |     />
69 |   </DropdownMenuPrimitive.Portal>
70 | ));
71 | DropdownMenuContent.displayName = DropdownMenuPrimitive.Content.displayName;
72 |
73 | const DropdownMenuItem = React.forwardRef<
74 |   React.ElementRef<typeof DropdownMenuPrimitive.Item>,
75 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Item> & {
76 |     inset?: boolean;
77 |   }
78 | >(({ className, inset, ...props }, ref) => (
79 |   <DropdownMenuPrimitive.Item
80 |     ref={ref}
81 |     className={cn(
82 |       "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none transiti
83 |       inset && "pl-8",
84 |       className,
85 |     )}
86 |     {...props}
87 |   />
88 | ));
89 | DropdownMenuItem.displayName = DropdownMenuPrimitive.Item.displayName;
90 |
91 | const DropdownMenuCheckboxItem = React.forwardRef<
92 |   React.ElementRef<typeof DropdownMenuPrimitive.CheckboxItem>,
93 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.CheckboxItem>
94 | >(({ className, children, checked, ...props }, ref) => (
95 |   <DropdownMenuPrimitive.CheckboxItem
96 |     ref={ref}
97 |     className={cn(
98 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none tra
99 |       className,
100 |     )}
101 |     checked={checked}
102 |     {...props}
103 |   >
104 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
```

```
105 |       <DropdownMenuPrimitive.ItemIndicator>
106 |         <Check className="h-4 w-4" />
107 |       </DropdownMenuPrimitive.ItemIndicator>
108 |     </span>
109 |     {children}
110 |   </DropdownMenuPrimitive.CheckboxItem>
111 | ));
112 | DropdownMenuCheckboxItem.displayName = DropdownMenuPrimitive.CheckboxItem.displayName;
113 |
114 | const DropdownMenuRadioItem = React.forwardRef<
115 |   React.ElementRef<typeof DropdownMenuPrimitive.RadioItem>,
116 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.RadioItem>
117 | >(({ className, children, ...props }, ref) => (
118 |   <DropdownMenuPrimitive.RadioItem
119 |     ref={ref}
120 |     className={cn(
121 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none tra
122 |       className,
123 |     )}
124 |     {...props}
125 |   >
126 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
127 |       <DropdownMenuPrimitive.ItemIndicator>
128 |         <Circle className="h-2 w-2 fill-current" />
129 |       </DropdownMenuPrimitive.ItemIndicator>
130 |     </span>
131 |     {children}
132 |   </DropdownMenuPrimitive.RadioItem>
133 | ));
134 | DropdownMenuRadioItem.displayName = DropdownMenuPrimitive.RadioItem.displayName;
135 |
136 | const DropdownMenuLabel = React.forwardRef<
137 |   React.ElementRef<typeof DropdownMenuPrimitive.Label>,
138 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Label> & {
139 |     inset?: boolean;
140 |   }
141 | >(({ className, inset, ...props }, ref) => (
142 |   <DropdownMenuPrimitive.Label
143 |     ref={ref}
144 |     className={cn("px-2 py-1.5 text-sm font-semibold", inset && "pl-8", className)}
145 |     {...props}
146 |   />
147 | ));
148 | DropdownMenuLabel.displayName = DropdownMenuPrimitive.Label.displayName;
149 |
150 | const DropdownMenuSeparator = React.forwardRef<
151 |   React.ElementRef<typeof DropdownMenuPrimitive.Separator>,
152 |   React.ComponentPropsWithoutRef<typeof DropdownMenuPrimitive.Separator>
153 | >(({ className, ...props }, ref) => (
154 |   <DropdownMenuPrimitive.Separator ref={ref} className={cn("-mx-1 my-1 h-px bg-muted", className)} {...props} />
155 | ));
156 | DropdownMenuSeparator.displayName = DropdownMenuPrimitive.Separator.displayName;
157 |
158 | const DropdownMenuShortcut = ({ className, ...props }: React.HTMLAttributes<HTMLSpanElement>) => {
```

```
159 |   return <span className={cn("ml-auto text-xs tracking-widest opacity-60", className)} {...props} />;
160 | };
161 | DropdownMenuShortcut.displayName = "DropdownMenuShortcut";
162 |
163 | export {
164 |   DropdownMenu,
165 |   DropdownMenuTrigger,
166 |   DropdownMenuContent,
167 |   DropdownMenuItem,
168 |   DropdownMenuCheckboxItem,
169 |   DropdownMenuRadioItem,
170 |   DropdownMenuLabel,
171 |   DropdownMenuSeparator,
172 |   DropdownMenuShortcut,
173 |   DropdownMenuGroup,
174 |   DropdownMenuPortal,
175 |   DropdownMenuSub,
176 |   DropdownMenuSubContent,
177 |   DropdownMenuSubTrigger,
178 |   DropdownMenuRadioGroup,
179 | };
180 |
```

21. components/ui/form.tsx

Path: src/components/ui/form.tsx

```
1 | import * as React from "react";
2 | import * as LabelPrimitive from "@radix-ui/react-label";
3 | import { Slot } from "@radix-ui/react-slot";
4 | import { Controller, ControllerProps, FieldPath, FieldValues, FormProvider, useFormContext } from "react-hook-for
5 |
6 | import { cn } from "@/lib/utils";
7 | import { Label } from "@/components/ui/label";
8 |
9 | const Form = FormProvider;
10 |
11 | type FormFieldContextValue<
12 |   TFieldValues extends FieldValues = FieldValues,
13 |   TName extends FieldPath<TFieldValues> = FieldPath<TFieldValues>,
14 | > = {
15 |   name: TName;
16 | };
17 |
18 | const FormFieldContext = React.createContext<FormFieldContextValue>({} as FormFieldContextValue);
19 |
20 | const FormField = <
21 |   TFieldValues extends FieldValues = FieldValues,
22 |   TName extends FieldPath<TFieldValues> = FieldPath<TFieldValues>,
23 | >({
24 |   ...props
25 | }: ControllerProps<TFieldValues, TName>) => {
26 |   return (
```

```
27 |     <FormFieldContext.Provider value={{ name: props.name }}>
28 |       <Controller {...props} />
29 |     </FormFieldContext.Provider>
30 |   );
31 | };
32 |
33 | const useFormField = () => {
34 |   const fieldContext = React.useContext(FormFieldContext);
35 |   const itemContext = React.useContext(FormItemContext);
36 |   const { getFieldState, formState } = useFormContext();
37 |
38 |   const fieldState = getFieldState(fieldContext.name, formState);
39 |
40 |   if (!fieldContext) {
41 |     throw new Error("useFormField should be used within <FormField>");
42 |   }
43 |
44 |   const { id } = itemContext;
45 |
46 |   return {
47 |     id,
48 |     name: fieldContext.name,
49 |     formItemId: `${id}-form-item`,
50 |     formDescriptionId: `${id}-form-item-description`,
51 |     formMessageId: `${id}-form-item-message`,
52 |     ...fieldState,
53 |   };
54 | };
55 |
56 | type FormItemContextValue = {
57 |   id: string;
58 | };
59 |
60 | const FormItemContext = React.createContext<FormItemContextValue>({} as FormItemContextValue);
61 |
62 | const FormItem = React.forwardRef<HTMLDivElement, React.HTMLAttributes<HTMLDivElement>>(
63 |   ({ className, ...props }, ref) => {
64 |     const id = React.useId();
65 |
66 |     return (
67 |       <FormItemContext.Provider value={{ id }}>
68 |         <div ref={ref} className={cn("space-y-2", className)} {...props} />
69 |       </FormItemContext.Provider>
70 |     );
71 |   },
72 | );
73 | FormItem.displayName = "FormItem";
74 |
75 | const FormLabel = React.forwardRef<
76 |   React.ElementRef<typeof LabelPrimitive.Root>,
77 |   React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root>
78 | >(({ className, ...props }, ref) => {
79 |   const { error, formItemId } = useFormField();
80 |
```

```
81 |   return <Label ref={ref} className={cn(error && "text-destructive", className)} htmlFor={formItemId} {...props}
82 | });
83 | FormLabel.displayName = "FormLabel";
84 |
85 | const FormControl = React.forwardRef<React.ElementRef<typeof Slot>, React.ComponentPropsWithoutRef<typeof Slot>>(
86 |   ({ ...props }, ref) => {
87 |     const { error, formItemId, formDescriptionId, formMessageId } = useFormField();
88 |
89 |     return (
90 |       <Slot
91 |         ref={ref}
92 |         id={formItemId}
93 |         aria-describedby={!error ? `${formDescriptionId}` : `${formDescriptionId} ${formMessageId}`}
94 |         aria-invalid={!!error}
95 |         {...props}
96 |       />
97 |     );
98 |   },
99 | );
100 | FormControl.displayName = "FormControl";
101 |
102 | const FormDescription = React.forwardRef<HTMLParagraphElement, React.HTMLAttributes<HTMLParagraphElement>>(
103 |   ({ className, ...props }, ref) => {
104 |     const { formDescriptionId } = useFormField();
105 |
106 |     return <p ref={ref} id={formDescriptionId} className={cn("text-sm text-muted-foreground", className)} {...pro
107 |   },
108 | );
109 | FormDescription.displayName = "FormDescription";
110 |
111 | const FormMessage = React.forwardRef<HTMLParagraphElement, React.HTMLAttributes<HTMLParagraphElement>>(
112 |   ({ className, children, ...props }, ref) => {
113 |     const { error, formMessageId } = useFormField();
114 |     const body = error ? String(error?.message) : children;
115 |
116 |     if (!body) {
117 |       return null;
118 |     }
119 |
120 |     return (
121 |       <p ref={ref} id={formMessageId} className={cn("text-sm font-medium text-destructive", className)} {...props
122 |         {body}
123 |       </p>
124 |     );
125 |   },
126 | );
127 | FormMessage.displayName = "FormMessage";
128 |
129 | export { useFormField, Form, FormItem, FormLabel, FormControl, FormDescription, FormMessage, FormField };
130 |
```

22. components/ui/hover-card.tsx

Path: src/components/ui/hover-card.tsx

```
 1 | import * as React from "react";
 2 | import * as HoverCardPrimitive from "@radix-ui/react-hover-card";
 3 |
 4 | import { cn } from "@/lib/utils";
 5 |
 6 | const HoverCard = HoverCardPrimitive.Root;
 7 |
 8 | const HoverCardTrigger = HoverCardPrimitive.Trigger;
 9 |
10 | const HoverCardContent = React.forwardRef<
11 |   React.ElementRef<typeof HoverCardPrimitive.Content>,
12 |   React.ComponentPropsWithoutRef<typeof HoverCardPrimitive.Content>
13 | >(({ className, align = "center", sideOffset = 4, ...props }, ref) => (
14 |   <HoverCardPrimitive.Content
15 |     ref={ref}
16 |     align={align}
17 |     sideOffset={sideOffset}
18 |     className={cn(
19 |       "z-50 w-64 rounded-md border bg-popover p-4 text-popover-foreground shadow-md outline-none data-[state=open
20 |       className,
21 |     )}
22 |     {...props}
23 |   />
24 | ));
25 | HoverCardContent.displayName = HoverCardPrimitive.Content.displayName;
26 |
27 | export { HoverCard, HoverCardTrigger, HoverCardContent };
28 |
```

23. components/ui/input-otp.tsx

Path: src/components/ui/input-otp.tsx

```
 1 | import * as React from "react";
 2 | import { OTPInput, OTPInputContext } from "input-otp";
 3 | import { Dot } from "lucide-react";
 4 |
 5 | import { cn } from "@/lib/utils";
 6 |
 7 | const InputOTP = React.forwardRef<React.ElementRef<typeof OTPInput>, React.ComponentPropsWithoutRef<typeof OTPInp
 8 |   ({ className, containerClassName, ...props }, ref) => (
 9 |     <OTPInput
10 |       ref={ref}
11 |       containerClassName={cn("flex items-center gap-2 has-[:disabled]:opacity-50", containerClassName)}
12 |       className={cn("disabled:cursor-not-allowed", className)}
13 |       {...props}
14 |     />
15 |   ),
16 | );
17 | InputOTP.displayName = "InputOTP";
```

```
18 |
19 | const InputOTPGroup = React.forwardRef<React.ElementRef<"div">, React.ComponentPropsWithoutRef<"div">>(
20 |   ({ className, ...props }, ref) => <div ref={ref} className={cn("flex items-center", className)} {...props} />,
21 | );
22 | InputOTPGroup.displayName = "InputOTPGroup";
23 |
24 | const InputOTPSlot = React.forwardRef<
25 |   React.ElementRef<"div">,
26 |   React.ComponentPropsWithoutRef<"div"> & { index: number }
27 | >(({ index, className, ...props }, ref) => {
28 |   const inputOTPContext = React.useContext(OTPInputContext);
29 |   const { char, hasFakeCaret, isActive } = inputOTPContext.slots[index];
30 |
31 |   return (
32 |     <div
33 |       ref={ref}
34 |       className={cn(
35 |         "relative flex h-10 w-10 items-center justify-center border-y border-r border-input text-sm transition-al
36 |         isActive && "z-10 ring-2 ring-ring ring-offset-background",
37 |         className,
38 |       )}
39 |       {...props}
40 |     >
41 |       {char}
42 |       {hasFakeCaret && (
43 |         <div className="pointer-events-none absolute inset-0 flex items-center justify-center">
44 |           <div className="animate-caret-blink h-4 w-px bg-foreground duration-1000" />
45 |         </div>
46 |       )}
47 |     </div>
48 |   );
49 | });
50 | InputOTPSlot.displayName = "InputOTPSlot";
51 |
52 | const InputOTPSeparator = React.forwardRef<React.ElementRef<"div">, React.ComponentPropsWithoutRef<"div">>(
53 |   ({ ...props }, ref) => (
54 |     <div ref={ref} role="separator" {...props}>
55 |       <Dot />
56 |     </div>
57 |   ),
58 | );
59 | InputOTPSeparator.displayName = "InputOTPSeparator";
60 |
61 | export { InputOTP, InputOTPGroup, InputOTPSlot, InputOTPSeparator };
62 |
```

24. components/ui/input.tsx

Path: src/components/ui/input.tsx

```
1 | import * as React from "react";
2 |
3 | import { cn } from "@/lib/utils";
```

```
 4 |
 5 | const Input = React.forwardRef<HTMLInputElement, React.ComponentProps<"input">>(
 6 |   ({ className, type, ...props }, ref) => {
 7 |     return (
 8 |       <input
 9 |         type={type}
10 |         className={cn(
11 |           "flex h-10 w-full rounded-md border border-input bg-background px-3 py-2 text-base ring-offset-backgrou
12 |           className,
13 |         )}
14 |         ref={ref}
15 |         {...props}
16 |       />
17 |     );
18 |   },
19 | );
20 | Input.displayName = "Input";
21 |
22 | export { Input };
23 |
```

25. components/ui/label.tsx

Path: src/components/ui/label.tsx

```
 1 | import * as React from "react";
 2 | import * as LabelPrimitive from "@radix-ui/react-label";
 3 | import { cva, type VariantProps } from "class-variance-authority";
 4 |
 5 | import { cn } from "@/lib/utils";
 6 |
 7 | const labelVariants = cva("text-sm font-medium leading-none peer-disabled:cursor-not-allowed peer-disabled:opacit
 8 |
 9 | const Label = React.forwardRef<
10 |   React.ElementRef<typeof LabelPrimitive.Root>,
11 |   React.ComponentPropsWithoutRef<typeof LabelPrimitive.Root> & VariantProps<typeof labelVariants>
12 | >(({ className, ...props }, ref) => (
13 |   <LabelPrimitive.Root ref={ref} className={cn(labelVariants(), className)} {...props} />
14 | ));
15 | Label.displayName = LabelPrimitive.Root.displayName;
16 |
17 | export { Label };
18 |
```

26. components/ui/menubar.tsx

Path: src/components/ui/menubar.tsx

```
 1 | import * as React from "react";
 2 | import * as MenubarPrimitive from "@radix-ui/react-menubar";
 3 | import { Check, ChevronRight, Circle } from "lucide-react";
```

```
 4 |
 5 | import { cn } from "@/lib/utils";
 6 |
 7 | const MenubarMenu = MenubarPrimitive.Menu;
 8 |
 9 | const MenubarGroup = MenubarPrimitive.Group;
10 |
11 | const MenubarPortal = MenubarPrimitive.Portal;
12 |
13 | const MenubarSub = MenubarPrimitive.Sub;
14 |
15 | const MenubarRadioGroup = MenubarPrimitive.RadioGroup;
16 |
17 | const Menubar = React.forwardRef<
18 |   React.ElementRef<typeof MenubarPrimitive.Root>,
19 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Root>
20 | >(({ className, ...props }, ref) => (
21 |   <MenubarPrimitive.Root
22 |     ref={ref}
23 |     className={cn("flex h-10 items-center space-x-1 rounded-md border bg-background p-1", className)}
24 |     {...props}
25 |   />
26 | ));
27 | Menubar.displayName = MenubarPrimitive.Root.displayName;
28 |
29 | const MenubarTrigger = React.forwardRef<
30 |   React.ElementRef<typeof MenubarPrimitive.Trigger>,
31 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Trigger>
32 | >(({ className, ...props }, ref) => (
33 |   <MenubarPrimitive.Trigger
34 |     ref={ref}
35 |     className={cn(
36 |       "flex cursor-default select-none items-center rounded-sm px-3 py-1.5 text-sm font-medium outline-none data-
37 |       className,
38 |     )}
39 |     {...props}
40 |   />
41 | ));
42 | MenubarTrigger.displayName = MenubarPrimitive.Trigger.displayName;
43 |
44 | const MenubarSubTrigger = React.forwardRef<
45 |   React.ElementRef<typeof MenubarPrimitive.SubTrigger>,
46 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubTrigger> & {
47 |     inset?: boolean;
48 |   }
49 | >(({ className, inset, children, ...props }, ref) => (
50 |   <MenubarPrimitive.SubTrigger
51 |     ref={ref}
52 |     className={cn(
53 |       "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none data-[state=open]
54 |       inset && "pl-8",
55 |       className,
56 |     )}
57 |     {...props}
```

```
58 |   >
59 |     {children}
60 |     <ChevronRight className="ml-auto h-4 w-4" />
61 |   </MenubarPrimitive.SubTrigger>
62 | ));
63 | MenubarSubTrigger.displayName = MenubarPrimitive.SubTrigger.displayName;
64 |
65 | const MenubarSubContent = React.forwardRef<
66 |   React.ElementRef<typeof MenubarPrimitive.SubContent>,
67 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.SubContent>
68 | >(({ className, ...props }, ref) => (
69 |   <MenubarPrimitive.SubContent
70 |     ref={ref}
71 |     className={cn(
72 |       "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground data-[state=ope
73 |       className,
74 |     )}
75 |     {...props}
76 |   />
77 | ));
78 | MenubarSubContent.displayName = MenubarPrimitive.SubContent.displayName;
79 |
80 | const MenubarContent = React.forwardRef<
81 |   React.ElementRef<typeof MenubarPrimitive.Content>,
82 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Content>
83 | >(({ className, align = "start", alignOffset = -4, sideOffset = 8, ...props }, ref) => (
84 |   <MenubarPrimitive.Portal>
85 |     <MenubarPrimitive.Content
86 |       ref={ref}
87 |       align={align}
88 |       alignOffset={alignOffset}
89 |       sideOffset={sideOffset}
90 |       className={cn(
91 |         "z-50 min-w-[12rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground shadow-md da
92 |         className,
93 |       )}
94 |       {...props}
95 |     />
96 |   </MenubarPrimitive.Portal>
97 | ));
98 | MenubarContent.displayName = MenubarPrimitive.Content.displayName;
99 |
100 | const MenubarItem = React.forwardRef<
101 |   React.ElementRef<typeof MenubarPrimitive.Item>,
102 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Item> & {
103 |     inset?: boolean;
104 |   }
105 | >(({ className, inset, ...props }, ref) => (
106 |   <MenubarPrimitive.Item
107 |     ref={ref}
108 |     className={cn(
109 |       "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none data-[di
110 |       inset && "pl-8",
111 |       className,
```

```
112 |     )}
113 |     {...props}
114 |   />
115 | ));
116 | MenubarItem.displayName = MenubarPrimitive.Item.displayName;
117 |
118 | const MenubarCheckboxItem = React.forwardRef<
119 |   React.ElementRef<typeof MenubarPrimitive.CheckboxItem>,
120 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.CheckboxItem>
121 | >(({ className, children, checked, ...props }, ref) => (
122 |   <MenubarPrimitive.CheckboxItem
123 |     ref={ref}
124 |     className={cn(
125 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none dat
126 |       className,
127 |     )}
128 |     checked={checked}
129 |     {...props}
130 |   >
131 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
132 |       <MenubarPrimitive.ItemIndicator>
133 |         <Check className="h-4 w-4" />
134 |       </MenubarPrimitive.ItemIndicator>
135 |     </span>
136 |     {children}
137 |   </MenubarPrimitive.CheckboxItem>
138 | ));
139 | MenubarCheckboxItem.displayName = MenubarPrimitive.CheckboxItem.displayName;
140 |
141 | const MenubarRadioItem = React.forwardRef<
142 |   React.ElementRef<typeof MenubarPrimitive.RadioItem>,
143 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.RadioItem>
144 | >(({ className, children, ...props }, ref) => (
145 |   <MenubarPrimitive.RadioItem
146 |     ref={ref}
147 |     className={cn(
148 |       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-none dat
149 |       className,
150 |     )}
151 |     {...props}
152 |   >
153 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
154 |       <MenubarPrimitive.ItemIndicator>
155 |         <Circle className="h-2 w-2 fill-current" />
156 |       </MenubarPrimitive.ItemIndicator>
157 |     </span>
158 |     {children}
159 |   </MenubarPrimitive.RadioItem>
160 | ));
161 | MenubarRadioItem.displayName = MenubarPrimitive.RadioItem.displayName;
162 |
163 | const MenubarLabel = React.forwardRef<
164 |   React.ElementRef<typeof MenubarPrimitive.Label>,
165 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Label> & {
```

```
166 |     inset?: boolean;
167 |   }
168 | >(({ className, inset, ...props }, ref) => (
169 |   <MenubarPrimitive.Label
170 |     ref={ref}
171 |     className={cn("px-2 py-1.5 text-sm font-semibold", inset && "pl-8", className)}
172 |     {...props}
173 |   />
174 | ));
175 | MenubarLabel.displayName = MenubarPrimitive.Label.displayName;
176 |
177 | const MenubarSeparator = React.forwardRef<
178 |   React.ElementRef<typeof MenubarPrimitive.Separator>,
179 |   React.ComponentPropsWithoutRef<typeof MenubarPrimitive.Separator>
180 | >(({ className, ...props }, ref) => (
181 |   <MenubarPrimitive.Separator ref={ref} className={cn("-mx-1 my-1 h-px bg-muted", className)} {...props} />
182 | ));
183 | MenubarSeparator.displayName = MenubarPrimitive.Separator.displayName;
184 |
185 | const MenubarShortcut = ({ className, ...props }: React.HTMLAttributes<HTMLSpanElement>) => {
186 |   return <span className={cn("ml-auto text-xs tracking-widest text-muted-foreground", className)} {...props} />;
187 | };
188 | MenubarShortcut.displayname = "MenubarShortcut";
189 |
190 | export {
191 |   Menubar,
192 |   MenubarMenu,
193 |   MenubarTrigger,
194 |   MenubarContent,
195 |   MenubarItem,
196 |   MenubarSeparator,
197 |   MenubarLabel,
198 |   MenubarCheckboxItem,
199 |   MenubarRadioGroup,
200 |   MenubarRadioItem,
201 |   MenubarPortal,
202 |   MenubarSubContent,
203 |   MenubarSubTrigger,
204 |   MenubarGroup,
205 |   MenubarSub,
206 |   MenubarShortcut,
207 | };
208 |
```

27. components/ui/navigation-menu.tsx

Path: src/components/ui/navigation-menu.tsx

```
1 | import * as React from "react";
2 | import * as NavigationMenuPrimitive from "@radix-ui/react-navigation-menu";
3 | import { cva } from "class-variance-authority";
4 | import { ChevronDown } from "lucide-react";
5 |
```

```
 6 | import { cn } from "@/lib/utils";
 7 |
 8 | const NavigationMenu = React.forwardRef<
 9 |   React.ElementRef<typeof NavigationMenuPrimitive.Root>,
10 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Root>
11 | >(({ className, children, ...props }, ref) => (
12 |   <NavigationMenuPrimitive.Root
13 |     ref={ref}
14 |     className={cn("relative z-10 flex max-w-max flex-1 items-center justify-center", className)}
15 |     {...props}
16 |   >
17 |     {children}
18 |     <NavigationMenuViewport />
19 |   </NavigationMenuPrimitive.Root>
20 | ));
21 | NavigationMenu.displayName = NavigationMenuPrimitive.Root.displayName;
22 |
23 | const NavigationMenuList = React.forwardRef<
24 |   React.ElementRef<typeof NavigationMenuPrimitive.List>,
25 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.List>
26 | >(({ className, ...props }, ref) => (
27 |   <NavigationMenuPrimitive.List
28 |     ref={ref}
29 |     className={cn("group flex flex-1 list-none items-center justify-center space-x-1", className)}
30 |     {...props}
31 |   />
32 | ));
33 | NavigationMenuList.displayName = NavigationMenuPrimitive.List.displayName;
34 |
35 | const NavigationMenuItem = NavigationMenuPrimitive.Item;
36 |
37 | const navigationMenuTriggerStyle = cva(
38 |   "group inline-flex h-10 w-max items-center justify-center rounded-md bg-background px-4 py-2 text-sm font-mediu
39 | );
40 |
41 | const NavigationMenuTrigger = React.forwardRef<
42 |   React.ElementRef<typeof NavigationMenuPrimitive.Trigger>,
43 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Trigger>
44 | >(({ className, children, ...props }, ref) => (
45 |   <NavigationMenuPrimitive.Trigger
46 |     ref={ref}
47 |     className={cn(navigationMenuTriggerStyle(), "group", className)}
48 |     {...props}
49 |   >
50 |     {children}{" "}
51 |     <ChevronDown
52 |       className="relative top-[1px] ml-1 h-3 w-3 transition duration-200 group-data-[state=open]:rotate-180"
53 |       aria-hidden="true"
54 |     />
55 |   </NavigationMenuPrimitive.Trigger>
56 | ));
57 | NavigationMenuTrigger.displayName = NavigationMenuPrimitive.Trigger.displayName;
58 |
59 | const NavigationMenuContent = React.forwardRef<
```

```
60 |   React.ElementRef<typeof NavigationMenuPrimitive.Content>,
61 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Content>
62 | >(({ className, ...props }, ref) => (
63 |   <NavigationMenuPrimitive.Content
64 |     ref={ref}
65 |     className={cn(
66 |       "left-0 top-0 w-full data-[motion^=from-]:animate-in data-[motion^=to-]:animate-out data-[motion^=from-]:fa
67 |       className,
68 |     )}
69 |     {...props}
70 |   />
71 | ));
72 | NavigationMenuContent.displayName = NavigationMenuPrimitive.Content.displayName;
73 |
74 | const NavigationMenuLink = NavigationMenuPrimitive.Link;
75 |
76 | const NavigationMenuViewport = React.forwardRef<
77 |   React.ElementRef<typeof NavigationMenuPrimitive.Viewport>,
78 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Viewport>
79 | >(({ className, ...props }, ref) => (
80 |   <div className={cn("absolute left-0 top-full flex justify-center")}>
81 |     <NavigationMenuPrimitive.Viewport
82 |       className={cn(
83 |         "origin-top-center relative mt-1.5 h-[var(--radix-navigation-menu-viewport-height)] w-full overflow-hidde
84 |         className,
85 |       )}
86 |       ref={ref}
87 |       {...props}
88 |     />
89 |   </div>
90 | ));
91 | NavigationMenuViewport.displayName = NavigationMenuPrimitive.Viewport.displayName;
92 |
93 | const NavigationMenuIndicator = React.forwardRef<
94 |   React.ElementRef<typeof NavigationMenuPrimitive.Indicator>,
95 |   React.ComponentPropsWithoutRef<typeof NavigationMenuPrimitive.Indicator>
96 | >(({ className, ...props }, ref) => (
97 |   <NavigationMenuPrimitive.Indicator
98 |     ref={ref}
99 |     className={cn(
100 |       "top-full z-[1] flex h-1.5 items-end justify-center overflow-hidden data-[state=visible]:animate-in data-[s
101 |       className,
102 |     )}
103 |     {...props}
104 |   >
105 |     <div className="relative top-[60%] h-2 w-2 rotate-45 rounded-tl-sm bg-border shadow-md" />
106 |   </NavigationMenuPrimitive.Indicator>
107 | ));
108 | NavigationMenuIndicator.displayName = NavigationMenuPrimitive.Indicator.displayName;
109 |
110 | export {
111 |   navigationMenuTriggerStyle,
112 |   NavigationMenu,
113 |   NavigationMenuList,
```

```
  NavigationMenuItem,
  NavigationMenuContent,
  NavigationMenuTrigger,
  NavigationMenuLink,
  NavigationMenuIndicator,
  NavigationMenuViewport,
};

```

28. components/ui/pagination.tsx

Path: src/components/ui/pagination.tsx

```
import * as React from "react";
import { ChevronLeft, ChevronRight, MoreHorizontal } from "lucide-react";

import { cn } from "@/lib/utils";
import { ButtonProps, buttonVariants } from "@/components/ui/button";

const Pagination = ({ className, ...props }: React.ComponentProps<"nav">) => (
  <nav
    role="navigation"
    aria-label="pagination"
    className={cn("mx-auto flex w-full justify-center", className)}
    {...props}
  />
);
Pagination.displayName = "Pagination";

const PaginationContent = React.forwardRef<HTMLUListElement, React.ComponentProps<"ul">>(
  ({ className, ...props }, ref) => (
    <ul ref={ref} className={cn("flex flex-row items-center gap-1", className)} {...props} />
  ),
);
PaginationContent.displayName = "PaginationContent";

const PaginationItem = React.forwardRef<HTMLLIElement, React.ComponentProps<"li">>(({ className, ...props }, ref)
  <li ref={ref} className={cn("", className)} {...props} />
));
PaginationItem.displayName = "PaginationItem";

type PaginationLinkProps = {
  isActive?: boolean;
} & Pick<ButtonProps, "size"> &
  React.ComponentProps<"a">;

const PaginationLink = ({ className, isActive, size = "icon", ...props }: PaginationLinkProps) => (
  <a
    aria-current={isActive ? "page" : undefined}
    className={cn(
      buttonVariants({
        variant: isActive ? "outline" : "ghost",
        size,
```

```
41 |       }),
42 |       className,
43 |     )}
44 |     {...props}
45 |   />
46 | );
47 | PaginationLink.displayName = "PaginationLink";
48 |
49 | const PaginationPrevious = ({ className, ...props }: React.ComponentProps<typeof PaginationLink>) => (
50 |   <PaginationLink aria-label="Go to previous page" size="default" className={cn("gap-1 pl-2.5", className)} {...p
51 |     <ChevronLeft className="h-4 w-4" />
52 |     <span>Previous</span>
53 |   </PaginationLink>
54 | );
55 | PaginationPrevious.displayName = "PaginationPrevious";
56 |
57 | const PaginationNext = ({ className, ...props }: React.ComponentProps<typeof PaginationLink>) => (
58 |   <PaginationLink aria-label="Go to next page" size="default" className={cn("gap-1 pr-2.5", className)} {...props
59 |     <span>Next</span>
60 |     <ChevronRight className="h-4 w-4" />
61 |   </PaginationLink>
62 | );
63 | PaginationNext.displayName = "PaginationNext";
64 |
65 | const PaginationEllipsis = ({ className, ...props }: React.ComponentProps<"span">) => (
66 |   <span aria-hidden className={cn("flex h-9 w-9 items-center justify-center", className)} {...props}>
67 |     <MoreHorizontal className="h-4 w-4" />
68 |     <span className="sr-only">More pages</span>
69 |   </span>
70 | );
71 | PaginationEllipsis.displayName = "PaginationEllipsis";
72 |
73 | export {
74 |   Pagination,
75 |   PaginationContent,
76 |   PaginationEllipsis,
77 |   PaginationItem,
78 |   PaginationLink,
79 |   PaginationNext,
80 |   PaginationPrevious,
81 | };
82 |
```

29. components/ui/popover.tsx

Path: src/components/ui/popover.tsx

```
1 | import * as React from "react";
2 | import * as PopoverPrimitive from "@radix-ui/react-popover";
3 |
4 | import { cn } from "@/lib/utils";
5 |
6 | const Popover = PopoverPrimitive.Root;
```

```
 7 |
 8 | const PopoverTrigger = PopoverPrimitive.Trigger;
 9 |
10 | const PopoverContent = React.forwardRef<
11 |   React.ElementRef<typeof PopoverPrimitive.Content>,
12 |   React.ComponentPropsWithoutRef<typeof PopoverPrimitive.Content>
13 | >(({ className, align = "center", sideOffset = 4, ...props }, ref) => (
14 |   <PopoverPrimitive.Portal>
15 |     <PopoverPrimitive.Content
16 |       ref={ref}
17 |       align={align}
18 |       sideOffset={sideOffset}
19 |       className={cn(
20 |         "z-50 w-72 rounded-md border bg-popover p-4 text-popover-foreground shadow-md outline-none data-[state=op
21 |         className,
22 |       )}
23 |       {...props}
24 |     />
25 |   </PopoverPrimitive.Portal>
26 | ));
27 | PopoverContent.displayName = PopoverPrimitive.Content.displayName;
28 |
29 | export { Popover, PopoverTrigger, PopoverContent };
30 |
```

30. components/ui/progress.tsx

Path: src/components/ui/progress.tsx

```
 1 | import * as React from "react";
 2 | import * as ProgressPrimitive from "@radix-ui/react-progress";
 3 |
 4 | import { cn } from "@/lib/utils";
 5 |
 6 | const Progress = React.forwardRef<
 7 |   React.ElementRef<typeof ProgressPrimitive.Root>,
 8 |   React.ComponentPropsWithoutRef<typeof ProgressPrimitive.Root>
 9 | >(({ className, value, ...props }, ref) => (
10 |   <ProgressPrimitive.Root
11 |     ref={ref}
12 |     className={cn("relative h-4 w-full overflow-hidden rounded-full bg-secondary", className)}
13 |     {...props}
14 |   >
15 |     <ProgressPrimitive.Indicator
16 |       className="h-full w-full flex-1 bg-primary transition-all"
17 |       style={{ transform: `translateX(-${100 - (value || 0)}%)` }}
18 |     />
19 |   </ProgressPrimitive.Root>
20 | ));
21 | Progress.displayName = ProgressPrimitive.Root.displayName;
22 |
23 | export { Progress };
24 |
```

31. components/ui/radio-group.tsx

Path: src/components/ui/radio-group.tsx

```
1 | import * as React from "react";
2 | import * as RadioGroupPrimitive from "@radix-ui/react-radio-group";
3 | import { Circle } from "lucide-react";
4 |
5 | import { cn } from "@/lib/utils";
6 |
7 | const RadioGroup = React.forwardRef<
8 |   React.ElementRef<typeof RadioGroupPrimitive.Root>,
9 |   React.ComponentPropsWithoutRef<typeof RadioGroupPrimitive.Root>
10 | >(({ className, ...props }, ref) => {
11 |   return <RadioGroupPrimitive.Root className={cn("grid gap-2", className)} {...props} ref={ref} />;
12 | });
13 | RadioGroup.displayName = RadioGroupPrimitive.Root.displayName;
14 |
15 | const RadioGroupItem = React.forwardRef<
16 |   React.ElementRef<typeof RadioGroupPrimitive.Item>,
17 |   React.ComponentPropsWithoutRef<typeof RadioGroupPrimitive.Item>
18 | >(({ className, ...props }, ref) => {
19 |   return (
20 |     <RadioGroupPrimitive.Item
21 |       ref={ref}
22 |       className={cn(
23 |         "aspect-square h-4 w-4 rounded-full border border-primary text-primary ring-offset-background focus:outli
24 |         className,
25 |       )}
26 |       {...props}
27 |     >
28 |       <RadioGroupPrimitive.Indicator className="flex items-center justify-center">
29 |         <Circle className="h-2.5 w-2.5 fill-current text-current" />
30 |       </RadioGroupPrimitive.Indicator>
31 |     </RadioGroupPrimitive.Item>
32 |   );
33 | });
34 | RadioGroupItem.displayName = RadioGroupPrimitive.Item.displayName;
35 |
36 | export { RadioGroup, RadioGroupItem };
37 |
```

32. components/ui/resizable.tsx

Path: src/components/ui/resizable.tsx

```
1 | import { GripVertical } from "lucide-react";
2 | import * as ResizablePrimitive from "react-resizable-panels";
3 |
4 | import { cn } from "@/lib/utils";
```

```
 5 |
 6 | const ResizablePanelGroup = ({ className, ...props }: React.ComponentProps<typeof ResizablePrimitive.PanelGroup>)
 7 |   <ResizablePrimitive.PanelGroup
 8 |     className={cn("flex h-full w-full data-[panel-group-direction=vertical]:flex-col", className)}
 9 |     {...props}
10 |   />
11 | );
12 |
13 | const ResizablePanel = ResizablePrimitive.Panel;
14 |
15 | const ResizableHandle = ({
16 |   withHandle,
17 |   className,
18 |   ...props
19 | }: React.ComponentProps<typeof ResizablePrimitive.PanelResizeHandle> & {
20 |   withHandle?: boolean;
21 | }) => (
22 |   <ResizablePrimitive.PanelResizeHandle
23 |     className={cn(
24 |       "relative flex w-px items-center justify-center bg-border after:absolute after:inset-y-0 after:left-1/2 aft
25 |       className,
26 |     )}
27 |     {...props}
28 |   >
29 |     {withHandle && (
30 |       <div className="z-10 flex h-4 w-3 items-center justify-center rounded-sm border bg-border">
31 |         <GripVertical className="h-2.5 w-2.5" />
32 |       </div>
33 |     )}
34 |   </ResizablePrimitive.PanelResizeHandle>
35 | );
36 |
37 | export { ResizablePanelGroup, ResizablePanel, ResizableHandle };
38 |
```

33. components/ui/scroll-area.tsx

Path: src/components/ui/scroll-area.tsx

```
 1 | import * as React from "react";
 2 | import * as ScrollAreaPrimitive from "@radix-ui/react-scroll-area";
 3 |
 4 | import { cn } from "@/lib/utils";
 5 |
 6 | const ScrollArea = React.forwardRef<
 7 |   React.ElementRef<typeof ScrollAreaPrimitive.Root>,
 8 |   React.ComponentPropsWithoutRef<typeof ScrollAreaPrimitive.Root>
 9 | >(({ className, children, ...props }, ref) => (
10 |   <ScrollAreaPrimitive.Root ref={ref} className={cn("relative overflow-hidden", className)} {...props}>
11 |     <ScrollAreaPrimitive.Viewport className="h-full w-full rounded-[inherit]">{children}</ScrollAreaPrimitive.Vie
12 |     <ScrollBar />
13 |     <ScrollAreaPrimitive.Corner />
14 |   </ScrollAreaPrimitive.Root>
```

```
15 | ));
16 | ScrollArea.displayName = ScrollAreaPrimitive.Root.displayName;
17 |
18 | const ScrollBar = React.forwardRef<
19 |   React.ElementRef<typeof ScrollAreaPrimitive.ScrollAreaScrollbar>,
20 |   React.ComponentPropsWithoutRef<typeof ScrollAreaPrimitive.ScrollAreaScrollbar>
21 | >(({ className, orientation = "vertical", ...props }, ref) => (
22 |   <ScrollAreaPrimitive.ScrollAreaScrollbar
23 |     ref={ref}
24 |     orientation={orientation}
25 |     className={cn(
26 |       "flex touch-none select-none transition-colors",
27 |       orientation === "vertical" && "h-full w-2.5 border-l border-l-transparent p-[1px]",
28 |       orientation === "horizontal" && "h-2.5 flex-col border-t border-t-transparent p-[1px]",
29 |       className,
30 |     )}
31 |     {...props}
32 |   >
33 |     <ScrollAreaPrimitive.ScrollAreaThumb className="relative flex-1 rounded-full bg-border" />
34 |   </ScrollAreaPrimitive.ScrollAreaScrollbar>
35 | ));
36 | ScrollBar.displayName = ScrollAreaPrimitive.ScrollAreaScrollbar.displayName;
37 |
38 | export { ScrollArea, ScrollBar };
39 |
```

34. components/ui/select.tsx

Path: src/components/ui/select.tsx

```
1 | import * as React from "react";
2 | import * as SelectPrimitive from "@radix-ui/react-select";
3 | import { Check, ChevronDown, ChevronUp } from "lucide-react";
4 |
5 | import { cn } from "@/lib/utils";
6 |
7 | const Select = SelectPrimitive.Root;
8 |
9 | const SelectGroup = SelectPrimitive.Group;
10 |
11 | const SelectValue = SelectPrimitive.Value;
12 |
13 | const SelectTrigger = React.forwardRef<
14 |   React.ElementRef<typeof SelectPrimitive.Trigger>,
15 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.Trigger>
16 | >(({ className, children, ...props }, ref) => (
17 |   <SelectPrimitive.Trigger
18 |     ref={ref}
19 |     className={cn(
20 |       "flex h-10 w-full items-center justify-between rounded-md border border-input bg-background px-3 py-2 text-
21 |       className,
22 |     )}
23 |     {...props}
```

```
24 |   >
25 |     {children}
26 |     <SelectPrimitive.Icon asChild>
27 |       <ChevronDown className="h-4 w-4 opacity-50" />
28 |     </SelectPrimitive.Icon>
29 |   </SelectPrimitive.Trigger>
30 | ));
31 | SelectTrigger.displayName = SelectPrimitive.Trigger.displayName;
32 |
33 | const SelectScrollUpButton = React.forwardRef<
34 |   React.ElementRef<typeof SelectPrimitive.ScrollUpButton>,
35 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollUpButton>
36 | >(({ className, ...props }, ref) => (
37 |   <SelectPrimitive.ScrollUpButton
38 |     ref={ref}
39 |     className={cn("flex cursor-default items-center justify-center py-1", className)}
40 |     {...props}
41 |   >
42 |     <ChevronUp className="h-4 w-4" />
43 |   </SelectPrimitive.ScrollUpButton>
44 | ));
45 | SelectScrollUpButton.displayName = SelectPrimitive.ScrollUpButton.displayName;
46 |
47 | const SelectScrollDownButton = React.forwardRef<
48 |   React.ElementRef<typeof SelectPrimitive.ScrollDownButton>,
49 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.ScrollDownButton>
50 | >(({ className, ...props }, ref) => (
51 |   <SelectPrimitive.ScrollDownButton
52 |     ref={ref}
53 |     className={cn("flex cursor-default items-center justify-center py-1", className)}
54 |     {...props}
55 |   >
56 |     <ChevronDown className="h-4 w-4" />
57 |   </SelectPrimitive.ScrollDownButton>
58 | ));
59 | SelectScrollDownButton.displayName = SelectPrimitive.ScrollDownButton.displayName;
60 |
61 | const SelectContent = React.forwardRef<
62 |   React.ElementRef<typeof SelectPrimitive.Content>,
63 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.Content>
64 | >(({ className, children, position = "popper", ...props }, ref) => (
65 |   <SelectPrimitive.Portal>
66 |     <SelectPrimitive.Content
67 |       ref={ref}
68 |       className={cn(
69 |         "relative z-50 max-h-96 min-w-[8rem] overflow-hidden rounded-md border bg-popover text-popover-foreground
70 |         position === "popper" &&
71 |           "data-[side=bottom]:translate-y-1 data-[side=left]:-translate-x-1 data-[side=right]:translate-x-1 data-
72 |         className,
73 |       )}
74 |       position={position}
75 |       {...props}
76 |     >
77 |       <SelectScrollUpButton />
```

```
78 |       <SelectPrimitive.Viewport
79 |         className={cn(
80 |           "p-1",
81 |           position === "popper" &&
82 |             "h-[var(--radix-select-trigger-height)] w-full min-w-[var(--radix-select-trigger-width)]",
83 |         )}
84 |       >
85 |         {children}
86 |       </SelectPrimitive.Viewport>
87 |       <SelectScrollDownButton />
88 |     </SelectPrimitive.Content>
89 |   </SelectPrimitive.Portal>
90 | ));
91 | SelectContent.displayName = SelectPrimitive.Content.displayName;
92 |
93 | const SelectLabel = React.forwardRef<
94 |   React.ElementRef<typeof SelectPrimitive.Label>,
95 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.Label>
96 | >(({ className, ...props }, ref) => (
97 |   <SelectPrimitive.Label ref={ref} className={cn("py-1.5 pl-8 pr-2 text-sm font-semibold", className)} {...props}
98 | ));
99 | SelectLabel.displayName = SelectPrimitive.Label.displayName;
100 |
101 | const SelectItem = React.forwardRef<
102 |   React.ElementRef<typeof SelectPrimitive.Item>,
103 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.Item>
104 | >(({ className, children, ...props }, ref) => (
105 |   <SelectPrimitive.Item
106 |     ref={ref}
107 |     className={cn(
108 |       "relative flex w-full cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm outline-n
109 |       className,
110 |     )}
111 |     {...props}
112 |   >
113 |     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
114 |       <SelectPrimitive.ItemIndicator>
115 |         <Check className="h-4 w-4" />
116 |       </SelectPrimitive.ItemIndicator>
117 |     </span>
118 |
119 |     <SelectPrimitive.ItemText>{children}</SelectPrimitive.ItemText>
120 |   </SelectPrimitive.Item>
121 | ));
122 | SelectItem.displayName = SelectPrimitive.Item.displayName;
123 |
124 | const SelectSeparator = React.forwardRef<
125 |   React.ElementRef<typeof SelectPrimitive.Separator>,
126 |   React.ComponentPropsWithoutRef<typeof SelectPrimitive.Separator>
127 | >(({ className, ...props }, ref) => (
128 |   <SelectPrimitive.Separator ref={ref} className={cn("-mx-1 my-1 h-px bg-muted", className)} {...props} />
129 | ));
130 | SelectSeparator.displayName = SelectPrimitive.Separator.displayName;
131 |
```

```
132 | export {
133 |   Select,
134 |   SelectGroup,
135 |   SelectValue,
136 |   SelectTrigger,
137 |   SelectContent,
138 |   SelectLabel,
139 |   SelectItem,
140 |   SelectSeparator,
141 |   SelectScrollUpButton,
142 |   SelectScrollDownButton,
143 | };
144 |
```

35. components/ui/separator.tsx

Path: src/components/ui/separator.tsx

```
1 | import * as React from "react";
2 | import * as SeparatorPrimitive from "@radix-ui/react-separator";
3 |
4 | import { cn } from "@/lib/utils";
5 |
6 | const Separator = React.forwardRef<
7 |   React.ElementRef<typeof SeparatorPrimitive.Root>,
8 |   React.ComponentPropsWithoutRef<typeof SeparatorPrimitive.Root>
9 | >(({ className, orientation = "horizontal", decorative = true, ...props }, ref) => (
10 |   <SeparatorPrimitive.Root
11 |     ref={ref}
12 |     decorative={decorative}
13 |     orientation={orientation}
14 |     className={cn("shrink-0 bg-border", orientation === "horizontal" ? "h-[1px] w-full" : "h-full w-[1px]", class
15 |     {...props}
16 |   />
17 | ));
18 | Separator.displayName = SeparatorPrimitive.Root.displayName;
19 |
20 | export { Separator };
21 |
```

36. components/ui/sheet.tsx

Path: src/components/ui/sheet.tsx

```
1 | import * as SheetPrimitive from "@radix-ui/react-dialog";
2 | import { cva, type VariantProps } from "class-variance-authority";
3 | import { X } from "lucide-react";
4 | import * as React from "react";
5 |
6 | import { cn } from "@/lib/utils";
7 |
```

```
 8 | const Sheet = SheetPrimitive.Root;
 9 |
10 | const SheetTrigger = SheetPrimitive.Trigger;
11 |
12 | const SheetClose = SheetPrimitive.Close;
13 |
14 | const SheetPortal = SheetPrimitive.Portal;
15 |
16 | const SheetOverlay = React.forwardRef<
17 |   React.ElementRef<typeof SheetPrimitive.Overlay>,
18 |   React.ComponentPropsWithoutRef<typeof SheetPrimitive.Overlay>
19 | >(({ className, ...props }, ref) => (
20 |   <SheetPrimitive.Overlay
21 |     className={cn(
22 |       "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=cl
23 |       className,
24 |     )}
25 |     {...props}
26 |     ref={ref}
27 |   />
28 | ));
29 | SheetOverlay.displayName = SheetPrimitive.Overlay.displayName;
30 |
31 | const sheetVariants = cva(
32 |   "fixed z-50 gap-4 bg-background p-6 shadow-lg transition ease-in-out data-[state=open]:animate-in data-[state=c
33 |   {
34 |     variants: {
35 |       side: {
36 |         top: "inset-x-0 top-0 border-b data-[state=closed]:slide-out-to-top data-[state=open]:slide-in-from-top",
37 |         bottom:
38 |           "inset-x-0 bottom-0 border-t data-[state=closed]:slide-out-to-bottom data-[state=open]:slide-in-from-bo
39 |         left: "inset-y-0 left-0 h-full w-3/4 border-r data-[state=closed]:slide-out-to-left data-[state=open]:sli
40 |         right:
41 |           "inset-y-0 right-0 h-full w-3/4  border-l data-[state=closed]:slide-out-to-right data-[state=open]:slid
42 |       },
43 |     },
44 |     defaultVariants: {
45 |       side: "right",
46 |     },
47 |   },
48 | );
49 |
50 | interface SheetContentProps
51 |   extends React.ComponentPropsWithoutRef<typeof SheetPrimitive.Content>,
52 |     VariantProps<typeof sheetVariants> {}
53 |
54 | const SheetContent = React.forwardRef<React.ElementRef<typeof SheetPrimitive.Content>, SheetContentProps>(
55 |   ({ side = "right", className, children, ...props }, ref) => (
56 |     <SheetPortal>
57 |       <SheetOverlay />
58 |       <SheetPrimitive.Content ref={ref} className={cn(sheetVariants({ side }), className)} {...props}>
59 |         {children}
60 |         <SheetPrimitive.Close className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background tran
61 |           <X className="h-4 w-4" />
```

```
62 |           <span className="sr-only">Close</span>
63 |         </SheetPrimitive.Close>
64 |       </SheetPrimitive.Content>
65 |     </SheetPortal>
66 |   ),
67 | );
68 | SheetContent.displayName = SheetPrimitive.Content.displayName;
69 |
70 | const SheetHeader = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
71 |   <div className={cn("flex flex-col space-y-2 text-center sm:text-left", className)} {...props} />
72 | );
73 | SheetHeader.displayName = "SheetHeader";
74 |
75 | const SheetFooter = ({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) => (
76 |   <div className={cn("flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2", className)} {...props} />
77 | );
78 | SheetFooter.displayName = "SheetFooter";
79 |
80 | const SheetTitle = React.forwardRef<
81 |   React.ElementRef<typeof SheetPrimitive.Title>,
82 |   React.ComponentPropsWithoutRef<typeof SheetPrimitive.Title>
83 | >(({ className, ...props }, ref) => (
84 |   <SheetPrimitive.Title ref={ref} className={cn("text-lg font-semibold text-foreground", className)} {...props} /
85 | ));
86 | SheetTitle.displayName = SheetPrimitive.Title.displayName;
87 |
88 | const SheetDescription = React.forwardRef<
89 |   React.ElementRef<typeof SheetPrimitive.Description>,
90 |   React.ComponentPropsWithoutRef<typeof SheetPrimitive.Description>
91 | >(({ className, ...props }, ref) => (
92 |   <SheetPrimitive.Description ref={ref} className={cn("text-sm text-muted-foreground", className)} {...props} />
93 | ));
94 | SheetDescription.displayName = SheetPrimitive.Description.displayName;
95 |
96 | export {
97 |   Sheet,
98 |   SheetClose,
99 |   SheetContent,
100 |   SheetDescription,
101 |   SheetFooter,
102 |   SheetHeader,
103 |   SheetOverlay,
104 |   SheetPortal,
105 |   SheetTitle,
106 |   SheetTrigger,
107 | };
108 |
```

37. components/ui/sidebar.tsx

Path: src/components/ui/sidebar.tsx

```
1 | import * as React from "react";
```

```
 2 | import { Slot } from "@radix-ui/react-slot";
 3 | import { VariantProps, cva } from "class-variance-authority";
 4 | import { PanelLeft } from "lucide-react";
 5 |
 6 | import { useIsMobile } from "@/hooks/use-mobile";
 7 | import { cn } from "@/lib/utils";
 8 | import { Button } from "@/components/ui/button";
 9 | import { Input } from "@/components/ui/input";
10 | import { Separator } from "@/components/ui/separator";
11 | import { Sheet, SheetContent } from "@/components/ui/sheet";
12 | import { Skeleton } from "@/components/ui/skeleton";
13 | import { Tooltip, TooltipContent, TooltipProvider, TooltipTrigger } from "@/components/ui/tooltip";
14 |
15 | const SIDEBAR_COOKIE_NAME = "sidebar:state";
16 | const SIDEBAR_COOKIE_MAX_AGE = 60 * 60 * 24 * 7;
17 | const SIDEBAR_WIDTH = "16rem";
18 | const SIDEBAR_WIDTH_MOBILE = "18rem";
19 | const SIDEBAR_WIDTH_ICON = "3rem";
20 | const SIDEBAR_KEYBOARD_SHORTCUT = "b";
21 |
22 | type SidebarContext = {
23 |   state: "expanded" | "collapsed";
24 |   open: boolean;
25 |   setOpen: (open: boolean) => void;
26 |   openMobile: boolean;
27 |   setOpenMobile: (open: boolean) => void;
28 |   isMobile: boolean;
29 |   toggleSidebar: () => void;
30 | };
31 |
32 | const SidebarContext = React.createContext<SidebarContext | null>(null);
33 |
34 | function useSidebar() {
35 |   const context = React.useContext(SidebarContext);
36 |   if (!context) {
37 |     throw new Error("useSidebar must be used within a SidebarProvider.");
38 |   }
39 |
40 |   return context;
41 | }
42 |
43 | const SidebarProvider = React.forwardRef<
44 |   HTMLDivElement,
45 |   React.ComponentProps<"div"> & {
46 |     defaultOpen?: boolean;
47 |     open?: boolean;
48 |     onOpenChange?: (open: boolean) => void;
49 |   }
50 | >(({ defaultOpen = true, open: openProp, onOpenChange: setOpenProp, className, style, children, ...props }, ref)
51 |   const isMobile = useIsMobile();
52 |   const [openMobile, setOpenMobile] = React.useState(false);
53 |
54 |   // This is the internal state of the sidebar.
55 |   // We use openProp and setOpenProp for control from outside the component.
```

```
56 |   const [_open, _setOpen] = React.useState(defaultOpen);
57 |   const open = openProp ?? _open;
58 |   const setOpen = React.useCallback(
59 |     (value: boolean | ((value: boolean) => boolean)) => {
60 |       const openState = typeof value === "function" ? value(open) : value;
61 |       if (setOpenProp) {
62 |         setOpenProp(openState);
63 |       } else {
64 |         _setOpen(openState);
65 |       }
66 |
67 |       // This sets the cookie to keep the sidebar state.
68 |       document.cookie = `${SIDEBAR_COOKIE_NAME}=${openState}; path=/; max-age=${SIDEBAR_COOKIE_MAX_AGE}`;
69 |     },
70 |     [setOpenProp, open],
71 |   );
72 |
73 |   // Helper to toggle the sidebar.
74 |   const toggleSidebar = React.useCallback(() => {
75 |     return isMobile ? setOpenMobile((open) => !open) : setOpen((open) => !open);
76 |   }, [isMobile, setOpen, setOpenMobile]);
77 |
78 |   // Adds a keyboard shortcut to toggle the sidebar.
79 |   React.useEffect(() => {
80 |     const handleKeyDown = (event: KeyboardEvent) => {
81 |       if (event.key === SIDEBAR_KEYBOARD_SHORTCUT && (event.metaKey || event.ctrlKey)) {
82 |         event.preventDefault();
83 |         toggleSidebar();
84 |       }
85 |     };
86 |
87 |     window.addEventListener("keydown", handleKeyDown);
88 |     return () => window.removeEventListener("keydown", handleKeyDown);
89 |   }, [toggleSidebar]);
90 |
91 |   // We add a state so that we can do data-state="expanded" or "collapsed".
92 |   // This makes it easier to style the sidebar with Tailwind classes.
93 |   const state = open ? "expanded" : "collapsed";
94 |
95 |   const contextValue = React.useMemo<SidebarContext>(
96 |     () => ({
97 |       state,
98 |       open,
99 |       setOpen,
100 |       isMobile,
101 |       openMobile,
102 |       setOpenMobile,
103 |       toggleSidebar,
104 |     }),
105 |     [state, open, setOpen, isMobile, openMobile, setOpenMobile, toggleSidebar],
106 |   );
107 |
108 |   return (
109 |     <SidebarContext.Provider value={contextValue}>
```

```
110 |       <TooltipProvider delayDuration={0}>
111 |         <div
112 |           style={
113 |             {
114 |               "--sidebar-width": SIDEBAR_WIDTH,
115 |               "--sidebar-width-icon": SIDEBAR_WIDTH_ICON,
116 |               ...style,
117 |             } as React.CSSProperties
118 |           }
119 |           className={cn("group/sidebar-wrapper flex min-h-svh w-full has-[[data-variant=inset]]:bg-sidebar", clas
120 |           ref={ref}
121 |           {...props}
122 |         >
123 |           {children}
124 |         </div>
125 |       </TooltipProvider>
126 |     </SidebarContext.Provider>
127 |   );
128 | });
129 | SidebarProvider.displayName = "SidebarProvider";
130 |
131 | const Sidebar = React.forwardRef<
132 |   HTMLDivElement,
133 |   React.ComponentProps<"div"> & {
134 |     side?: "left" | "right";
135 |     variant?: "sidebar" | "floating" | "inset";
136 |     collapsible?: "offcanvas" | "icon" | "none";
137 |   }
138 | >(({ side = "left", variant = "sidebar", collapsible = "offcanvas", className, children, ...props }, ref) => {
139 |   const { isMobile, state, openMobile, setOpenMobile } = useSidebar();
140 |
141 |   if (collapsible === "none") {
142 |     return (
143 |       <div
144 |         className={cn("flex h-full w-[--sidebar-width] flex-col bg-sidebar text-sidebar-foreground", className)}
145 |         ref={ref}
146 |         {...props}
147 |       >
148 |         {children}
149 |       </div>
150 |     );
151 |   }
152 |
153 |   if (isMobile) {
154 |     return (
155 |       <Sheet open={openMobile} onOpenChange={setOpenMobile} {...props}>
156 |         <SheetContent
157 |           data-sidebar="sidebar"
158 |           data-mobile="true"
159 |           className="w-[--sidebar-width] bg-sidebar p-0 text-sidebar-foreground [&>button]:hidden"
160 |           style={
161 |             {
162 |               "--sidebar-width": SIDEBAR_WIDTH_MOBILE,
163 |             } as React.CSSProperties
```

```
164 |          }
165 |          side={side}
166 |        >
167 |          <div className="flex h-full w-full flex-col">{children}</div>
168 |        </SheetContent>
169 |      </Sheet>
170 |    );
171 |  }
172 |
173 |  return (
174 |    <div
175 |      ref={ref}
176 |      className="group peer hidden text-sidebar-foreground md:block"
177 |      data-state={state}
178 |      data-collapsible={state === "collapsed" ? collapsible : ""}
179 |      data-variant={variant}
180 |      data-side={side}
181 |    >
182 |      {/* This is what handles the sidebar gap on desktop */}
183 |      <div
184 |        className={cn(
185 |          "relative h-svh w-[--sidebar-width] bg-transparent transition-[width] duration-200 ease-linear",
186 |          "group-data-[collapsible=offcanvas]:w-0",
187 |          "group-data-[side=right]:rotate-180",
188 |          variant === "floating" || variant === "inset"
189 |            ? "group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-icon)_+_theme(spacing.4))]"
190 |            : "group-data-[collapsible=icon]:w-[--sidebar-width-icon]",
191 |        )}
192 |      />
193 |      <div
194 |        className={cn(
195 |          "fixed inset-y-0 z-10 hidden h-svh w-[--sidebar-width] transition-[left,right,width] duration-200 ease-
196 |          side === "left"
197 |            ? "left-0 group-data-[collapsible=offcanvas]:left-[calc(var(--sidebar-width)*-1)]"
198 |            : "right-0 group-data-[collapsible=offcanvas]:right-[calc(var(--sidebar-width)*-1)]",
199 |          // Adjust the padding for floating and inset variants.
200 |          variant === "floating" || variant === "inset"
201 |            ? "p-2 group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-icon)_+_theme(spacing.4)_+2px)]"
202 |            : "group-data-[collapsible=icon]:w-[--sidebar-width-icon] group-data-[side=left]:border-r group-data-
203 |          className,
204 |        )}
205 |        {...props}
206 |      >
207 |        <div
208 |          data-sidebar="sidebar"
209 |          className="flex h-full w-full flex-col bg-sidebar group-data-[variant=floating]:rounded-lg group-data-[
210 |        >
211 |          {children}
212 |        </div>
213 |      </div>
214 |    </div>
215 |  );
216 | });
217 | Sidebar.displayName = "Sidebar";
```

```
218 |
219 | const SidebarTrigger = React.forwardRef<React.ElementRef<typeof Button>, React.ComponentProps<typeof Button>>(
220 |   ({ className, onClick, ...props }, ref) => {
221 |     const { toggleSidebar } = useSidebar();
222 |
223 |     return (
224 |       <Button
225 |         ref={ref}
226 |         data-sidebar="trigger"
227 |         variant="ghost"
228 |         size="icon"
229 |         className={cn("h-7 w-7", className)}
230 |         onClick={(event) => {
231 |           onClick?.(event);
232 |           toggleSidebar();
233 |         }}
234 |         {...props}
235 |       >
236 |         <PanelLeft />
237 |         <span className="sr-only">Toggle Sidebar</span>
238 |       </Button>
239 |     );
240 |   },
241 | );
242 | SidebarTrigger.displayName = "SidebarTrigger";
243 |
244 | const SidebarRail = React.forwardRef<HTMLButtonElement, React.ComponentProps<"button">>(
245 |   ({ className, ...props }, ref) => {
246 |     const { toggleSidebar } = useSidebar();
247 |
248 |     return (
249 |       <button
250 |         ref={ref}
251 |         data-sidebar="rail"
252 |         aria-label="Toggle Sidebar"
253 |         tabIndex={-1}
254 |         onClick={toggleSidebar}
255 |         title="Toggle Sidebar"
256 |         className={cn(
257 |           "absolute inset-y-0 z-20 hidden w-4 -translate-x-1/2 transition-all ease-linear after:absolute after:in
258 |           "[[data-side=left]_&]:cursor-w-resize [[data-side=right]_&]:cursor-e-resize",
259 |           "[[data-side=left][data-state=collapsed]_&]:cursor-e-resize [[data-side=right][data-state=collapsed]_&]
260 |           "group-data-[collapsible=offcanvas]:translate-x-0 group-data-[collapsible=offcanvas]:after:left-full gr
261 |           "[[data-side=left][data-collapsible=offcanvas]_&]:-right-2",
262 |           "[[data-side=right][data-collapsible=offcanvas]_&]:-left-2",
263 |           className,
264 |         )}
265 |         {...props}
266 |       />
267 |     );
268 |   },
269 | );
270 | SidebarRail.displayName = "SidebarRail";
271 |
```

```
272 | const SidebarInset = React.forwardRef<HTMLDivElement, React.ComponentProps<"main">>(({ className, ...props }, ref
273 |   return (
274 |     <main
275 |       ref={ref}
276 |       className={cn(
277 |         "relative flex min-h-svh flex-1 flex-col bg-background",
278 |         "peer-data-[variant=inset]:min-h-[calc(100svh-theme(spacing.4))] md:peer-data-[variant=inset]:m-2 md:peer
279 |         className,
280 |       )}
281 |       {...props}
282 |     />
283 |   );
284 | });
285 | SidebarInset.displayName = "SidebarInset";
286 |
287 | const SidebarInput = React.forwardRef<React.ElementRef<typeof Input>, React.ComponentProps<typeof Input>>(
288 |   ({ className, ...props }, ref) => {
289 |     return (
290 |       <Input
291 |         ref={ref}
292 |         data-sidebar="input"
293 |         className={cn(
294 |           "h-8 w-full bg-background shadow-none focus-visible:ring-2 focus-visible:ring-sidebar-ring",
295 |           className,
296 |         )}
297 |         {...props}
298 |       />
299 |     );
300 |   },
301 | );
302 | SidebarInput.displayName = "SidebarInput";
303 |
304 | const SidebarHeader = React.forwardRef<HTMLDivElement, React.ComponentProps<"div">>(({ className, ...props }, ref
305 |   return <div ref={ref} data-sidebar="header" className={cn("flex flex-col gap-2 p-2", className)} {...props} />;
306 | });
307 | SidebarHeader.displayName = "SidebarHeader";
308 |
309 | const SidebarFooter = React.forwardRef<HTMLDivElement, React.ComponentProps<"div">>(({ className, ...props }, ref
310 |   return <div ref={ref} data-sidebar="footer" className={cn("flex flex-col gap-2 p-2", className)} {...props} />;
311 | });
312 | SidebarFooter.displayName = "SidebarFooter";
313 |
314 | const SidebarSeparator = React.forwardRef<React.ElementRef<typeof Separator>, React.ComponentProps<typeof Separat
315 |   ({ className, ...props }, ref) => {
316 |     return (
317 |       <Separator
318 |         ref={ref}
319 |         data-sidebar="separator"
320 |         className={cn("mx-2 w-auto bg-sidebar-border", className)}
321 |         {...props}
322 |       />
323 |     );
324 |   },
325 | );
```

```
326 | SidebarSeparator.displayName = "SidebarSeparator";
327 |
328 | const SidebarContent = React.forwardRef<HTMLDivElement, React.ComponentProps<"div">>(({ className, ...props }, re
329 |   return (
330 |     <div
331 |       ref={ref}
332 |       data-sidebar="content"
333 |       className={cn(
334 |         "flex min-h-0 flex-1 flex-col gap-2 overflow-auto group-data-[collapsible=icon]:overflow-hidden",
335 |         className,
336 |       )}
337 |       {...props}
338 |     />
339 |   );
340 | });
341 | SidebarContent.displayName = "SidebarContent";
342 |
343 | const SidebarGroup = React.forwardRef<HTMLDivElement, React.ComponentProps<"div">>(({ className, ...props }, ref)
344 |   return (
345 |     <div
346 |       ref={ref}
347 |       data-sidebar="group"
348 |       className={cn("relative flex w-full min-w-0 flex-col p-2", className)}
349 |       {...props}
350 |     />
351 |   );
352 | });
353 | SidebarGroup.displayName = "SidebarGroup";
354 |
355 | const SidebarGroupLabel = React.forwardRef<HTMLDivElement, React.ComponentProps<"div"> & { asChild?: boolean }>(
356 |   ({ className, asChild = false, ...props }, ref) => {
357 |     const Comp = asChild ? Slot : "div";
358 |
359 |     return (
360 |       <Comp
361 |         ref={ref}
362 |         data-sidebar="group-label"
363 |         className={cn(
364 |           "flex h-8 shrink-0 items-center rounded-md px-2 text-xs font-medium text-sidebar-foreground/70 outline-
365 |           "group-data-[collapsible=icon]:-mt-8 group-data-[collapsible=icon]:opacity-0",
366 |           className,
367 |         )}
368 |         {...props}
369 |       />
370 |     );
371 |   },
372 | );
373 | SidebarGroupLabel.displayName = "SidebarGroupLabel";
374 |
375 | const SidebarGroupAction = React.forwardRef<HTMLButtonElement, React.ComponentProps<"button"> & { asChild?: boole
376 |   ({ className, asChild = false, ...props }, ref) => {
377 |     const Comp = asChild ? Slot : "button";
378 |
379 |     return (
```

```
380 |       <Comp
381 |         ref={ref}
382 |         data-sidebar="group-action"
383 |         className={cn(
384 |           "absolute right-3 top-3.5 flex aspect-square w-5 items-center justify-center rounded-md p-0 text-sideba
385 |           // Increases the hit area of the button on mobile.
386 |           "after:absolute after:-inset-2 after:md:hidden",
387 |           "group-data-[collapsible=icon]:hidden",
388 |           className,
389 |         )}
390 |         {...props}
391 |       />
392 |     );
393 |   },
394 | );
395 | SidebarGroupAction.displayName = "SidebarGroupAction";
396 |
397 | const SidebarGroupContent = React.forwardRef<HTMLDivElement, React.ComponentProps<"div">>(
398 |   ({ className, ...props }, ref) => (
399 |     <div ref={ref} data-sidebar="group-content" className={cn("w-full text-sm", className)} {...props} />
400 |   ),
401 | );
402 | SidebarGroupContent.displayName = "SidebarGroupContent";
403 |
404 | const SidebarMenu = React.forwardRef<HTMLUListElement, React.ComponentProps<"ul">>(({ className, ...props }, ref)
405 |   <ul ref={ref} data-sidebar="menu" className={cn("flex w-full min-w-0 flex-col gap-1", className)} {...props} />
406 | ));
407 | SidebarMenu.displayName = "SidebarMenu";
408 |
409 | const SidebarMenuItem = React.forwardRef<HTMLLIElement, React.ComponentProps<"li">>(({ className, ...props }, ref
410 |   <li ref={ref} data-sidebar="menu-item" className={cn("group/menu-item relative", className)} {...props} />
411 | ));
412 | SidebarMenuItem.displayName = "SidebarMenuItem";
413 |
414 | const sidebarMenuButtonVariants = cva(
415 |   "peer/menu-button flex w-full items-center gap-2 overflow-hidden rounded-md p-2 text-left text-sm outline-none
416 |   {
417 |     variants: {
418 |       variant: {
419 |         default: "hover:bg-sidebar-accent hover:text-sidebar-accent-foreground",
420 |         outline:
421 |           "bg-background shadow-[0_0_0_1px_hsl(var(--sidebar-border))] hover:bg-sidebar-accent hover:text-sidebar
422 |       },
423 |       size: {
424 |         default: "h-8 text-sm",
425 |         sm: "h-7 text-xs",
426 |         lg: "h-12 text-sm group-data-[collapsible=icon]:!p-0",
427 |       },
428 |     },
429 |     defaultVariants: {
430 |       variant: "default",
431 |       size: "default",
432 |     },
433 |   },
```

```
434 | );
435 |
436 | const SidebarMenuButton = React.forwardRef<
437 |   HTMLButtonElement,
438 |   React.ComponentProps<"button"> & {
439 |     asChild?: boolean;
440 |     isActive?: boolean;
441 |     tooltip?: string | React.ComponentProps<typeof TooltipContent>;
442 |   } & VariantProps<typeof sidebarMenuButtonVariants>
443 | >(({ asChild = false, isActive = false, variant = "default", size = "default", tooltip, className, ...props }, re
444 |   const Comp = asChild ? Slot : "button";
445 |   const { isMobile, state } = useSidebar();
446 |
447 |   const button = (
448 |     <Comp
449 |       ref={ref}
450 |       data-sidebar="menu-button"
451 |       data-size={size}
452 |       data-active={isActive}
453 |       className={cn(sidebarMenuButtonVariants({ variant, size }), className)}
454 |       {...props}
455 |     />
456 |   );
457 |
458 |   if (!tooltip) {
459 |     return button;
460 |   }
461 |
462 |   if (typeof tooltip === "string") {
463 |     tooltip = {
464 |       children: tooltip,
465 |     };
466 |   }
467 |
468 |   return (
469 |     <Tooltip>
470 |       <TooltipTrigger asChild>{button}</TooltipTrigger>
471 |       <TooltipContent side="right" align="center" hidden={state !== "collapsed" || isMobile} {...tooltip} />
472 |     </Tooltip>
473 |   );
474 | });
475 | SidebarMenuButton.displayName = "SidebarMenuButton";
476 |
477 | const SidebarMenuAction = React.forwardRef<
478 |   HTMLButtonElement,
479 |   React.ComponentProps<"button"> & {
480 |     asChild?: boolean;
481 |     showOnHover?: boolean;
482 |   }
483 | >(({ className, asChild = false, showOnHover = false, ...props }, ref) => {
484 |   const Comp = asChild ? Slot : "button";
485 |
486 |   return (
487 |     <Comp
```

```
488 |       ref={ref}
489 |       data-sidebar="menu-action"
490 |       className={cn(
491 |         "absolute right-1 top-1.5 flex aspect-square w-5 items-center justify-center rounded-md p-0 text-sidebar-
492 |         // Increases the hit area of the button on mobile.
493 |         "after:absolute after:-inset-2 after:md:hidden",
494 |         "peer-data-[size=sm]/menu-button:top-1",
495 |         "peer-data-[size=default]/menu-button:top-1.5",
496 |         "peer-data-[size=lg]/menu-button:top-2.5",
497 |         "group-data-[collapsible=icon]:hidden",
498 |         showOnHover &&
499 |           "group-focus-within/menu-item:opacity-100 group-hover/menu-item:opacity-100 data-[state=open]:opacity-1
500 |         className,
501 |       )}
502 |       {...props}
503 |     />
504 |   );
505 | });
506 | SidebarMenuAction.displayName = "SidebarMenuAction";
507 |
508 | const SidebarMenuBadge = React.forwardRef<HTMLDivElement, React.ComponentProps<"div">>(
509 |   ({ className, ...props }, ref) => (
510 |     <div
511 |       ref={ref}
512 |       data-sidebar="menu-badge"
513 |       className={cn(
514 |         "pointer-events-none absolute right-1 flex h-5 min-w-5 select-none items-center justify-center rounded-md
515 |         "peer-hover/menu-button:text-sidebar-accent-foreground peer-data-[active=true]/menu-button:text-sidebar-a
516 |         "peer-data-[size=sm]/menu-button:top-1",
517 |         "peer-data-[size=default]/menu-button:top-1.5",
518 |         "peer-data-[size=lg]/menu-button:top-2.5",
519 |         "group-data-[collapsible=icon]:hidden",
520 |         className,
521 |       )}
522 |       {...props}
523 |     />
524 |   ),
525 | );
526 | SidebarMenuBadge.displayName = "SidebarMenuBadge";
527 |
528 | const SidebarMenuSkeleton = React.forwardRef<
529 |   HTMLDivElement,
530 |   React.ComponentProps<"div"> & {
531 |     showIcon?: boolean;
532 |   }
533 | >(({ className, showIcon = false, ...props }, ref) => {
534 |   // Random width between 50 to 90%.
535 |   const width = React.useMemo(() => {
536 |     return `${Math.floor(Math.random() * 40) + 50}%`;
537 |   }, []);
538 |
539 |   return (
540 |     <div
541 |       ref={ref}
```

```
542 |       data-sidebar="menu-skeleton"
543 |       className={cn("flex h-8 items-center gap-2 rounded-md px-2", className)}
544 |       {...props}
545 |     >
546 |       {showIcon && <Skeleton className="size-4 rounded-md" data-sidebar="menu-skeleton-icon" />}
547 |       <Skeleton
548 |         className="h-4 max-w-[--skeleton-width] flex-1"
549 |         data-sidebar="menu-skeleton-text"
550 |         style={
551 |           {
552 |             "--skeleton-width": width,
553 |           } as React.CSSProperties
554 |         }
555 |       />
556 |     </div>
557 |   );
558 | });
559 | SidebarMenuSkeleton.displayName = "SidebarMenuSkeleton";
560 |
561 | const SidebarMenuSub = React.forwardRef<HTMLUListElement, React.ComponentProps<"ul">>(
562 |   ({ className, ...props }, ref) => (
563 |     <ul
564 |       ref={ref}
565 |       data-sidebar="menu-sub"
566 |       className={cn(
567 |         "mx-3.5 flex min-w-0 translate-x-px flex-col gap-1 border-l border-sidebar-border px-2.5 py-0.5",
568 |         "group-data-[collapsible=icon]:hidden",
569 |         className,
570 |       )}
571 |       {...props}
572 |     />
573 |   ),
574 | );
575 | SidebarMenuSub.displayName = "SidebarMenuSub";
576 |
577 | const SidebarMenuSubItem = React.forwardRef<HTMLLIElement, React.ComponentProps<"li">>(({ ...props }, ref) => (
578 |   <li ref={ref} {...props} />
579 | ));
580 | SidebarMenuSubItem.displayName = "SidebarMenuSubItem";
581 |
582 | const SidebarMenuSubButton = React.forwardRef<
583 |   HTMLAnchorElement,
584 |   React.ComponentProps<"a"> & {
585 |     asChild?: boolean;
586 |     size?: "sm" | "md";
587 |     isActive?: boolean;
588 |   }
589 | >(({ asChild = false, size = "md", isActive, className, ...props }, ref) => {
590 |   const Comp = asChild ? Slot : "a";
591 |
592 |   return (
593 |     <Comp
594 |       ref={ref}
595 |       data-sidebar="menu-sub-button"
```

```
596 |       data-size={size}
597 |       data-active={isActive}
598 |       className={cn(
599 |         "flex h-7 min-w-0 -translate-x-px items-center gap-2 overflow-hidden rounded-md px-2 text-sidebar-foregro
600 |         "data-[active=true]:bg-sidebar-accent data-[active=true]:text-sidebar-accent-foreground",
601 |         size === "sm" && "text-xs",
602 |         size === "md" && "text-sm",
603 |         "group-data-[collapsible=icon]:hidden",
604 |         className,
605 |       )}
606 |       {...props}
607 |     />
608 |   );
609 | });
610 | SidebarMenuSubButton.displayName = "SidebarMenuSubButton";
611 |
612 | export {
613 |   Sidebar,
614 |   SidebarContent,
615 |   SidebarFooter,
616 |   SidebarGroup,
617 |   SidebarGroupAction,
618 |   SidebarGroupContent,
619 |   SidebarGroupLabel,
620 |   SidebarHeader,
621 |   SidebarInput,
622 |   SidebarInset,
623 |   SidebarMenu,
624 |   SidebarMenuAction,
625 |   SidebarMenuBadge,
626 |   SidebarMenuButton,
627 |   SidebarMenuItem,
628 |   SidebarMenuSkeleton,
629 |   SidebarMenuSub,
630 |   SidebarMenuSubButton,
631 |   SidebarMenuSubItem,
632 |   SidebarProvider,
633 |   SidebarRail,
634 |   SidebarSeparator,
635 |   SidebarTrigger,
636 |   useSidebar,
637 | };
638 |
```

38. components/ui/skeleton.tsx

Path: src/components/ui/skeleton.tsx

```
1 | import { cn } from "@/lib/utils";
2 |
3 | function Skeleton({ className, ...props }: React.HTMLAttributes<HTMLDivElement>) {
4 |   return <div className={cn("animate-pulse rounded-md bg-muted", className)} {...props} />;
5 | }
```

```
 6 |
 7 | export { Skeleton };
 8 |
```

39. components/ui/slider.tsx

Path: src/components/ui/slider.tsx

```
 1 | import * as React from "react";
 2 | import * as SliderPrimitive from "@radix-ui/react-slider";
 3 |
 4 | import { cn } from "@/lib/utils";
 5 |
 6 | const Slider = React.forwardRef<
 7 |   React.ElementRef<typeof SliderPrimitive.Root>,
 8 |   React.ComponentPropsWithoutRef<typeof SliderPrimitive.Root>
 9 | >(({ className, ...props }, ref) => (
10 |   <SliderPrimitive.Root
11 |     ref={ref}
12 |     className={cn("relative flex w-full touch-none select-none items-center", className)}
13 |     {...props}
14 |   >
15 |     <SliderPrimitive.Track className="relative h-2 w-full grow overflow-hidden rounded-full bg-secondary">
16 |       <SliderPrimitive.Range className="absolute h-full bg-primary" />
17 |     </SliderPrimitive.Track>
18 |     <SliderPrimitive.Thumb className="block h-5 w-5 rounded-full border-2 border-primary bg-background ring-offse
19 |   </SliderPrimitive.Root>
20 | ));
21 | Slider.displayName = SliderPrimitive.Root.displayName;
22 |
23 | export { Slider };
24 |
```

40. components/ui/sonner.tsx

Path: src/components/ui/sonner.tsx

```
 1 | import { useTheme } from "next-themes";
 2 | import { Toaster as Sonner, toast } from "sonner";
 3 |
 4 | type ToasterProps = React.ComponentProps<typeof Sonner>;
 5 |
 6 | const Toaster = ({ ...props }: ToasterProps) => {
 7 |   const { theme = "system" } = useTheme();
 8 |
 9 |   return (
10 |     <Sonner
11 |       theme={theme as ToasterProps["theme"]}
12 |       className="toaster group"
13 |       toastOptions={{
14 |         classNames: {
```

```
15 |          toast:
16 |            "group toast group-[.toaster]:bg-background group-[.toaster]:text-foreground group-[.toaster]:border-
17 |          description: "group-[.toast]:text-muted-foreground",
18 |          actionButton: "group-[.toast]:bg-primary group-[.toast]:text-primary-foreground",
19 |          cancelButton: "group-[.toast]:bg-muted group-[.toast]:text-muted-foreground",
20 |        },
21 |      }}
22 |      {...props}
23 |    />
24 |  );
25 | };
26 |
27 | export { Toaster, toast };
28 |
```

41. components/ui/switch.tsx

Path: src/components/ui/switch.tsx

```
1 | import * as React from "react";
2 | import * as SwitchPrimitives from "@radix-ui/react-switch";
3 |
4 | import { cn } from "@/lib/utils";
5 |
6 | const Switch = React.forwardRef<
7 |   React.ElementRef<typeof SwitchPrimitives.Root>,
8 |   React.ComponentPropsWithoutRef<typeof SwitchPrimitives.Root>
9 | >(({ className, ...props }, ref) => (
10 |   <SwitchPrimitives.Root
11 |     className={cn(
12 |       "peer inline-flex h-6 w-11 shrink-0 cursor-pointer items-center rounded-full border-2 border-transparent tr
13 |       className,
14 |     )}
15 |     {...props}
16 |     ref={ref}
17 |   >
18 |     <SwitchPrimitives.Thumb
19 |       className={cn(
20 |         "pointer-events-none block h-5 w-5 rounded-full bg-background shadow-lg ring-0 transition-transform data-
21 |       )}
22 |     />
23 |   </SwitchPrimitives.Root>
24 | ));
25 | Switch.displayName = SwitchPrimitives.Root.displayName;
26 |
27 | export { Switch };
28 |
```

42. components/ui/table.tsx

Path: src/components/ui/table.tsx

```
 1 | import * as React from "react";
 2 |
 3 | import { cn } from "@/lib/utils";
 4 |
 5 | const Table = React.forwardRef<HTMLTableElement, React.HTMLAttributes<HTMLTableElement>>(
 6 |   ({ className, ...props }, ref) => (
 7 |     <div className="relative w-full overflow-auto">
 8 |       <table ref={ref} className={cn("w-full caption-bottom text-sm", className)} {...props} />
 9 |     </div>
10 |   ),
11 | );
12 | Table.displayName = "Table";
13 |
14 | const TableHeader = React.forwardRef<HTMLTableSectionElement, React.HTMLAttributes<HTMLTableSectionElement>>(
15 |   ({ className, ...props }, ref) => <thead ref={ref} className={cn("[&_tr]:border-b", className)} {...props} />,
16 | );
17 | TableHeader.displayName = "TableHeader";
18 |
19 | const TableBody = React.forwardRef<HTMLTableSectionElement, React.HTMLAttributes<HTMLTableSectionElement>>(
20 |   ({ className, ...props }, ref) => (
21 |     <tbody ref={ref} className={cn("[&_tr:last-child]:border-0", className)} {...props} />
22 |   ),
23 | );
24 | TableBody.displayName = "TableBody";
25 |
26 | const TableFooter = React.forwardRef<HTMLTableSectionElement, React.HTMLAttributes<HTMLTableSectionElement>>(
27 |   ({ className, ...props }, ref) => (
28 |     <tfoot ref={ref} className={cn("border-t bg-muted/50 font-medium [&>tr]:last:border-b-0", className)} {...pro
29 |   ),
30 | );
31 | TableFooter.displayName = "TableFooter";
32 |
33 | const TableRow = React.forwardRef<HTMLTableRowElement, React.HTMLAttributes<HTMLTableRowElement>>(
34 |   ({ className, ...props }, ref) => (
35 |     <tr
36 |       ref={ref}
37 |       className={cn("border-b transition-colors data-[state=selected]:bg-muted hover:bg-muted/50", className)}
38 |       {...props}
39 |     />
40 |   ),
41 | );
42 | TableRow.displayName = "TableRow";
43 |
44 | const TableHead = React.forwardRef<HTMLTableCellElement, React.ThHTMLAttributes<HTMLTableCellElement>>(
45 |   ({ className, ...props }, ref) => (
46 |     <th
47 |       ref={ref}
48 |       className={cn(
49 |         "h-12 px-4 text-left align-middle font-medium text-muted-foreground [&:has([role=checkbox])]:pr-0",
50 |         className,
51 |       )}
52 |       {...props}
53 |     />
```

```
54 |   ),
55 | );
56 | TableHead.displayName = "TableHead";
57 |
58 | const TableCell = React.forwardRef<HTMLTableCellElement, React.TdHTMLAttributes<HTMLTableCellElement>>(
59 |   ({ className, ...props }, ref) => (
60 |     <td ref={ref} className={cn("p-4 align-middle [&:has([role=checkbox])]:pr-0", className)} {...props} />
61 |   ),
62 | );
63 | TableCell.displayName = "TableCell";
64 |
65 | const TableCaption = React.forwardRef<HTMLTableCaptionElement, React.HTMLAttributes<HTMLTableCaptionElement>>(
66 |   ({ className, ...props }, ref) => (
67 |     <caption ref={ref} className={cn("mt-4 text-sm text-muted-foreground", className)} {...props} />
68 |   ),
69 | );
70 | TableCaption.displayName = "TableCaption";
71 |
72 | export { Table, TableHeader, TableBody, TableFooter, TableHead, TableRow, TableCell, TableCaption };
73 |
```

43. components/ui/tabs.tsx

Path: src/components/ui/tabs.tsx

```
1 | import * as React from "react";
2 | import * as TabsPrimitive from "@radix-ui/react-tabs";
3 |
4 | import { cn } from "@/lib/utils";
5 |
6 | const Tabs = TabsPrimitive.Root;
7 |
8 | const TabsList = React.forwardRef<
9 |   React.ElementRef<typeof TabsPrimitive.List>,
10 |   React.ComponentPropsWithoutRef<typeof TabsPrimitive.List>
11 | >(({ className, ...props }, ref) => (
12 |   <TabsPrimitive.List
13 |     ref={ref}
14 |     className={cn(
15 |       "inline-flex h-10 items-center justify-center rounded-md bg-muted p-1 text-muted-foreground",
16 |       className,
17 |     )}
18 |     {...props}
19 |   />
20 | ));
21 | TabsList.displayName = TabsPrimitive.List.displayName;
22 |
23 | const TabsTrigger = React.forwardRef<
24 |   React.ElementRef<typeof TabsPrimitive.Trigger>,
25 |   React.ComponentPropsWithoutRef<typeof TabsPrimitive.Trigger>
26 | >(({ className, ...props }, ref) => (
27 |   <TabsPrimitive.Trigger
28 |     ref={ref}
```

```
29 |     className={cn(
30 |       "inline-flex items-center justify-center whitespace-nowrap rounded-sm px-3 py-1.5 text-sm font-medium ring-
31 |       className,
32 |     )}
33 |     {...props}
34 |   />
35 | ));
36 | TabsTrigger.displayName = TabsPrimitive.Trigger.displayName;
37 |
38 | const TabsContent = React.forwardRef<
39 |   React.ElementRef<typeof TabsPrimitive.Content>,
40 |   React.ComponentPropsWithoutRef<typeof TabsPrimitive.Content>
41 | >(({ className, ...props }, ref) => (
42 |   <TabsPrimitive.Content
43 |     ref={ref}
44 |     className={cn(
45 |       "mt-2 ring-offset-background focus-visible:outline-none focus-visible:ring-2 focus-visible:ring-ring focus-
46 |       className,
47 |     )}
48 |     {...props}
49 |   />
50 | ));
51 | TabsContent.displayName = TabsPrimitive.Content.displayName;
52 |
53 | export { Tabs, TabsList, TabsTrigger, TabsContent };
54 |
```

44. components/ui/textarea.tsx

Path: src/components/ui/textarea.tsx

```
1 | import * as React from "react";
2 |
3 | import { cn } from "@/lib/utils";
4 |
5 | export interface TextareaProps extends React.TextareaHTMLAttributes<HTMLTextAreaElement> {}
6 |
7 | const Textarea = React.forwardRef<HTMLTextAreaElement, TextareaProps>(({ className, ...props }, ref) => {
8 |   return (
9 |     <textarea
10 |       className={cn(
11 |         "flex min-h-[80px] w-full rounded-md border border-input bg-background px-3 py-2 text-sm ring-offset-back
12 |         className,
13 |       )}
14 |       ref={ref}
15 |       {...props}
16 |     />
17 |   );
18 | });
19 | Textarea.displayName = "Textarea";
20 |
21 | export { Textarea };
22 |
```

45. components/ui/toast.tsx

Path: src/components/ui/toast.tsx

```
 1 | import * as React from "react";
 2 | import * as ToastPrimitives from "@radix-ui/react-toast";
 3 | import { cva, type VariantProps } from "class-variance-authority";
 4 | import { X } from "lucide-react";
 5 |
 6 | import { cn } from "@/lib/utils";
 7 |
 8 | const ToastProvider = ToastPrimitives.Provider;
 9 |
10 | const ToastViewport = React.forwardRef<
11 |   React.ElementRef<typeof ToastPrimitives.Viewport>,
12 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Viewport>
13 | >(({ className, ...props }, ref) => (
14 |   <ToastPrimitives.Viewport
15 |     ref={ref}
16 |     className={cn(
17 |       "fixed top-0 z-[100] flex max-h-screen w-full flex-col-reverse p-4 sm:bottom-0 sm:right-0 sm:top-auto sm:fl
18 |       className,
19 |     )}
20 |     {...props}
21 |   />
22 | ));
23 | ToastViewport.displayName = ToastPrimitives.Viewport.displayName;
24 |
25 | const toastVariants = cva(
26 |   "group pointer-events-auto relative flex w-full items-center justify-between space-x-4 overflow-hidden rounded-
27 |   {
28 |     variants: {
29 |       variant: {
30 |         default: "border bg-background text-foreground",
31 |         destructive: "destructive group border-destructive bg-destructive text-destructive-foreground",
32 |       },
33 |     },
34 |     defaultVariants: {
35 |       variant: "default",
36 |     },
37 |   },
38 | );
39 |
40 | const Toast = React.forwardRef<
41 |   React.ElementRef<typeof ToastPrimitives.Root>,
42 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Root> & VariantProps<typeof toastVariants>
43 | >(({ className, variant, ...props }, ref) => {
44 |   return <ToastPrimitives.Root ref={ref} className={cn(toastVariants({ variant }), className)} {...props} />;
45 | });
46 | Toast.displayName = ToastPrimitives.Root.displayName;
47 |
48 | const ToastAction = React.forwardRef<
```

```
49 |   React.ElementRef<typeof ToastPrimitives.Action>,
50 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Action>
51 | >(({ className, ...props }, ref) => (
52 |   <ToastPrimitives.Action
53 |     ref={ref}
54 |     className={cn(
55 |       "inline-flex h-8 shrink-0 items-center justify-center rounded-md border bg-transparent px-3 text-sm font-me
56 |       className,
57 |     )}
58 |     {...props}
59 |   />
60 | ));
61 | ToastAction.displayName = ToastPrimitives.Action.displayName;
62 |
63 | const ToastClose = React.forwardRef<
64 |   React.ElementRef<typeof ToastPrimitives.Close>,
65 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Close>
66 | >(({ className, ...props }, ref) => (
67 |   <ToastPrimitives.Close
68 |     ref={ref}
69 |     className={cn(
70 |       "absolute right-2 top-2 rounded-md p-1 text-foreground/50 opacity-0 transition-opacity group-hover:opacity-
71 |       className,
72 |     )}
73 |     toast-close=""
74 |     {...props}
75 |   >
76 |     <X className="h-4 w-4" />
77 |   </ToastPrimitives.Close>
78 | ));
79 | ToastClose.displayName = ToastPrimitives.Close.displayName;
80 |
81 | const ToastTitle = React.forwardRef<
82 |   React.ElementRef<typeof ToastPrimitives.Title>,
83 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Title>
84 | >(({ className, ...props }, ref) => (
85 |   <ToastPrimitives.Title ref={ref} className={cn("text-sm font-semibold", className)} {...props} />
86 | ));
87 | ToastTitle.displayName = ToastPrimitives.Title.displayName;
88 |
89 | const ToastDescription = React.forwardRef<
90 |   React.ElementRef<typeof ToastPrimitives.Description>,
91 |   React.ComponentPropsWithoutRef<typeof ToastPrimitives.Description>
92 | >(({ className, ...props }, ref) => (
93 |   <ToastPrimitives.Description ref={ref} className={cn("text-sm opacity-90", className)} {...props} />
94 | ));
95 | ToastDescription.displayName = ToastPrimitives.Description.displayName;
96 |
97 | type ToastProps = React.ComponentPropsWithoutRef<typeof Toast>;
98 |
99 | type ToastActionElement = React.ReactElement<typeof ToastAction>;
100 |
101 | export {
102 |   type ToastProps,
```

```
  type ToastActionElement,
  ToastProvider,
  ToastViewport,
  Toast,
  ToastTitle,
  ToastDescription,
  ToastClose,
  ToastAction,
};

```

46. components/ui/toaster.tsx

Path: src/components/ui/toaster.tsx

```
import { useToast } from "@/hooks/use-toast";
import { Toast, ToastClose, ToastDescription, ToastProvider, ToastTitle, ToastViewport } from "@/components/ui/to

export function Toaster() {
  const { toasts } = useToast();

  return (
    <ToastProvider>
      {toasts.map(function ({ id, title, description, action, ...props }) {
        return (
          <Toast key={id} {...props}>
            <div className="grid gap-1">
              {title && <ToastTitle>{title}</ToastTitle>}
              {description && <ToastDescription>{description}</ToastDescription>}
            </div>
            {action}
            <ToastClose />
          </Toast>
        );
      })}
      <ToastViewport />
    </ToastProvider>
  );
}

```

47. components/ui/toggle-group.tsx

Path: src/components/ui/toggle-group.tsx

```
import * as React from "react";
import * as ToggleGroupPrimitive from "@radix-ui/react-toggle-group";
import { type VariantProps } from "class-variance-authority";

import { cn } from "@/lib/utils";
import { toggleVariants } from "@/components/ui/toggle";
```

```
 7 |
 8 | const ToggleGroupContext = React.createContext<VariantProps<typeof toggleVariants>>({
 9 |   size: "default",
10 |   variant: "default",
11 | });
12 |
13 | const ToggleGroup = React.forwardRef<
14 |   React.ElementRef<typeof ToggleGroupPrimitive.Root>,
15 |   React.ComponentPropsWithoutRef<typeof ToggleGroupPrimitive.Root> & VariantProps<typeof toggleVariants>
16 | >(({ className, variant, size, children, ...props }, ref) => (
17 |   <ToggleGroupPrimitive.Root ref={ref} className={cn("flex items-center justify-center gap-1", className)} {...pr
18 |     <ToggleGroupContext.Provider value={{ variant, size }}>{children}</ToggleGroupContext.Provider>
19 |   </ToggleGroupPrimitive.Root>
20 | ));
21 |
22 | ToggleGroup.displayName = ToggleGroupPrimitive.Root.displayName;
23 |
24 | const ToggleGroupItem = React.forwardRef<
25 |   React.ElementRef<typeof ToggleGroupPrimitive.Item>,
26 |   React.ComponentPropsWithoutRef<typeof ToggleGroupPrimitive.Item> & VariantProps<typeof toggleVariants>
27 | >(({ className, children, variant, size, ...props }, ref) => {
28 |   const context = React.useContext(ToggleGroupContext);
29 |
30 |   return (
31 |     <ToggleGroupPrimitive.Item
32 |       ref={ref}
33 |       className={cn(
34 |         toggleVariants({
35 |           variant: context.variant || variant,
36 |           size: context.size || size,
37 |         }),
38 |         className,
39 |       )}
40 |       {...props}
41 |     >
42 |       {children}
43 |     </ToggleGroupPrimitive.Item>
44 |   );
45 | });
46 |
47 | ToggleGroupItem.displayName = ToggleGroupPrimitive.Item.displayName;
48 |
49 | export { ToggleGroup, ToggleGroupItem };
50 |
```

48. components/ui/toggle.tsx

Path: src/components/ui/toggle.tsx

```
 1 | import * as React from "react";
 2 | import * as TogglePrimitive from "@radix-ui/react-toggle";
 3 | import { cva, type VariantProps } from "class-variance-authority";
 4 |
```

```
 5 | import { cn } from "@/lib/utils";
 6 |
 7 | const toggleVariants = cva(
 8 |   "inline-flex items-center justify-center rounded-md text-sm font-medium ring-offset-background transition-color
 9 |   {
10 |     variants: {
11 |       variant: {
12 |         default: "bg-transparent",
13 |         outline: "border border-input bg-transparent hover:bg-accent hover:text-accent-foreground",
14 |       },
15 |       size: {
16 |         default: "h-10 px-3",
17 |         sm: "h-9 px-2.5",
18 |         lg: "h-11 px-5",
19 |       },
20 |     },
21 |     defaultVariants: {
22 |       variant: "default",
23 |       size: "default",
24 |     },
25 |   },
26 | );
27 |
28 | const Toggle = React.forwardRef<
29 |   React.ElementRef<typeof TogglePrimitive.Root>,
30 |   React.ComponentPropsWithoutRef<typeof TogglePrimitive.Root> & VariantProps<typeof toggleVariants>
31 | >(({ className, variant, size, ...props }, ref) => (
32 |   <TogglePrimitive.Root ref={ref} className={cn(toggleVariants({ variant, size, className }))} {...props} />
33 | ));
34 |
35 | Toggle.displayName = TogglePrimitive.Root.displayName;
36 |
37 | export { Toggle, toggleVariants };
38 |
```

49. components/ui/tooltip.tsx

Path: src/components/ui/tooltip.tsx

```
 1 | import * as React from "react";
 2 | import * as TooltipPrimitive from "@radix-ui/react-tooltip";
 3 |
 4 | import { cn } from "@/lib/utils";
 5 |
 6 | const TooltipProvider = TooltipPrimitive.Provider;
 7 |
 8 | const Tooltip = TooltipPrimitive.Root;
 9 |
10 | const TooltipTrigger = TooltipPrimitive.Trigger;
11 |
12 | const TooltipContent = React.forwardRef<
13 |   React.ElementRef<typeof TooltipPrimitive.Content>,
14 |   React.ComponentPropsWithoutRef<typeof TooltipPrimitive.Content>
```

```
15 | >(({ className, sideOffset = 4, ...props }, ref) => (
16 |   <TooltipPrimitive.Content
17 |     ref={ref}
18 |     sideOffset={sideOffset}
19 |     className={cn(
20 |       "z-50 overflow-hidden rounded-md border bg-popover px-3 py-1.5 text-sm text-popover-foreground shadow-md an
21 |       className,
22 |     )}
23 |     {...props}
24 |   />
25 | ));
26 | TooltipContent.displayName = TooltipPrimitive.Content.displayName;
27 |
28 | export { Tooltip, TooltipTrigger, TooltipContent, TooltipProvider };
29 |
```

50. components/ui/use-toast.ts

Path: src/components/ui/use-toast.ts

```
1 | import { useToast, toast } from "@/hooks/use-toast";
2 |
3 | export { useToast, toast };
4 |
```

51. hooks/use-mobile.tsx

Path: src/hooks/use-mobile.tsx

```
1 | import * as React from "react";
2 |
3 | const MOBILE_BREAKPOINT = 768;
4 |
5 | export function useIsMobile() {
6 |   const [isMobile, setIsMobile] = React.useState<boolean | undefined>(undefined);
7 |
8 |   React.useEffect(() => {
9 |     const mql = window.matchMedia(`(max-width: ${MOBILE_BREAKPOINT - 1}px)`);
10 |     const onChange = () => {
11 |       setIsMobile(window.innerWidth < MOBILE_BREAKPOINT);
12 |     };
13 |     mql.addEventListener("change", onChange);
14 |     setIsMobile(window.innerWidth < MOBILE_BREAKPOINT);
15 |     return () => mql.removeEventListener("change", onChange);
16 |   }, []);
17 |
18 |   return !!isMobile;
19 | }
20 |
```

52. hooks/use-toast.ts

Path: src/hooks/use-toast.ts

```
 1 | import * as React from "react";
 2 |
 3 | import type { ToastActionElement, ToastProps } from "@/components/ui/toast";
 4 |
 5 | const TOAST_LIMIT = 1;
 6 | const TOAST_REMOVE_DELAY = 1000000;
 7 |
 8 | type ToasterToast = ToastProps & {
 9 |   id: string;
10 |   title?: React.ReactNode;
11 |   description?: React.ReactNode;
12 |   action?: ToastActionElement;
13 | };
14 |
15 | const actionTypes = {
16 |   ADD_TOAST: "ADD_TOAST",
17 |   UPDATE_TOAST: "UPDATE_TOAST",
18 |   DISMISS_TOAST: "DISMISS_TOAST",
19 |   REMOVE_TOAST: "REMOVE_TOAST",
20 | } as const;
21 |
22 | let count = 0;
23 |
24 | function genId() {
25 |   count = (count + 1) % Number.MAX_SAFE_INTEGER;
26 |   return count.toString();
27 | }
28 |
29 | type ActionType = typeof actionTypes;
30 |
31 | type Action =
32 |   | {
33 |       type: ActionType["ADD_TOAST"];
34 |       toast: ToasterToast;
35 |     }
36 |   | {
37 |       type: ActionType["UPDATE_TOAST"];
38 |       toast: Partial<ToasterToast>;
39 |     }
40 |   | {
41 |       type: ActionType["DISMISS_TOAST"];
42 |       toastId?: ToasterToast["id"];
43 |     }
44 |   | {
45 |       type: ActionType["REMOVE_TOAST"];
46 |       toastId?: ToasterToast["id"];
47 |     };
48 |
49 | interface State {
50 |   toasts: ToasterToast[];
```

```
51 | }
52 |
53 | const toastTimeouts = new Map<string, ReturnType<typeof setTimeout>>();
54 |
55 | const addToRemoveQueue = (toastId: string) => {
56 |   if (toastTimeouts.has(toastId)) {
57 |     return;
58 |   }
59 |
60 |   const timeout = setTimeout(() => {
61 |     toastTimeouts.delete(toastId);
62 |     dispatch({
63 |       type: "REMOVE_TOAST",
64 |       toastId: toastId,
65 |     });
66 |   }, TOAST_REMOVE_DELAY);
67 |
68 |   toastTimeouts.set(toastId, timeout);
69 | };
70 |
71 | export const reducer = (state: State, action: Action): State => {
72 |   switch (action.type) {
73 |     case "ADD_TOAST":
74 |       return {
75 |         ...state,
76 |         toasts: [action.toast, ...state.toasts].slice(0, TOAST_LIMIT),
77 |       };
78 |
79 |     case "UPDATE_TOAST":
80 |       return {
81 |         ...state,
82 |         toasts: state.toasts.map((t) => (t.id === action.toast.id ? { ...t, ...action.toast } : t)),
83 |       };
84 |
85 |     case "DISMISS_TOAST": {
86 |       const { toastId } = action;
87 |
88 |       // ! Side effects ! - This could be extracted into a dismissToast() action,
89 |       // but I'll keep it here for simplicity
90 |       if (toastId) {
91 |         addToRemoveQueue(toastId);
92 |       } else {
93 |         state.toasts.forEach((toast) => {
94 |           addToRemoveQueue(toast.id);
95 |         });
96 |       }
97 |
98 |       return {
99 |         ...state,
100 |         toasts: state.toasts.map((t) =>
101 |           t.id === toastId || toastId === undefined
102 |             ? {
103 |                 ...t,
104 |                 open: false,
```

```
105 |               }
106 |             : t,
107 |         ),
108 |       };
109 |     }
110 |     case "REMOVE_TOAST":
111 |       if (action.toastId === undefined) {
112 |         return {
113 |           ...state,
114 |           toasts: [],
115 |         };
116 |       }
117 |       return {
118 |         ...state,
119 |         toasts: state.toasts.filter((t) => t.id !== action.toastId),
120 |       };
121 |   }
122 | };
123 |
124 | const listeners: Array<(state: State) => void> = [];
125 |
126 | let memoryState: State = { toasts: [] };
127 |
128 | function dispatch(action: Action) {
129 |   memoryState = reducer(memoryState, action);
130 |   listeners.forEach((listener) => {
131 |     listener(memoryState);
132 |   });
133 | }
134 |
135 | type Toast = Omit<ToasterToast, "id">;
136 |
137 | function toast({ ...props }: Toast) {
138 |   const id = genId();
139 |
140 |   const update = (props: ToasterToast) =>
141 |     dispatch({
142 |       type: "UPDATE_TOAST",
143 |       toast: { ...props, id },
144 |     });
145 |   const dismiss = () => dispatch({ type: "DISMISS_TOAST", toastId: id });
146 |
147 |   dispatch({
148 |     type: "ADD_TOAST",
149 |     toast: {
150 |       ...props,
151 |       id,
152 |       open: true,
153 |       onOpenChange: (open) => {
154 |         if (!open) dismiss();
155 |       },
156 |     },
157 |   });
158 |
```

```
159 |   return {
160 |     id: id,
161 |     dismiss,
162 |     update,
163 |   };
164 | }
165 |
166 | function useToast() {
167 |   const [state, setState] = React.useState<State>(memoryState);
168 |
169 |   React.useEffect(() => {
170 |     listeners.push(setState);
171 |     return () => {
172 |       const index = listeners.indexOf(setState);
173 |       if (index > -1) {
174 |         listeners.splice(index, 1);
175 |       }
176 |     };
177 |   }, [state]);
178 |
179 |   return {
180 |     ...state,
181 |     toast,
182 |     dismiss: (toastId?: string) => dispatch({ type: "DISMISS_TOAST", toastId }),
183 |   };
184 | }
185 |
186 | export { useToast, toast };
187 |
```

53. integrations/supabase/client.ts

Path: src/integrations/supabase/client.ts

```
1 | // This file is automatically generated. Do not edit it directly.
2 | import { createClient } from '@supabase/supabase-js';
3 | import type { Database } from './types';
4 |
5 | const SUPABASE_URL = import.meta.env.VITE_SUPABASE_URL;
6 | const SUPABASE_PUBLISHABLE_KEY = import.meta.env.VITE_SUPABASE_PUBLISHABLE_KEY;
7 |
8 | // Import the supabase client like this:
9 | // import { supabase } from "@/integrations/supabase/client";
10 |
11 | export const supabase = createClient<Database>(SUPABASE_URL, SUPABASE_PUBLISHABLE_KEY, {
12 |   auth: {
13 |     storage: localStorage,
14 |     persistSession: true,
15 |     autoRefreshToken: true,
16 |   }
17 | });
```

54. integrations/supabase/types.ts

Path: src/integrations/supabase/types.ts

```
 1 | export type Json =
 2 |   | string
 3 |   | number
 4 |   | boolean
 5 |   | null
 6 |   | { [key: string]: Json | undefined }
 7 |   | Json[]
 8 |
 9 | export type Database = {
10 |   // Allows to automatically instantiate createClient with right options
11 |   // instead of createClient<Database, { PostgrestVersion: 'XX' }>(URL, KEY)
12 |   __InternalSupabase: {
13 |     PostgrestVersion: "13.0.5"
14 |   }
15 |   public: {
16 |     Tables: {
17 |       [_ in never]: never
18 |     }
19 |     Views: {
20 |       [_ in never]: never
21 |     }
22 |     Functions: {
23 |       [_ in never]: never
24 |     }
25 |     Enums: {
26 |       [_ in never]: never
27 |     }
28 |     CompositeTypes: {
29 |       [_ in never]: never
30 |     }
31 |   }
32 | }
33 |
34 | type DatabaseWithoutInternals = Omit<Database, "__InternalSupabase">
35 |
36 | type DefaultSchema = DatabaseWithoutInternals[Extract<keyof Database, "public">]
37 |
38 | export type Tables<
39 |   DefaultSchemaTableNameOrOptions extends
40 |     | keyof (DefaultSchema["Tables"] & DefaultSchema["Views"])
41 |     | { schema: keyof DatabaseWithoutInternals },
42 |   TableName extends DefaultSchemaTableNameOrOptions extends {
43 |     schema: keyof DatabaseWithoutInternals
44 |   }
45 |     ? keyof (DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"] &
46 |         DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Views"])
47 |     : never = never,
48 | > = DefaultSchemaTableNameOrOptions extends {
49 |   schema: keyof DatabaseWithoutInternals
```

```
50 | }
51 |   ? (DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"] &
52 |       DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Views"])[TableName] extends {
53 |       Row: infer R
54 |     }
55 |     ? R
56 |     : never
57 |   : DefaultSchemaTableNameOrOptions extends keyof (DefaultSchema["Tables"] &
58 |         DefaultSchema["Views"])
59 |     ? (DefaultSchema["Tables"] &
60 |         DefaultSchema["Views"])[DefaultSchemaTableNameOrOptions] extends {
61 |         Row: infer R
62 |       }
63 |       ? R
64 |       : never
65 |     : never
66 |
67 | export type TablesInsert<
68 |   DefaultSchemaTableNameOrOptions extends
69 |     | keyof DefaultSchema["Tables"]
70 |     | { schema: keyof DatabaseWithoutInternals },
71 |   TableName extends DefaultSchemaTableNameOrOptions extends {
72 |     schema: keyof DatabaseWithoutInternals
73 |   }
74 |     ? keyof DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"]
75 |     : never = never,
76 | > = DefaultSchemaTableNameOrOptions extends {
77 |   schema: keyof DatabaseWithoutInternals
78 | }
79 |   ? DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"][TableName] extends {
80 |       Insert: infer I
81 |     }
82 |     ? I
83 |     : never
84 |   : DefaultSchemaTableNameOrOptions extends keyof DefaultSchema["Tables"]
85 |     ? DefaultSchema["Tables"][DefaultSchemaTableNameOrOptions] extends {
86 |         Insert: infer I
87 |       }
88 |       ? I
89 |       : never
90 |     : never
91 |
92 | export type TablesUpdate<
93 |   DefaultSchemaTableNameOrOptions extends
94 |     | keyof DefaultSchema["Tables"]
95 |     | { schema: keyof DatabaseWithoutInternals },
96 |   TableName extends DefaultSchemaTableNameOrOptions extends {
97 |     schema: keyof DatabaseWithoutInternals
98 |   }
99 |     ? keyof DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"]
100 |     : never = never,
101 | > = DefaultSchemaTableNameOrOptions extends {
102 |   schema: keyof DatabaseWithoutInternals
103 | }
```

```
104 |   ? DatabaseWithoutInternals[DefaultSchemaTableNameOrOptions["schema"]]["Tables"][TableName] extends {
105 |       Update: infer U
106 |     }
107 |     ? U
108 |     : never
109 |   : DefaultSchemaTableNameOrOptions extends keyof DefaultSchema["Tables"]
110 |     ? DefaultSchema["Tables"][DefaultSchemaTableNameOrOptions] extends {
111 |         Update: infer U
112 |       }
113 |       ? U
114 |       : never
115 |     : never
116 |
117 | export type Enums<
118 |   DefaultSchemaEnumNameOrOptions extends
119 |     | keyof DefaultSchema["Enums"]
120 |     | { schema: keyof DatabaseWithoutInternals },
121 |   EnumName extends DefaultSchemaEnumNameOrOptions extends {
122 |     schema: keyof DatabaseWithoutInternals
123 |   }
124 |     ? keyof DatabaseWithoutInternals[DefaultSchemaEnumNameOrOptions["schema"]]["Enums"]
125 |     : never = never,
126 | > = DefaultSchemaEnumNameOrOptions extends {
127 |   schema: keyof DatabaseWithoutInternals
128 | }
129 |   ? DatabaseWithoutInternals[DefaultSchemaEnumNameOrOptions["schema"]]["Enums"][EnumName]
130 |   : DefaultSchemaEnumNameOrOptions extends keyof DefaultSchema["Enums"]
131 |     ? DefaultSchema["Enums"][DefaultSchemaEnumNameOrOptions]
132 |     : never
133 |
134 | export type CompositeTypes<
135 |   PublicCompositeTypeNameOrOptions extends
136 |     | keyof DefaultSchema["CompositeTypes"]
137 |     | { schema: keyof DatabaseWithoutInternals },
138 |   CompositeTypeName extends PublicCompositeTypeNameOrOptions extends {
139 |     schema: keyof DatabaseWithoutInternals
140 |   }
141 |     ? keyof DatabaseWithoutInternals[PublicCompositeTypeNameOrOptions["schema"]]["CompositeTypes"]
142 |     : never = never,
143 | > = PublicCompositeTypeNameOrOptions extends {
144 |   schema: keyof DatabaseWithoutInternals
145 | }
146 |   ? DatabaseWithoutInternals[PublicCompositeTypeNameOrOptions["schema"]]["CompositeTypes"][CompositeTypeName]
147 |   : PublicCompositeTypeNameOrOptions extends keyof DefaultSchema["CompositeTypes"]
148 |     ? DefaultSchema["CompositeTypes"][PublicCompositeTypeNameOrOptions]
149 |     : never
150 |
151 | export const Constants = {
152 |   public: {
153 |     Enums: {},
154 |   },
155 | } as const
156 |
```

55. lib/utils.ts

Path: src/lib/utils.ts

```
1 | import { clsx, type ClassValue } from "clsx";
2 | import { twMerge } from "tailwind-merge";
3 |
4 | export function cn(...inputs: ClassValue[]) {
5 |   return twMerge(clsx(inputs));
6 | }
7 |
```

56. main.tsx

Path: src/main.tsx

```
1 | import { createRoot } from "react-dom/client";
2 | import App from "./App.tsx";
3 | import "./index.css";
4 |
5 | createRoot(document.getElementById("root")!).render(<App />);
6 |
```

57. pages/Auth.tsx

Path: src/pages/Auth.tsx

```
1 | import { useState } from "react";
2 | import { useNavigate } from "react-router-dom";
3 | import { Button } from "@/components/ui/button";
4 | import { Input } from "@/components/ui/input";
5 | import { Label } from "@/components/ui/label";
6 | import { toast } from "@/hooks/use-toast";
7 |
8 | const Auth = () => {
9 |   const [isLogin, setIsLogin] = useState(true);
10 |   const [email, setEmail] = useState("");
11 |   const [password, setPassword] = useState("");
12 |   const [name, setName] = useState("");
13 |   const navigate = useNavigate();
14 |
15 |   const handleSubmit = (e: React.FormEvent) => {
16 |     e.preventDefault();
17 |
18 |     if (!email || !password) {
19 |       toast({
20 |         title: "Error",
21 |         description: "Please fill in all fields.",
22 |         variant: "destructive",
23 |       });
```

```
24 |       return;
25 |     }
26 |
27 |     if (isLogin) {
28 |       // Mock login - check localStorage
29 |       const users = JSON.parse(localStorage.getItem("study-users") || "[]");
30 |       const user = users.find(
31 |         (u: { email: string; password: string }) =>
32 |           u.email === email && u.password === password
33 |       );
34 |
35 |       if (user) {
36 |         localStorage.setItem("study-current-user", JSON.stringify(user));
37 |         toast({
38 |           title: "Welcome back!",
39 |           description: `Logged in as ${user.name || user.email}`,
40 |         });
41 |         navigate("/");
42 |       } else {
43 |         toast({
44 |           title: "Login failed",
45 |           description: "Invalid email or password.",
46 |           variant: "destructive",
47 |         });
48 |       }
49 |     } else {
50 |       // Mock signup
51 |       if (!name) {
52 |         toast({
53 |           title: "Error",
54 |           description: "Please enter your name.",
55 |           variant: "destructive",
56 |         });
57 |         return;
58 |       }
59 |
60 |       const users = JSON.parse(localStorage.getItem("study-users") || "[]");
61 |       const existingUser = users.find((u: { email: string }) => u.email === email);
62 |
63 |       if (existingUser) {
64 |         toast({
65 |           title: "Error",
66 |           description: "An account with this email already exists.",
67 |           variant: "destructive",
68 |         });
69 |         return;
70 |       }
71 |
72 |       const newUser = { email, password, name, createdAt: new Date().toISOString() };
73 |       users.push(newUser);
74 |       localStorage.setItem("study-users", JSON.stringify(users));
75 |       localStorage.setItem("study-current-user", JSON.stringify(newUser));
76 |
77 |       toast({
```

```
78 |         title: "Account created!",
79 |         description: "Welcome to Study Time Tracker.",
80 |       });
81 |       navigate("/");
82 |     }
83 |   };
84 |
85 |   return (
86 |     <div className="min-h-screen bg-background flex flex-col items-center justify-center px-4">
87 |       <div className="w-full max-w-md">
88 |         <h1 className="font-serif text-4xl md:text-5xl text-primary text-center mb-2">
89 |           Study Time Tracker
90 |         </h1>
91 |         <p className="text-muted-foreground text-center mb-8 font-sans">
92 |           {isLogin ? "Sign in to continue" : "Create your account"}
93 |         </p>
94 |
95 |         <div className="bg-card border-2 border-border rounded-2xl p-8 shadow-lg">
96 |           <form onSubmit={handleSubmit} className="space-y-6">
97 |             {!isLogin && (
98 |               <div className="space-y-2">
99 |                 <Label htmlFor="name" className="font-sans text-foreground">
100 |                   Name
101 |                 </Label>
102 |                 <Input
103 |                   id="name"
104 |                   type="text"
105 |                   value={name}
106 |                   onChange={(e) => setName(e.target.value)}
107 |                   placeholder="Your name"
108 |                   className="h-12 rounded-xl border-2 border-border font-sans"
109 |                 />
110 |               </div>
111 |             )}
112 |
113 |             <div className="space-y-2">
114 |               <Label htmlFor="email" className="font-sans text-foreground">
115 |                 Email
116 |               </Label>
117 |               <Input
118 |                 id="email"
119 |                 type="email"
120 |                 value={email}
121 |                 onChange={(e) => setEmail(e.target.value)}
122 |                 placeholder="you@example.com"
123 |                 className="h-12 rounded-xl border-2 border-border font-sans"
124 |               />
125 |             </div>
126 |
127 |             <div className="space-y-2">
128 |               <Label htmlFor="password" className="font-sans text-foreground">
129 |                 Password
130 |               </Label>
131 |               <Input
```

```
132 |                id="password"
133 |                type="password"
134 |                value={password}
135 |                onChange={(e) => setPassword(e.target.value)}
136 |                placeholder="••••••••"
137 |                className="h-12 rounded-xl border-2 border-border font-sans"
138 |              />
139 |            </div>
140 |
141 |            <Button
142 |              type="submit"
143 |              className="w-full h-12 font-sans text-lg rounded-xl bg-primary text-primary-foreground hover:bg-pri
144 |            >
145 |              {isLogin ? "Sign In" : "Create Account"}
146 |            </Button>
147 |          </form>
148 |
149 |          <div className="mt-6 text-center">
150 |            <button
151 |              type="button"
152 |              onClick={() => setIsLogin(!isLogin)}
153 |              className="text-muted-foreground hover:text-foreground font-sans text-sm transition-colors"
154 |            >
155 |              {isLogin
156 |                ? "Don't have an account? Sign up"
157 |                : "Already have an account? Sign in"}
158 |            </button>
159 |          </div>
160 |        </div>
161 |      </div>
162 |
163 |      <footer className="mt-12 py-6 text-center">
164 |        <p className="font-serif text-lg text-foreground">Made by Iris for IB CS IA</p>
165 |      </footer>
166 |    </div>
167 |  );
168 | };
169 |
170 | export default Auth;
171 |
```

58. pages/Home.tsx

Path: src/pages/Home.tsx

```
1 | import { useState, useEffect } from "react";
2 | import { Link } from "react-router-dom";
3 | import { Play, Pause, RotateCcw, Plus, X } from "lucide-react";
4 | import { Button } from "@/components/ui/button";
5 | import {
6 |   Select,
7 |   SelectContent,
8 |   SelectItem,
```

```
 9 |   SelectTrigger,
10 |   SelectValue,
11 | } from "@/components/ui/select";
12 | import { Input } from "@/components/ui/input";
13 | import {
14 |   Dialog,
15 |   DialogContent,
16 |   DialogHeader,
17 |   DialogTitle,
18 |   DialogTrigger,
19 | } from "@/components/ui/dialog";
20 | import { cn } from "@/lib/utils";
21 | import { toast } from "@/hooks/use-toast";
22 |
23 | const DEFAULT_SUBJECTS = ["Math", "English", "ESS", "French", "Computer Science", "Economics"];
24 |
25 | export interface StudySession {
26 |   id: string;
27 |   subject: string;
28 |   duration: number;
29 |   date: Date;
30 | }
31 |
32 | function formatDuration(seconds: number): string {
33 |   const hours = Math.floor(seconds / 3600);
34 |   const minutes = Math.floor((seconds % 3600) / 60);
35 |   const secs = seconds % 60;
36 |
37 |   if (hours > 0) {
38 |     return `${hours}h ${minutes}m`;
39 |   }
40 |   return `${minutes}m ${secs}s`;
41 | }
42 |
43 | const Home = () => {
44 |   const [subjects, setSubjects] = useState<string[]>(() => {
45 |     const saved = localStorage.getItem("study-subjects");
46 |     return saved ? JSON.parse(saved) : DEFAULT_SUBJECTS;
47 |   });
48 |
49 |   const [selectedSubject, setSelectedSubject] = useState<string>(() => {
50 |     const saved = localStorage.getItem("study-selected-subject");
51 |     return saved || DEFAULT_SUBJECTS[0];
52 |   });
53 |
54 |   const [newSubject, setNewSubject] = useState("");
55 |   const [isDialogOpen, setIsDialogOpen] = useState(false);
56 |
57 |   useEffect(() => {
58 |     localStorage.setItem("study-subjects", JSON.stringify(subjects));
59 |   }, [subjects]);
60 |
61 |   const handleAddSubject = () => {
62 |     const trimmed = newSubject.trim();
```

```
63 |     if (!trimmed) {
64 |       toast({ title: "Please enter a subject name", variant: "destructive" });
65 |       return;
66 |     }
67 |     if (subjects.includes(trimmed)) {
68 |       toast({ title: "Subject already exists", variant: "destructive" });
69 |       return;
70 |     }
71 |     setSubjects([...subjects, trimmed]);
72 |     setSelectedSubject(trimmed);
73 |     setNewSubject("");
74 |     setIsDialogOpen(false);
75 |     toast({ title: "Subject added!", description: `${trimmed} has been added.` });
76 |   };
77 |
78 |   const handleRemoveSubject = (subject: string) => {
79 |     if (subjects.length <= 1) {
80 |       toast({ title: "Cannot remove", description: "You need at least one subject.", variant: "destructive" });
81 |       return;
82 |     }
83 |     const updated = subjects.filter((s) => s !== subject);
84 |     setSubjects(updated);
85 |     if (selectedSubject === subject) {
86 |       setSelectedSubject(updated[0]);
87 |     }
88 |     toast({ title: "Subject removed", description: `${subject} has been removed.` });
89 |   };
90 |
91 |   const [seconds, setSeconds] = useState(0);
92 |   const [isRunning, setIsRunning] = useState(false);
93 |
94 |   useEffect(() => {
95 |     localStorage.setItem("study-selected-subject", selectedSubject);
96 |   }, [selectedSubject]);
97 |
98 |   useEffect(() => {
99 |     let interval: NodeJS.Timeout | null = null;
100 |
101 |     if (isRunning) {
102 |       interval = setInterval(() => {
103 |         setSeconds((prev) => prev + 1);
104 |       }, 1000);
105 |     }
106 |
107 |     return () => {
108 |       if (interval) clearInterval(interval);
109 |     };
110 |   }, [isRunning]);
111 |
112 |   const formatTime = (totalSeconds: number) => {
113 |     const hours = Math.floor(totalSeconds / 3600);
114 |     const minutes = Math.floor((totalSeconds % 3600) / 60);
115 |     const secs = totalSeconds % 60;
116 |
```

```
    return `${hours.toString().padStart(2, "0")}:${minutes
      .toString()
      .padStart(2, "0")}:${secs.toString().padStart(2, "0")}`;
  };

  const handleStart = () => {
    setIsRunning(true);
  };

  const handlePause = () => {
    setIsRunning(false);
  };

  const handleReset = () => {
    if (seconds >= 60 && selectedSubject) {
      const sessions = JSON.parse(localStorage.getItem("study-sessions") || "[]");
      const newSession: StudySession = {
        id: Date.now().toString(),
        subject: selectedSubject,
        duration: seconds,
        date: new Date(),
      };
      localStorage.setItem("study-sessions", JSON.stringify([newSession, ...sessions]));
      toast({
        title: "Session saved!",
        description: `${formatDuration(seconds)} of ${selectedSubject} recorded.`,
      });
    }
    setIsRunning(false);
    setSeconds(0);
  };

  return (
    <div className="min-h-screen bg-background flex flex-col">
      <main className="flex-1 container max-w-2xl mx-auto px-4 py-12 flex flex-col items-center">
        {/* Title */}
        <h1 className="font-serif text-4xl md:text-5xl text-primary mb-12">
          Study Time Tracker
        </h1>

        {/* Subject Selector */}
        <div className="w-full max-w-xs mb-8 flex gap-2">
          <Select value={selectedSubject} onValueChange={setSelectedSubject}>
            <SelectTrigger className="flex-1 rounded-xl border-2 border-border bg-card h-12 font-sans">
              <SelectValue placeholder="Select Subject" />
            </SelectTrigger>
            <SelectContent>
              {subjects.map((subject) => (
                <SelectItem key={subject} value={subject} className="font-sans">
                  <div className="flex items-center justify-between w-full">
                    {subject}
                  </div>
                </SelectItem>
              ))}
```

```
171 |           </SelectContent>
172 |         </Select>
173 |
174 |         <Dialog open={isDialogOpen} onOpenChange={setIsDialogOpen}>
175 |           <DialogTrigger asChild>
176 |             <Button
177 |               variant="outline"
178 |               size="icon"
179 |               className="h-12 w-12 rounded-xl border-2 border-border"
180 |             >
181 |               <Plus className="w-5 h-5" />
182 |             </Button>
183 |           </DialogTrigger>
184 |           <DialogContent className="sm:max-w-md">
185 |             <DialogHeader>
186 |               <DialogTitle className="font-serif">Manage Subjects</DialogTitle>
187 |             </DialogHeader>
188 |             <div className="space-y-4 pt-4">
189 |               <div className="flex gap-2">
190 |                 <Input
191 |                   placeholder="New subject name"
192 |                   value={newSubject}
193 |                   onChange={(e) => setNewSubject(e.target.value)}
194 |                   onKeyDown={(e) => e.key === "Enter" && handleAddSubject()}
195 |                   className="flex-1 rounded-xl border-2 border-border"
196 |                 />
197 |                 <Button onClick={handleAddSubject} className="rounded-xl">
198 |                   Add
199 |                 </Button>
200 |               </div>
201 |               <div className="space-y-2">
202 |                 <p className="text-sm text-muted-foreground font-sans">Current subjects:</p>
203 |                 <div className="flex flex-wrap gap-2">
204 |                   {subjects.map((subject) => (
205 |                     <div
206 |                       key={subject}
207 |                       className="flex items-center gap-1 bg-secondary text-secondary-foreground px-3 py-1.5 rou
208 |                     >
209 |                       {subject}
210 |                       <button
211 |                         onClick={() => handleRemoveSubject(subject)}
212 |                         className="ml-1 hover:text-destructive transition-colors"
213 |                       >
214 |                         <X className="w-3 h-3" />
215 |                       </button>
216 |                     </div>
217 |                   ))}
218 |                 </div>
219 |               </div>
220 |             </div>
221 |           </DialogContent>
222 |         </Dialog>
223 |       </div>
224 |
```

```
225 |       {/* Timer Display */}
226 |       <div className="relative mb-8">
227 |         <div
228 |           className={cn(
229 |             "w-64 h-64 md:w-80 md:h-80 rounded-full flex items-center justify-center",
230 |             "bg-card border-4 transition-all duration-500 shadow-lg",
231 |             isRunning
232 |               ? "border-primary"
233 |               : seconds > 0
234 |                 ? "border-accent"
235 |                 : "border-border"
236 |           )}
237 |         >
238 |           <span
239 |             className={cn(
240 |               "font-serif text-4xl md:text-5xl tracking-tight transition-colors",
241 |               isRunning ? "text-primary" : "text-foreground"
242 |             )}
243 |           >
244 |             {formatTime(seconds)}
245 |           </span>
246 |         </div>
247 |       </div>
248 |
249 |       {/* Controls */}
250 |       <div className="flex items-center gap-4 mb-8">
251 |         {!isRunning ? (
252 |           <Button
253 |             size="lg"
254 |             onClick={handleStart}
255 |             className="h-12 px-8 font-sans rounded-xl bg-secondary text-secondary-foreground hover:bg-secondary
256 |           >
257 |             <Play className="w-5 h-5 mr-2" />
258 |             {seconds > 0 ? "Resume" : "Start"}
259 |           </Button>
260 |         ) : (
261 |           <Button
262 |             size="lg"
263 |             onClick={handlePause}
264 |             className="h-12 px-8 font-sans rounded-xl bg-secondary text-secondary-foreground hover:bg-secondary
265 |           >
266 |             <Pause className="w-5 h-5 mr-2" />
267 |             Pause
268 |           </Button>
269 |         )}
270 |
271 |         {seconds > 0 && (
272 |           <Button
273 |             size="lg"
274 |             variant="outline"
275 |             onClick={handleReset}
276 |             className="h-12 w-12 rounded-xl border-2 border-border"
277 |           >
278 |             <RotateCcw className="w-5 h-5" />
```

```
279 |           </Button>
280 |         )}
281 |       </div>
282 |
283 |       {seconds > 0 && !isRunning && (
284 |         <p className="text-sm text-muted-foreground font-sans mb-8">
285 |           Reset to save session (min 1 minute)
286 |         </p>
287 |       )}
288 |
289 |       {/* Navigation Buttons */}
290 |       <div className="flex gap-4">
291 |         <Button
292 |           asChild
293 |           className="h-12 px-8 font-sans rounded-xl bg-secondary text-secondary-foreground hover:bg-secondary/8
294 |         >
295 |           <Link to="/summary">View Summary</Link>
296 |         </Button>
297 |         <Button
298 |           asChild
299 |           className="h-12 px-8 font-sans rounded-xl bg-muted text-muted-foreground hover:bg-muted/80 border-2 b
300 |         >
301 |           <Link to="/progress">View Graph</Link>
302 |         </Button>
303 |       </div>
304 |
305 |       {/* Login Link */}
306 |       <div className="mt-8">
307 |         <Link
308 |           to="/auth"
309 |           className="text-muted-foreground hover:text-foreground font-sans text-sm transition-colors"
310 |         >
311 |           Sign In / Sign Up
312 |         </Link>
313 |       </div>
314 |     </main>
315 |
316 |     {/* Footer */}
317 |     <footer className="py-6 text-center">
318 |       <p className="font-serif text-lg text-foreground">Made by Iris for IB CS IA</p>
319 |     </footer>
320 |   </div>
321 |   );
322 | };
323 |
324 | export default Home;
325 |
```

59. pages/NotFound.tsx

Path: src/pages/NotFound.tsx

```
1 | import { useLocation } from "react-router-dom";
```

```
import { useEffect } from "react";

const NotFound = () => {
  const location = useLocation();

  useEffect(() => {
    console.error("404 Error: User attempted to access non-existent route:", location.pathname);
  }, [location.pathname]);

  return (
    <div className="flex min-h-screen items-center justify-center bg-muted">
      <div className="text-center">
        <h1 className="mb-4 text-4xl font-bold">404</h1>
        <p className="mb-4 text-xl text-muted-foreground">Oops! Page not found</p>
        <a href="/" className="text-primary underline hover:text-primary/90">
          Return to Home
        </a>
      </div>
    </div>
  );
};

export default NotFound;

```

60. pages/Progress.tsx

Path: src/pages/Progress.tsx

```
import { useState, useEffect, useMemo } from "react";
import { Link } from "react-router-dom";
import { Button } from "@/components/ui/button";
import {
  LineChart,
  Line,
  BarChart,
  Bar,
  XAxis,
  YAxis,
  ResponsiveContainer,
  Tooltip,
  Legend,
} from "recharts";

interface StudySession {
  id: string;
  subject: string;
  duration: number;
  date: Date;
}

const DEFAULT_SUBJECTS = ["Math", "English", "ESS", "French", "Computer Science", "Economics"];

```

```
25 | const SUBJECT_COLORS: Record<string, string> = {
26 |   "Math": "#8B7355",
27 |   "English": "#A0522D",
28 |   "ESS": "#6B8E23",
29 |   "French": "#CD853F",
30 |   "Computer Science": "#8B4513",
31 |   "Economics": "#D2691E",
32 | };
33 |
34 | const Progress = () => {
35 |   const [sessions, setSessions] = useState<StudySession[]>([]);
36 |   const [selectedSubject, setSelectedSubject] = useState<string | null>(null);
37 |   const [subjects] = useState<string[]>(DEFAULT_SUBJECTS);
38 |   const [chartType, setChartType] = useState<"line" | "bar">("line");
39 |
40 |   useEffect(() => {
41 |     const saved = localStorage.getItem("study-sessions");
42 |     if (saved) {
43 |       setSessions(
44 |         JSON.parse(saved).map((s: StudySession) => ({
45 |           ...s,
46 |           date: new Date(s.date),
47 |         }))
48 |       );
49 |     }
50 |   }, []);
51 |
52 |   const lineChartData = useMemo(() => {
53 |     const filtered = selectedSubject
54 |       ? sessions.filter((s) => s.subject === selectedSubject)
55 |       : sessions;
56 |
57 |     // Group by date
58 |     const grouped: Record<string, number> = {};
59 |     filtered.forEach((session) => {
60 |       const dateKey = session.date.toLocaleDateString([], {
61 |         month: "short",
62 |         day: "numeric",
63 |       });
64 |       grouped[dateKey] = (grouped[dateKey] || 0) + session.duration / 3600;
65 |     });
66 |
67 |     // Convert to array and sort by date
68 |     return Object.entries(grouped)
69 |       .map(([date, hours]) => ({
70 |         date,
71 |         hours: parseFloat(hours.toFixed(1)),
72 |       }))
73 |       .slice(-10); // Last 10 entries
74 |   }, [sessions, selectedSubject]);
75 |
76 |   const barChartData = useMemo(() => {
77 |     // Group by date, then by subject for stacked bars
78 |     const dateMap: Record<string, Record<string, number>> = {};
```

```
79 |
80 |     sessions.forEach((session) => {
81 |       const dateKey = session.date.toLocaleDateString([], {
82 |         month: "short",
83 |         day: "numeric",
84 |       });
85 |       if (!dateMap[dateKey]) {
86 |         dateMap[dateKey] = {};
87 |       }
88 |       dateMap[dateKey][session.subject] =
89 |         (dateMap[dateKey][session.subject] || 0) + session.duration / 3600;
90 |     });
91 |
92 |     return Object.entries(dateMap)
93 |       .map(([date, subjects]) => ({
94 |         date,
95 |         ...Object.fromEntries(
96 |           Object.entries(subjects).map(([k, v]) => [k, parseFloat(v.toFixed(1))])
97 |         ),
98 |       }))
99 |       .slice(-10);
100 |   }, [sessions]);
101 |
102 |   return (
103 |     <div className="min-h-screen bg-background flex flex-col">
104 |       <main className="flex-1 container max-w-4xl mx-auto px-4 py-12">
105 |         {/* Title */}
106 |         <h1 className="font-serif text-4xl md:text-5xl text-primary text-center mb-4">
107 |           Study Progress
108 |         </h1>
109 |
110 |         <p className="font-sans text-muted-foreground text-center mb-4">
111 |           Track your learning hours over time
112 |         </p>
113 |
114 |         {/* Chart Type Toggle */}
115 |         <div className="flex justify-center gap-2 mb-8">
116 |           <Button
117 |             onClick={() => setChartType("line")}
118 |             className={`h-10 px-6 font-sans rounded-xl border-2 border-border ${
119 |               chartType === "line"
120 |                 ? "bg-primary text-primary-foreground"
121 |                 : "bg-card text-muted-foreground hover:bg-muted/50"
122 |             }`}
123 |           >
124 |             Line Chart
125 |           </Button>
126 |           <Button
127 |             onClick={() => setChartType("bar")}
128 |             className={`h-10 px-6 font-sans rounded-xl border-2 border-border ${
129 |               chartType === "bar"
130 |                 ? "bg-primary text-primary-foreground"
131 |                 : "bg-card text-muted-foreground hover:bg-muted/50"
132 |             }`}
```

```
133 |          >
134 |            Bar Chart
135 |          </Button>
136 |        </div>
137 |
138 |        <div className="grid md:grid-cols-[200px_1fr] gap-8">
139 |          {/* Subject Filter - only show for line chart */}
140 |          {chartType === "line" && (
141 |            <div className="space-y-2">
142 |              <Button
143 |                onClick={() => setSelectedSubject(null)}
144 |                className={`w-full h-12 font-sans rounded-xl border-2 border-border justify-start ${
145 |                  selectedSubject === null
146 |                    ? "bg-muted text-foreground"
147 |                    : "bg-card text-muted-foreground hover:bg-muted/50"
148 |                }`}
149 |              >
150 |                All Subjects
151 |              </Button>
152 |              {subjects.map((subject) => (
153 |                <Button
154 |                  key={subject}
155 |                  onClick={() => setSelectedSubject(subject === selectedSubject ? null : subject)}
156 |                  className={`w-full h-12 font-sans rounded-xl border-2 border-border justify-start ${
157 |                    selectedSubject === subject
158 |                      ? "bg-muted text-foreground"
159 |                      : "bg-card text-muted-foreground hover:bg-muted/50"
160 |                  }`}
161 |                >
162 |                  {subject}
163 |                </Button>
164 |              ))}
165 |            </div>
166 |          )}
167 |
168 |          {/* Graph */}
169 |          <div className={`bg-card rounded-xl border-2 border-border p-6 ${chartType === "bar" ? "md:col-span-2"
170 |            {chartType === "line" ? (
171 |              lineChartData.length > 0 ? (
172 |                <ResponsiveContainer width="100%" height={300}>
173 |                  <LineChart data={lineChartData}>
174 |                    <XAxis
175 |                      dataKey="date"
176 |                      tick={{ fill: "hsl(var(--muted-foreground))", fontSize: 12 }}
177 |                      axisLine={{ stroke: "hsl(var(--border))" }}
178 |                      tickLine={{ stroke: "hsl(var(--border))" }}
179 |                    />
180 |                    <YAxis
181 |                      tick={{ fill: "hsl(var(--muted-foreground))", fontSize: 12 }}
182 |                      axisLine={{ stroke: "hsl(var(--border))" }}
183 |                      tickLine={{ stroke: "hsl(var(--border))" }}
184 |                      label={{
185 |                        value: "Hours",
186 |                        angle: -90,
```

```
187 |                    position: "insideLeft",
188 |                    fill: "hsl(var(--muted-foreground))",
189 |                  }}
190 |                />
191 |                <Tooltip
192 |                  contentStyle={{
193 |                    backgroundColor: "hsl(var(--card))",
194 |                    border: "2px solid hsl(var(--border))",
195 |                    borderRadius: "0.75rem",
196 |                    fontFamily: "'Playfair Display', serif",
197 |                  }}
198 |                />
199 |                <Line
200 |                  type="monotone"
201 |                  dataKey="hours"
202 |                  stroke={
203 |                    selectedSubject
204 |                      ? SUBJECT_COLORS[selectedSubject] || "hsl(var(--primary))"
205 |                      : "hsl(var(--primary))"
206 |                  }
207 |                  strokeWidth={3}
208 |                  dot={{
209 |                    fill: selectedSubject
210 |                      ? SUBJECT_COLORS[selectedSubject] || "hsl(var(--primary))"
211 |                      : "hsl(var(--primary))",
212 |                    strokeWidth: 2,
213 |                  }}
214 |                />
215 |              </LineChart>
216 |            </ResponsiveContainer>
217 |          ) : (
218 |            <div className="h-[300px] flex items-center justify-center text-muted-foreground font-sans">
219 |              <p>No data to display. Start tracking your study time!</p>
220 |            </div>
221 |          )
222 |        ) : barChartData.length > 0 ? (
223 |          <ResponsiveContainer width="100%" height={300}>
224 |            <BarChart data={barChartData}>
225 |              <XAxis
226 |                dataKey="date"
227 |                tick={{ fill: "hsl(var(--muted-foreground))", fontSize: 12 }}
228 |                axisLine={{ stroke: "hsl(var(--border))" }}
229 |                tickLine={{ stroke: "hsl(var(--border))" }}
230 |              />
231 |              <YAxis
232 |                tick={{ fill: "hsl(var(--muted-foreground))", fontSize: 12 }}
233 |                axisLine={{ stroke: "hsl(var(--border))" }}
234 |                tickLine={{ stroke: "hsl(var(--border))" }}
235 |                label={{
236 |                  value: "Hours",
237 |                  angle: -90,
238 |                  position: "insideLeft",
239 |                  fill: "hsl(var(--muted-foreground))",
240 |                }}
```

```
241 |                />
242 |                <Tooltip
243 |                  contentStyle={{
244 |                    backgroundColor: "hsl(var(--card))",
245 |                    border: "2px solid hsl(var(--border))",
246 |                    borderRadius: "0.75rem",
247 |                    fontFamily: "'Playfair Display', serif",
248 |                  }}
249 |                />
250 |                <Legend
251 |                  wrapperStyle={{
252 |                    fontFamily: "'DM Sans', sans-serif",
253 |                    fontSize: "12px"
254 |                  }}
255 |                />
256 |                {subjects.map((subject) => (
257 |                  <Bar
258 |                    key={subject}
259 |                    dataKey={subject}
260 |                    stackId="a"
261 |                    fill={SUBJECT_COLORS[subject]}
262 |                  />
263 |                ))}
264 |              </BarChart>
265 |            </ResponsiveContainer>
266 |          ) : (
267 |            <div className="h-[300px] flex items-center justify-center text-muted-foreground font-sans">
268 |              <p>No data to display. Start tracking your study time!</p>
269 |            </div>
270 |          )}
271 |        </div>
272 |      </div>
273 |
274 |      {/* Navigation Buttons */}
275 |      <div className="flex justify-center gap-4 mt-12">
276 |        <Button
277 |          asChild
278 |          className="h-12 px-8 font-sans rounded-xl bg-secondary text-secondary-foreground hover:bg-secondary/8
279 |        >
280 |          <Link to="/">Back to Home</Link>
281 |        </Button>
282 |        <Button
283 |          asChild
284 |          className="h-12 px-8 font-sans rounded-xl bg-muted text-muted-foreground hover:bg-muted/80 border-2 b
285 |        >
286 |          <Link to="/summary">View Summary</Link>
287 |        </Button>
288 |      </div>
289 |    </main>
290 |
291 |    {/* Footer */}
292 |    <footer className="py-6 text-center">
293 |      <p className="font-serif text-lg text-foreground">Made by Iris for IB CS IA</p>
294 |    </footer>
```

```
295 |     </div>
296 |   );
297 | };
298 |
299 | export default Progress;
300 |
```

61. pages/Summary.tsx

Path: src/pages/Summary.tsx

```
  1 | import { useState, useEffect } from "react";
  2 | import { Link } from "react-router-dom";
  3 | import { X, Plus } from "lucide-react";
  4 | import { Button } from "@/components/ui/button";
  5 | import {
  6 |   Dialog,
  7 |   DialogContent,
  8 |   DialogHeader,
  9 |   DialogTitle,
 10 |   DialogTrigger,
 11 | } from "@/components/ui/dialog";
 12 | import { Input } from "@/components/ui/input";
 13 | import { Label } from "@/components/ui/label";
 14 | import {
 15 |   Select,
 16 |   SelectContent,
 17 |   SelectItem,
 18 |   SelectTrigger,
 19 |   SelectValue,
 20 | } from "@/components/ui/select";
 21 | import { toast } from "@/hooks/use-toast";
 22 |
 23 | interface StudySession {
 24 |   id: string;
 25 |   subject: string;
 26 |   duration: number;
 27 |   date: Date;
 28 | }
 29 |
 30 | const DEFAULT_SUBJECTS = ["Math", "English", "ESS", "French", "Computer Science", "Economics"];
 31 |
 32 | function formatDuration(seconds: number): string {
 33 |   const hours = (seconds / 3600).toFixed(1);
 34 |   return `${hours}h`;
 35 | }
 36 |
 37 | function formatDate(date: Date): string {
 38 |   return date.toLocaleDateString([], {
 39 |     month: "short",
 40 |     day: "numeric",
 41 |     year: "numeric",
 42 |   });
```

```
43 | }
44 |
45 | const Summary = () => {
46 |   const [sessions, setSessions] = useState<StudySession[]>([]);
47 |   const [isAddDialogOpen, setIsAddDialogOpen] = useState(false);
48 |   const [newSubject, setNewSubject] = useState(DEFAULT_SUBJECTS[0]);
49 |   const [newHours, setNewHours] = useState("");
50 |   const [newDate, setNewDate] = useState(new Date().toISOString().split("T")[0]);
51 |
52 |   useEffect(() => {
53 |     const saved = localStorage.getItem("study-sessions");
54 |     if (saved) {
55 |       setSessions(
56 |         JSON.parse(saved).map((s: StudySession) => ({
57 |           ...s,
58 |           date: new Date(s.date),
59 |         }))
60 |       );
61 |     }
62 |   }, []);
63 |
64 |   const handleDeleteSession = (id: string) => {
65 |     const updated = sessions.filter((s) => s.id !== id);
66 |     setSessions(updated);
67 |     localStorage.setItem("study-sessions", JSON.stringify(updated));
68 |     toast({
69 |       title: "Entry deleted",
70 |       description: "The study entry has been removed.",
71 |     });
72 |   };
73 |
74 |   const handleAddEntry = () => {
75 |     if (!newHours || parseFloat(newHours) <= 0) {
76 |       toast({
77 |         title: "Invalid hours",
78 |         description: "Please enter a valid number of hours.",
79 |         variant: "destructive",
80 |       });
81 |       return;
82 |     }
83 |
84 |     const durationInSeconds = parseFloat(newHours) * 3600;
85 |     const newSession: StudySession = {
86 |       id: Date.now().toString(),
87 |       subject: newSubject,
88 |       duration: durationInSeconds,
89 |       date: new Date(newDate),
90 |     };
91 |
92 |     const updated = [newSession, ...sessions];
93 |     setSessions(updated);
94 |     localStorage.setItem("study-sessions", JSON.stringify(updated));
95 |
96 |     setNewHours("");
```

```
    setNewDate(new Date().toISOString().split("T")[0]);
    setIsAddDialogOpen(false);

    toast({
      title: "Entry added",
      description: `${newHours}h of ${newSubject} recorded.`,
    });
  };

  return (
    <div className="min-h-screen bg-background flex flex-col">
      <main className="flex-1 container max-w-2xl mx-auto px-4 py-12">
        {/* Title */}
        <h1 className="font-serif text-4xl md:text-5xl text-primary text-center mb-12">
          Study Summary
        </h1>

        {/* Table Header */}
        <div className="grid grid-cols-[1fr_1fr_1fr_40px] gap-4 px-4 mb-2">
          <span className="font-sans text-sm text-muted-foreground">Subject</span>
          <span className="font-sans text-sm text-muted-foreground text-center">Hours</span>
          <span className="font-sans text-sm text-muted-foreground text-center">Date</span>
          <span></span>
        </div>

        {/* Sessions List */}
        <div className="space-y-2 mb-8">
          {sessions.length === 0 ? (
            <div className="text-center py-12 text-muted-foreground font-sans">
              <p>No entries yet</p>
              <p className="text-sm">Add a study session to see your summary</p>
            </div>
          ) : (
            sessions.map((session) => (
              <div
                key={session.id}
                className="grid grid-cols-[1fr_1fr_1fr_40px] gap-4 items-center p-4 rounded-xl bg-card border-2 b
              >
                <span className="font-sans text-foreground">{session.subject}</span>
                <span className="font-sans text-foreground text-center">
                  {formatDuration(session.duration)}
                </span>
                <span className="font-sans text-foreground text-center">
                  {formatDate(session.date)}
                </span>
                <button
                  onClick={() => handleDeleteSession(session.id)}
                  className="text-foreground hover:text-destructive transition-colors"
                >
                  <X className="w-5 h-5" />
                </button>
              </div>
            ))
          )}
```

```
151 |       </div>
152 |
153 |       {/* Action Buttons */}
154 |       <div className="flex justify-center gap-4">
155 |         <Dialog open={isAddDialogOpen} onOpenChange={setIsAddDialogOpen}>
156 |           <DialogTrigger asChild>
157 |             <Button className="h-12 px-8 font-sans rounded-xl bg-secondary text-secondary-foreground hover:bg-s
158 |               <Plus className="w-5 h-5 mr-2" />
159 |               Add Entry
160 |             </Button>
161 |           </DialogTrigger>
162 |           <DialogContent className="bg-card border-2 border-border">
163 |             <DialogHeader>
164 |               <DialogTitle className="font-serif text-2xl text-primary">
165 |                 Add Study Entry
166 |               </DialogTitle>
167 |             </DialogHeader>
168 |             <div className="space-y-4 mt-4">
169 |               <div>
170 |                 <Label className="font-sans text-foreground">Subject</Label>
171 |                 <Select value={newSubject} onValueChange={setNewSubject}>
172 |                   <SelectTrigger className="mt-1 rounded-xl border-2 border-border">
173 |                     <SelectValue />
174 |                   </SelectTrigger>
175 |                   <SelectContent>
176 |                     {DEFAULT_SUBJECTS.map((subject) => (
177 |                       <SelectItem key={subject} value={subject}>
178 |                         {subject}
179 |                       </SelectItem>
180 |                     ))}
181 |                   </SelectContent>
182 |                 </Select>
183 |               </div>
184 |               <div>
185 |                 <Label className="font-sans text-foreground">Hours</Label>
186 |                 <Input
187 |                   type="number"
188 |                   step="0.5"
189 |                   min="0"
190 |                   value={newHours}
191 |                   onChange={(e) => setNewHours(e.target.value)}
192 |                   placeholder="e.g., 1.5"
193 |                   className="mt-1 rounded-xl border-2 border-border"
194 |                 />
195 |               </div>
196 |               <div>
197 |                 <Label className="font-sans text-foreground">Date</Label>
198 |                 <Input
199 |                   type="date"
200 |                   value={newDate}
201 |                   onChange={(e) => setNewDate(e.target.value)}
202 |                   className="mt-1 rounded-xl border-2 border-border"
203 |                 />
204 |               </div>
```

```
205 |                <Button
206 |                  onClick={handleAddEntry}
207 |                  className="w-full h-12 font-sans rounded-xl bg-primary text-primary-foreground hover:bg-primary
208 |                >
209 |                  Add Entry
210 |                </Button>
211 |              </div>
212 |            </DialogContent>
213 |          </Dialog>
214 |
215 |          <Button
216 |            asChild
217 |            className="h-12 px-8 font-sans rounded-xl bg-muted text-muted-foreground hover:bg-muted/80 border-2 b
218 |          >
219 |            <Link to="/progress">View Graph</Link>
220 |          </Button>
221 |        </div>
222 |
223 |        {/* Back to Home */}
224 |        <div className="flex justify-center mt-8">
225 |          <Button
226 |            asChild
227 |            variant="ghost"
228 |            className="font-sans text-muted-foreground hover:text-foreground"
229 |          >
230 |                <Link to="/">!• Back to Home</Link>
231 |          </Button>
232 |        </div>
233 |      </main>
234 |
235 |      {/* Footer */}
236 |      <footer className="py-6 text-center">
237 |        <p className="font-serif text-lg text-foreground">Made by Iris for IB CS IA</p>
238 |      </footer>
239 |    </div>
240 |  );
241 | };
242 |
243 | export default Summary;
244 |
```

62. vite-env.d.ts

Path: src/vite-env.d.ts

```
1 | /// <reference types="vite/client" />
2 |
```