

AC/DC Clamp Meter



ST-3600



ST-3602

FEATURES

- 3½ digit LCD with maximum reading of 1999.
- Over range indication : "1" is displayed on highest digit.
- Low battery indication: "B" sign appears on the display.
- Response time: approx. 1 second.
- Data hold: for all ranges

SPECIFICATIONS

	ST-3600	ST-3602
AC A	200 / 1500A ±(2.0%rdg+4dgt) (40Hz-1kHz)	200 / 1500A ±(2.0%rdg+4dgt) (40Hz-1kHz)
AC V	200 / 750V ±(1.5%rdg+2dgt) (40Hz-1kHz)	200 / 750V ±(1.5%rdg+2dgt) (40Hz-1kHz)
DC A	200 / 1500A ±(2%rdg+4dgt)	200 / 1500A ±(2%rdg+4dgt)
DC V	20 / 200 / 1000V ±(1%rdg+2dgt)	200 / 1000V ±(1%rdg+2dgt)
Ω	200 / 1500Ω ±(1.5%rdg+2dgt)	200 / 1500Ω ±(1.5%rdg+2dgt)
Diode check	0-1500mV ±(1.5%rdg+2dgt)	0-1500mV ±(1.5%rdg+2dgt)
Buzzer	—	Resistance is less than 100Ω
Conductor size	55mm Max.	55mm Max.
Operating temperature	0°C ~ 40°C	
Humidity	85% R.H.	
Current consumption	Approx. 10mA	
Dimensions	245(L) × 70(W) × 41.7(D)mm	
Weight (battery Included)	Approx. 480g	
Power source	9V(6F22) × 1	
Accessories	Instruction manual Test leads Soft pouch Battery	