

TECHNICAL DATA

Fluke 303 Clamp Meter



Key features

- 600 A ac current measurement
- Cat IV 300V / CAT III 600V safety rated
- 30 mm jaw size for numerous applications
- Resistance range of 40 kΩ
- Slim, ergonomic design is easy to carry and simple to use
- Easy to read backlight display

Product overview: Fluke 303 Clamp Meter

Compact. Easy to use. Fluke tested.

The Fluke 303 comes with all the rugged, reliable and accurate features you have come to trust, in a small, ergonomic design. The innovative body design offers a more compact tool to meet your needs. With features of AC current measurements up to 600 A, a large 30 mm jaw opening and CAT IV 300 V/CAT III 600 V safety rating, you get an easy-to-use tool that handles your everyday electrical maintenance needs.

Specifications: Fluke 303 Clamp Meter

Technical Specifications



AC current	Range	600.0A
	Accuracy	1.8% ±5
AC voltage	Range	400/600
	Accuracy	1.5% ±5
DC voltage	Range	400/600
	Accuracy	1.5% ±5
DC mV range		-
Resistance	Range	4000 Ω
	Accuracy	1% ±5
Continuity		≤ 70 Ω
Backlight display		Yes
Data hold		Yes
Size	H x W x D (mm)	208 x 58.5 x 28
	Jaw size	30 mm
Safety rating		CAT III 600 V
Temperature		0 ~ 40 °C
Screen refresh rate		> 2 times / sec.
Test leads		TL75
Battery		2 AA batteries
Warranty		2 years



Ordering information



Fluke 303

Compact. Easy to use. Fluke tested.

The Fluke 303 comes with all the rugged, reliable and accurate features you have come to trust, in a small, ergonomic design. The innovative body design offers a more compact tool to meet your needs. With features of AC current measurements up to 600 A, a large 30 mm jaw opening and CAT IV 300 V/CAT III 600 V safety rating, you get an easy-to-use tool that handles your everyday electrical maintenance needs.

Includes:

- Clamp Meter
- Two AA Batteries
- User's Manual
- Test Leads
- Two-year Warranty



Fluke. Keeping your world up and running.®

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

For more information call: In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2024 Fluke Corporation. Specifications subject to change without notice. 07/2024

Modification of this document is not permitted without written permission from Fluke Corporation.