



Search:

Not logged in

[Reference](#) [<ios>](#) [noshowpos](#) [register](#) [log in](#)

C++

Information

Tutorials

Reference

Articles

Forum

Reference

Library:

Containers:

Input/Output:

<fstream>

<iomanip>

<ios>

<iosfwd>

<iostream>

<istream>

<ostream>

<sstream>

<streambuf>

Multi-threading:

Other:

<ios>

types:

basic_ios

fpos

ios

ios_base

io_errc

streamoff

streampos

streamsize

wios

wstreampos

manipulators:

boolalpha

dec

defaultfloat

fixed

hex

hexfloat

internal

left

noboolalpha

noshowbase

noshowpoint

noshowpos

noskipws

nounitbuf

nouppercase

oct

right

scientific

showbase

showpoint

showpos

skipws

unitbuf

uppercase

other functions:

istream_category

function

<ios> <iostream>

std::noshowpos

`ios_base& noshowpos (ios_base& str);`

Do not show positive signs

Clears the showpos format flag for the *str* stream.

When the showpos format flag is not set, no plus signs precede positive values inserted in *str*.

This flag can be set with the [showpos](#) manipulator, which forces the writing of a plus sign (+) before every non-negative numerical value inserted into the stream (including zeros).

For standard streams, the showpos flag is **not set** on initialization.

Parameters

str

Stream object whose *format flag* is affected.
Because this function is a manipulator, it is designed to be used alone with no arguments in conjunction with the *insertion* (<<) and *extraction* (>>) operations on streams (see example below).

Return Value

Argument *str*.

Example

```
1 // modify showpos flag
2 #include <iostream>      // std::cout, std::showpos, std::noshowpos
3
4 int main () {
5     int p = 1;
6     int z = 0;
7     int n = -1;
8     std::cout << std::showpos << p << '\t' << z << '\t' << n << '\n';
9     std::cout << std::noshowpos << p << '\t' << z << '\t' << n << '\n';
10    return 0;
11 }
```

Possible output:

+1	+0	-1
1	0	-1

Data races

Modifies *str*. Concurrent access to the same stream object may cause data races.

Exception safety

Basic guarantee: if an exception is thrown, *str* is in a valid state.

See also

showpos	Show positive signs (function)
ios_base::flags	Get/set format flags (public member function)
ios_base::setf	Set specific format flags (public member function)
ios_base::unsetf	Clear specific format flags (public member function)

Engineering Consultants

Development of hardware a. software for military and industrial

● ○

Home page | Privacy policy

© cplusplus.com, 2000-2015 - All rights reserved - v3.1

Spotted an error? [contact us](#)