



Search:

[Reference](#)
[<ios>](#)
[noskipws](#)

[register](#)
[log in](#)

C++

[Information](#)
[Tutorials](#)
[Reference](#)
[Articles](#)
[Forum](#)

Reference

C library:

Containers:

Input/Output:

<fstream>

<iomanip>

<ios>

<iosfwd>

<iostream>

<istream>

<ostream>

<sstream>

<streambuf>

Multi-threading:

Other:

<ios>

types:

basic_ios

fpos

ios

ios_base

io_errc

streamoff

streampos

streamsize

wios

wstreampos

manipulators:

boolalpha

dec

defaultfloat

fixed

hex

hexfloat

internal

left

noboolalpha

noshowbase

noshowpoint

noshowpos

noskipws

nounitbuf

nouppercase

oct

right

scientific

showbase

showpoint

showpos

skipws

unitbuf

uppercase

other functions:

istream_category

C++ Function

Free Answers to Your C++ Language Questions. Register Now!

function

std::noskipws

<ios> <iostream>

```
ios_base& noskipws (ios_base& str);
```

Do not skip whitespaces

Clears the skipws format flag for the *str* stream.

When the skipws format flag is not set, all operations on the stream consider initial whitespace characters as valid content to be extracted.

Tab spaces, carriage returns and blank spaces are all considered whitespaces (see [isspace](#)).

This flag can be set with the [skipws](#) manipulator. When set, as many initial whitespace characters as necessary are read and discarded from the stream until a non-whitespace character is found. This would apply to every formatted input operation performed with [operator>>](#) on the stream.

Notice that many extraction operations consider the whitespaces themselves as the terminating character, therefore, with the skipws flag disabled, some extraction operations may extract no characters at all from the stream.

For standard streams, the skipws flag **is set** on initialization.

Parameters

str

Stream object whose *format flag* is affected.

Because this function is a manipulator, it is designed to be used alone with no arguments in conjunction with the *insertion* (<<) and *extraction* (>>) operations on streams (see example below).

Return Value

Argument *str*.

Example

```
1 // skipws flag example
2 #include <iostream>      // std::cout, std::skipws, std::noskipws
3 #include <sstream>       // std::stringstream
4
5 int main () {
6     char a, b, c;
7
8     std::stringstream iss (" 123");
9     iss >> std::skipws >> a >> b >> c;
10    std::cout << a << b << c << '\n';
11
12    iss.seekg(0);
13    iss >> std::noskipws >> a >> b >> c;
14    std::cout << a << b << c << '\n';
15    return 0;
16 }
```

Output:

```
123
1
```

Notice that in the first set of extractions, the leading spaces were ignored, while in the second they were extracted as valid characters.

Data races

Modifies *str*. Concurrent access to the same stream object may cause data races.

Exception safety

Basic guarantee: if an exception is thrown, *str* is in a valid state.

See also

skipws

Skip whitespaces (function)

ios_base::flags

Get/set format flags (public member function)

	ios_base::setf	Set specific format flags (public member function)
	ios_base::unsetf	Clear specific format flags (public member function)
<div>Home page Privacy policy</div> <div>© cplusplus.com, 2000-2015 - All rights reserved - v3.1</div> <div>Spotted an error? contact us</div>		