

Libraries/Testing in Java

Libraries

- Included in your project via jar files
- Use a build tool or the jar executable (included in JDK) to create a jar file of your project
- To include a library jar add it on the classpath
 - See example
- Many (many) libraries available for Java.
 - Search online -> maven central repository is best source for quality libraries
 - If the problem is encountered by more than one person there's probably a library available (so search before creating your own)
- We'll cover Guava, Jackson, Mockito and Junit today

Guava

- Provides a large amount of supplemental “core” Java type functionality
 - New Collections
 - Caching
 - String utilities
 - Optionals
- See <https://code.google.com/p/guava-libraries/wiki/GuavaExplained>
- Examples!

Guava - Optional

```
1 public class Optionals {
2
3     public static void main(String[] args) {
4         Optionals optionals = new Optionals(Collections.<String, String>emptyMap());
5         String key = "foo";
6         Optional<String> value = optionals.getValue(key);
7         if (value.isPresent()) {
8             System.out.printf("Value mapped to %s is %s\n", key, value.get());
9         } else {
10             System.out.printf("Nothing mapped to %s", key);
11         }
12     }
13
14     private final Map<String, String> mapping;
15
16     public Optionals(Map<String, String> mapping) {
17         this.mapping = mapping;
18     }
19
20     public Optional<String> getValue(String key) {
21         return Optional.fromNullable(mapping.get(key));
22     }
23
24 }
```

避免
null check

Guava - Immutable Collections

```
1 public class Immutables {  
2  
3     public static void main(String[] args) {  
4  
5         Set<String> days = ImmutableSet.of("Sunday", "Monday", "Tuesday", "Wednesday",  
6             "Thursday", "Friday", "Saturday");  
7  
8         Map<String, Integer> primaryColors = ImmutableMap.<String, Integer>builder()  
9             .put("Red", 0xFF0000)  
10            .put("Yellow", 0xFFFF00)  
11            .put("Blue", 0x0000FF).build();  
12  
13         List<String> mutableSeasons = new ArrayList<>(4);  
14         mutableSeasons.add("Autumn");  
15         mutableSeasons.add("Winter");  
16         mutableSeasons.add("Spring");  
17         mutableSeasons.add("Summer");  
18  
19         List<String> seasons = ImmutableList.copyOf(mutableSeasons);  
20  
21     }
```

final

*用 builder 产生的
都是 immutable*

```
23 }
```

Guava - Collections

- See <https://code.google.com/p/guava-libraries/wiki/NewCollectionTypesExplained> for all types

```
1 public class Collections {
2
3     public static void main(String[] args) {
4
5         Multimap<String, Integer> homeworkGrades = new HashMultimap<>();
6
7         homeworkGrades.putItem("Brian", 88);
8         homeworkGrades.putItem("Brian", 90);
9         homeworkGrades.putItem("Brian", 77);
10        homeworkGrades.putItem("Brian", 95);
11        homeworkGrades.putItem("Amey", 95);
12        homeworkGrades.putItem("Amey", 99);
13        homeworkGrades.putItem("Amey", 92);
14
15        Multiset<String> wordCounts = HashMultiset.create();
16        wordCounts.add("Age of Innocence", 12);
17        wordCounts.add("Moby Dick");
18        wordCounts.add("Age of Innocence");
19        wordCounts.add("Tale of Two Cities");
20
21        BiMap<String, String> names = HashBiMap.create();
22        names.put("Brian", "Langel");
23
24        // names.keySet -> {"Brian"}
25        BiMap<String, String> inverted = names.inverse();
26        // inverted.keySet -> {"Langel"}
27    }
28
29 }
```

Guava - Caching

```
1 public class Caches {
2
3     public static void main(String[] args) {
4
5         CacheLoader<String, String> loader = new CacheLoader<String, String>() {
6             @Override public String load(String key) throws Exception {
7                 return Caches.load(key);
8             }
9         };
10
11         // max - sized
12         LoadingCache<String, String> cache = CacheBuilder.newBuilder().maximumSize(1000L).build(loader);
13
14         // expire after access
15         cache = CacheBuilder.newBuilder().expireAfterAccess(12, TimeUnit.DAYS).build(loader);
16
17         // expire after write
18         cache = CacheBuilder.newBuilder().expireAfterWrite(12, TimeUnit.DAYS).build(loader);
19
20     }
21
22     private static String load(String key) {
23         // TODO - load from DB / over the network
24         return key;
25     }
26 }
```

Guava - String Utilities

- See here for reasoning/examples: <https://code.google.com/p/guava-libraries/wiki/StringsExplained#Charsets>

```
1  public class Strings {
2
3      public static void main(String[] args) {
4
5          Joiner joiner = Joiner.on(", ").useForNull("-");
6          String result = joiner.join("Brian", "John", null, "Reggie");
7          assert result.equals("Brian, John, -, Reggie");
8
9          joiner = Joiner.on(", ").skipNulls();
10         result = joiner.join("Brian", "John", null, "Reggie");
11         assert result.equals("Brian, John, Reggie");
12
13         Iterable<String> split = Splitter.on(",")
14             .omitEmptyStrings()
15             .trimResults().split(result);
16         for (String value : split) {
17             System.out.printf("%s%n", value);
18         }
19     }
20 }
```


Jackson - Easy JSON

- See here for information / examples: <https://github.com/FasterXML/jackson>

```
1 public class Person {
2
3     private final String firstName;
4
5     private final String lastName;
6
7     private Person() {
8         this(null, null);
9     }
10
11     public Person(String firstName, String lastName) {
12         this.firstName = firstName;
13         this.lastName = lastName;
14     }
15
16     public String getFirstName() {
17         return firstName;
18     }
19
20     public String getLastName() {
21         return lastName;
22     }
23
24     @Override public boolean equals(Object o) {
```

```
1 public class Jacksons {
2
3     public static void main(String[] args) throws IOException {
4         ObjectMapper mapper = new ObjectMapper();
5
6         Person person = new Person("Brian", "Langel");
7         String value = mapper.writeValueAsString(person);
8
9         System.out.printf("%s%n", value);
10
11         Person deserialized = mapper.readValue(value, Person.class);
12         assert "Brian".equals(deserialized.getFirstName());
13         assert "Langel".equals(deserialized.getLastName());
14     }
15
16 }
```

Testing (unit testing in particular)

- Good developers always unit test.
- Testing code by units (i.e. methods) makes reasoning about the correctness of your code much easier.
- Testing ensures you've correctly created working code
 - I.e., "A Person object can be serialized and deserialized by Jackson" -> make a unit test to ensure this.
- Testing also ensures the integrity of your assumptions across time.
 - I.e., "No one should pass null to this method" -> make a unit test to ensure this.
- Testing also allows you to refactor with confidence.
 - I.e., "I want to rewrite this method but am unsure if it'll break other portions of the code base" -> if everything has unit tests you can refactor with confidence.

JUnit - Framework for Unit Testing

- Only going to cover version 4 and above which leverages annotations.

```
1 public class PersonTest {
2
3     @Test
4     public void json() throws IOException {
5         ObjectMapper mapper = new ObjectMapper();
6         Person person = new Person("Brian", "Langel");
7         String serialized = mapper.writeValueAsString(person);
8         assertEquals("{\"firstName\":\"Brian\",\"lastName\":\"Langel\"}", serialized);
9
10        Person deserialized = mapper.readValue(serialized, Person.class);
11        assertEquals("Brian", deserialized.getFirstName());
12        assertEquals("Langel", deserialized.getLastName());
13    }
14
15 }
```

JUnit static method

二名相称

检查出现问题则会抛出 AssertionError

没有 error 则程序没问题

JUnit

- By convention, put test classes in **src/test**
- By convention, name the test class **ClassNameToBeTestedTest**
 - The class name with the **Test** suffix *For 测试*
- By convention, write a unit test for every public method
 - Also a good practice to test private/protected/default methods as well - necessitates using reflection
- By convention, name the unit test method the same as the method being tested.
- To mark a method as a testing method annotate it with **@Test**
- To invoke code prior to every test, make a method and annotate it with **@Before** *测试前执行的代码*
- To invoke code after every test, make a method and annotate it with **@After**
- Can ignore tests by annotating the method with **@Ignore**

Better Unit Testing - Mockito

- Often when unit testing you'll want to “mock” the implementation of a class so that you can test all scenarios.
 - For instance, how to test this class?

```
1 public class Jsons {
2
3     private final ObjectMapper mapper;
4
5     public Jsons(ObjectMapper mapper) {
6         this.mapper = mapper;
7     }
8
9     public void serialize(Object value, FileOutputStream stream) {
10         try {
11             mapper.writeValue(stream, value);
12         } catch (IOException ioe) {
13             throw new RuntimeException(ioe);
14         }
15     }
16
17     public <T> T deserialize(Class<T> type, FileInputStream stream) {
18         try {
19             return mapper.readValue(stream, type);
20         } catch (IOException ioe) {
21             throw new RuntimeException(ioe);
22         }
23     }
24 }
```

Mockito - Mocking Objects

```
1 public class JsonsTest {
2
3     @Test
4     public void serialize() throws IOException {
5         ObjectMapper mapper = mock(ObjectMapper.class);
6         Jsons jsons = new Jsons(mapper);
7
8         FileOutputStream stream = mock(FileOutputStream.class);
9         Person person = new Person("Brian", "Langel");
10
11         doThrow(new IOException()).when(mapper).writeValue(eq(stream), eq(person));
12
13         try {
14             jsons.serialize(person, stream);
15             fail("Expecting a RuntimeException as ObjectMapper should throw an IOException");
16         } catch (RuntimeException re) {
17             // expected
18         }
19
20         verify(mapper, times(1)).writeValue(eq(stream), eq(person));
21         verifyNoMoreInteractions(mapper);
22     }
23
24     @Test
25     public void deserialize() throws IOException {
26         ObjectMapper mapper = mock(ObjectMapper.class);
27         Jsons jsons = new Jsons(mapper);
28
29         FileInputStream stream = mock(FileInputStream.class);
30
31         when(mapper.readValue(eq(stream), eq(Person.class))).thenThrow(new IOException());
32
33         try {
34             jsons.deserialize(Person.class, stream);
35             fail("Expecting a RuntimeException as ObjectMapper should throw an IOException");
36         } catch (RuntimeException re) {
37             // expected
38         }
39
40         verify(mapper, times(1)).readValue(eq(stream), eq(Person.class));
41         verifyNoMoreInteractions(mapper);
42     }
43 }
```

Mockito (cont)

- See <https://code.google.com/p/mockito/> for more examples
- Most important methods are
 - mock -> given a class returns a “mocked” object of that type
 - when -> given a mock will allow you to control the behavior
 - verify -> verifies that the expected method calls happened on the object
- Keep in mind that final classes and final methods **cannot** be mocked
 - This is an artifact of how mockito leverages the Java language to perform its “magic”
 - as it uses Reflection, subclassing and proxies

Questions

- Regarding libraries?
- Regarding testing?