Notes 6

Command Definitions

1. **mkdir** command
    1. **Definition** - the mkdir command is used to create a new directory or folder in linux
    2. **Usage/Formula**
        1. `mkdir [directory_name]`
    3. **Example**
        1. `mkdir Website` - creates a folder/directory named "Website"
2. **touch** command
    1. **Definition** - the touch command creates an empty new file
    2. **Usage/Formula**
        1. `touch [file_name]`
    3. **Example**
        1. `touch index.html` - creates an empty html file
3. **rm** command
    1. **Definition** - the rm command deletes files and folders
    2. **Usage/Formula**
        1. `rm [file_name]`
    3. **Example**
        1. `rm index.html` - deletes the index.html file
4. **cp** command
    1. **Definition** - the cp command copies files or folders from one location to another while keeping the original file in its original location
    2. **Usage/Formula**
        1. `cp [file/folder name] [destination]`
    3. **Example**
        1. `cp Website Desktop/` - copies the Website directory to desktop directory
5. **mv** command
    1. **Definition** - the mv command can move files and folders from one location to another and rename them
    2. **Usage/Formula**
        1. `mv [file_name] [new destination]`
    3. **Example**
        1. `mv index.html Documents/website.html` - moves the index.html file to the Documents directory while renaming it to website.html