

A Cognitive Science Meta-Analysis of Schema-Driven Scaffolds in Object-Oriented Programming for Neurodivergent Learners

Tchaas Alexander-Wright
CS-6795 Intro to Cognitive Science
Summer 2026 – Literature Review

Abstract—The traditional teachings of computer science show-cases codes as a dense wall of text that students read line by line. The learning of a new programming language places heavy demand on working memory, which most individuals can only hold about seven pieces of information at a time. For entry level programmers with ADHD or autism, this overload adds extraneous cognitive load which mental effort does not help learning, creates barriers tied to executive function, and raises the rate at which students give up while learning object-oriented programming (OOP). The paper presents a systematic, interdisciplinary review of how schema-driven, pattern-based visuals supports affects three skills in Java and C++ such as remembering syntax, writing working code, and finding bugs. Reviewing fifteen peer-reviewed sources from human-factors, computing, clinical psychology, and computer science education, will highlight the stages of learning OOP onto three cognitive science ideas such as mental schemas, analogical mapping, and distributed cognition. The information would suggest that turning abstract class hierarchies into stable visual blocks and showing errors as breaks in a visible shape would help students use working memory more efficiently. By moving the job of tracking program state out of the mind and onto the screen would shorten the delays before ADHD learners can start a task that makes uses of the strong pattern-matching ability common in autistic learners. The paper would conclude with design principles for inclusive programming tools and suggestions for future research.

I. INTRODUCTION AND PROBLEM STATEMENT

The introductory courses in Object-Oriented Programming (OOP) typically are taught in languages such as Java and C++ and asks students to manage the small details of syntax and the larger logic of how programing works at the same time. Student would have to keep tract of abstract pieces of codes such as visibility modifiers, variable types, encapsulation blocks, and scope markers. When processing this information, it creates an immediate bottleneck, because human working memory can hold about seven chunks of information at a time [1]. When too much of that limited space goes to reading and parsing notations, students would face heave extraneous cognitive load in which the effort spends on the surface form of code rather than its meaning. This leaves little room for germane cognitive load in which the productive effort of building a lasting mental model of how the program behaves

[3]. For neurodivergent learners this heavy dependency on text creates a serious problem at three key states of learning OOP.

Research Question: “How does existing cognitive science and programming education explain the role of schema-driven, visual, and pattern-based learning supports for object-oriented programming comprehension, implementation, and debugging for individuals that have ADHD and/or autism?”

A. Syntax Learning Barriers

People that have ADHD often find it hard to manage attention, hold back impulses, and staying focus. Individuals with ADHD must face rows of code that all look alike, they can tire quickly, abandon the task, and often leave out small marks such as semicolons. People that have autism are often very good at systemizing rule-based patterns out of objects they are viewing [4]. The heavy coding environments hide the big-picture structure of a program behind arbitrary notation. This would force autistic beginners to switch back and forth in working memory to connect written commands with the program functionality.

B. The Implementation Leap

There is a large gap between understanding individual pieces of syntax and developing a complete program. When individuals with ADHD face blank editor, they often cannot get started developing and this is a king of “blank-page paralysis”. By breaking down analogical mapping, the mind cannot find a similar past example (a sources case) in the long-term memory to use as a guide [5]. Without having an external structure to depend on, the individual would lose the working memory as the learner tries to coordinate many code requirements as once.

II. TROUBLESHOOTING AND ERROR DIAGNOSTICS

When the individual code fails, the traditional tools report the problem as long lines of text. For someone with ADHD, reading the large components of text is mentally difficult and forces constant switching of attention. These tools do not show errors visually or shape-based problems, learners cannot easily match a new error to ones they have viewed previously. This

makes it difficult for individuals to store useful “failed case” records in long-term memory [8].

III. PROPOSED THESIS

To reduce these problems and building on the pattern-matching strengths of neurodivergent learners, the project highlights a systematic review of schema-driven, pattern-based cognitive supports in OOP education. Working from the Computational-Representation Understanding of Mind (CRUM), the paper will argue that replacing lines of text with stable visuals shapes lets teaching tools work around the working-memory bottleneck. They do this by grouping low-level code rules into mental schemas [15].

IV. COGNITIVE LOAD THEORY AND OOP SCHEMA CONSTRUCTION

A. The Textual Bottleneck of Traditional OOP Syntax

When new programmers work with the full-featured OOP languages, they would have to manage a long list of syntax details. Based on Sweller’s Cognitive Load Theory, reading characters, managing formatting, and decoding uniform strings of code all add heavy extraneous load that does not help learning [1]. Managing all these details would limit the working-memory buffer and leaves little room for productive effort of building a working mental model [3].

For neurodivergent learners, the issue is worse because people with ADHD are more likely to overload working memory when scanning columns of similar-looking characters; in which would lead to fatigue from switching attention and delays development [14]. Autistic learners, whose strengths are fixed, rule-based systemizing, find that plain text separates class-inheritance relationship from any visible structure. As a result, the learners must spend mental energy lining up low-level syntax instead of understanding the entire system.

B. Visual Chunking and Schema-Driven Representations

Research in cognitive engineering suggest that redesigning programming tools around visual and schema-based layouts. Thagard highlights that schemas are organized mental structures that hold typical features, part and whole relationships, and open slots that can be applied to new situations [15]. By replacing code characters with stable visual boundaries and containing shapes changes how the rules of programming are processed. Weintrop and Wilensky highlights that presenting variable declarations as color-coded slots, and wrapping algorithms in distinct shapes, lowers syntax errors while improving the understanding of the logic concepts [2].

The schema driven and visual tools for programming takes advantage of chunking [15]. Instead of using separate working-memory slots for keywords such as public class, extends, and an open brace, a nested visual design groups them into a class module [2]. Extraneous load drops help neurodivergent learners put their full mental capacity towards the productive work of solving the algorithm.

V. LITERATURE REVIEW DESIGN

A. Research Question and Scope

The review main question: How much does schema driven, pattern-based visuals support the reduction of cognitive barriers and improve OOP learning for neurodivergent students with ADHD and autism spectrum disorder? The scope covers three areas such as cognitive load and working-memory theory, neurodivergent learning profiles in computing education, and human-factors research on visual supports in programming tools.

B. Source Selection and Search Strategy

The sources were used came from the course readings in cognitive science such as Sweller, Simon, and Thagard whose ideas help shape the framework of this review [1], [7], [15]. The references were expanded by tracing citations and targeting searches in Google Scholar, IEEE Xplore, the ACM Digital Library, and PubMed. The searches fall into three categories: (1) cognitive load, working memory, and chunking; (2) ADHD, autism, neurodivergent, executive function, and (3) block-based programming, visual scaffolding, UML, IDE design. All sources offered useful data, theory, or design ideas tied directly to the research question.

VI. CORPUS AND CONSISTENCY OF FOCUS

The sources include peer-reviewed publications from human factors computing clinical psychology, and computer science education. The focus is consistent throughout because the research question was defined before finding the sources that rooted in the meeting points of CRUM-based cognitive modeling. The accessible programming teaching highlights three main themes of schema construction, analogical scaffolding, and distributed cognition were chosen early and kept steady as the organizing structure across all the sources.

VII. RESULTS

A. Theme 1: Textual OOP Environments Impose Disproportionate Cognitive Costs on Neurodivergent Learners

The clearest pattern across the reviewed work is that standard text-based OOP tools create barriers that fall hardest on neurodivergent learners. Sweller’s Cognitive Load Theory explains the general mechanism, while clinical description explain why ADHD and autistic learners are especially affected [1],[3],[4],[14]. Individuals with ADHD learning to program the differences in executive control increase fatigue from switching attention and making it harder to start task at every stage of learning. Individuals that are autistic learning to program have strong systemizing skills that are blocked rather than used, because text separates structural relationships from any visible form. The literature treats these two different failure modes, although most studies lump them together under novice learner measures [8],[10].

B. Theme 2: Schema-Driven Visual Scaffolds Reduce Extraneous Load Across All Three Milestones

Visuals support will improve the outcomes at each stage of learning OOP. Weintrop and Wilensky highlights that block-based visual tools lowers syntax error rates and improve understanding [2]. Moor, Deek, and the UML literature discuss that the writing stage, showing planned structure before coding reduces blank-page paralysis by supplying a ready-made example to reason [5],[6]. At the debugging stage, Cook et al. show that immediate visual feedback in direct-manipulation tools increases error detection and helps learners remember pass mistakes [9]. Across all three stages the mechanism is the same by turning abstract OOP relationships into stable visual structures lowers extraneous load and frees up productive thinking.

VIII. THEME 3: DISTRIBUTED COGNITION PROVIDES THE UNIFYING THEORETICAL FRAME

Hutchin's framework of distributed cognition provides the full explanation of why visuals support works at a large scale [11]. Individual studies explain that Cognitive Load Theory or through analogical reasoning specific to on task, but the explanation do not transfer well to large, multi-file projects [1],[3],[5]. Hutchin's model highlights that intelligent behavior comes from processing spread across the brain and external physical tools. The coding workspaces should act as the material anchor that moves mental state out of working memory and into the surroundings [11]. Sillito et al. and Rodriguez add evidence that developers speed as much as 35% of their time simply navigating code, but a well-designed visual workspace could remove that dependency.

IX. CONTRADICTION: SCAFFOLD UTILITY VS. SCALABILITY TO INDUSTRIAL LANGUAGES

One clear issue in the literature is the gap between the proven benefits of visual support in a controlled setting and how well it scales to full industrial OOP languages. Block-based tools succeed at removing extra syntax load but hide features such as pointer arithmetic, manual memory management, and compiler-specific behavior that learners must eventually master in object-oriented languages [2]. Simon's framework highlights that any model of thinking must respect the hard limits of the real task environment [7]. The literature does not offer an agreed way to close the gap with a step by step, which makes the central unresolved problem in the field.

X. ANALOGICAL SCAFFOLDING AND THE IMPLEMENTATION LEAP

A. The Cognitive Penalty of Blank-Page Task Initialization

By transitioning from remembering isolated OOP terms to building a complete program is a major break in the learning process. Real programming requires a top-down planning, mapping structures, and developing manageable goals [5]. When individuals face a blank editor, learners with executive control differences often have issues getting started. The analogical mapping would solve a new problem by retrieving

a structurally similar past example from long-term memory [5]. Text editors do not provide external structure to lean on, so individuals with ADHD would hold abstract code requirements, pointer scopes, and execution order entirely in the mind and quickly causing bottlenecks and fatigue.

B. UML Blueprints as Externalized Cognitive Schemas

Human-factor research in computing identifies Unified Modeling Language (UML) class diagrams as roadmaps for crossing this gap [5]. Instead of forcing learners to trace code paths in their heads, a UML diagram would make object hierarchies visible through simple shapes such as inheritances arrows, boxes marking visibility, and links to dependencies [6]. Building on Simon's layered systems, this type of diagram supports near-decomposability which is a codebase that can be broken into separate, self-contained outlines, so a single class can be examined without losing sight of the whole [7]. The diagram works as a stable external memory aid, cutting the split-attention problem by gathering requirements into clear visual symbols [11], [6]. For autistic learners with strong systemizing skills, a clean UML layout converts the writing stage from an open-ended planning task into low-stress and step-by-steps.

XI. COGNITIVE DEBUGGING PATTERNS AND THE ARCHIVING OF FAILED CASES

A. Semantic Misconceptions and Compiler Trace Fatigue

When an OOP program fails to compile or does not function as expected, the tools today would report the problem as long text logs and deep memory stack traces. Reading a message such as `NullPointerException` means decoding the text and matching it to an invisible mental picture of the program functions [8], [10]. Research in educational software highlights that the process drains beginner's working memory and can drive solo-troubleshooting abandonment rates as high as 41% [8]. For individuals with ADHD, the lack of visual or spatial framing forces constant switching between source files, lines numbers, and terminal output, which impacts their limited attention and leads to discouragement.

B. The Cognitive Role of Failed Cases in Schema Revision

In cognitive science, debugging is a clear loop of testing, checking, and revising schemas [1]. As Case-Based Reasoning (CBR) shows failed cases have a special value which successful cases tell individuals what to do, but failed cases act as guards that showcase what should not do [5]. The long-term memory, the failure must be understood and not fixed by blind trial and error.

Visual engineering research helps by turning debugging into a visual pattern-matching task [9]. For autistic learners with strong systemizing skills would be able to break in a system's regular pattern easily and spot when visuals are available [4]. When a tool shows an out-of-bounds error as a distortion in a loop block or class shape, the learner can visually locate the logic error [9]. Cook et al. highlights that immediate visual feedback in direct-manipulation tools improves error detection

compared with text-only debugging [9]. The learner would be

able to file the mistake away cleanly as a “failed case” and build a mental guard against repeating it.

Traditional Text-Based Output



Schema-Driven Visual Representation




Fig. 1. Traditional Text-Based Output and Schema-Driven Visual Representation

XII. DISTRIBUTED COGNITION AND LARGE CODEBASE COMPREHENSION

A. The Cognitive Overhead of Non-Linear Code Exploration

As software develops into large, complex systems, the ability to understand it no longer is a straight-line process. Navigating through the large codebase forces developers into a scattered, non-linear pattern that consist of jumping across nested folders, following chains of methods calls, and keeping dozens of files open at once [12]. Rodriquez highlights that reading across many disconnected views creates a heavy mental overhead, because the developer would need to keep track of hidden cross-references and constantly switch context [13]. Developers spend up to 35% of their time just navigating code to rebuild lost context [12].

For individuals with ADHD, moving through many files is an immediate barrier because there is a difference in executive function that makes it hard to hold long chains of file relationships in mind without visual cues which leads to disorientation and loss of focus. For autistic developers, when a tool splits an object-oriented relationship across separate text-only folders, the underlying structure becomes invisible. This forces individuals with ADHD and autism to spend their mental budget on blind text searches instead of applying their systemizing strengths to the architecture [4].

B. IDE Frameworks as Material Anchors for Distributed Cognition

To prevent mental exhaustion and support neurodivergent focus, development tools should be built around distributed cognition [11]. Hutchins highlights that intelligent behavior emerges when processing is shared between the brain and external physical tools [11]. To work pass the working memory

ceiling while exploring a codebase, the tool must act as a material anchor for developer’s mental map [1],[11]. A neurodivergent-friendly environment would help the relationship paths out into the visible workspace which is where drawing lives, interactive dependency graphs, and filling side panels with relevant method definitions based on where the cursor is located so the tracking file state no longer is dependent on the individual [12]. This turns a complex, multi-layer lookup into a simple visual scanning, protecting executive-function resources and letting users explore large systems without tiring themselves.

XIII. DISCUSSION

A. Implications for Cognitive Science

The review findings are important for the matters of how cognitive science models human learning with technology. The first is the fact that schema-driven visual support helps at all three stages of learning OOP gives behavioral evidence for a core CRUM claim that the format of information is not just content, but shapes how it is processed and stored [15]. Basically, the choices how to represent information is a first-class factor in designing cognitive systems.

The second finding is the different effects of visual support on ADHD versus autistic learners confirms that these are different cognitive profiles with different ideal conditions, not simply weaker versions of typical processing [4],[14]. One well-designed visual tool can ease attention bottlenecks for ADHD learners while switching on systemizing strengths for autistic learners suggests that external representations can serve as a common ground that supports several kinds of minds without needing a separate system for each.

The third is applying Hutchin’s distributed cognition framework to IDE design extends that model beyond its original

settings [11]. If the layout of a development environment changes how well it users can reason, then the IDE design is not only a software engineering question but a cognitive engineering problem. It should follow the same principles used for cockpits, operating rooms, and air-traffic-control systems.

B. Real-World Applications

The findings point to practical design principles for three groups. For computer science educators suggest that making UML diagramming a required first step before coding compared to optional add on that could noticeably reduce blank-page paralysis for neurodivergent students without needing separate accommodations [5],[6]. For IDE developers, the material-anchor idea gives a concrete specification that live dependency graphs, context-sensitive method panels, and persistent class visuals should be treated as tools for managing cognitive load and not as decoration [11],[12]. For accessibility policymakers in computing education, the review supports moving from an accommodation model toward universal design built into the learning environment itself and leveling the cognitive playing field during instruction rather than fixing problems afterward.

XIV. LIMITATIONS AND METHODOLOGICAL GAPS

A. Diagnostic Conflation and Cohort Granularity

The main weakness is that current computer science student education research is only study groups are rarely broken down by diagnosis. While human-factors studies test block-based tools and visual scaffolds on general student groups, but very few peer-reviewed studies separate out clinically diagnosed neurodivergent subgroups [2],[5],[6],[8],[10]. This is important because ADHD and autism works differently, Barkley highlights that ADHD bottlenecks are centered on scattered attention and troubles getting started, while Baron-Cohen shows that autistic learners have strong systemizing ability tuned for rule-based matching when the surface layout lines up with the underlying structure [4],[14]. By folding these two groups into a single accessible learning category, the literature hides which support groups actually needs the tools that fixes split attention problems for ADHD learners and does not support the switch on anomaly-detection strengths of an autistic learner [4],[6],[9],[13].

B. The Granularity Gap across Marr's Tri-Level Tiers

Based on Marr's Tri-Level hypothesis there are clear mismatch between what accessible-programming tools claim and how those claims are tested [16]. Marr calls for explanation at three separate levels such as computational level (the problem and its constraints), the algorithmic/representation level (the data structures and the rules that transform symbols), and the implementation level (the physical or biological hardware) [16]. The literature works almost entirely at the computational level, watching high-level inputs and outputs [2],[5]. There are no studies that use tools such as eye-tracking grids, after-the fact protocol analysis, or cognitive-architecture simulations

such as ACT-R or SOAR) to trace the exact symbol-by-symbol steps inside a neurodivergent learner's working memory during visual block work. Without checking those step-by-step processes, claims about how psychologically realistic blocked-based tools will remain mostly guesswork.

XV. LANGUAGE AGNOSTICISM VERSUS LOWER-LEVEL C++ REALITIES

A final gap is the heavy reliance on simple, language-neutral visual tools such as Scratch to make broad claims about how beginners learn [2]. Block tools do remove extra syntax load for early tasks, but they struggle to capture how industrial OOP truly operates. Block interfaces hid lower-level details such as manual memory management, pointer logic, call-by-reference addresses, and compiler-specific hardware bindings. Simon highlights that an agent's internal rules must satisfy the hard limits of the outside task environment [7]. By hiding these realities, language neutral tools fail to give a model that scales and it leaves neurodivergent learners unprepared for the text-heavy demands of industrial languages.

XVI. CONCLUSION

A. Summary of Key Insights

The purpose of this paper is to showcase the interdisciplinary review of the syntax and executive barriers that learners with ADHD and autism face while learning OOP in Java and C++. The main finding is that schema-driven, pattern-based cognitive support are grounded in CRUM but offers an evidence-based way to address these barriers at all three stages of learning. Visual, shaped-based block environments group arbitrary commands into stable mental schemas [2],[3]. UML blueprints supply ready-made examples that enable analogical mapping without freezing up, and visual error displays will speed up the storing of failed cases in long-term memory [5],[6], [9]. Hutchin's distributed cognition framework ties these findings together under one principle which is the IDE workspace should act as a material anchor that moves mental state out of working memory and into the environment [11].

B. Directions for Future Work

Future studies should use more careful screening so they can measure the separate, long-term effects of visual supports on clearly defined ADHD and autistic groups. Research should close the gap across Marr's three level by using algorithmic-level tools such as eye-tracking grids, after-the-fact protocol analyses, and cognitive-architecture simulations to trace the exact symbolic steps inside a neurodivergent learner's working memory during visual block work [16]. Lastly, cognitive engineers should design representations that scale such as ones that keep the friendly simplicity of block-based tools while still respecting the low-level demands of industrial OOP languages. Then start to gradually introduce features such as pointers and manual memory management through adaptive visuals that do not overload the learners.

REFERENCES

- [1] J. Sweller, "Cognitive load during problem solving," *Cognit. Sci.*, vol. 12, no. 2, 1988.
- [2] D. Weintrop and U. Wilensky, "To block or not to block," *Comput. Educ.*, vol. 92, 2016.
- [3] J. J. G. van Merriënboer and J. Sweller, "Cognitive load theory and complex learning," *Educ. Psychol. Rev.*, vol. 17, no. 2, 2005.
- [4] S. Baron-Cohen, "Autism: The empathizing–systemizing (E-S) theory," *Ann. N.Y. Acad. Sci.*, vol. 1156, 2009.
- [5] S. Moor and F. P. Deek, "A UML-based visual environment for novice programmers," *J. Inf. Technol. Educ.*, vol. 5, 2006.
- [6] H. C. Purchase, L. Colpoys, M. McGill, D. Carrington, and C. Britton, "UML class diagram syntax: An empirical study of comprehension," in *Proc. Australian Symp. Inf. Visualisation (InVis.au)*, Sydney, Australia, Dec. 2001, pp. 113–120.
- [7] H. A. Simon, *The Sciences of the Artificial*, 3rd ed. MIT Press, 1996.
- [8] M. Chmiel and J. Loui, "Debugging object-oriented software," *IEEE Trans. Educ.*, vol. 47, no. 2, 2004.
- [9] C. Cook, M. Burnett, and D. Boom, "A bug's eye view of immediate visual feedback in direct-manipulation programming systems," in *Empirical Studies of Programmers: 7th Workshop*, Alexandria, VA, USA, Oct. 1997, pp. 20–41.
- [10] E. Boulay, "Some difficulties of learning to program," *J. Educ. Comput. Res.*, vol. 14, no. 3, 1986.
- [11] E. Hutchins, "Material anchors for conceptual mappings," *Cogn. Sci.*, vol. 29, no. 1, 2005.
- [12] J. Sillito, G. C. Murphy, and K. De Volder, "Questions programmers ask," *IEEE Trans. Softw. Eng.*, vol. 32, no. 12, 2006.
- [13] N. Rodriguez, "The cognitive overhead of non-linear reading," *HCC Hum. Factors Q.*, vol. 19, no. 2, 2023.
- [14] R. A. Barkley, "Behavioral inhibition, sustained attention," *Psychol. Bull.*, vol. 121, no. 1, 1997.
- [15] P. Thagard, *MIND: An Introduction to Cognitive Science*, 2nd ed. MIT Press, 2005.
- [16] D. Marr, *Vision: A Computational Investigation into the Human Representation and Processing of Visual Information*, Ch. 1. MIT Press, 1982.

APPENDIX
PROJECT PLAN SUMMARY

Note: This appendix is required for grading purposes and does not count toward the report word limit. Please update the fields below to reflect completed stages, any timeline changes, and total effort hours before submission.

TABLE I: Project Plan Summary

Field	Details
Project Title	A Cognitive Science Meta-Analysis of Schema-Driven Scaffolds in Object-Oriented Programming for Neurodivergent Learners
Student	Tchaas Alexander-Wright
Course	CS-6795 Intro to Cognitive Science, Summer 2026
Track	Literature Review
Research Question	How does existing cognitive science and programming education explain the role of schema-driven, visual, and pattern-based learning supports for OOP comprehension, implementation, and debugging for individuals with ADHD and/or autism?
Completed Stages	Task 1: Finalize literature review scope, research question, and source categories (3 hrs) Task 2: Find scholarly research supporting the identified plan and citation set (8 hrs) Task 3: Read and summarize sources on cognitive load, schemas, and mental representations (7 hrs) Task 4: Read and summarize sources on OOP learning, mental models, and novice programming (7 hrs) Task 5: Read and summarize sources on visual scaffolds, UML, and worked examples (7 hrs) Task 6: Read and summarize sources on ADHD/autism/neurodiversity in computing education (7 hrs) Task 7: Read and summarize sources on debugging, compiler errors, IDE accessibility, and distributed cognition (7 hrs) Task 8: Organize evidence into literature matrix by source area and cognitive concept (6 hrs) Task 9: Synthesize themes into conceptual framework and identify limitations (6 hrs) Task 10: Draft final literature review report (7 hrs) Task 11: Revise citations, IEEE formatting, and project plan appendix (3 hrs) Task 12: Prepare final presentation/video summary (2 hrs)
Remaining Stages	None — all tasks completed.
Timeline Changes	None — all tasks completed on schedule per original project pitch plan.
Total Effort (hours)	All 12 tasks completed — Total: 70 hrs
Human Subjects (CITI)	N/A — Literature Review track; no human subjects, interviews, surveys, or experiments involved.
Code Repository	N/A — Literature Review track; no programming involved.