

# Multi-Scale Oriented Patches



Computer Vision

**Carnegie Mellon University (Kris Kitani)**



# Multi-Scale Oriented Patches (MOPS)

Multi-Image Matching using Multi-Scale Oriented Patches. M. Brown, R. Szeliski and S. Winder.  
International Conference on Computer Vision and Pattern Recognition (CVPR2005). pages 510-517




# Multi-Scale Oriented Patches (MOPS)

Multi-Image Matching using Multi-Scale Oriented Patches. M. Brown, R. Szeliski and S. Winder.  
International Conference on Computer Vision and Pattern Recognition (CVPR2005). pages 510-517

Given a feature  $(x, y, s, \theta)$

Get 40 x 40 image patch,  
subsample every 5th pixel  
(*what's the purpose of this step?*)



Subtract the mean, divide by  
standard deviation  
(*what's the purpose of this step?*)


Haar Wavelet Transform  
(*what's the purpose of this step?*)

# Multi-Scale Oriented Patches (MOPS)

Multi-Image Matching using Multi-Scale Oriented Patches. M. Brown, R. Szeliski and S. Winder.  
International Conference on Computer Vision and Pattern Recognition (CVPR2005). pages 510-517


Given a feature  $(x, y, s, \theta)$

Get 40 x 40 image patch,  
subsample every 5th pixel  
(low frequency filtering, absorbs localization errors)



Subtract the mean, divide by  
standard deviation

*(what's the purpose of this step?)*



Haar Wavelet Transform


*(what's the purpose of this step?)*

# Multi-Scale Oriented Patches (MOPS)


Multi-Image Matching using Multi-Scale Oriented Patches. M. Brown, R. Szeliski and S. Winder.  
International Conference on Computer Vision and Pattern Recognition (CVPR2005). pages 510-517

Given a feature  $(x, y, s, \theta)$

Get 40 x 40 image patch,  
subsample every 5th pixel  
(low frequency filtering, absorbs localization errors)



Subtract the mean, divide by  
standard deviation  
(removes bias and gain)



Haar Wavelet Transform  
(*what's the purpose of this step?*)






# Multi-Scale Oriented Patches (MOPS)


Multi-Image Matching using Multi-Scale Oriented Patches. M. Brown, R. Szeliski and S. Winder.  
International Conference on Computer Vision and Pattern Recognition (CVPR2005). pages 510-517

Given a feature  $(x, y, s, \theta)$

Get 40 x 40 image patch,  
subsample every 5th pixel  
(low frequency filtering, absorbs localization errors)



Subtract the mean, divide by  
standard deviation  
(removes bias and gain)



Haar Wavelet Transform  
(low frequency projection)




# Multi-Scale Oriented Patches (MOPS)


Multi-Image Matching using Multi-Scale Oriented Patches. M. Brown, R. Szeliski and S. Winder.  
International Conference on Computer Vision and Pattern Recognition (CVPR2005). pages 510-517

Given a feature  $(x, y, s, \theta)$

Get 40 x 40 image patch,  
subsample every 5th pixel  
(low frequency filtering, absorbs localization errors)



Subtract the mean, divide by  
standard deviation  
(removes bias and gain)




Haar Wavelet Transform  
(low frequency projection)



# Haar Wavelets


(actually, Haar-like features)

Use responses of a bank of filters as a descriptor





Haar wavelet responses can be computed with filtering



Haar wavelet responses can be computed  
**efficiently** (in constant time) with integral images