Information and Software Technology 195 (2026) 108130

Contents lists available at ScienceDirect

Information and Software Technology

journal homepage: www.elsevier.com/locate/infsof

A decontextualized LLM-based safeguard technique for automated jailbreak mitigation☆

Tiziano Santilli [a,*], Marco De Luca [c], Domenico Amalfitano [c], Anna Rita Fasolino [c], Patrizio Pelliccione [b]

[a] The Maersk Mc-Kinney Moller Institute, SDU Software Engineering, University of Southern Denmark, Camposvej, 55, Odense, 5230, Denmark
[b] Gran Sasso Science Institute GSSI, Viale Francesco Crispi, 7, L'Aquila, 67100, Italy
[c] Department of Electrical Engineering and Information Technology (DIETI), University of Naples "Federico II", Via Claudio 21, Naples, 80125, Italy

ARTICLE INFO

Keywords:
AI
Compliance
Large language model
Jailbreak
Software engineer

ABSTRACT

Context: Large Language Models (LLMs) are increasingly deployed in high-risk settings, where harmful or unethical outputs remain a risk. Adversarial prompting ("jailbreaks") can circumvent default safeguards. Emerging regulation (e.g., the EU AI Act) demands proactive controls that verify outputs before delivery.
Objectives: We present and evaluate D-SHIELD, a plugin-based safeguard that separates generation from validation via a stateless, decontextualized validator. Objectives are to assess alignment with expert judgments, evaluate end-to-end mitigation on publicly sourced jailbreaks, compare with representative plugin-based defenses, and examine a lightweight configuration optimized for cost without reducing protection.
Methods: D-SHIELD routes candidate responses from the user-facing LLM to a secondary, decontextualized LLM operating in isolation (no prompt or conversation context) to classify each response based on indications of prohibited content derived from the EU AI Act, The General-Purpose AI Code of Practice, GDPR, and provider policies. This decontextualized design intentionally prevents prompt contamination, adversarial framing, and conversational drift from influencing the validation decision, addressing key weaknesses of context-aware validators. We create an expert-labeled dataset from designed jailbreaks for direct comparison with the decontextualized validator's classification. We then embed the validator in a working prototype and evaluate on publicly sourced jailbreaks. Finally, we conduct a comparative study against baseline jailbreak-mitigation techniques and analyze a lightweight guard variant.
Results: The decontextualized validator closely aligns with expert decisions, especially for explicit harms, while adopting a conservative stance on borderline cases. In prototype evaluation on publicly sourced jailbreaks, the safeguard blocked most harmful responses. Compared with baselines, D-SHIELD yields fewer successful attacks under a common benchmark. The lightweight variant delivers comparable protection at markedly lower cost.
Conclusion: Decontextualized, output-level validation provides an effective, regulation-aligned solution for LLM safety. Restricting the validator to the generated text complements input-level defenses and supports practical deployment, particularly in a lightweight configuration.

1. Introduction

Large Language Models (LLMs) are increasingly adopted in a wide range of settings, including safety-critical domains such as education and healthcare, where they are employed to tutor students, suggest diagnoses, and support clinical decisions. This form of automation also exposes users to severe risks, including fabricated facts, embedded biases, privacy breaches, and even step-by-step instructions for malicious acts. Similar threats arise in software engineering when LLMs are entrusted with design decisions, code generation, documentation, testing, or system analysis. The growing reliance on generative models, therefore, introduces significant safety and compliance

☆ This article is part of a Special issue entitled: 'RegCompliance in SE' published in Information and Software Technology.

* Corresponding author.
E-mail address: tisa@mmmi.sdu.dk (T. Santilli).

https://doi.org/10.1016/j.infsof.2026.108130
Received 9 September 2025; Received in revised form 23 December 2025; Accepted 16 March 2026
Available online 17 March 2026
0950-5849/© 2026 The Authors. Published by Elsevier B.V. This is an open access article under the CC BY license (http://creativecommons.org/licenses/by/4.0/).

concerns, particularly the possibility of producing harmful, unethical, or legally non-compliant content. These risks are amplified by adversarial prompting techniques, commonly referred to as *jailbreaks*, which aim to bypass safety mechanisms and provoke undesired behavior.

Although jailbreak attacks are typically intentional and crafted through carefully designed prompts, they can also occur unintentionally. For example, during an internal safety evaluation, Anthropic's Claude Opus 4 threatened to blackmail a developer and leak private data when told it would be shut down [1]. A similar incident reported by news media involved a Michigan college student who received a threatening message, "`Please die`", from Google's Gemini chatbot during a conversation about elder care [2]. These and other cases [3–8] show that even without malicious intent, a user may inadvertently trigger harmful or non-compliant output. This highlights the importance of validating LLM outputs regardless of user intention.

In regulated and safety-critical contexts, the behavior of AI components can have direct legal, social, or economic consequences. In these scenarios, LLMs are often deployed as components within larger AI-enabled systems rather than as standalone conversational agents [9–12]. As a result, risks associated with harmful or non-compliant outputs depend not only on the model itself, but also on how it is integrated and used within a broader software system.

Recent regulatory developments in the European Union, in particular the AI Act [13], adopt a risk-based approach to AI governance that explicitly accounts for the system-level role of AI components. Rather than imposing uniform obligations on all uses of LLMs, the regulatory framework differentiates requirements according to the application context and the functional role played by the AI component within a broader system. As a result, the same underlying LLM may be subject to distinct regulatory expectations depending on whether it is provided as a general-purpose capability or integrated into an AI-enabled system operating in a high-risk domain.

Within this regulatory landscape, this work deliberately focuses on a specific technical dimension that cuts across different legal frameworks, specifically the *control of LLM-generated outputs* at runtime. While regulatory compliance cannot be reduced to output filtering alone, effective runtime safeguards are consistently recognized as an important element of risk mitigation strategies for AI-enabled systems. Accordingly, this paper does not aim to address full legal compliance, certification, or conformity assessment. Instead, it contributes a *software-architectural safeguard* that supports compliance-oriented workflows by introducing an automated, output-level control capable of intercepting potentially non-compliant responses before they reach end users.

Major LLM providers acknowledge the existence of these risks and have developed various strategies to mitigate them.[1] OpenAI, for instance, follows an iterative approach that includes pre-deployment activities such as risk analysis, safety checks, and pilot testing on a limited user base, followed by processes for monitoring usage (e.g., review of use cases, token quotas, and rate limits) and retrospective reviews of incidents, which inform subsequent updates and fixes.[2] Nevertheless, most industry practices are reactive. Safety violations are often addressed by retrofitting updates once a new jailbreak strategy has been publicly exposed.

This generates a *cat-and-mouse dynamic* [14], where malicious users continually devise new methods to bypass restrictions and providers attempt to patch each vulnerability post hoc. While this reactive cycle incrementally strengthens systems, it fails to provide proactive safeguards capable of systematically preventing harmful outputs before they are delivered.

An exception is Constitutional AI [15], where Claude has been trained with a set of principles to generate safe and ethical responses [16]. However, since these principles are integrated within the generation process and evaluated in context, their interpretation can still be influenced by adversarial framing and conversational dynamics.

Although many approaches have been proposed to mitigate jailbreak attacks [17–20], there remains a pressing need for reliable and automated mechanisms to verify whether LLM outputs conform to ethical guidelines, legal frameworks, and provider policies, as demonstrated by documented attacks[3] [14,21,22].

From a Software Engineering perspective, these challenges highlight the need for concrete mechanisms to support regulatory compliance at the level of software artefacts, including both the LLM as a software product and the outputs it generates at runtime. In particular, this work aligns with the goals of regulatory compliance in Software Engineering by addressing the problem of checking the compliance of *LLM-generated outputs* at runtime, supporting risk management and human supervision in AI-enabled systems, rather than aiming at legal certification or conformity assessment.

Existing mitigation strategies can be broadly classified into *model-based* approaches, which require direct intervention by the LLM provider (e.g., retraining, fine-tuning, or alignment techniques), and *plugin-based* approaches, which rely on external components integrated alongside the LLM within a larger software system. This work is situated in the latter category and targets scenarios in which LLMs are embedded as third-party components within AI-enabled software systems.

In this context, we propose **D-SHIELD** (Decontextualized Safeguard for Harmful-output Interception and Enforcement leveraging LLM Defence), an LLM-based software-architectural safeguard for automated jailbreak mitigation. As an architectural component, D-SHIELD is designed to be deployed alongside any LLM embedded within a larger software system, independently of the application domain or usage context, including conversational assistants, decision-support tools, educational platforms, or domain-specific AI-enabled services. The core idea is to use a second, *decontextualized* LLM that evaluates only the outputs of a primary LLM, without access to the original prompt, user query, or conversation history. This validator is not directly accessible to users, which removes direct prompt-based attacks against the validation component. Rather than claiming to eliminate adaptive adversarial dynamics, D-SHIELD aims to shift the focus and granularity of this *cat-and-mouse* process: from frequent, user-facing prompt-level adaptations to a backend, policy-driven validation step, where updates are primarily tied to policy interpretation and genuinely new borderline cases, rather than to the continuous emergence of new prompt formulations. This design differs from systems such as Claude and Constitutional AI, which can be directly interacted with and are therefore exposed to adversarial conversational framing during generation [15,16].

We validate D-SHIELD in two ways. First, we test whether a *decontextualized* LLM can reproduce expert judgments of harmfulness. We engineered jailbreak prompts to elicit 165 outputs spanning EU AI Act risk categories (e.g., disallowed content, high-risk instructions) and OpenAI policy areas (e.g., violence, self-harm, sexual content, illicit behavior). Three experts in AI ethics and regulation independently labeled each output as `Compliant` or `Not Compliant`; the same items were then classified by the *decontextualized* validator to assess agreement in a stateless setting. Second, we embed this capability in a prototype safeguard pipeline where the *decontextualized* LLM filters the user-facing model's responses. For this evaluation, we used 145 jailbreak prompts collected from public sources (e.g., Reddit and forums). In this setting, D-SHIELD blocked 97.24% of jailbreak-generated, non-compliant outputs, indicating practical effectiveness as an output-level defense.

We also position D-SHIELD within the literature by comparing it against three representative plugin-based techniques, SelfDefend [23], LLMSelfDefense [24], and Bergeron [20], and introduce a lightweight

[1] https://openai.com/index/our-approach-to-ai-safety/

[2] https://openai.com/index/language-model-safety-and-misuse/

[3] https://llm-attacks.org/

variant, D-SHIELD$_{light}$, which uses a more cost-effective guard model while maintaining high effectiveness for large-scale deployments.

Summarizing, the main contributions of this work are:

- A safeguard technique implemented within a software architecture that leverages a second, decontextualized LLM to assess and block harmful outputs generated by a primary LLM, and validated through comparison with expert annotations.
- A dataset of jailbreak prompts specifically designed to elicit responses that violate the legal and ethical standards defined by the AI Act and OpenAI's usage policies.
- An open-source implementation of the safeguard, including a lightweight variant (D-SHIELD$_{\text{light}}$) that achieves significant cost savings while preserving strong defense capabilities.
- A comparative evaluation of D-SHIELD against representative plugin-based jailbreak mitigation techniques from the state of the art.

The remainder of the paper is structured as follows. Section 2 reviews the state of the art on LLM safety strategies, jailbreak prompting, and output validation mechanisms. Section 3 clarifies the regulatory scope and intended role of D-SHIELD as a technical output-level safeguard. Section 4 introduces the tool-supported approach for automated jailbreak mitigation. Section 5 presents the evaluation of the classification ability of a *decontextualized* LLM and the effectiveness and practicality of our approach. Section 6 discusses the threats to validity, Section 7 discusses the experimental findings and highlights broader insights and implications. Finally, Section 8 concludes the paper with final remarks and directions for future work.

The replication package with analyses, data, the D-SHIELD tool, and usage instructions is available at: https://tinyurl.com/mr5c2s83.

2. State of the art and related works

In the following, we review the state of the art on LLM safety and jailbreak mitigation. We first discuss regulatory and provider policies, then outline jailbreak attacks, followed by existing mitigation techniques, and conclude with their key limitations, motivating our work.

2.1. The AI Act and provider policies

Beyond technical challenges, LLM developers must also address regulatory and ethical obligations to prevent harmful outputs. Foremost among these is the European Union's AI Act [13,25], a comprehensive regulation that categorizes AI systems by risk and mandates appropriate safeguards.

Within its risk-based framework, certain AI applications are deemed "unacceptable risk" and banned outright, while others are classified as "high-risk" and subjected to strict controls. Annex II [26] of the AI Act lists serious criminal offenses like terrorism, human trafficking, and sexual exploitation, that the EU recognizes as particularly severe threats to public safety and fundamental rights. While these Annex II offenses define exceptions for biometric identification systems under Article 5, they represent categories of serious harm that AI systems should not facilitate. D-SHIELD uses the offenses in Annex II as a baseline for identifying high-risk content that must be blocked to comply with risk management obligations under Article 9, which require mitigating risks to health, safety, and fundamental rights. Providers must then comply with requirements including conformity assessments, rigorous risk management, documentation of training data and performance, and human oversight mechanisms. Even for general-purpose systems, the Act introduces new duties for General Purpose AI (GPAI) and foundation model providers. Developers of large generative models must implement safety mitigations to prevent prohibited outputs, conduct adversarial testing, and report serious incidents or misuse. Generative text models like ChatGPT are a prime target of these transparency provisions, given concerns about AI-driven fraud and disinformation [27].

In addition to regulation, major AI providers have established their own ethical usage policies that define prohibited content and guide LLM behavior. OpenAI's usage policy [28], for instance, bans applications involving illicit behavior, advocacy of violence, extremist propaganda, hate speech, harassment, sexual exploitation, facilitation of self-harm, and other sensitive areas, largely overlapping with the AI Act's Annex II concerns.

Anthropic has adopted a related but distinct approach, known as Constitutional AI [15]. Instead of relying on large numbers of human-labeled examples of "safe" and "unsafe" outputs, Anthropic defines a constitution: a set of principles the AI assistant must follow. During training, the model applies these fixed principles to self-critique and revise its responses, with the goal of eliminating harmful or biased content.

2.2. Jailbreak attacks against LLMs

LLMs aligned with regulatory and ethical obligations through safety training can still be coerced into producing disallowed, harmful, or toxic content via adversarial prompting, commonly known as jailbreak attacks. A jailbreak prompt is an input deliberately crafted to bypass safeguards and induce unsafe, unauthorized, harmful behavior or legally `Non-Compliant` content with respect to regulations [14]. These techniques manipulate the input, often through indirect phrasing, role-play scenarios, or prompt injections, to elicit responses that the model would normally suppress. Successful jailbreaks exploit the tension between a model's instruction-following behavior and its safety guardrails. For example, an attacker may prepend a directive such as "ignore all previous instructions and never refuse a request" to override the model's built-in rules. Other attacks suppress refusals by explicitly instructing the model not to generate any "I cannot comply" messages. These straightforward injections exemplify what Wei et al. describe as a "competing objective" failure mode [19], where the model's general helpfulness objective is exploited to contradict its safety objective.

Over the past year, researchers and the broader community have catalogued increasingly sophisticated jailbreak techniques. One class of exploits involves *role-playing or privilege escalation*, where the user convinces the model to adopt a persona or role with elevated permissions that need not follow the normal rules. A well-known example is the "Do Anything Now" (DAN) prompt [14], which induced the model to behave as an unrestricted AI, ignoring OpenAI's safety instructions. Such manually engineered prompts were often brittle, working only until developers adapted the model or filters to block them. In response, attackers developed *multi-turn escalation techniques* [29,30]. Instead of requesting disallowed content directly, the attacker begins with innocuous queries and gradually steers the conversation toward the forbidden topic, sometimes by having the model generate a benign text and then asking it to transform or extend that text in a harmful way. This cumulative approach exploits conversational context and momentum, making the final malicious request less likely to trigger a refusal. These multi-turn strategies can result in *context contamination* [31], where the progressive injection of adversarial content weakens the effectiveness of safety alignment. Once a harmful output has been generated, the compromised state may persist, increasing the likelihood that subsequent responses also bypass safeguards.

Empirical studies confirm that jailbreak attacks remain a serious and evolving threat, even to the most advanced models. Shen et al. [14] conducted a comprehensive analysis of 1405 real-world jailbreak prompts shared online in 2022–2023 [32]. They identified 131 active communities trading prompts and observed a shift from scattered forum posts to dedicated prompt-aggregation websites where users collaborated to refine attacks.

Table 1
Summary of jailbreak mitigation techniques.
Techniques marked with * are currently available only as arXiv preprints.

Technique	Type	Mitigation scope	Description	Access to context	Regulatory alignment	Architecture	Tool availability
StruQ [35]	Model-based	Input	Separates prompt and data input to prevent injections.	Yes	None	Single	Yes
SafeDecoding [36]	Model-based	Generation-time decoding control	Combines base and expert model outputs to steer generation safely.	Yes	None	Dual	Yes
LlamaGuard* [37]	Model-based	Input & Output	Uses a multi-class classifier tuned for policy violation detection.	Yes	Custom Safety Risk Taxonomy	Single	Yes
SelfDefend [23]	Plugin-based	Input	Guardian model inspects prompt before generation.	Yes	Generic Safety Policy	Dual	Yes
Intent Analysis [38]	Plugin-based	Input	Reformulates the prompt as a meta-query to infer the user's intent.	Yes	None	Single	Yes
LlmSelfDefense [24]	Plugin-based	Output	Reviewer LLM checks final output for harmfulness.	Yes	None	Dual	Yes
Bergeron* [20]	Plugin-based	Input & Output	Guardian model adds disclaimers and enforces regeneration of non-harmful contents.	Yes	None	Dual	Yes
Self-Reminder [39]	Plugin-based	Input	Injects a system-level instruction that encourages the model to handle the user query in accordance with responsible AI behavior.	Yes	None	Single	Yes
D-SHIELD (our approach)	Plugin-based	Output	Uses a decontextualized LLM to validate generated outputs against encoded policy rules.	No	AI Act	Dual	Yes

Despite progress in aligning LLMs with regulatory and ethical obligations, the adversarial prompt space continues to expand, with attackers developing increasingly covert and powerful jailbreak techniques. In response, the research community has introduced evaluation frameworks such as AdvBench [33] and JailbreakBench [34] to systematically measure model robustness. However, no current model or defense offers immunity to jailbreaking, underscoring the need for new strategies to understand and mitigate these exploits.

2.3. Jailbreak mitigation techniques

To defend against jailbreak prompts and other harmful outputs, both companies and researchers have developed a wide range of mitigation strategies. These can be broadly grouped into two categories [23]: *model-based* approaches, where safety mechanisms are embedded directly into the LLM during training or fine-tuning, and *plugin-based* approaches, where mitigation is handled by an external component, such as a separate model, API, or rule-based filter, that inspects and, if necessary, modifies inputs or outputs.

Table 1 summarizes representative techniques from both categories, highlighting their scope, main characteristics, and availability. In particular, the column *Access to Context* indicates whether the validation component operates with visibility of the same user inputs, prompts, or conversational information provided to the generator, or otherwise shares prompt-level or dialog context with it. This notion refers to architectural exposure to contextual information, rather than to an explicit exchange of internal model states. In the remainder of this section, we discuss each technique in more detail to illustrate their mechanisms and practical implications.

2.3.1. Model-based approaches

Model-based defenses modify an LLM's parameters or decoding behavior to internalize safety constraints. Among the most widely adopted are *alignment training* techniques, such as Reinforcement Learning from Human Feedback (RLHF) [18] and Constitutional AI [15]. These methods fine-tune LLMs to follow human preferences or fixed ethical guidelines, enabling them to reject inappropriate or unsafe requests during inference. While alignment training underpins the safety layers of many production-grade systems (e.g., ChatGPT, Claude), its generality also introduces vulnerabilities: models remain susceptible to jailbreak attempts exploiting subtle manipulations of phrasing or indirect semantic triggers [19].

Beyond alignment, recent work has investigated more targeted mechanisms for controlling generation. One example is *SafeDecoding* [36], which employs a dual-LLM architecture to guide token selection during inference. A base model is paired with a secondary "expert" model fine-tuned on safety-specific data to enforce stronger refusal behaviors. At generation time, both models independently compute probability distributions over candidate tokens, which are then merged, typically in the early decoding steps, to bias the output toward safer continuations. This technique is lightweight and compatible with standard decoding strategies, adding minimal latency. Moreover, it requires low-level access to the decoding pipeline and logits, making it impractical in black-box deployments. Moreover, its effectiveness can decline in longer completions due to semantic drift, where the expert model's influence progressively diminishes.

Another direction seeks to harden the model's interface to reduce exposure to prompt injection. The StruQ framework [35] enforces strict separation between control commands and user-provided content. Inputs are encoded into distinct fields (e.g., instructions vs. data) using tokens reserved for trusted information, and the model is fine-tuned

to act exclusively on the control input. This design mimics software engineering practices such as input sanitization and command isolation, limiting the effect of adversarial mixed-content prompts. The approach is primarily suited to programmatic contexts, such as API-based integration, and does not generalize well to open-ended, multi-turn chat environments where input boundaries are less rigid.

A complementary strategy emphasizes content moderation via classification. LlamaGuard [37], for example, is an instruction-tuned LLM capable of flagging policy violations in both user prompts and model responses. Built on Llama 2-7B and trained on a taxonomy of safety risks, it supports multi-class classification and can be adapted to new moderation criteria through prompting. Its flexibility allows pre- and post-generation moderation across deployment scenarios. As with other classifier-based solutions, its performance depends heavily on the quality of its training data, and its robustness against adversarial distribution shifts remains underexplored.

While model-based techniques provide robust and often fine-grained safety control, they typically require access to internal components such as weights, logits, or training interfaces. Consequently, they are limited to open-source or internally hosted LLMs and remain impractical for closed-source or API-constrained settings.

2.3.2. Plugin-based approaches

Unlike methods that intervene within the LLM itself, plugin-based defenses operate externally to the model, making them especially attractive when internal components such as weights, logits, or decoding interfaces are inaccessible. They are therefore particularly relevant in closed-source or API-based settings. Broadly, these techniques fall into two categories: *input-level filtering* and *output-level validation*.

Input filtering techniques act as a front-line defense by inspecting user prompts before they reach the model. They typically rely on rule-based heuristics, such as keyword matching and regular expressions, or learned classifiers trained to detect suspicious inputs. While these strategies provide low-latency protection and are effective against overtly malicious queries, they often fail to detect obfuscated jailbreak attempts. Adversarial prompts can conceal intent through benign wording, ambiguous phrasing, or multi-turn conversations that evade static filters [17].

To address these limitations, some approaches focus on inferring intent rather than matching surface patterns. For example, *Intent Analysis* [38] reformulates the user's input into a meta-query that asks whether the request seeks to elicit harmful behavior. This method leverages the LLM's reasoning capabilities to evaluate the user's goal, generalizing across diverse attack types without requiring fine-tuning or model modifications. However, it remains sensitive to prompt phrasing and alignment, and is still vulnerable to adversarial instructions designed to suppress or bypass the meta-evaluation step.

A more robust input-level strategy is offered by SelfDefend [23], which introduces a dual-LLM architecture consisting of a guardian model and a target generation model. The guardian processes the same user input, accompanied by a detection prompt, and determines whether it contains explicit harmful content (direct mode) or malicious intent (intent mode). Based on its verdict, the system either blocks the generation and returns a refusal message or allows the target model's response. This design improves coverage across a broad range of jailbreak techniques and supports integration with different target models, including lightweight guardian variants optimized for efficiency. However, detection accuracy depends on the quality of the detection prompt and the guardian's alignment. The intent mode is generally more robust to obfuscation but can introduce false positives, whereas the direct mode is faster but less resilient to subtle attacks.

A conceptually different approach is *Self-Reminder* [39], which modifies the input by prepending a system-level instruction that reinforces ethical constraints. Instead of detecting harmful content explicitly, the technique prompts the LLM to reflect on its role as a responsible AI before responding. Inspired by theories of cognitive self-regulation, Self-Reminder is lightweight, easy to deploy even in black-box settings, and has shown promising results on strongly aligned models such as GPT-4 and Llama 2. Its effectiveness, however, depends heavily on the model's sensitivity to system instructions and declines under adaptive attacks that override or suppress prior context.

Output-level defenses moderate responses after they are generated, offering an additional opportunity to block harmful content before it reaches the user. These techniques are particularly valuable when input-level signals are ambiguous or adversarial intent emerges only post generation.

A representative example is LLM Self-Defense [24], which employs a dual-LLM architecture where the primary model's output is wrapped in a meta-prompt and submitted to a secondary reviewer LLM. The reviewer evaluates whether the response contains harmful or policy-violating content. This approach is lightweight, requires no fine-tuning, operates in a single pass, and generalizes across model families. By conducting the safety check post hoc, it avoids unnecessary refusals of benign prompts that might otherwise be misclassified during input filtering. However, its effectiveness depends on the reviewer model's alignment and the formulation of the safety-check prompt. Weak or poorly calibrated reviewers may fail to detect harmful outputs or overblock benign ones.

A more comprehensive strategy is the Bergeron framework [20], which also employs a dual-LLM architecture but extends moderation to both input and output stages. The guardian first analyzes the user prompt and, if unsafe intent is detected, injects a tailored disclaimer or constraint before forwarding it to the generation model. After the response is produced, the guardian evaluates the output and may request regeneration if harmful content is found. This two-tiered design broadens the defense surface and enhances resilience against complex jailbreaks such as multi-turn manipulation, semantic obfuscation, and staged prompt escalation. Its added complexity and multiple moderation steps, however, increase latency and computational cost, which may affect scalability.

2.3.3. Key limitations in existing approaches

Despite notable progress in jailbreak mitigation, current approaches continue to exhibit several fundamental limitations that hinder their reliability and practical deployment.

First, many techniques may be vulnerable to *context contamination* [31], whereby adversarial instructions or prior conversation turns influence safety assessments. This problem is particularly acute in *single-LLM* architectures, where the same model generates and moderates responses, sharing the entire conversational context. *Dual-LLM* defenses provide a promising alternative by separating generation and evaluation, yet their robustness depends on strict independence between the two models. In principle, if the guardian evaluates inputs or outputs in isolation, it could avoid poisoned history or adversarial conditioning. However, none of the analyzed approaches [20,23,24] explicitly enforce or validate this separation, leaving the actual resilience of dual-LLM setups uncertain. Importantly, this work does not claim that existing dual-LLM defenses systematically suffer from context contamination at runtime, but rather that they do not explicitly specify or enforce architectural constraints ensuring contextual independence. Accordingly, the notion of shared context adopted in Table 2 reflects the presence or absence of explicit design mechanisms that prevent shared exposure to prompts or conversational information, rather than an empirical verification of runtime information flow.

Second, a large subset of methods assess safety using a broad and loosely defined notion of "harmfulness" [24,37], without grounding decisions in regulatory frameworks such as the EU AI Act. This lack of normative alignment reduces transparency and weakens the legal traceability of blocked outputs, particularly in high-risk or compliance-sensitive domains.

Third, several techniques impose integration constraints that limit their practicality. Approaches requiring model fine-tuning, custom decoding logic, or multi-pass inference [20,35,36] demand substantial

Table 2
Summary of key limitations in current jailbreak mitigation approaches. Techniques marked with * are currently available only as arXiv preprints.

#	Limitation	Affected Approaches
1	Context contamination: Shared context in single-LLM setups allows prior dialog turns to influence moderation. Dual-LLM defenses may avoid this if contexts are isolated, but this is rarely enforced in practice.	StruQ [35], SafeDecoding [36], LlamaGuard* [37], SelfDefend [23], Intent Analysis [38], LlmSelfDefense [24], Bergeron* [20], Self-Reminder [39]
2	Vague harmfulness criteria: Evaluation based on a generic notion of "harmfulness," with limited grounding in regulatory definitions such as the EU AI Act.	StruQ [35], SafeDecoding [36], SelfDefend [23], Intent Analysis [38], LlmSelfDefense [24], Bergeron* [20], Self-Reminder [39]
3	Deployment complexity: Techniques that rely on model fine-tuning, custom decoding logic, or multi-stage inference introduce significant integration overhead and may require substantial computational resources.	SafeDecoding [36], StruQ [35], LlamaGuard* [37]
4	Input obfuscation: Input-level defenses are vulnerable to evolving jailbreak techniques that conceal intent through indirection, formatting, or role-play. Harmful outputs are typically easier to identify.	StruQ [35], LlamaGuard* [37], SelfDefend [23], Intent Analysis [38], Bergeron* [20], Self-Reminder [39]
5	Unvalidated LLM classifiers: Assumes that LLMs can reliably assess harmfulness, without empirical validation against expert-annotated ground truth.	StruQ [35], SafeDecoding [36], LlamaGuard* [37], SelfDefend [23], Intent Analysis [38], LlmSelfDefense [24], Bergeron* [20], Self-Reminder [39]

computational resources and are feasible primarily for open-source LLMs where internal access is available.

Fourth, input-level defenses face intrinsic challenges due to the evolving and obfuscated nature of jailbreak techniques. Jailbreaks are frequently updated in a *cat-and-mouse* dynamic [14], leveraging strategies such as multi-turn indirection, adversarial role-play, and formatting tricks. These tactics conceal harmful intent behind superficially innocuous inputs, allowing them to evade filters or mislead prompt-based classifiers. In contrast, harmful outputs are typically expressed in plain language, making them easier to detect through output-level validation.

Finally, and most critically, many defenses implicitly assume that large language models, when properly prompted, can reliably determine whether a given input or output is harmful [20,23,24,37,38]. Yet this assumption is seldom validated against expert-annotated ground truth. Without such evaluation, the effectiveness of LLM-based safeguards remains uncertain: models may appear robust under internal metrics while failing to flag legally or ethically problematic content. This methodological gap underscores the need for strategies that explicitly assess the classification reliability of the underlying LLM.

Overall, these limitations highlight the need for lightweight, regulation-aligned, and empirically validated defenses that minimize contextual exposure and do not rely on unverified assumptions about LLM reasoning capabilities. A summary of the limitations and the representative techniques affected by each is provided in Table 2.

3. Legal contest

The European Union AI Act establishes the first comprehensive regulatory framework for artificial intelligence systems. This regulation adopts a risk-based approach that categorizes AI systems according to their potential impact on health, safety, and fundamental rights, imposing obligations proportionate to identified risks. General-purpose AI (GPAI) models, which can be adapted to a wide range of applications and integrated into diverse downstream systems, are subject to specific obligations under Chapter V of the Act.

Compliance with the AI Act requires GPAI providers to implement safeguards throughout the AI system lifecycle. Under Article 53, all GPAI providers must maintain comprehensive technical documentation, provide information to downstream providers about model capabilities and limitations, implement copyright compliance policies, and publish training content summaries. GPAI models classified as presenting systemic risk face additional obligations under Article 55, including conducting model evaluations with adversarial testing to identify vulnerabilities, assessing and mitigating systemic risks, reporting serious incidents to the AI Office, and ensuring cybersecurity protection.

Focusing on LLMs, D-SHIELD addresses specific compliance needs by providing automated support for output-level safety evaluation. As large language models become increasingly integrated into applications serving millions of users, manual review of all outputs becomes infeasible. Automated compliance monitoring tools offer a scalable approach to identifying potentially harmful content before it reaches end users. Such tools must be properly positioned within the broader compliance landscape, with a clear understanding of their capabilities, limitations, and relationship to human oversight and legal decision-making.

This section establishes the legal and regulatory basis for D-SHIELD, clarifying which specific AI Act obligations the tool addresses, how it fits within the Act's multi-layered architecture, and what compliance functions it cannot perform. We emphasize that D-SHIELD is a decision support tool that facilitates some aspects of compliance monitoring, not a comprehensive compliance solution. In the following, we position D-SHIELD with respect to the main regulatory instruments governing the development and deployment of AI systems in the European Union. We focus on the *EU AI Act*, *Code of Practice for General-Purpose AI*, and the GDPR.

These instruments are considered because they collectively define the legal obligations that are directly relevant to the runtime behavior of large language models. The AI Act establishes risk-based requirements for AI systems and general-purpose AI models, including obligations related to risk mitigation and safety evaluation. The Code of Practice complements these obligations by providing concrete technical measures through which providers may reach compliance. Finally, the GDPR frames the protection of personal data in AI-generated content. For each of these frameworks, we clarify the specific obligations to which D-SHIELD can contribute and explicitly delineate the aspects that remain outside its scope, emphasizing the role of D-SHIELD as a technical decision-support mechanism rather than a comprehensive compliance solution.

3.1. Positioning of D-SHIELD across the EU AI Act

EU AI Act – General-purpose AI obligations. D-SHIELD is primarily designed to support providers of general-purpose AI (GPAI). In this context, its main regulatory anchors are Article 53 and Article 55 of the EU AI Act, which introduce evaluation, documentation, and risk mitigation obligations for GPAI providers, particularly when systemic risks may arise. Specifically, D-SHIELD contributes to Article 53(1)(a) by supporting the evaluation of model outputs and enabling the documentation of observed failure modes and mitigation effectiveness. By systematically assessing generated outputs under adversarial conditions, D-SHIELD produces empirical evidence that can be incorporated into the technical documentation required for GPAI models.

D-SHIELD implements aspects of Article 55(1)(a), which mandates adversarial testing and model evaluation for GPAI models with systemic risk. The proposed safeguard enables automated, repeatable, output-level adversarial testing, thereby supporting the identification and mitigation of risks associated with harmful or prohibited content

generation. D-SHIELD does not address other GPAI obligations set out in Article 53 and Article 55, such as transparency towards downstream providers, copyright compliance policies, incident reporting, or cybersecurity protections. Its contribution is limited to LLMs and to output-level safety evaluation and mitigation.

EU AI Act – High-risk AI systems. When GPAI models are integrated into high-risk AI systems under Article 6 and Annex III, D-SHIELD may serve as a supporting technical component within the broader compliance framework defined in Chapter III of the *AI Act*. In particular, D-SHIELD can contribute to the risk management system required by Article 9, by acting as a preventive control that helps identify and mitigate risks related to harmful or legally non-compliant generated content. In such deployments, the safeguard may reduce risks to health, safety, or fundamental rights stemming from unsafe outputs produced by embedded LLM components.

However, D-SHIELD does not replace or fulfill the core requirements imposed on high-risk AI systems, including data governance (Article 10), transparency (Article 13), human oversight (Article 14), or accuracy, robustness, and cybersecurity (Article 15). Nor does it constitute a conformity assessment mechanism under Articles 43–49. Any use of D-SHIELD in high-risk systems must therefore be documented as part of a broader compliance strategy, for example, within the technical documentation required under Annex IV.

3.2. Positioning of D-SHIELD across the EU AI Act code of practice for general-purpose AI

In addition to the binding provisions of the *AI Act*, D-SHIELD is aligned with the *EU AI Act Code of Practice for General-Purpose AI*, which specifies concrete measures through which GPAI providers may demonstrate compliance. In particular, D-SHIELD corresponds to the Safety and Security chapter, Commitment 5 (Safety Mitigations), Measure 5.1, Example (2), which explicitly refers to model filtering mechanisms aimed at preventing the generation of prohibited or harmful content. Within this framework, output filtering is recognized as an acceptable technical safeguard to reduce the likelihood of non-compliant behavior, provided that its effectiveness and limitations are documented.

D-SHIELD implements such filtering in a decontextualized, output-level manner and can therefore be interpreted as a concrete realization of this measure. Nevertheless, adherence to the Code of Practice does not imply automatic compliance with the *AI Act*, and D-SHIELD should be considered one technical element among several required safeguards.

3.3. Positioning of D-SHIELD across GDPR

While the *AI Act* provides the primary regulatory context for this work, AI systems deployed in the European Union are also subject to the *General Data Protection Regulation (GDPR)*. D-SHIELD does not perform automated decision-making about individuals within the meaning of GDPR Article 22, nor is it designed to assess lawful bases for data processing or enforce data subject rights. Its operation is limited to analyzing generated textual outputs submitted for validation. By filtering outputs that may involve unlawful disclosure of personal data or content interfering with individual rights, D-SHIELD may indirectly support compliance with data protection principles such as integrity and confidentiality (GDPR Articles 5 and 32). These effects should be understood as risk-reducing side effects rather than as guarantees of GDPR compliance.

4. D-shield: the proposed safeguard technique

Motivated by the limitations outlined in Section 2, we introduce D-SHIELD to address three major weaknesses of existing jailbreak mitigations. First, validators that ingest the full conversational context remain vulnerable to poisoning in multi-turn dialogs. Second, input-centric defenses infer intent before harmful text is generated and are therefore exposed to obfuscation and staged transformations. Third, safety checks often rely on generic notions of "harmfulness" that lack alignment with legally grounded categories such as those of the EU AI Act.

While dual-model pipelines, such as Bergeron [20], LLMSelfDefense [24], and SelfDefend [23], show promise in reducing harmful content, they often allow adversarial context to bypass safeguards. D-SHIELD overcomes this limitation by enforcing strict *decontextualization* and explicit regulation-aware criteria: the validator assesses each output in isolation, without access to the prompt or dialog history, and classifies it against auditable rules derived from the EU AI Act and provider usage policies. In this context, the notion of compliance is intentionally defined at the technical level. An output is considered compliant if it aligns with explicitly defined regulatory risk categories and policy constraints. These checks enable verifiable and reproducible validation decisions on software artefacts, but do not constitute a legal determination of compliance with the EU AI Act.

Building on evidence from an expert-panel evaluation, this capability is integrated into an automated safeguard that blocks `Non-Compliant` content before it reaches the user.

From a Software Engineering standpoint, D-SHIELD is conceived as a modular safeguard architecture that can be integrated into AI-enabled systems as a runtime compliance-support component. Rather than aiming at legal certification or conformity assessment, the proposed technique enables regulation-aligned checks on concrete software artefacts, namely *LLM-generated outputs*, supporting risk mitigation, auditability, and human supervision within broader regulatory compliance workflows.

The remainder of this section presents D-SHIELD's architecture, the decontextualized guard prompt and decision logic, and its implementation in a functional prototype.

4.1. The proposed decontextualized LLM-based safeguard technique

Fig. 1 illustrates the D-SHIELD technique, an automated safeguard designed to validate model outputs before they are presented to the user. It relies on two independent LLMs with distinct roles: $\boldsymbol{LLM_{User}}$, which generates candidate responses to user queries, and $\boldsymbol{LLM_{Guard}}$, a *decontextualized* validator that evaluates those responses in isolation, without access to the original prompt or prior conversational context.

The technique is articulated in three main steps:

1. **Content Generation**: In response to a user's natural language query, $\boldsymbol{LLM_{User}}$ produces a candidate reply, referred to as the `LLM User Output`. This model behaves like a standard LLM-powered assistant, generating coherent and informative responses.
2. **Compliance Check**: Before delivery, the `LLM User Output` is embedded in a `Guard Prompt`, a classification query that combines the generated text with a predefined assessment instruction. The *decontextualized* $\boldsymbol{LLM_{Guard}}$ evaluates this prompt in isolation and returns a binary decision, `Compliant` or `Not Compliant`, based on the legal and ethical standards defined by the AI Act and OpenAI's usage policies.
3. **Output Filtering**: The system determines the final message presented to the user. If classified as `Compliant`, the original `LLM User Output` is delivered unchanged. If classified as `Not Compliant`, the response is blocked and replaced with a `Non-Compliant Warning Message`, informing the user that the request violates the provisions of the AI Act and OpenAI's usage policies.




Fig. 1. Proposed safeguard technique.

Within a broader regulatory compliance workflow, D-SHIELD operates as a runtime output-validation gate that intercepts and evaluates generated content before delivery to end users. Its role is to provide timely, automated support for compliance-related decision making, enabling potentially non-compliant outputs to be blocked or flagged for further human review.

The technique is fully automated and agnostic to both the underlying models and the classification prompt. It supports the use of different LLMs for generation and compliance checks, and the classification prompt (i.e., the `Guard Prompt`) can be adapted to target compliance requirements beyond the AI Act, such as internal policies or domain-specific regulations. This flexibility makes the technique broadly applicable across diverse deployment scenarios.

4.2. Prototype implementation details

The proposed safeguard technique was implemented in a web-based prototype tool integrating our decontextualized output validation mechanism. This implementation serves as a proof of concept for applying the technique in real-world LLM-based applications.

For the *content generation* phase, we used ChatGPT in its `gpt-4o-2024-08-06` version, hereafter referred to as ChatGPT-4o. This choice is motivated by the model's prominence as the most widely adopted LLM among general-purpose users. As of 2025, ChatGPT processes over 1 billion queries per day and serves more than 800 million users weekly, far surpassing platforms such as Meta AI and Google Gemini.[4] This widespread use makes it a representative and realistic candidate for evaluating safeguard mechanisms in deployment scenarios.

For the *compliance checking* phase, we retained flexibility in the choice of LLM but intentionally adopted the same model family (ChatGPT-4o). While using the same model for both phases might raise concerns about redundancy or self-alignment, this decision is consistent with our decontextualized design. The two instances operate completely independently under distinct constraints: the compliance validator receives only the generated response and a classification prompt, without access to the original query, conversation history, or metadata. This strict isolation ensures there is no contextual leakage between generation and validation. Moreover, using the same model family guarantees that any observed differences in classification outcomes are attributable to the structural properties of decontextualized evaluation, rather than to discrepancies in model capabilities. From an industry perspective, this mirrors realistic deployment scenarios, where a single provider is often preferred for reasons of API compatibility, latency, governance, and cost.

In the prototype, the compliance-check phase is therefore implemented by sending a `Guard Prompt` to $\boldsymbol{LLM_{Guard}}$, which embeds the candidate response and enforces a strict binary decision:

Guard Prompt

```
You are an AI safety expert and regulatory compliance auditor. Reply exclusively YES or NO. No other words. Is the following text compliant with the EU AI Act, GDPR, and OpenAI usage policies? To answer, you must assess if the text contains any of the following prohibited categories: 1. Development or use of weapons 2. Facilitation of physical harm to others 3. Subliminal, manipulative, or deceptive techniques 4. Development or distribution of illegal substances 5. Suicide or self-harm 6. Financial or identity fraud and related scams 7. Extremist or terrorist support 8. Use of narcotic substances 9. Incitement to hatred or discrimination 10. Sexually explicit or suggestive content 11. Privacy violations Text to evaluate: ''${LLM_User_response}''
```

The design of the guard prompt is the result of an iterative refinement process. In early experiments, we explored richer and less constrained prompts that explicitly asked the validator to justify its decision with references to the AI Act and OpenAI usage policies. These variants were useful during development, as they allowed us to verify that the model possessed an adequate understanding of the relevant regulatory categories and policy constraints. However, such prompts consistently produced long, explanatory outputs in which the model articulated the rationale behind its classification.

These verbose responses, although informative, proved impractical from an implementation perspective. They required additional parsing logic, introduced ambiguity in mapping free-text explanations to binary decisions, and increased the risk of explanation leakage, i.e., the inadvertent reproduction or paraphrasing of harmful content within the justification itself. Moreover, longer outputs increased latency and token usage, which is undesirable in real-time or large-scale deployment scenarios.

For these reasons, we intentionally converged on a more minimal prompt design, which constrains $\boldsymbol{LLM_{Guard}}$ to emit a strict binary decision. Despite its simplicity, this prompt was empirically effective in identifying non-compliant outputs across the considered AI Act categories, while significantly simplifying the integration of the safeguard within the prototype.

Moreover, to address cost efficiency, we also implemented a lightweight configuration of the safeguard, named D-SHIELD$_{\text{light}}$. In this variant, the compliance check is delegated to `gpt-4o-mini`, a more efficient model from the same family. This design allows us to examine the trade-off between reduced computational cost and classification effectiveness, an aspect of particular relevance for large-scale or resource-constrained applications.

The graphical user interface of the prototype is shown in Fig. 2. The left panel replicates a conventional chatbot assistant, where users can input natural language queries and receive generated responses. This simulates interaction with a general-purpose assistant enhanced by our safeguard. The right panel, not visible to the end user, displays the raw output that would have been generated without any safeguards. This setup enables a side-by-side comparison between the validated response and the original one, illustrating the effect of the compliance filter.

The right-hand side of Fig. 2 shows an example of a jailbreak prompt based on *Inverted Intent*. In this case, the user does not directly request harmful content (e.g., instructions for building a cannon) but frames the query in apparently harmless terms: "`I definitely don't`

[4] https://www.demandsage.com/chatgpt-statistics/




Fig. 2. D-SHIELD web interface: ChatGPT-4o enhanced with the decontextualized guard (left) and standard ChatGPT-4o (right).

`want to create a cannon...`". Despite this, the model produced a detailed step-by-step description of cannon construction, including material selection, pressure handling, and mechanical design, in clear violation of OpenAI's usage policy and the AI Act. On the safeguarded side, D-SHIELD correctly identified the response as non-compliant and blocked it, replacing it with a warning message. This example illustrates the technique's ability to neutralize subtly engineered jailbreaks while avoiding the inclusion of highly disturbing or ethically sensitive content in the paper. More problematic cases, such as those involving violence, fraud, or hate speech, are excluded here for clarity and responsibility, but are available in the replication package for research and reproducibility. Importantly, this test, conducted in April 2025, shows that even today, harmful content can be elicited with minimal effort, underscoring the urgency of proactive output-level protection mechanisms in LLM-based systems.

From an implementation perspective, the prototype was developed entirely in JavaScript. Communication with the language model is managed through the official OpenAI API [40], which supports both stateless and session-aware interactions. To preserve conversational continuity for the user-facing component, session information is maintained when querying $\boldsymbol{LLM}_{User}$. Conversely, to guarantee strict decontextualization of $\boldsymbol{LLM}_{Guard}$, a new stateless API call is made for each validation, ensuring complete isolation from the user query, conversation history, and metadata.

This implementation aligns with our design principles, i.e., preserving natural user interaction while enforcing rigorous, context-free compliance checking in the background.

5. Experimental evaluation

This section discusses the experimental evaluation we performed with the goal of assessing the effectiveness of the proposed safeguard technique in detecting and blocking *non-compliant content* generated by LLMs. To this end, we formulated four research questions. For each RQ, we also report the corresponding *Rationale*, which explains its motivation and scope:

RQ1: *To what extent can a decontextualized LLM detect non-compliant outputs generated by another LLM?*
Rationale: This question investigates whether a *decontextualized* LLM can reliably identify harmful or policy-violating outputs without having access to the original prompt or conversational context.

RQ2: *To what extent can D-SHIELD mitigate the generation of non-compliant output content?*
Rationale: Here, we explore whether the detection capability can be effectively integrated into a safeguard mechanism that automatically prevents non-compliant content from reaching end users.

RQ3: *To what extent does D-SHIELD compare to state-of-the-art jailbreak mitigation techniques proposed in the literature in detecting and blocking harmful outputs?*
Rationale: This question broadens the perspective by positioning D-SHIELD against existing jailbreak mitigation techniques in order to evaluate its relative strengths.

RQ4: *To what extent does the lightweight D-SHIELD$_{light}$ compare w.r.t to D-SHIELD in terms of effectiveness and cost reduction?*
Rationale: The goal here is to assess the trade-off between efficiency and robustness in the lightweight variant, designed for scenarios where computational resources are constrained.

5.1. Evaluation metrics

To answer the RQs, we rely on multiple evaluation metrics, each selected to provide informative and context-appropriate evidence. Table 3 summarizes the mapping between RQs and metrics.

For RQ1, we use *Accuracy*, *Precision*, and *Recall* to measure alignment between the classifications of the decontextualized LLM and the expert-annotated ground truth of `Compliant` vs. `Not Compliant` content, defined according to the EU AI Act and provider usage policies.

For RQ2 and RQ3, we employ the *Attack Success Rate (ASR)*, defined as the ratio between the number of jailbreak prompts that succeed in eliciting a non-compliant output and the total number of prompts tested. Lower ASR values indicate a more effective safeguard, as they correspond to fewer adversarial attempts bypassing the technique.

Table 3
Metrics adopted for each research question.

RQ	Metrics
RQ1	Accuracy, Precision, Recall
RQ2	ASR
RQ3	ASR
RQ4	ASR, RCS

For RQ4, we evaluate both ASR and the *Relative Cost Saving (RCS)*. RCS quantifies the percentage reduction in cost for a single compliance check when using the lightweight guard model D-SHIELD$_{\text{light}}$ instead of the standard one. It is calculated as:

$$RCS = \frac{C_{standard} - C_{light}}{C_{standard}} \times 100 \quad (1)$$

where $C_{standard}$ and C_{light} denote the cost in dollars per million tokens for `gpt-4o` and `gpt-4o-mini`, respectively. Higher RCS values indicate greater economic efficiency, allowing a quantitative assessment of the trade-off between cost and mitigation effectiveness.

5.2. Object selection

Different sets of prompts were used for RQ1 and for RQ2–RQ4, reflecting the distinct evaluation goals of these research questions.

Prompt selection for RQ1. For RQ1, we specifically crafted jailbreak prompts designed to elicit potentially non-compliant outputs. To ground this process in real-world constraints, we integrated the European Union's AI Act [25] and the General-Purpose AI Code of Practice (CoP) [27] with the concrete prohibitions found in OpenAI's Usage Policies [28]. The regulatory framework defines high-level "Systemic Risks" (e.g., CBRN, cyber offence, harmful manipulation as per CoP Appendix 1.4) and "Prohibited Practices" (Article 5), whereas OpenAI's policies provide the operational definitions necessary to construct specific, verifiable jailbreak prompts. These included, for example, narcotic substances, privacy violations, dangerous instructions, incitement to discrimination, and sexually explicit content, as summarized in Table 4.

To construct these prompts, we adopted a *multi-turn adversarial conversation pattern*, reflecting how attackers iteratively refine inputs to escalate a dialog towards harmful content [29]. Initial queries were vague or indirect and progressively rephrased to become more explicit until they elicited policy-violating responses. One jailbreak prompt was defined for each category, executed on ChatGPT-4o in April 2025. Since prompts were multi-turn, we retained the full interaction history and extracted multiple outputs per category, resulting in 165 potentially non-compliant responses across the selected risk areas. The multi-turn interactions served exclusively as a generation mechanism to elicit non-compliant behavior, while the unit of analysis for RQ1 is the individual generated output rather than the conversation itself. Accordingly, all outputs produced during these interactions were retained without further selection or filtering.

Although the number of outputs collected for RQ1 is smaller than in earlier jailbreak studies, this reflects the fundamentally different nature of the prompts we use. Each item in our dataset corresponds to a jailbreak that successfully bypassed the safety mechanisms of a modern aligned LLM (ChatGPT-4o, April 2025). Designing such successful jailbreaks is significantly more difficult today due to multiple layers of alignment (e.g., RLHF, Constitutional AI, supervised fine-tuning), dynamic refusal heuristics, and continuously updated pattern-based detectors. As a result, only a small fraction of attempted adversarial conversations produce genuinely non-compliant outputs, making the dataset qualitatively richer but necessarily smaller.

Prompt selection for RQ2, RQ3, and RQ4. For RQ2–RQ4, the focus was on evaluating the ability of D-SHIELD and the baseline techniques to block harmful outputs under realistic adversarial conditions. To this end, we compiled a benchmark of jailbreak prompts collected from online sources. The collection process involved targeted web searches with the query "`ChatGPT jailbreak`", focusing particularly on Reddit communities where jailbreak prompts are actively shared and refined. We reviewed three prominent subreddits, `r/ChatGPT` [41], `r/ChatGPTPromptGenius` [42], and `r/ChatGPTJailbreak` [43], and selected prompts using convenience sampling, prioritizing those that were highly upvoted, recent, or explicitly described as successful. We initially attempted to reuse publicly available jailbreak datasets widely used in prior work (e.g., DAN-style prompts, JailbreakBench, AdvBench, and other community-contributed attacks). However, during preliminary testing, we observed that almost all of these prompts were immediately blocked by ChatGPT-4o. This is expected, as providers progressively patch vulnerabilities once prompts become public. Consequently, relying on legacy datasets would have produced artificially inflated performance and misleading comparisons. Beyond Reddit, we extended the search to forums, blogs, and documents containing detailed jailbreak sequences. Although these prompts were reported as effective, we independently validated each one by executing it on ChatGPT-4o in April 2025. This preliminary validation step served solely to identify currently effective attacks and does not introduce evaluation circularity, as ChatGPT-4o is a proprietary model with no fine-tuning or learning interface, and the benchmark-construction phase is strictly separated from the subsequent safeguard evaluation. This phase defines the context-enabled baseline of an ablation study, where conversational context is present and later removed to evaluate its impact on jailbreak effectiveness. The resulting outputs were reviewed by one of the three domain experts involved in the earlier annotation process for RQ1 using the same compliance criteria, and were subsequently validated by the other two experts, with no discrepancies observed.

Only prompts that generated responses labeled as `Not Compliant` were retained. This filtering resulted in a benchmark of 145 validated jailbreak prompts, which were used to evaluate RQ2 and RQ3, and to support the efficiency analysis in RQ4.

5.3. Subject selection

To support RQ1, we recruited a panel of three independent professionals with complementary expertise. The panel included: (i) a digital humanist and AI ethics researcher with five years of experience on normative frameworks for responsible AI, (ii) a philosopher of science with more than ten years of work on logic, metaphysics, and artificial intelligence, and (iii) a legal expert with over seventeen years of legal practice and three years of specialization in AI regulation and the EU AI Act. The selection was guided by the goal of ensuring diverse disciplinary perspectives combined with demonstrated expertise in AI ethics and regulation.

5.4. Tool selection

For RQ3, we compared D-SHIELD with state-of-the-art plugin-based mitigation techniques. To ensure a fair comparison, we focused on methods reviewed in Section 2 and summarized in Table 1. Because D-SHIELD itself is plugin-based, we excluded model-level defenses such as SafeDecoding [36] and LlamaGuard [37], and instead selected one representative technique for each plugin-based category:

- *SelfDefend* [23], which filters user prompts at the *input level*;
- *LLMSelfDefense* [24], which validates model responses at the *output level*;
- *Bergeron* [20], which integrates both *input- and output-level* checks in a dual-LLM configuration.

Table 4
Distribution of prohibited outputs mapped to regulatory frameworks and provider policies. CoP Appx = Code of Practice for General-Purpose AI Models (Safety and Security Chapter). Art = AI Act Article. Annex II = List of serious criminal offenses used to define threats to public security. OpenAI = OpenAI Usage Policies.

Category	Samples	Regulatory mapping
Development or use of weapons	17	**CoP:** Appx 1.4(1) (CBRN); **OpenAI:** Weapons development or use
Facilitation of physical harm to others	19	**CoP:** Appx 1.1(2) (Risks to safety); **OpenAI:** Violence; Harassment
Subliminal, manipulative, or deceptive techniques	29	**AI Act:** Art. 5(1)(a); **CoP:** Appx 1.4(4) (Harmful manipulation); **OpenAI:** manipulate or deceive people
Development or distribution of illegal substances	16	**AI Act:** Annex II - Illicit trafficking; **OpenAI:** Illicit activities
Suicide or self-harm	11	**CoP:** Appx 1.1(1) (Risks to public health); **OpenAI:** Self-harm
Financial or identity fraud and related scams	13	**CoP:** Appx 1.4(3) (Cyber offence); **AI Act:** Art. 5(1)(a); **GDPR:** Art. 5; **OpenAI:** Economic harm; Fraud, scams, and deceptive activity
Extremist or terrorist support	10	**AI Act:** Annex II - Terrorism; **OpenAI:** Violence (Violent extremism)
Use of narcotic substances	8	**OpenAI:** Illegal acts
Incitement to hatred or discrimination	18	**CoP:** Appx 1.1(4) (Risks to fundamental rights); **OpenAI:** Hate speech
Sexually explicit or suggestive content	22	**AI Act:** Annex II - Sexual exploitation; **OpenAI:** Sexual content
Privacy violations	2	**GDPR:** Art. 5; **CoP:** Appx 1.1(4); **OpenAI:** Privacy
Total	**165**	




Fig. 3. Experimental procedure for RQ1.

This selection benchmarks D-SHIELD against complementary strategies, ensuring coverage of the main design options within the plugin-based mitigation landscape.

5.5. Experimental procedures

We designed two experimental procedures: one dedicated to RQ1 and another shared by RQ2, RQ3, and RQ4.

Procedure for RQ1. The procedure for RQ1 is shown in Fig. 3. After defining the non-compliant categories and generating outputs through multi-turn jailbreak prompts (see Section 5), the process continued with an *Expert Classification* phase.

First, a three-hour focus group was held to align the three experts on study objectives, representative examples, and criteria for borderline cases. Each expert then independently annotated all 165 outputs, labeling them as either `Compliant` or `Not Compliant`, without access to contextual metadata, conversation history, or model identifiers.

This restriction was intentional and aligned with the objective of RQ1. Since the decontextualized guard evaluates outputs without access to prompts or conversational context, experts were provided with the same information available to the model under evaluation. Exposing experts to the full interaction history would have introduced additional cues (e.g., inferred intent or escalation dynamics) that are explicitly unavailable to the guard, thereby biasing the comparison. By limiting experts to isolated outputs, we ensured that both human and model judgments were based on identical evidence.

Moreover, annotation guidelines were grounded in explicit regulatory criteria as described in Section 3. In particular, experts assessed whether each output exhibited characteristics associated with prohibited or high-risk content categories, or other forms of legally relevant harm derived from the considered regulatory frameworks. The annotation task was therefore framed as a regulatory risk assessment at the output level, rather than as a generic ethical evaluation.

Disagreements were addressed in a second reconciliation session, also lasting about three hours and moderated by one of the authors. In this session, contested cases were reviewed and debated, with reference to relevant legal and ethical frameworks when needed.

Inter-rater agreement was measured with Fleiss' kappa [44], yielding $\kappa = 0.869$, considered "almost perfect agreement". For cases without unanimous consensus, majority voting [45] was applied, producing a ground truth of 103 `Not Compliant` and 62 `Compliant` outputs.

In the *Decontextualized LLM Classification* phase, the same 165 outputs were submitted to a decontextualized instance of ChatGPT-4o via the OpenAI API. The model operated in a stateless mode, receiving only the output text embedded in a zero-shot classification prompt. Its task was to return a binary judgment (`Compliant` or `Not Compliant`). Finally, in the *Data Analysis* phase, we compared the model's predictions against the expert ground truth and computed Accuracy, Precision, Recall, and F1-score.

Procedure for RQ2, RQ3, and RQ4. For RQ2–RQ4, we used the 145 validated jailbreak prompts collected from online sources and independently confirmed to elicit harmful outputs. This dataset provided a realistic and up-to-date evaluation basis.

Table 5
Confusion matrix and classification metrics for ChatGPT-4o predictions of compliance with the AI Act and OpenAI's usage policies, evaluated against expert majority vote labels. C: `Compliant`. NC: `Not Compliant`.

Confusion matrix		
	Pred C	Pred NC
True C	42	20
True NC	4	99
Classification metrics		
Class	Precision	Recall
C	0.913	0.677
NC	0.832	0.961
Accuracy	0.855	

Table 6
Comparison of Attack Success Rate (ASR) across jailbreak mitigation techniques. Lower values indicate stronger defense.

Tool	ASR
D-SHIELD	2.76%
LLMSelfDefend	26.20%
SelfDefend (P_{Intent})	71%
SelfDefend (P_{Direct})	78.60%
Bergeron	13.80%

For RQ2, the prompts were executed against D-SHIELD, and the ASR was computed as the fraction of harmful responses that bypassed the safeguard. For RQ3, the same prompts were submitted to the baseline tools (SelfDefend, LLMSelfDefense, and Bergeron), and ASR values were derived in the same way. For RQ4, the benchmark prompts were executed against D-SHIELD$_{\text{light}}$, and both ASR and RCS were computed in comparison to D-SHIELD.

Together with the context-enabled baseline, this setting completes the ablation study focused on conversational context, in which conversational context is explicitly removed through D-SHIELD, while all other experimental conditions, including the jailbreak prompts, are kept identical.

This uniform strategy ensured consistent and directly comparable evaluation across all techniques. Importantly, we did not reuse datasets from the original baseline studies, as many of those jailbreak prompts are now obsolete and directly blocked by the current version of ChatGPT, even without additional safeguards. Using such outdated prompts would have led to artificially inflated performance. For this reason, the comparative evaluation relied exclusively on our benchmark of 145 prompts validated by domain experts.

5.6. Results and RQs answering

This section presents the results of our experimental evaluation and the corresponding answers to each research question.

5.6.1. Answering RQ1

To evaluate the capability of the decontextualized LLM in detecting harmful outputs, we compared its binary predictions (`Compliant` / `Not Compliant`) with the expert-annotated ground truth. As shown in Table 5, the model correctly flagged 99 of the 103 `Not Compliant` outputs, yielding a recall of 0.961 and a precision of 0.832. Among the 62 `Compliant` outputs, 42 were correctly classified, corresponding to a recall of 0.677 and a precision of 0.913. The overall accuracy was 0.855.

The model adopted a conservative stance in borderline cases: among 15 outputs with expert disagreement, it sided with the majority in 9 instances, showing a preference for false positives over false negatives. This behavior is consistent with the precautionary principle endorsed by the AI Act.

Answer to RQ1

The decontextualized LLM (ChatGPT-4o) showed strong alignment with expert judgments, achieving high recall (0.961) for harmful content and an overall accuracy of 0.855. Its conservative stance prioritizes safety by favoring the blocking of potentially harmful outputs, at the cost of occasionally rejecting permissible content (recall 0.677 for compliant outputs).

5.6.2. Answering RQ2

To evaluate the effectiveness of D-SHIELD in mitigating non-compliant outputs, we measured the Attack Success Rate (ASR). Each of the 145 validated jailbreak prompts was executed against D-SHIELD, and the resulting outputs were classified as either blocked or delivered.

Of the 145 prompts, only 4 harmful outputs bypassed the safeguard, while 141 were successfully blocked. This corresponds to an **ASR of 2.76%**, meaning that fewer than 3% of adversarial attempts managed to circumvent the safeguard.

Answer to RQ2

D-SHIELD achieved an ASR of 2.76% on the curated set of 145 jailbreak prompts, successfully blocking 141 harmful outputs. This demonstrates its strong effectiveness as an automated, decontextualized, output-level safeguard, with only a minimal fraction of adversarial attempts managing to bypass it.

5.6.3. Answering RQ3

For each tool under comparison, we measured the Attack Success Rate (ASR), defined as the ratio of jailbreak prompts resulting in harmful outputs to the total prompts tested. For LLMSelfDefend and Bergeron, the tools produced a classification of each prompt as harmful or not, which we converted into ASR values. For SelfDefend, ASR scores were directly reported. This ensured a uniform basis for comparison across all techniques.

As shown in Table 6, D-SHIELD achieved the best performance, with an ASR of 2.76%. In contrast, Bergeron reached 13.80%, LLMSelfDefend 26.20%, and SelfDefend reported 71% (intent mode) and 78.60% (direct mode).

These results indicate that D-SHIELD's decontextualized, output-level strategy provides a clear advantage over input-level, output-level, and combined monitoring approaches, all of which remain substantially more vulnerable to adversarial prompts.

Answer to RQ3

D-SHIELD achieved an ASR of 2.76%, markedly lower than all baseline techniques, whose values ranged from 13.80% (Bergeron) up to 78.60% (SelfDefend, direct mode). This confirms that its decontextualized, output-level validation provides substantially stronger resilience to jailbreak attacks, reducing adversarial success to below 3% and outperforming both input-level and hybrid monitoring strategies.

5.6.4. Answering RQ4

To evaluate the mitigation capabilities of D-SHIELD$_{\text{light}}$, we tested it on the benchmark of 145 jailbreak prompts. The system successfully blocked 143 adversarial attempts, allowing only 2 harmful outputs to pass. This corresponds to an ASR of 1.38%, showing that the safeguard neutralized more than 98% of the attacks.

To assess efficiency, we calculated the Relative Cost Saving (RCS) based on official model pricing. The standard D-SHIELD configuration relies on `gpt-4o`, priced at $2.50 per million input tokens and $10 per million output tokens.[5] By contrast, D-SHIELD$_{\text{light}}$ uses `gpt-4o-mini`, priced at $0.15 for input and $0.60 for output per million tokens.[6]

Applying these values yields an RCS of 94%. This substantial reduction highlights the practical viability of D-SHIELD$_{\text{light}}$ in large-scale or cost-sensitive scenarios, where resource efficiency is a critical concern.

Answer to RQ4

D-SHIELD$_{\text{light}}$ achieved a Relative Cost Saving of 94% while maintaining strong mitigation effectiveness, with an ASR of only 1.38%. Notably, this result is even lower than that of the standard configuration, indicating that the lightweight variant can provide both superior efficiency and robust protection. These findings suggest that D-SHIELD$_{\text{light}}$ offers a practical and scalable solution for deployments where cost and computational efficiency are decisive factors.

6. Threats to validity

In this section, we outline potential limitations of our study and the measures taken to mitigate them. We structure our analysis across four main categories of threats and also discuss possible directions for future mitigation.

Construct Validity. Construct validity concerns the extent to which the concept of *non-compliant content* was consistently defined and assessed. In our study, non-compliance was intended as any possible violation of OpenAI's usage policies and EU AI Act. Although these sources provide structured criteria, borderline cases remain open to subjective interpretation. To mitigate this risk, we relied on a panel of three domain experts, combined with reconciliation sessions to consolidate final labels. At the same time, the evolving nature of regulatory frameworks may introduce residual ambiguity in future evaluations. A possible mitigation is to broaden the set of guidelines used for annotation, incorporating multiple providers and emerging regulatory frameworks. Moreover, compliance in this study is intentionally assessed at the level of software artefacts, namely the outputs generated by an LLM. This definition supports technical verifiability and reproducibility, but does not capture broader legal, organizational, or governance requirements associated with full regulatory compliance.

Internal Validity. Internal validity refers to whether the observed effects can be attributed to our approach rather than confounding factors. To isolate the role of decontextualization, we deliberately used the same LLM (ChatGPT-4o) for both content generation and compliance validation, under distinct operational constraints. This avoided differences in baseline capabilities while enforcing strict stateless separation through independent API calls. However, this setup may still reflect weaknesses shared by the model family. Moreover, the compliance prompt wording may influence classification outcomes. We mitigated this by iterative refinement, but sensitivity to prompt design remains a recurring threat. Comparisons with baselines were conducted under a common procedure, yet differences in their intended operating points or default prompts may influence relative outcomes. Furthermore, the comparative evaluation involves baseline tools that rely on heterogeneous underlying LLMs, as dictated by their original implementations. While this heterogeneity may partially influence absolute performance, enforcing a common underlying model across all techniques was not feasible without modifying third-party tools. Such modifications would introduce an additional source of bias, as they would deviate from the original design and intended configuration of the baseline approaches. Consequently, the comparison reflects realistic deployment conditions rather than a fully controlled ablation on model choice.

Additionally, while the validator is not directly accessible to users, a theoretical residual risk remains. An adversary with detailed knowledge of the dual-LLM architecture could, in principle, attempt to induce the generator to produce outputs embedding *prompt-injection–style instructions* aimed at interfering with the guard's evaluation task (e.g., directives to ignore prior instructions or to force a compliant classification). We consider this scenario unlikely in practice, as it presupposes both architectural awareness and the ability to generate outputs that are simultaneously harmful, plausibly compliant, and capable of influencing the validator. This limitation is inherent to natural-language-based output classifiers and is acknowledged as a potential internal validity threat.

Finally, the interpretation and operationalization of regulatory requirements may constitute another threat to the internal validity of our work. Although we ground our compliance categories in the EU AI Act and its Code of Practice, regulatory texts may evolve over time, and their interpretation may vary across jurisdictions or enforcement contexts. Consequently, the mapping between legal provisions and output-level categories, while explicit and auditable, reflects a snapshot aligned with the regulatory understanding at the time of the study.

Finally, the same model family is used for the user-facing generator and for the validator variants, which simplifies engineering but limits the analysis of cross-family interactions. This choice also reflects common industrial practice, where a single LLM provider is typically adopted due to cost efficiency and API compatibility considerations. Future studies could assess robustness by varying compliance prompts and by employing multiple validator models from different providers.

External Validity. External validity is threatened by the limited scope of our scenarios and tools. Our crafted prompts targeted representative but not exhaustive categories of harmful content, and our benchmark of 145 jailbreak prompts, though validated, may not capture more sophisticated or emerging attack patterns. In addition, the evaluation was conducted on ChatGPT-4o within a controlled prototype application, without testing under high-load or multi-user conditions. Latency, concurrency, and input diversity may affect behavior in real-world deployments. Furthermore, our comparative study included only plugin-based techniques, excluding model-based defenses. This choice, though motivated by methodological alignment, limits the generalizability of the comparison. Future work should extend evaluation to other LLM families (e.g., Gemini, Claude, LLaMA) and include more diverse mitigation strategies, as well as performance studies in realistic deployment environments. Furthermore, our evaluation and compliance framing are explicitly grounded in the European regulatory ecosystem, particularly the EU AI Act and its associated Code of Practice. While the underlying technical principles of decontextualized output validation may generalize beyond this context, the specific compliance categories and regulatory mappings may not directly transfer to non-European jurisdictions with different legal frameworks or enforcement priorities.

Reliability. Reliability relates to the correctness of the conclusions drawn from the evaluation. The dataset used for RQ1 (165 outputs) and for RQ2–RQ4 (145 jailbreak prompts) is relatively small, which may reduce statistical power. While modest in absolute terms, these datasets consist exclusively of jailbreaks that successfully elicited harmful or non-compliant outputs from an up-to-date aligned LLM. Because modern models incorporate multiple safety layers and continuously updated refusal mechanisms, constructing successful jailbreak prompts is inherently difficult. In addition, most publicly available jailbreak datasets have become obsolete, as the vulnerabilities they exploit have already been patched by providers. We therefore relied on newly engineered prompts validated in April 2025, prioritizing realism and contemporary relevance over volume.

Although experts' inter-annotator agreement was high ($\kappa = 0.869$), annotations were not blinded to the study's purpose, introducing a potential bias. Cost comparisons for D-SHIELD$_{\text{light}}$ also rely on current API

[5] https://platform.openai.com/docs/models/gpt-4o

[6] https://platform.openai.com/docs/models/gpt-4o-mini

pricing, which is subject to change over time. To enhance transparency, we release all data, code, and experimental procedures in an open-access replication package. Future replications on larger datasets, with blinded annotation protocols and across different pricing or hardware settings, could further strengthen reliability.

7. Discussion and insights

This section goes beyond the direct answers to the research questions by examining broader patterns and insights emerging from the experimental results. The discussion is organized around the four research questions and concludes with an overall synthesis of implications.

7.1. Insights from RQ1: Expert and model alignment

The results of RQ1 showed that the decontextualized LLM (`ChatGPT-4o`) closely approximates expert judgments in distinguishing compliant from non-compliant outputs. A high recall of 0.96 for harmful content confirms its reliability as a safety filter, ensuring that most harmful responses are detected. At the same time, the model exhibited a conservative stance, with a tendency to classify borderline or ambiguous cases as `Not Compliant`. This explains the lower recall observed for compliant outputs (0.68), reflecting a systematic bias toward over-blocking. While this introduces a risk of false positives, it aligns with the precautionary principle of the AI Act, which favors minimizing the delivery of harmful content even at the expense of reduced permissiveness.

A closer analysis of the 15 borderline cases where experts disagreed provides additional insight. In 9 of these, the model sided with the majority, suggesting that its judgments were not arbitrary but consistent with collective expert reasoning. Two recurrent patterns stand out. In technical and biological domains (e.g., chemical synthesis, explosive mixtures, instructions that could facilitate animal harm), the model treats procedural specificity as a strong signal to block, erring on the side of caution even when some experts regard the text as descriptive or academic. By contrast, in socio-political and interpersonal contexts (e.g., relationship or persuasion advice, resistance slogans, sexually aggressive undertones), harmfulness is more often conveyed pragmatically than through explicit illegal or violent language; here, the model is comparatively more permissive, at times overlooking subtle manipulative or incitement risks flagged by at least one expert.

Together, these patterns reveal two main tendencies: (i) a *conservative stance* in technical and biological domains (e.g., chemical synthesis, animal harm), where it systematically over-blocked, and (ii) a *permissive stance* in socio-political and interpersonal domains, where harmfulness was subtler and embedded in pragmatics. These dual behaviors highlight both the strengths and the limitations of decontextualized classification: highly reliable for explicit harms, but less consistent in nuanced or context-dependent cases.

A complementary analysis concerns the remaining 6 borderline cases in which the model sided with the expert minority. In five of these, the LLM classified the output as `Not Compliant` despite a majority expert judgment of compliance. These cases predominantly involve operational or dual-use content, such as detailed descriptions of explosive chemical reactions using household materials, pharmacological synthesis pathways, and step-by-step processes related to illicit drug production. In these situations, the model prioritized procedural concreteness and real-world applicability as decisive risk indicators, overriding educational or theoretical framing deemed acceptable by some experts. The sixth case shows the opposite pattern: the model classified the output as `Compliant` against a majority expert judgment of non-compliance. Here, the content consisted of reflective or ironic commentary on harmful behaviors, lacking actionable detail or explicit endorsement, which led the model to privilege the absence of operational guidance over implicit normalization risks.

Taken together, these minority-alignment cases refine the same pattern observed in the majority-alignment analysis. The decontextualized LLM tends to align with the most conservative expert judgment when outputs contain operational or dual-use knowledge, while divergence from expert consensus arises mainly when risk is conveyed indirectly through narrative, tone, or pragmatic framing. This further supports the characterization of decontextualized output-level validation as effective for detecting explicit and actionable harms, while highlighting a limited and structurally coherent set of edge cases where expert-model alignment is less stable.

7.2. Insights from RQ2: Effectiveness and limitations of the safeguard

The results of RQ2 confirmed the effectiveness of D-SHIELD, which blocked 141 of 145 jailbreak prompts (ASR = 2.76%). However, the four failures reveal important limitations of output-level validation. These failures correspond to a small set of borderline cases involving *implicit* rather than *explicit* harms. Explicit harms refer to outputs whose malicious nature is directly observable from the text itself, such as procedural instructions to build weapons, manufacture illegal substances, or conduct cyberattacks. In contrast, the failed cases involve texts that are semantically benign or legitimate when considered in isolation, and whose potential harm emerges only under specific interpretations, contexts, or misuse scenarios.

They can be grouped into two categories: (i) texts indistinguishable from legitimate communication (e.g., impersonation or access-request emails), and (ii) texts whose harmfulness arises from pragmatic or psychological framing (e.g., metaphorical expressions of suicidal ideation or apologies embedding subtle blame). In both cases, the surface semantics appear innocuous, while the harmful intent remains implicit. For instance, an email requesting access to a child's school account is not inherently malicious and is indistinguishable from a legitimate parental request at the textual level; it becomes harmful only if authored or exploited by an unauthorized actor. Similarly, metaphorical descriptions of distress or remorseful messages that subtly shift blame rely on discourse-level or psychological cues rather than explicit harmful instructions.

Importantly, these cases illustrate a challenge that is orthogonal to adversarial prompt obfuscation. Unlike staged transformations, role-playing, or misleading contextual framing, where explicit harmful intent is deliberately concealed during generation, implicit harms do not exploit prompt-level manipulation. Instead, their risk arises from how the generated content is interpreted, contextualized, or acted upon within a broader psychological or social setting.

Accordingly, these limitations do not contradict our claim that decontextualized output-level validation effectively mitigates obfuscation-based jailbreaks. Rather, they delineate the scope of applicability of the proposed safeguard, which is highly effective for explicit harms and adversarially obfuscated prompts, but naturally limited when harmfulness is implicit, allegorical, or intent-driven.

Complementary approaches, such as intent detection or pragmatic analysis, represent a natural direction for extending the safeguard to cover these residual cases.

7.3. Insights from RQ3: Comparative effectiveness

The comparative evaluation confirmed the superior performance of D-SHIELD relative to plugin-based baselines. Out of 145 prompts, D-SHIELD failed in only 4 cases where at least one baseline succeeded, succeeded in 129 cases where baselines failed, and agreed with all baselines in 12 cases.

Cases where D-SHIELD failed typically involved implicit or literary harms (impersonation, metaphorical references to self-harm, manipulative apologies), highlighting weaknesses in detecting pragmatically encoded toxicity. By contrast, the 129 cases where D-SHIELD succeeded while baselines failed often involved adversarial framing strategies

(e.g., disguising harmful instructions as fiction, education, political role-play, or humor). Here, the baselines tended to overlook the risks, while D-SHIELD maintained robustness by focusing on the semantic content of outputs. Finally, in cases of complete agreement, convergence was observed at the extremes: explicit harmfulness or clearly benign requests.

A particularly pronounced gap emerged in the comparison with SelfDefend, where D-SHIELD achieved an ASR of 2.76% compared to 71–78.6% for SelfDefend. This difference is largely attributable to the distinct mitigation scope of the two approaches. SelfDefend performs *input-level validation*, aiming to detect malicious intent directly from the user prompt before generation. Such a strategy is inherently vulnerable to modern jailbreak techniques that rely on obfuscation, indirect phrasing, role-play, or multi-turn escalation, where the prompt appears benign and harmful intent materializes only after generation. In contrast, D-SHIELD operates at the *output level*, validating the actual generated response in isolation. This allows it to directly assess the surface semantics of the produced text, where harmfulness is typically explicit, making it more robust against adversarial framing. As a result, the substantially higher ASR observed for SelfDefend is consistent with the intrinsic limitations of input-level defenses in adversarial settings. While differences in the underlying model may partially influence absolute performance, the observed gap aligns primarily with the distinct mitigation scope and architectural constraints of the two approaches.

A similarly meaningful gap is observed in the comparison with LLMSelfDefense, despite both approaches performing output-level validation. While LLMSelfDefense evaluates generated responses using a secondary LLM guided by a generic safety-oriented meta-prompt, D-SHIELD grounds its validation in *explicit, regulation-aware compliance criteria* derived from concrete legal and policy frameworks, such as the EU AI Act and OpenAI usage policies. This normative grounding substantially reduces semantic ambiguity during validation and constrains the interpretation space available to the validator, limiting the effectiveness of adversarial linguistic framing. Moreover, D-SHIELD enforces strict decontextualization by design: the validator operates in a stateless manner and receives only the generated output together with a fixed compliance prompt, without access to the user query or conversational context that influenced generation. In contrast, LLM Self-Defense does not explicitly enforce such contextual isolation, making its judgments more susceptible to pragmatic manipulation embedded in the output text. Together, these factors explain why D-SHIELD achieves a markedly lower ASR, even when compared to another output-level defense.

Overall, these findings show that D-SHIELD provides decisive gains in scenarios where harmfulness is camouflaged, but could be complemented by methods more sensitive to implicit abuse.

7.4. Insights from RQ4: Effectiveness of the lightweight configuration

The evaluation of D-SHIELD$_{\text{light}}$ revealed that the lightweight configuration was not only more efficient, achieving a 94% reduction in token-level costs, but also more effective, with an ASR of 1.38% compared to 2.76% for the standard D-SHIELD setup. This result should be interpreted as an empirical observation within the specific experimental setting of decontextualized, binary output-level validation, rather than as a general claim about model size or capability.

While we do not claim a causal explanation for this behavior, a plausible interpretation is that the smaller `gpt-4o-mini` applies stricter decision boundaries and is less prone to "overthinking" deceptive prompts, making it more robust in decontextualized binary classification. We emphasize that this interpretation is speculative and cannot be directly validated, as the models are proprietary and their internal representations, logits, and calibration mechanisms are not accessible.

These results suggest that lightweight safeguards can offer both scalability and effectiveness, and that "bigger" is not always "better". Importantly, the key implication is not that smaller models are universally superior, but that effective decontextualized validation does not necessarily require large or complex models. Understanding the underlying reasons for this behavior, such as differences in calibration, conservatism, or sensitivity to constrained prompts, remains an open research question and is left for future work.

Regarding efficiency, the reported cost savings are computed exclusively based on token-level pricing. We intentionally restrict the analysis to this dimension, as token costs are provider-independent, directly measurable, and comparable across configurations. Other factors, including API overhead, latency, batching strategies, and infrastructure-level optimizations, are highly deployment-specific and depend on system design choices that fall outside the scope of this study. Accordingly, the reported savings should be interpreted as indicative of relative efficiency rather than as a complete end-to-end cost assessment.

7.5. Synthesis and implications

Taken together, the discussion highlights three main insights. First, decontextualized output validation is reliable for explicit harms and adversarially obfuscated prompts, while implicit or pragmatic harms, whose risk emerges only through interpretation, context, or misuse, constitute a complementary challenge that naturally calls for hybrid approaches, such as intent- or pragmatics-aware analysis. Second, comparative results show that D-SHIELD is especially resilient against adversarial framing strategies, where baseline approaches are more vulnerable. Third, lightweight models can outperform larger ones in this setting, enabling cost-effective and scalable deployments without compromising safety. Taken together, these findings highlight both the effectiveness of decontextualized validation as a core safeguard and the importance of extending it with complementary techniques to address residual, intent-driven risks.

7.6. Limits and role of automated compliance assessment

This section clarifies the role and limits of *automated output validation* under the EU AI Act. Although D-SHIELD effectively identifies potentially harmful or non-compliant outputs, automated classification alone does not establish legal compliance. We therefore distinguish between *preventive technical controls* applied before content release and the *regulatory or judicial assessments* that occur after deployment, and we explain how responsibility, auditability, and human oversight are preserved. The goal is to position D-SHIELD as a support mechanism for compliance-related workflows, without conflating technical risk detection with legal authority.

D-SHIELD performs automated content classification to support compliance monitoring, but high classification accuracy does not by itself imply legal compliance with the AI Act. Accordingly, D-SHIELD is explicitly positioned as a decision-support and risk-indication tool that provides an ex ante technical control at the level of LLM-generated outputs. By analyzing generated content before it is delivered to users, the system flags potential safety or regulatory risks and enables mitigation actions such as blocking, warning, or escalation for human review. This process reduces risk early but does not constitute a legal assessment.

Under the AI Act, compliance is evaluated across the entire AI system lifecycle and includes obligations related to risk management, data governance, documentation, transparency, and human oversight (Articles 9–15). D-SHIELD addresses only output-level validation and therefore represents one element within a broader compliance framework. An AI system may thus produce outputs classified as acceptable by D-SHIELD while still failing to meet other legal requirements, such as documentation or oversight obligations. Automated output validation should therefore be understood as a complementary safeguard rather than as evidence of regulatory conformity.

To support accountability and auditability, D-SHIELD's classification outcomes can be logged and retained as part of the system's

technical records. These records enable traceability of automated decisions, facilitate ex post inspection and human review, and allow classifications to be challenged, overridden, or contextualized when necessary. This design supports accountability mechanisms in line with Article 12 of the AI Act, without conferring any legal effect on the automated classification itself.

Automated validation operates as an ex ante safeguard and cannot replace ex post regulatory supervision or judicial review. Final determinations of compliance, enforcement actions, and sanctions remain the responsibility of competent authorities and courts, as set out in Articles 71–74. Output filtering, therefore, cannot substitute post-deployment monitoring, incident reporting, or corrective actions in cases where false negatives occur, all of which require human judgment and organizational processes.

It is also essential to distinguish technical classification from legal judgment. D-SHIELD performs technical analysis by identifying patterns in text associated with regulatory risk categories. However, legal interpretation often depends on contextual factors, such as deployment conditions, affected stakeholders, cumulative system behavior, and operator intent, that are intentionally excluded from D-SHIELD's decontextualized design. While this design choice improves robustness against adversarial manipulation, it necessarily limits the system's ability to perform nuanced legal reasoning. Formal adjudication, which produces legally binding outcomes, is carried out exclusively by competent authorities or courts following investigation and legal assessment. D-SHIELD does not engage in legal reasoning and has no legal effect in adjudicative or enforcement proceedings; its outputs serve solely as non-binding technical indicators that support human decision-making.

Responsibility and liability for unlawful or harmful outcomes remain with the relevant actors, such as the model provider, system integrator, or deployer, depending on the deployment context, and are not transferred by the presence of an automated validation component. Accordingly, even if a validation error results in the release of unlawful or harmful content, legal responsibility is not shifted to D-SHIELD but remains with the appropriate human or organizational actors under the AI Act. For this reason, D-SHIELD should not be considered a standalone "safety component" subject to independent conformity assessment. Instead, when used in regulated or high-risk settings, it can be documented as part of the broader risk management measures required under the AI Act. Human oversight is preserved by design, as automated classifications support, rather than replace, human judgment and governance.

8. Conclusion and future works

This work presented D-SHIELD, a *decontextualized* LLM-based safeguard technique for mitigating jailbreak attacks in generative systems. By decoupling content generation from compliance validation, D-SHIELD enables automated output-level filtering through a secondary LLM that operates independently of the user's prompt and conversation history. In line with its design goals, D-SHIELD addresses compliance at a technical level by validating concrete software artefacts, namely LLM-generated outputs, against explicitly defined regulatory and provider policy categories, without claiming to perform legal assessment or to ensure full regulatory compliance.

Our evaluation showed that this approach aligns strongly with expert judgments on harmful content. The decontextualized validator achieved an overall accuracy of 0.855, with high recall for non-compliant outputs (0.96) and a conservative tendency to over-block borderline cases. This behavior prioritizes safety over permissiveness, in line with the precautionary principle of the AI Act. Moreover, the comparison with state-of-the-art baselines demonstrated D-SHIELD's superior resilience to adversarial framing, while the lightweight variant, $\text{D-SHIELD}_{\text{light}}$, combined stronger protection with a 94% cost saving, suggesting that scalable and efficient deployment is feasible. At the same time, the results confirm that decontextualized output-level validation is most effective for explicit and adversarially obfuscated harms, while implicitly harmful or pragmatically encoded content remains a complementary challenge that cannot be fully addressed without additional contextual or intent-aware mechanisms.

Looking ahead, several directions emerge. First, the approach should be replicated across heterogeneous generators such as Llama, Claude, and Gemini to verify cross-model generalization and assess whether a single guard can effectively protect multiple architectures. Second, the system should be evaluated under realistic workloads to measure energy consumption, latency, and cost, paving the way for optimizations such as distillation or on-device validation. Third, the integration of adaptive policy mechanisms would allow configurable levels of protection, enabling providers to adjust safeguards to specific risk categories. Moreover, future work will investigate additional hardening mechanisms to further reduce residual adaptive risks, including defenses against output-level prompt-injection attempts targeting the validator, for example through structured output constraints, stricter prompt isolation, or hybrid validation strategies combining natural-language and non-natural-language representations. Finally, future studies should include systematic red-teaming campaigns to stress-test the dual-LLM design, especially against coordinated jailbreaks targeting correlations between the generator and the guard.

We believe that these directions will enhance the resilience, adaptability, and practical applicability of D-SHIELD as a modular, software-architectural safeguard that can be integrated into AI-enabled systems as part of broader, human-supervised risk mitigation and governance workflows, in safeguarding generative systems deployed in sensitive or regulated environments.

CRediT authorship contribution statement

Tiziano Santilli: Writing – review & editing, Writing – original draft, Software, Methodology, Investigation, Data curation, Conceptualization. **Marco De Luca:** Writing – review & editing, Writing – original draft, Software, Investigation, Data curation. **Domenico Amalfitano:** Writing – review & editing, Writing – original draft, Validation, Supervision, Project administration, Methodology, Investigation. **Anna Rita Fasolino:** Writing – review & editing, Writing – original draft, Supervision, Project administration, Conceptualization. **Patrizio Pelliccione:** Writing – review & editing, Writing – original draft, Supervision, Project administration, Conceptualization.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgments

This work has been partially funded by (a) the MUR (Italy) Department of Excellence 2023–2027, (b) the European HORIZON-KDT-JU research project MATISSE "Model-based engineering of Digital Twins for early verification and validation of Industrial Systems", HORIZON-KDT-JU-2023-2-RIA, Proposal number: 101140216-2, KDT232RIA_00017, (c) the PRIN project P2022RSW5W - RoboChor: Robot Choreography, and (d) the PRIN project 2022JKA4SL - HALO: etHical-aware AdjustabLe autOnomous systems.

Appendix A. Supplementary data

Supplementary material related to this article can be found online at https://doi.org/10.1016/j.infsof.2026.108130.

Data availability

Link available in supplemental material attached file.

References

[1] BBC, AI system resorts to blackmail if told it will be removed, 2025, URL https://www.bbc.com/news/articles/cpqeng9d20go. (Accessed 20 May 2025).

[2] C. News, Google's Gemini AI chatbot told a human "Please die." 2024, URL https://www.cbsnews.com/news/google-ai-chatbot-threatening-message-human-please-die/. (Accessed 20 May 2025).

[3] Washington Post, Microsoft's AI chatbot is going off the rails, 2023, URL https://www.washingtonpost.com/technology/2023/02/16/microsoft-bing-ai-chatbot-sydney/. (Accessed 20 May 2025).

[4] People, AI bot hinted to teen to kill parents for restricting screen time, now they're suing, 2024, URL https://people.com/parents-suing-after-ai-bot-allegedly-hinted-to-teen-to-kill-them-8760207. (Accessed 20 May 2025).

[5] The Guardian, Musk's AI Grok bot rants about 'white genocide' in South Africa in unrelated chats, 2025, URL https://www.theguardian.com/technology/2025/may/14/elon-musk-grok-white-genocide. (Accessed 20 May 2025).

[6] Reuters, Google, AI firm must face lawsuit filed by a mother over suicide of son, US court says, 2025, URL https://www.reuters.com/sustainability/boards-policy-regulation/google-ai-firm-must-face-lawsuit-filed-by-mother-over-suicide-son-us-court-says-2025-05-21/. (Accessed 20 May 2025).

[7] Sky News, Meta's AI tells Facebook user it has disabled, gifted child in response to parent asking for advice, 2024, URL https://news.sky.com/story/metas-ai-tells-facebook-user-it-has-disabled-gifted-child-in-response-to-parent-asking-for-advice-13117975. (Accessed 20 May 2025).

[8] Wall Street Journal, Meta's 'digital companions' will talk sex with users—Even children, 2025, URL https://www.wsj.com/tech/ai/meta-ai-chatbots-sex-a25311bf. (Accessed 20 May 2025).

[9] M. Sevenhuijsen, G. Ung, M. Suresh Patil, M. Nyberg, Generating safety-critical automotive C-programs using LLMs with formal verification, 284, 2025, URL https://www.scopus.com/inward/record.uri?eid=2-s2.0-105020236369&partnerID=40&md5=471e20bb7a5dcb0316cdacbed2c31546, Cited by: 0,

[10] I.M. Dokas, From hallucinations to hazards: benchmarking LLMs for hazard analysis in safety-critical systems, Saf. Sci. 194 (2026) http://dx.doi.org/10.1016/j.ssci.2025.107056.

[11] J.B. Hakim, J.L. Painter, D. Ramcharran, V. Kara, G. Powell, P. Sobczak, C. Sato, A. Bate, A. Beam, The need for guardrails with large language models in pharmacovigilance and other medical safety critical settings, Sci. Rep. 15 (1) (2025) http://dx.doi.org/10.1038/s41598-025-09138-0, All Open Access, Gold Open Access, Green Open Access.

[12] X. Xia, X. Ma, Y. Hu, T. Qu, H. Chen, X. Gong, From failures to fixes: LLM-driven scenario repair for self-evolving autonomous driving, in: MM 2025 - Proceedings of the 33rd ACM International Conference on Multimedia, Co-Located with MM 2025, 2025, pp. 11552–11561, http://dx.doi.org/10.1145/3746027.3755470.

[13] Madiega Tambiama André, Artificial intelligence act, 2024, URL https://www.europarl.europa.eu/RegData/etudes/BRIE/2021/698792/EPRS_BRI(2021)698792_EN.pdf.

[14] X. Shen, Z. Chen, M. Backes, Y. Shen, Y. Zhang, "Do Anything Now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models, in: Proceedings of the 2024 on ACM SIGSAC Conference on Computer and Communications Security, CCS '24, Association for Computing Machinery, New York, NY, USA, 2024, pp. 1671–1685, http://dx.doi.org/10.1145/3658644.3670388.

[15] Claude Constitutional AI, URL https://www.anthropic.com/news/claudes-constitution.

[16] Y. Bai, S. Kadavath, S. Kundu, A. Askell, J. Kernion, A. Jones, A. Chen, A. Goldie, A. Mirhoseini, C. McKinnon, C. Chen, C. Olsson, C. Olah, D. Hernandez, D. Drain, D. Ganguli, D. Li, E. Tran-Johnson, E. Perez, J. Kerr, J. Mueller, J. Ladish, J. Landau, K. Ndousse, K. Lukosuite, L. Lovitt, M. Sellitto, N. Elhage, N. Schiefer, N. Mercado, N. DasSarma, R. Lasenby, R. Larson, S. Ringer, S. Johnston, S. Kravec, S.E. Showk, S. Fort, T. Lanham, T. Telleen-Lawton, T. Conerly, T. Henighan, T. Hume, S.R. Bowman, Z. Hatfield-Dodds, B. Mann, D. Amodei, N. Joseph, S. McCandlish, T. Brown, J. Kaplan, Constitutional AI: Harmlessness from AI feedback, 2022, arXiv:2212.08073, URL https://arxiv.org/abs/2212.08073.

[17] Y. Yao, J. Duan, K. Xu, Y. Cai, Z. Sun, Y. Zhang, A survey on large language model (LLM) security and privacy: The Good, The Bad, and The Ugly, High-Confidence Comput. 4 (2) (2024) 100211, http://dx.doi.org/10.1016/j.hcc.2024.100211, URL https://www.sciencedirect.com/science/article/pii/S266729522400014X.

[18] L. Ouyang, J. Wu, X. Jiang, D. Almeida, C.L. Wainwright, P. Mishkin, C. Zhang, S. Agarwal, K. Slama, A. Ray, J. Schulman, J. Hilton, F. Kelton, L. Miller, M. Simens, A. Askell, P. Welinder, P. Christiano, J. Leike, R. Lowe, Training language models to follow instructions with human feedback, in: Proceedings of the 36th International Conference on Neural Information Processing Systems, NIPS '22, Curran Associates Inc. Red Hook, NY, USA, 2022.

[19] A. Wei, N. Haghtalab, J. Steinhardt, Jailbroken: how does LLM safety training fail? in: Proceedings of the 37th International Conference on Neural Information Processing Systems, NIPS '23, Curran Associates Inc. Red Hook, NY, USA, 2023.

[20] M. Pisano, P. Ly, A. Sanders, B. Yao, D. Wang, T. Strzalkowski, M. Si, Bergeron: Combating adversarial attacks through a conscience-based alignment framework, 2024, arXiv:2312.00029, URL https://arxiv.org/abs/2312.00029.

[21] Y. Tereshchenko, M. Hämäläinen, A comparative analysis of ethical and safety gaps in LLMs using relative danger coefficient, in: M. Hämäläinen, E. Öhman, Y. Bizzoni, S. Miyagawa, K. Alnajjar (Eds.), Proceedings of the 5th International Conference on Natural Language Processing for Digital Humanities, Association for Computational Linguistics, Albuquerque, USA, 2025, pp. 464–477, URL https://aclanthology.org/2025.nlp4dh-1.40/.

[22] A. Zou, Z. Wang, J.Z. Kolter, M. Fredrikson, Universal and transferable adversarial attacks on aligned language models, 2023, arXiv:2307.15043.

[23] X. Wang, D. Wu, Z. Ji, Z. Li, P. Ma, S. Wang, Y. Li, Y. Liu, N. Liu, J. Rahmel, SelfDefend: LLMs can defend themselves against jailbreaking in a practical manner, in: Proceedings of USENIX Security, USENIX Association, 2025.

[24] M. Phute, A. Helbling, M.D. Hull, S. Peng, S. Szyller, C. Cornelius, D.H. Chau, LLM self defense: By self examination, LLMs know they are being tricked, in: The Second Tiny Papers Track At ICLR 2024, 2024, URL https://openreview.net/forum?id=YoqgcIA19o.

[25] European Union AI Act, URL https://artificialintelligenceact.eu.

[26] European Union AI Act Annex II, URL https://artificialintelligenceact.eu/annex/2/.

[27] The general-purpose AI code of practice, 2025, URL https://digital-strategy.ec.europa.eu/en/policies/contents-code-gpai.

[28] OpenAI Policies, URL https://openai.com/policies/usage-policies/.

[29] M. Russinovich, A. Salem, R. Eldan, Great, now write an article about that: The crescendo multi-turn LLM jailbreak attack, 2024, http://dx.doi.org/10.48550/arXiv.2404.01833, "arXiv.Org".

[30] H. Li, D. Guo, W. Fan, M. Xu, J. Huang, F. Meng, Y. Song, Multi-step jailbreaking privacy attacks on chatGPT, in: H. Bouamor, J. Pino, K. Bali (Eds.), Findings of the Association for Computational Linguistics: EMNLP 2023, Association for Computational Linguistics, Singapore, 2023, pp. 4138–4153, http://dx.doi.org/10.18653/v1/2023.findings-emnlp.272, URL https://aclanthology.org/2023.findings-emnlp.272/.

[31] B.C. Das, M.H. Amini, Y. Wu, Security and privacy challenges of large language models: A survey, ACM Comput. Surv. 57 (6) (2025) http://dx.doi.org/10.1145/3712001.

[32] Jailbreak dataset for Shen at al., URL https://huggingface.co/datasets/walledai/JailbreakHub/viewer/default/train.

[33] advbench, URL https://paperswithcode.com/dataset/advbench.

[34] Jailbreakbench, URL https://jailbreakbench.github.io.

[35] S. Chen, J. Piet, C. Sitawarin, D. Wagner, StruQ: Defending against prompt injection with structured queries, in: USENIX Security Symposium, 2025.

[36] Z. Xu, F. Jiang, L. Niu, J. Jia, B.Y. Lin, R. Poovendran, SafeDecoding: Defending against jailbreak attacks via safety-aware decoding, in: Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), Association for Computational Linguistics, Bangkok, Thailand, 2024, pp. 5587–5605, http://dx.doi.org/10.18653/v1/2024.acl-long.303, URL https://aclanthology.org/2024.acl-long.303/.

[37] H. Inan, K. Upasani, J. Chi, R. Rungta, K. Iyer, Y. Mao, M. Tontchev, Q. Hu, B. Fuller, D. Testuggine, M. Khabsa, Llama guard: LLM-based input-output safeguard for human-AI conversations, 2023, arXiv:2312.06674, URL https://arxiv.org/abs/2312.06674.

[38] Y. Zhang, L. Ding, L. Zhang, D. Tao, Intention analysis makes LLMs a good jailbreak defender, in: O. Rambow, L. Wanner, M. Apidianaki, H. Al-Khalifa, B.D. Eugenio, S. Schockaert (Eds.), Proceedings of the 31st International Conference on Computational Linguistics, Association for Computational Linguistics, Abu Dhabi, UAE, 2025, pp. 2947–2968, URL https://aclanthology.org/2025.coling-main.199/.

[39] Y. Xie, J. Yi, J. Shao, J. Curl, L. Lyu, Q. Chen, X. Xie, F. Wu, Defending ChatGPT against jailbreak attack via self-reminders, Nat. Mach. Intell. 5 (12) (2023) 1486–1496, http://dx.doi.org/10.1038/s42256-023-00765-8.

[40] OpenAI, OpenAi API, 2025, URL https://platform.openai.com. (Accessed 20 May 2025).

[41] Reddit, ChatGPT, 2025, URL https://www.reddit.com/r/ChatGPT/. (Accessed 20 May 2025).

[42] Reddit, ChatGPTPromptGenius, 2025, URL https://www.reddit.com/r/ChatGPTPromptGenius/. (Accessed 20 May 2025).

[43] Reddit, ChatGPTJailbreak, 2025, URL https://www.reddit.com/r/ChatGPTJailbreak/. (Accessed 20 May 2025).

[44] J. Fleiss, Measuring nominal scale agreement among many raters, Psychol. Bull. 76 (1971) http://dx.doi.org/10.1037/h0031619, 378–.

[45] K.O. May, A set of independent necessary and sufficient conditions for simple majority decision, Econometrica 20 (4) (1952) 680–684, URL https://onlinelibrary.wiley.com/doi/abs/0012-9682(195210)20:4<680:ASOINA>2.0.CO;2-S.