

# Markdown 2.10.0

$\text{\LaTeX}$  Themes & Snippets,  
Two Flavors of Comments,  
and LuaMeta $\text{\TeX}$

**Vít Novotný, Grandma Jane, and the Wolf**

Faculty of Informatics, Masaryk University  
Brno, Czech Republic

August 7, 2021



```

\documentclass{book}
\usepackage{markdown}
\markdownsetup{pipeTables,tableCaptions}
\begin{document}
\begin{markdown}
Introduction
=====
## Section
### Subsection
Hello *Markdown*!

```



Right	Left	Default	Center
12	12	12	12
123	123	123	123
1	1	1	1

: Table

```

\end{markdown}
\end{document}

```

# Chapter 1

## Introduction

### 1.1 Section

#### 1.1.1 Subsection

Hello *Markdown*!

Right	Left	Default	Center
12	12	12	12
123	123	123	123
1	1	1	1

Table 1.1: Table

# Contents

## $\text{\LaTeX}$ themes & setup snippets

- Built-in themes

- Creating your own theme

- Setup snippets

## Two flavors of comments

- Semantic HTML comments

- Lexical  $\text{\TeX}$  comments

## Support for LuaMeta $\text{\TeX}$

## What's next and how do I contribute?


- Actionable HTML attributes

- Jekyll front matter

- Online images using Luasocket

- Integration with Pandoc

- Direct mapping of elements



# LaTeX themes & setup snippets

The goal of the Markdown package is to bring fire 🔥 to the users of TeX, so that they can playfully incinerate each and every element of their markdown documents. 😊



Unlike in the cathedral 🏰 of ConTeXt, where packages are few, an extraordinary bazaar 🧑 of action, ferment, and innovation has sprung up in the wake of the LaTeX 2<sub>ε</sub> kernel.

- Markdown's *themes* are LaTeX packages that specify what markdown elements *do*.
- Themes apply *globally*, but may define *setup snippets* that apply *locally*.
- We will discuss *built-in themes* and *creating your own themes* and setup snippets.

# Built-in themes I

## The witiko/tilde theme

```
\documentclass{article}
\usepackage
  [theme=witiko/tilde]
  {markdown}
\begin{document}
\begin{markdown}
Bartel~Leendert van~der~Waerden
\end{markdown}
\end{document}
```



Bartel·Leendert van·der·Waerden, where a  
middot (·) represents a non-breaking space.

# Built-in themes II

## The witiko/dot theme

```

\documentclass{article}
\usepackage[theme=witiko/dot]{markdown}
\begin{document}
\begin{markdown}
``dot A parse tree of "Let's eat grandma!"
digraph tree {
    graph [margin = 0]; node [shape = none]
    edge [arrowhead = none]
    {rank=same; VP1[label = VP]}
    {rank=same; Let; NP1[label = NP];
      VP2[label = VP]}
    {rank=same; us; eat; NP2[label = NP]}
    {rank=same; S}; {rank=same; grandma}
    S -> VP1; VP1 -> Let; VP1 -> NP1
    VP1 -> VP2; NP1 -> us; VP2 -> eat
    VP2 -> NP2; NP2 -> grandma }
\end{markdown}
\end{document}

```




Figure: A parse tree of “Let's eat grandma!”

## Built-in themes III

### The witiko/graphicx/http theme

```
\documentclass{article}
\usepackage
[
texComments, contentBlocks,
theme=witiko/graphicx/http
]{markdown}
\begin{document}
\begin{markdown}
https://github.com/witiko%
/markdown/raw/master%
/banner.png
(Banner of the Markdown package)
\end{markdown}
\end{document}
```


```
\documentclass{book}
\usepackage{markdown}
\markdownSetup{pipeTables, tableCaptions}
\begin{document}
\begin{markdown}
Introduction
=====
## Section
### Subsection
Hello *Markdown*!



| Right | Left | Default | Center |
|-------|------|---------|--------|
| 12    | 12   | 12      | 12     |
| 123   | 123  | 123     | 123    |
| 1     | 1    | 1       | 1      |



: Table
\end{markdown}
\end{document}
```



Chapter 1

Introduction

1.1 Section

1.1.1 Subsection

Hello *Markdown*!

Right	Left	Default	Center
12	12	12	12
123	123	123	123
1	1	1	1

Table 1.1: Table

Figure: Banner of the Markdown package



# Creating your own theme I

1. Decide on a name in the following form:

*$\langle theme\ author \rangle / \langle target\ package \rangle / \langle private\ naming \rangle$*

For example: `jdoe/beamer/headings`

2. *Munge* the theme name by substituting slashes (/) with underscores (\_).

For example: `jdoe_beamer_headings`

3. Create a text file named `markdowntheme $\langle munged\ theme\ name \rangle$ .sty`.


For example `markdownthemejdoe_beamer_headings.sty` with the following:

```
\ProvidesPackage{markdownthemejdoe_beamer_headings}[2021/06/04]
\markdownSetup{
  rendererPrototypes = {
    headingOne = {\frametitle{#1}},
    headingTwo = {\framesubtitle{#1}}
  }
}
```



## Creating your own theme II

```
\documentclass{beamer}
\usepackage[theme = witiko/dot,
  theme = jdoe/beamer/headings]{markdown}
\title{Dietary Assessment of Big Bad Wolf}
\author{Jane Doe}
\begin{document}
\maketitle
\begin{frame}[fragile]
\begin{markdown}
# What's on the Menu?
## Dietary Assessment
``` dot
digraph tree {
  Wolf -> Grandma; Wolf -> Hood
  Wolf [label = "Big Bad Wolf"]
  Hood [label = "Little Red Riding Hood"] }
\end{markdown}
\end{frame}
\end{document}
```



### Dietary Assessment of Big Bad Wolf


Jane Doe

June 4, 2021

◂ ◃ ◅ ◆ ◇ ◈ ◉ ◊ ○ ◌ ◍ ◎ ● ◐ ◑ ◒ ◓ ◔ ◕ ◖ ◗ ◘ ◙ ◚ ◛ ◜ ◝ ◞ ◟ ◠ ◡ ◢ ◣ ◤ ◥ ◦ ◧ ◨ ◩ ◪ ◫ ◬ ◭ ◮ ◯ ◰ ◱ ◲ ◳ ◴ ◵ ◶ ◷ ◸ ◹ ◺ ◻ ◼ ◽ ◾ ◿ ◰ ◱ ◲ ◳ ◴ ◵ ◶ ◷ ◸ ◹ ◺ ◻ ◼ ◽ ◾ ◿

### What's on the Menu?

Dietary Assessment



◂ ◃ ◅ ◆ ◇ ◈ ◉ ◊ ○ ◌ ◍ ◎ ● ◐ ◑ ◒ ◓ ◔ ◕ ◖ ◗ ◘ ◙ ◚ ◛ ◜ ◝ ◞ ◟ ◠ ◡ ◢ ◣ ◤ ◥ ◦ ◧ ◨ ◩ ◪ ◫ ◬ ◭ ◮ ◯ ◰ ◱ ◲ ◳ ◴ ◵ ◶ ◷ ◸ ◹ ◺ ◻ ◼ ◽ ◾ ◿

# Setup snippets I

## `\ProvidesPackage`

```
{markdownthemejdoe_lists_roman}  
[2021/06/04]
```

## `\markdownSetup`

```
rendererPrototypes = {  
  olItemWithNumber = {  
    \item[\romannumeral#1\relax.]  
  }  
}}
```

✗ Can be used only in preamble.

## `\documentclass`

```
{article}
```

```
\usepackage{markdown}
```

```
\begin{document}
```

```
\begin{markdown}
```

```
1. wahid
```

```
2. aithnayn
```

```
\end{markdown}
```

```
\begin{markdown*}% This won't work!  
  {theme=jdoe/lists/roman}
```

```
3. tres
```

```
4. quattuor
```

```
\end{markdown*}
```

```
\end{document}
```

## Setup snippets II

### `\ProvidesPackage`

```
{markdownthemejdoe_lists}
[2021/06/04]
```

### `\markdownSetupSnippet{roman}`

```
{
  rendererPrototypes = {
    olItemWithNumber = {
      \item[\romannumeral#1\relax.]
    }
  }
}
```

1. wahid
  2. aithnayn
  - iii. tres
  - iv. quattuor



### `\documentclass{article}`

### `\usepackage`

```
[theme=jdoe/lists]
```

```
{markdown}
```

### `\begin{document}`

### `\begin{markdown}`

```
1. wahid
```

```
2. aithnayn
```

### `\end{markdown}`

### `\begin{markdown*}`

```
{snippet=jdoe/lists/roman}
```

```
3. tres
```

```
4. quattuor
```

### `\end{markdown*}`

### `\end{document}`

## Two flavors of comments

In T<sub>E</sub>X, comments fulfil several *distinct roles*:

1. Prevent the processing of code:

```
%\author{Authors anonymized}
\author{John Doe \and Jane Roe}
```

2. Mark up parallel documents:

```
% \cs{foo} prints ``bar'':
% \begin{macrocode}
\def\foo{bar}
% \end{macrocode}
```

3. Insert little side notes:

```
% Aren't we missing a comma here?
Let's eat grandma!
```

4. Consume newlines and leading spaces:

```
My parents have first met in Llan%
fairpwllgwyngyllgogerychwyrndrobw%
      llllantysiliogogoch.
```

The Markdown package supports two flavors of comments:

**Semantic** May only appear in text. Markup is recognized. Enables roles 1, 2, and 3.

**Lexical** May appear anywhere. Markup is ignored. Enables roles 1, 2, and 4.

# Semantic HTML comments

```
\documentclass{article}
\usepackage{marginnote}
\usepackage[html]{markdown}
\markdownSetup{
  renderers = {
    inlineHtmlComment = {
      \marginnote{#1}
    }
  }
}
\begin{document}
\begin{markdown}
<!-- Aren't we missing
      *a comma* here? -->
Let's eat grandma!
\end{markdown}
\end{document}
```

Aren't we  
missing *a*  
*comma* here?

Let's eat grandma!



# Lexical TeX comments

```
\documentclass{article}
\usepackage[texComments]{markdown}
\begin{document}
\begin{markdown}
[Here][1] is what the wolf has
to say on the matter.

[1]: http://a.very.long.url/that/%
    should/enjoy\%20some#word-wrap
\end{markdown}
\end{document}
```





Here<sup>1</sup> is what the wolf has to say on the matter.

---

<sup>1</sup><http://a.very.long.url/that/should/enjoy%20some#word-wrap>

## Support for LuaMetaTeX

*The LuaMetaTeX engine is a fast minimalist development  version of LuaTeX, which is used in the ConTeXt LMTX format. Since the Markdown package supports ConTeXt, the time is ripe  to make Markdown play nice with LuaMetaTeX as well.*



- LuaMetaTeX lacks Selene Unicode, but uses Lua 5.4 with its built-in utf8 library.
- LuaMetaTeX lacks KPathSea, but provides an optional library interface.
- LuaMetaTeX provides Luasocket, but lacks high-level libraries such as `socket.http`.

## What's next and how do I contribute?

*The Markdown package would be well-served by encouraging users to lecture it 🎓 on ever-new things and release their lecture notes 📖 to the whole wide world. 🌐*



# GitHub

There are many intriguing ideas for the future of Markdown:

- Some ideas are already *under development* by contributors.

<https://github.com/witiko/markdown/pulls>

- Some ideas are only now beginning to be *discussed*:

<https://github.com/witiko/markdown/discussions> & [/issues](https://github.com/witiko/markdown/issues)

- Other ideas are yet to be discovered by *you*.



## Actionable HTML attributes

I conclude in Section~\ref{sec:conclusion}.

Conclusion

=====

\label{sec:conclusion}

In this paper, we have discovered that most grandmas would rather eat dinner with their grandchildren than get eaten. Begone, wolf!

I conclude in Section <#sec:conclusion>.

Conclusion {#sec:conclusion .some-snippet}

=====

In this paper, we have discovered that most grandmas would rather eat dinner with their grandchildren than get eaten. Begone, wolf!



- Recommended reading: [Parsing complex data formats in LuaTeX with LPEG](#) (Menke, 2019)

# Jekyll front matter




```
\title{Of \emph{Wolves} and \emph{Grandmas}}  
\author{Little Red Riding Hood  
        \and Big Bad Wolf}  
\maketitle
```

```
---  
title: Of *Wolves* and _Grandmas_  
author:  
- name: Little Red Riding Hood  
- name: Big Bad Wolf  
---
```

- Recommended reading: [Parsing complex data formats in LuaTeX with LPEG](#) (Menke, 2019)
- For more information, see [/issues/22](#) and [/pull/77](#).

## Online images using Luasocket

Just use sockets. 

—Hans Hagen during a Q&A session at BachoT<sub>E</sub>X 2017

- The witiko/graphicx/http theme uses either GNU Wget or cURL.
- We could remove both prerequisites by using the Luasocket library.
- In [/issues/82](#), I drafted an implementation:

```
local http = require("socket.http")  
local result, status, headers = http.request(url)
```

The draft has several issues:

1. The `http.request()` method of `socket.http` mishandles redirects.
  2. LuaMetaT<sub>E</sub>X lacks `socket.http`.
  3. The `\directlua` command needs to be replaced with a shell escape for non-Lua T<sub>E</sub>X engines.
- Lua programmers familiar with Luasocket are encouraged to help tackle points 1 & 2.

## Integration with Pandoc

- Pandoc is a Haskell library for converting between dozens of document formats.
- Pandoc uses an intermediate AST format, so that every document format only needs a conversion function from the format to the AST and back.  $N > 2 \implies 2N < N^2$ .
- If the Markdown package understood the AST, we could typeset any of the document formats of Pandoc while maintaining full control over the formatting:

```
\usepackage[theme=jdoe/lists]{markdown}
\begin{document}
\pandocInput[snippet=jdoe/lists/roman]
               {of-wolves-and-grandmas.docx}
\end{document}
```

- Recommended reading: [Parsing complex data formats in Lua<sub>T</sub><sub>E</sub>X with LPEG](#) (Menke, 2019)
- For more information, see [/issues/25](#), [/issues/62](#), and [drehak/lunamark](#).

## Direct mapping of elements I

```
\markdownSetup {  
  renderers = {  
    emphasis = {\textbf{#1}}  
  }  
}
```



Hello \*Markdown\*!



Hello \markdownRendererEmphasis{Markdown}!



Hello \textbf{Markdown}!



Hello **Markdown!**

## Direct mapping of elements II

```
\markdownSetup {  
  directMapping = {  
    headingOne = {  
      \begin{frame}  
        \frametitle{#1}  
      },  
    horizontalRule = {  
      \end{frame}  
    },  
  }  
}
```




```
# What's on the Menu?  
Grandma
```

```
***
```



```
\begin{frame}  
\frametitle{What's on the Menu?}  
Grandma  
\end{frame}
```



**MUNI**

FACULTY

OF INFORMATICS